

Rajalakshmi Engineering College

Name: Rajeshwar s
Email: 240701413@rajalakshmi.edu.in
Roll no: 2116240701413
Phone: 9003785151
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and table_size — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers – the roll numbers to insert.

The third line contains an integer q – the number of queries.

The fourth line contains q space-separated integers – the roll numbers to search for.

Output Format

The output print q lines – for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>
```

```
#define MAX 100
```

```
void initializeTable(int table[], int size)
```

```
{  
    for (int i = 0; i < size; i++) {  
        table[i] = -1;  
    }  
}
```

```
void insertIntoHashTable(int table[], int size, int arr[], int n)
```

```
{  
    for (int i = 0; i < n; i++) {  
        int roll = arr[i];
```

```

    int index = roll % size;
    while (table[index] != -1) {
        index = (index + 1) % size;
    }

    table[index] = roll;
}

}

int searchInHashTable(int table[], int size, int num)
{
    int index = num % size;
    int start = index;
    while (table[index] != -1) {
        if (table[index] == num) {
            return 1;
        }
        index = (index + 1) % size;
        if (index == start) break;
    }

    return 0;
}

int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);

    int arr[MAX], table[MAX];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    initializeTable(table, table_size);
    insertIntoHashTable(table, table_size, arr, n);

    int q, x;
    scanf("%d", &q);
    for (int i = 0; i < q; i++) {
        scanf("%d", &x);
        if (searchInHashTable(table, table_size, x))
            printf("Value %d: Found\n", x);
        else

```

```
        printf("Value %d: Not Found\n", x);  
    }  
    return 0;  
}
```

Status : Correct

Marks : 10/10