

CSS Pseudo-classes

[< Previous](#)[Next >](#)

What are Pseudo-classes?

A pseudo-class is used to define a special state of an element.

For example, it can be used to:

- Style an element when a user mouses over it
- Style visited and unvisited links differently
- Style an element when it gets focus

Mouse Over Me

Click Me To Get Focus

Syntax

The syntax of pseudo-classes:

```
selector:pseudo-class {  
  property:value;  
}
```

Anchor Pseudo-classes

Links can be displayed in different ways:

[HTML](#) [CSS](#) [MORE ▼](#)

```
/* unvisited link */
a:link {
    color: #FF0000;
}

/* visited link */
a:visited {
    color: #00FF00;
}

/* mouse over link */
a:hover {
    color: #FF00FF;
}

/* selected link */
a:active {
    color: #0000FF;
}
```

[Try it Yourself »](#)

Note: `a:hover` MUST come after `a:link` and `a:visited` in the CSS definition in order to be effective! `a:active` MUST come after `a:hover` in the CSS definition in order to be effective! Pseudo-class names are not case-sensitive.

Pseudo-classes and CSS Classes

Pseudo-classes can be combined with CSS classes:

When you hover over the link in the example, it will change color:

Example

```
a.highlight:hover {
    color: #ff0000;
}
```

[HTML](#) [CSS](#) [MORE ▼](#)[Try it Yourself »](#)

Hover on <div>

An example of using the `:hover` pseudo-class on a `<div>` element:

Example

```
div:hover {  
    background-color: blue;  
}
```

[Try it Yourself »](#)

Simple Tooltip Hover

Hover over a `<div>` element to show a `<p>` element (like a tooltip):

Hover over me to show the `<p>` element.

Example

```
p {  
    display: none;  
    background-color: yellow;  
    padding: 20px;  
}  
  
div:hover p {  
    display: block;  
}
```

[Try it Yourself »](#)

CSS - The :first-child Pseudo-class

The `:first-child` pseudo-class matches a specified element that is the first child of another element.

[HTML](#) [CSS](#) [MORE ▼](#)

In the following example, the selector matches any `<p>` element that is the first child of any element:

Example

```
p:first-child {  
    color: blue;  
}
```

[Try it Yourself »](#)

Match the first `<i>` element in all `<p>` elements

In the following example, the selector matches the first `<i>` element in all `<p>` elements:

Example

```
p i:first-child {  
    color: blue;  
}
```

[Try it Yourself »](#)

Match all `<i>` elements in all first child `<p>` elements

In the following example, the selector matches all `<i>` elements in `<p>` elements that are the first child of another element:

Example

```
p:first-child i {  
    color: blue;  
}
```

[Try it Yourself »](#)

[HTML](#) [CSS](#) [MORE ▼](#)

The `:lang` pseudo-class allows you to define special rules for different languages.

In the example below, `:lang` defines the quotation marks for `<q>` elements with `lang="no"`:

Example

```
<html>
<head>
<style>
q:lang(no) {
  quotes: "~" "~";
}
</style>
</head>

<body>
<p>Some text <q lang="no">A quote in a paragraph</q> Some text.</p>
</body>
</html>
```

[Try it Yourself »](#)

More Examples

Add different styles to hyperlinks

This example demonstrates how to add other styles to hyperlinks.

Use of :focus

This example demonstrates how to use the `:focus` pseudo-class.

Test Yourself with Exercises!

[Exercise 1 »](#)

[Exercise 2 »](#)

[Exercise 3 »](#)

[Exercise 4 »](#)

All CSS Pseudo Classes

| Selector | Example | Example description |
|---------------------------------|---------------|--|
| <u>:active</u> | a:active | Selects the active link |
| <u>:checked</u> | input:checked | Selects every checked <code><input></code> element |

HTML CSS MORE ▼

| | | |
|---|-----------------------|--|
| <u>:empty</u> | p:empty | Selects every <p> element that has no children |
| <u>:enabled</u> | input:enabled | Selects every enabled <input> element |
| <u>:first-child</u> | p:first-child | Selects every <p> elements that is the first child of its parent |
| <u>:first-of-type</u> | p:first-of-type | Selects every <p> element that is the first <p> element of its parent |
| <u>:focus</u> | input:focus | Selects the <input> element that has focus |
| <u>:hover</u> | a:hover | Selects links on mouse over |
| <u>:in-range</u> | input:in-range | Selects <input> elements with a value within a specified range |
| <u>:invalid</u> | input:invalid | Selects all <input> elements with an invalid value |
| <u>:lang(<i>language</i>)</u> | p:lang(it) | Selects every <p> element with a lang attribute value starting with "it" |
| <u>:last-child</u> | p:last-child | Selects every <p> elements that is the last child of its parent |
| <u>:last-of-type</u> | p:last-of-type | Selects every <p> element that is the last <p> element of its parent |
| <u>:link</u> | a:link | Selects all unvisited links |
| <u>:not(selector)</u> | :not(p) | Selects every element that is not a <p> element |
| <u>:nth-child(n)</u> | p:nth-child(2) | Selects every <p> element that is the second child of its parent |
| <u>:nth-last-child(n)</u> | p:nth-last-child(2) | Selects every <p> element that is the second child of its parent, counting from the last child |
| <u>:nth-last-of-type(n)</u> | p:nth-last-of-type(2) | Selects every <p> element that is the second <p> element of its parent, counting from the last child |
| <u>:nth-of-type(n)</u> | p:nth-of-type(2) | Selects every <p> element that is the second <p> element of its parent |
| <u>:only-of-type</u> | p:only-of-type | Selects every <p> element that is the only <p> element of its parent |
| <u>:only-child</u> | p:only-child | Selects every <p> element that is the only child of its parent |
| <u>:optional</u> | input:optional | Selects <input> elements with no "required" attribute |
| <u>:out-of-range</u> | input:out-of-range | Selects <input> elements with a value outside a specified range |

[HTML](#) [CSS](#) [MORE ▼](#)

| | |
|-------------------------------|---|
| <code>input:read-write</code> | Selects <input> elements with no "readonly" attribute |
| <code>input:required</code> | Selects <input> elements with a "required" attribute specified |
| <code>root</code> | Selects the document's root element |
| <code>#news:target</code> | Selects the current active #news element (clicked on a URL containing that anchor name) |
| <code>input:valid</code> | Selects all <input> elements with a valid value |
| <code>a:visited</code> | Selects all visited links |


Pseudo Elements

| Example | Example description |
|------------------------------------|--|
| <code>p::after</code> | Insert content after every <p> element |
| <code>p::before</code> | Insert content before every <p> element |
| <code>p::first-letter</code> | Selects the first letter of every <p> element |
| <code>p::first-line</code> | Selects the first line of every <p> element |
| <u>::selection</u> | <code>p::selection</code> Selects the portion of an element that is selected by a user |

[< Previous](#)[Next >](#)

[HTML](#) [CSS](#) [MORE ▼](#)

COLOR PICKER



LEARN MORE

[Tabs](#)
[Dropdowns](#)
[Accordions](#)
[Convert Weights](#)
[Animated Buttons](#)
[Side Navigation](#)
[Top Navigation](#)
[JS Animations](#)
[Modal Boxes](#)
[Progress Bars](#)
[Parallax](#)
[Login Form](#)
[HTML Includes](#)
[Google Maps](#)
[Loaders](#)

[HTML](#) [CSS](#) [MORE ▼](#)

[Filter List](#)

[Sort List](#)

SHARE



CERTIFICATES

HTML, CSS, JavaScript, PHP, jQuery, Bootstrap and XML.

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

[HTML](#) [CSS](#) [MORE ▼](#)

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [SQL Tutorial](#)
- [PHP Tutorial](#)
- [jQuery Tutorial](#)
- [Angular Tutorial](#)
- [XML Tutorial](#)

Top 10 References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [W3.CSS Reference](#)
- [Browser Statistics](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [HTML Character Sets](#)
- [jQuery Reference](#)
- [AngularJS Reference](#)

Top 10 Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [W3.CSS Examples](#)
- [HTML DOM Examples](#)
- [PHP Examples](#)
- [ASP Examples](#)
- [jQuery Examples](#)
- [Angular Examples](#)
- [XML Examples](#)

Web Certificates

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [jQuery Certificate](#)
- [PHP Certificate](#)
- [Bootstrap Certificate](#)
- [XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2017 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

