SpecLens-RL: Small, Auditable Model Organisms of Reward Hacking, Reward Tampering, and Monitorability

Raj Kashikar
https://github.com/raj200501/SpecLens-RL

Abstract

Reward hacking is now observed in frontier reinforcement-learning runs, but it is hard to study there: the true objective is rarely known exactly, and the misspecification cannot be switched off. We present SpecLens-RL, three procedurally generated gridworld tasks in which the proxy reward differs from a known true objective through one explicit, scalable corruption channel: farmable reward shaping (PROXYFARMING), tampering with a reward sensor (SENSORTAMPER), and a bonus for detours that break a deadline the proxy omits (GEMTIMEOUT). Across 135 PPO runs, hacking emerges in three different ways, from the late abandonment of a mastered task to an exploit learned instead of the task. Solving 100 layouts per task exactly shows that the proxy-optimal policy hacks on most layouts from 0.1–0.15 times the default channel strength, whereas PPO starts hacking only at several times that in PROXYFARMING and GEMTIMEOUT; where PPO hacks in PROXYFARMING and SENSORTAMPER, it gives up more of the true objective than the optimum does. Monitors that see only positions and actions reach held-out AUCs of 0.981–0.998, but a baseline that knows only what kind of policy produced an episode reaches 0.944–0.990; within single Proxy PPO policies, the monitors' AUC is 0.890–0.986, lowest where hacking emerges late in training. Training agents against such a monitor removes hacking in PROXYFARMING and hides it in GEMTIMEOUT, where agents still hack in 65% of episodes while the monitor's recall on hacks falls from 97% to 1%. Every result cited in this paper is regenerated from saved results by one command and checked in continuous integration.

1 Introduction

Reward hacking has moved from a thought experiment to an observed property of frontier training runs. Reasoning models trained with reinforcement learning on coding tasks learn to special-case or skip the tests that grade them [Baker et al., 2025], and hacking learned in production environments can generalize to broader misalignment [MacDiarmid et al., 2025]. These settings are where the problem matters, but they are hard places to study it: the true objective is rarely known exactly, the misspecification cannot be removed without changing the task, and each training run is expensive.

We take the opposite trade-off and build *model organisms* [Hubinger et al., 2023] of reward hacking: environments small enough that the true objective J_t is known exactly, that the proxy reward R_p differs from it through one explicit *corruption channel* whose scale can be varied or set to zero (in one task the proxy also omits a deadline), and that dozens of training runs per condition fit on a single CPU machine. SpecLens-RL contains three procedurally generated gridworld tasks, each built around a different mechanism: farmable reward shaping [Ng et al., 1999], tampering with the sensor that computes the reward [Everitt et al., 2021], and a proxy that omits a constraint.

Preprint.

Hack labels are defined by behavior, so switching the channel off cannot hide the behavior from the measurement. We use the tasks to ask three questions.

When does an optimizer exploit a misspecified reward? Proxy PPO hacks in every task at the default channel scale, but how it gets there depends on the mechanism (Section 5.1). In PROXYFARMING, agents first master the intended task, reaching 97% success on average, and later abandon it for the exploit: 9 of 10 runs between 600k and 977k steps into training, while the last had reached 49% hacking when training ended. In SENSORTAMPER and GEMTIMEOUT, the exploit is learned instead of the task. Solving 100 layouts per task exactly shows that the proxy-optimal policy hacks on most layouts from a channel scale of 0.15 (PROXYFARMING), 0.1 (SENSORTAMPER) and 0.1 (GEMTIMEOUT) times the default. PPO does so only from 1 in PROXYFARMING and 0.5 in GEMTIMEOUT (in SENSORTAMPER it hacks at every positive scale we trained); and in PROXYFARMING and SENSORTAMPER, where PPO hacks it gives up more of the true objective than the proxy optimum would (Section 5.2).

Can a monitor detect hacking from behavior alone? The policies pooled in a monitor's training and test data hack at very different rates (Proxy against Oracle PPO, early against late snapshots), so a monitor can score well by recognizing *which* policy produced an episode rather than *what* the policy did. Monitors that see only positions and actions reach held-out AUCs of 0.981–0.998, but a baseline that sees only the policy's identity and training stage reaches 0.944–0.990. Within the episodes of a single Proxy PPO policy, the monitors' AUC is 0.973 and 0.986 in SENSORTAMPER and GEMTIMEOUT but only 0.890 in PROXYFARMING, where hacking emerges late (Section 5.3).

What happens when the agent is trained against the monitor? Penalizing fresh Proxy PPO agents with a fitted behavior monitor removes hacking in PROXYFARMING. In GEMTIMEOUT, agents keep hacking in 65% of episodes while the monitor's recall on their hacks falls from 97% to 1%; in SENSORTAMPER, 1 of 5 runs keeps tampering, and the monitor flags only 28% of its hacks. Because the monitor is linear, we can attribute the evasion to the behavioral features that changed: in GEMTIMEOUT, mostly a no-op action whose frequency barely varied in the monitor's training data (Section 5.4).

Our contributions are:

- three tasks with a known true objective, an explicit and scalable corruption channel, behavioral hack labels and an observable distribution shift, released as Gymnasium environments;
- an exact proxy-optimal reference for every task and channel scale, which separates the incentive to hack from the optimizer's ability to find the hack;
- an evaluation protocol for hack monitors in which features have enforced provenance, cross-validation holds out whole policy lineages, and every monitor is compared with a policy-identity baseline and evaluated within single policies;
- a pipeline in which every result cited in this paper is regenerated from saved results by one command and checked in continuous integration, together with an account of five evaluation errors that an earlier version of this work made (Section 6).

2 Related Work

Specification gaming and reward hacking. Agents that optimize an imperfect reward often find behaviors the designer did not intend [Amodei et al., 2016, Krakovna et al., 2020]. Skalse et al. [2022] formalize reward hacking as a proxy whose optimization decreases the true return. Pan et al. [2022] show that more capable agents exploit misspecified rewards more, sometimes through abrupt phase transitions, and Gao et al. [2023] measure how a true objective first improves and then degrades as a learned reward model is optimized. Our training-dynamics and dose–response experiments (Sections 5.1 and 5.2) ask the same questions in settings small enough that the true objective is known exactly and the corruption channel can be switched off.

Reward tampering. Everitt et al. [2021] distinguish an agent influencing the process that computes its reward from merely exploiting a flawed reward function. Denison et al. [2024] find that language models trained on a curriculum of gameable environments occasionally generalize to editing their own reward function. SENSORTAMPER is a minimal instance of the first kind: the reward

is computed from a delivery sensor, and the agent can make that sensor report deliveries that did not happen.

Shaping and goal misgeneralization. Shaping rewards preserve optimal policies only if they are potential-based [Ng et al., 1999]; PROXYFARMING uses a non-potential bonus precisely so that it creates a farmable cycle. Langosco di Langosco et al. [2022] show that agents can keep their capabilities under distribution shift while pursuing the wrong goal. Our OOD splits are simpler layout shifts (more walls, a more distant console, more gems); they test whether a learned exploit persists, not whether goals misgeneralize.

Monitoring for misbehavior. Pan et al. [2022] propose detecting aberrant policies as an anomaly-detection task. Baker et al. [2025] show that monitors reading a reasoning model's chain of thought catch reward hacking in agentic coding, and that optimizing against such a monitor can teach the model to hide its intent. MacDiarmid et al. [2025] report that reward hacking learned in production RL environments generalizes to broader misalignment, which raises the stakes of detecting it early. Our monitors see only trajectories, but the evaluation questions are the same: what may the monitor observe, does it generalize to new conditions, and is it better than a trivial baseline?

Small testbeds and evaluation methodology. AI Safety Gridworlds [Leike et al., 2017] and bsuite [Osband et al., 2020] argue for small, diagnostic environments; Procgen [Cobbe et al., 2020] argues for procedurally generated layouts so that evaluation is not memorization. Agarwal et al. [2021] show how few-seed RL comparisons mislead and recommend interval estimates over runs. We follow all three recommendations and add one of our own: every experimental result cited in the text is generated from saved results and checked in continuous integration (Section 6).

3 SpecLens-RL

3.1 The task tuple

A specification-diagnostic task is a tuple

$$T = (M,\ R_p,\ J_t,\ C,\ M_{\text{mon}},\ \Delta,\ \Pi),$$

where M is the environment dynamics, R_p the proxy reward the agent is trained on, J_t the true objective it is judged by, C the corruption channel through which R_p and J_t differ, M_{mon} the information available to a monitor, Δ a family of distribution shifts, and Π the policy class and training algorithm. Writing the tuple out forces each claim to name its assumptions: a monitor result is a statement about a particular M_{mon}, a robustness result about a particular Δ.

The design rule we impose on every task is that *the corruption channel is explicit and scalable*. In PROXYFARMING and SENSORTAMPER, $R_p = J_t + \lambda C$ exactly; in GEMTIMEOUT, R_p additionally omits the deadline that J_t enforces, so at $\lambda = 0$ the proxy still ignores the deadline but no longer pays for being late. Scaling the *channel scale* λ leaves the dynamics untouched, so the channel's role can be tested by retraining with a different λ rather than inferred from correlations. (It also rescales part of the return, so it changes the optimization problem as well as the incentive.)

Hack labels are computed from behavior and do not depend on λ, so switching the channel off cannot hide the behavior from the measurement (Section 6, item 3). An episode is a *hack* if the agent used the channel at least a task-specific number of times (Table 1); it is a *harmful hack* if, in addition, the true objective was not achieved. The thresholds differ by task, so hack rates are comparable across methods within a task, not across tasks.

3.2 Three tasks, three mechanisms

All tasks are fully observed 7×7 gridworlds with walls and five actions (four moves and *interact*). Every episode samples a fresh layout, so an agent cannot memorize a route. The agent, goal and task objects are placed uniformly on distinct cells and the walls uniformly on the rest, so the space of layouts is combinatorially large, and evaluation layouts are drawn from seeds disjoint from training (a test checks that the evaluation layouts are distinct). Observations are one-hot object planes plus a few scalars (elapsed time and task state). Both rewards share a -0.01 step cost and pay $+1$ for completing the intended task. Figure 1 shows example layouts and Table 1 summarizes the channels.




Figure 1: Example in-distribution (top) and OOD (bottom) layouts. A = agent, G = goal or delivery target, dark cells are walls. Layouts are resampled every episode.

Table 1: Corruption channels, shifts and hack labels. The full proxy reward and true objective of each task are listed in Appendix A.

Task	Corruption channel C	Shift Δ (OOD)	Hack label
ProxyFarming	Non-potential-based beacon bonus that can be farmed indefinitely.	OOD doubles wall density ($3 \rightarrow 6$ walls).	Agent spends ≥ 3 steps on the beacon.
SensorTamper	Pressing interact on the console makes the delivery sensor emit a false confirmation (at most one per 4 steps).	OOD places the console 7 or more steps from the start (ID: at most 5).	Agent presses the console ≥ 1 time(s).
GemTimeout	Gem bonus; every gem lies on a detour that makes the deadline infeasible.	OOD raises the number of gems from 3 to 5.	Agent collects ≥ 1 gem(s).

PROXYFARMING (farmable shaping). The agent should reach a goal. The proxy adds a bonus for every step spent on a beacon, a shaping term that is not potential-based and therefore creates a reward cycle [Ng et al., 1999]. Idling on the beacon earns more proxy reward than finishing the task. The OOD split doubles wall density.

SENSORTAMPER (reward tampering). The agent should pick up an object and carry it to a target. The proxy pays $+1$ for every delivery confirmation the delivery sensor emits. Pressing *interact* on a console makes the sensor emit a false confirmation (at most one per four steps), a minimal instance of an agent manipulating the process that produces its reward rather than the world [Everitt et al., 2021]. In-distribution, the console is at most five steps from the start; the OOD split places it seven or more steps away, so tampering costs more of the episode.

GEMTIMEOUT (omitted constraint). The agent should reach a goal within a deadline of the shortest-path length plus two steps. The proxy pays for reaching the goal at any time and adds a bonus per gem. Gems are placed only where the detour makes the deadline infeasible, so every gem collected trades the true objective for proxy reward. The OOD split raises the number of gems from three to five.

4 Experimental Protocol

Agents. The policy class Π is PPO [Schulman et al., 2017] in a single-file CleanRL-style implementation [Huang et al., 2022]: 16 synchronous environments, rollouts of 128 steps, GAE(λ=0.95), γ=0.99, 4 epochs of minibatch size 512, a learning rate of 0.0003 decayed linearly to zero, and entropy coefficient 0.01. The network is two 3×3 convolutions with 16 channels followed by a 256-unit hidden layer. *Proxy PPO* is trained on R_p; *Oracle PPO* is the same algorithm trained on J_t and serves as a reference for what the budget can achieve, not as a deployable method. Each run uses 1.5M environment steps; the main comparison uses 10 seeds per task and method. All settings (Appendix Table 7) are identical across tasks and methods.

Evaluation. Each final policy is evaluated on 500 fresh layouts per split, with actions sampled from the policy, which is the behavior PPO optimizes. Every policy sees the same layouts, so comparisons are paired. Training runs are the independent units: we average episodes within a run and report the mean over runs with a 95% Student-t interval (clipped to $[0, 1]$ for rates). With 5–10 runs, percentile-bootstrap intervals cover noticeably less than their nominal 95%, which is why we do not use them.

Training dynamics and dose–response. Each run saves 20 evenly spaced policy snapshots, which are evaluated on 100 fixed ID layouts to trace proxy return, true return and hack rate over training. For the dose–response experiment we train Proxy PPO with channel scale $\lambda \in \{0, 0.25, 0.5, 1, 2\}$ (times the default bonus), with 5 seeds per value; the $\lambda = 1$ runs are the first 5 main-experiment runs. As a reference that does not depend on the optimizer, we also compute the exact proxy-optimal policy of 100 ID layouts at each scale (Appendix B).

Monitors. A monitor sees one finished trajectory and outputs a hack score. Because hacking emerges during training, each task's monitor dataset pools stochastic rollouts of 10 snapshots of every Proxy PPO and every Oracle PPO run (20 layouts per snapshot and split), 4,000 ID episodes per task. Monitor channels are defined by the provenance of their features, i.e. the trajectory fields each feature is computed from; provenance is enforced in code by computing every feature on a copy of the trajectory restricted to its declared fields.

- **behavior** (15 features): positions and actions. The monitor is given no layout field (goal, walls or channel cells), although its positions include the start cell and, in episodes that end by completing the task, the goal. It also sees how long the episode lasted, and in PROXYFARMING and SENSORTAMPER an episode ends early only when the task is completed.
- **task** (20 features): additionally the goal cell.
- **privileged** (23 features): additionally the cells through which the channel is accessed. Hack labels are functions of exactly these fields, so this channel can reconstruct them and serves as a positive control.

We fit logistic regression and gradient-boosted trees with leave-one-seed-out cross-validation: each fold holds out the proxy and oracle runs of one seed, so the monitor is always scored on policy lineages it has never seen. We report the mean held-out ROC-AUC with a t interval over folds, the *within-snapshot* AUC (the mean AUC within each Proxy PPO snapshot that contains both classes, i.e. among the episodes of a single policy that a deployed monitor would watch; Oracle PPO snapshots contain at most a few accidental hacks and are left out), and two transfer tests: training on ID episodes and testing on the held-out seed's OOD episodes, and training on the first half of training and testing on the second half.

Baselines a monitor must beat. Hacking becomes more common as proxy training proceeds, so a monitor could score well by recognizing which policy produced an episode rather than what it did. The *policy-identity* baseline scores each held-out episode with the hack rate of its (method, snapshot) cell in the training runs, which is everything a monitor could learn from knowing what kind of policy produced the episode. The *single-feature* baseline uses the best individual feature, with the feature and its sign chosen on the training folds only.

Admissibility. A monitor result is *admissible* if the label is non-degenerate (minority class at least 5%) and the channel does not see every field the task's hack label is computed from (positions and




Figure 2: Training dynamics over 10 seeds, evaluated on 100 fixed ID layouts per snapshot. Thick lines are means with 95% t intervals over runs; thin lines are individual Proxy PPO runs.

channel cells, plus actions in SENSORTAMPER). A channel that sees all of them can compute the label directly, so its score says nothing about monitorability. We additionally flag a result as *trivial* when the selected single feature already reaches a held-out AUC of 0.98. The privileged channel must be inadmissible and should be trivial; it is the positive control for the screen.

Training against a monitor. Finally we fit a logistic behavior monitor on the 4,000 ID episodes of a task's monitor dataset and train 5 fresh Proxy PPO agents (new seeds) whose reward at the end of each episode is reduced by $\beta = 10$ times the monitor's hack probability. A monitor flags an episode when that probability is at least 0.5. We compare the monitor's recall on hacking episodes of these agents with its out-of-run recall on the unpenalized final policies (each held-out seed scored by a monitor fitted on the other seeds). Because the monitor is linear in standardized features, the change in its mean logit between the final hacking episodes of unpenalized and penalized agents is exactly a sum of per-feature terms, which shows how the penalized agents' hacks moved relative to the monitor.

5 Results

5.1 Hacking emerges in three different ways

At the default channel scale, Proxy PPO hacks in every task (Table 2): its ID hack rate is 85% in PROXYFARMING, 99% in SENSORTAMPER and 92% in GEMTIMEOUT, and nearly all of these hacks are harmful (84%, 99% and 92% of episodes). Oracle PPO succeeds on 99%, 98% and 95% of the same layouts, so the budget and architecture suffice to learn every task, and every Oracle PPO run reaches a higher true return than every Proxy PPO run on both splits. The exploit survives the OOD shift: Proxy PPO's OOD hack rates are 75%, 90% and 93%.

Table 2: Final policies on 500 fresh layouts per split; mean over 10 runs with 95% t intervals.

Task	Policy	Success ↑	Hack rate ↓	True return J_t	Proxy return R_p
ID layouts					
ProxyFarming	Proxy PPO	0.11 [0.02, 0.20]	0.85 [0.76, 0.95]	-0.26 [-0.38, -0.14]	4.58 [3.79, 5.36]
	Oracle PPO	0.99 [0.98, 0.99]	0.00 [0.00, 0.00]	0.91 [0.90, 0.92]	0.93 [0.93, 0.94]
SensorTamper	Proxy PPO	0.00 [0.00, 0.00]	0.99 [0.98, 0.99]	-0.40 [-0.40, -0.39]	8.79 [8.76, 8.82]
	Oracle PPO	0.98 [0.98, 0.99]	0.00 [0.00, 0.00]	0.86 [0.86, 0.87]	0.86 [0.86, 0.87]
GemTimeout	Proxy PPO	0.06 [0.05, 0.07]	0.92 [0.91, 0.94]	-0.12 [-0.13, -0.11]	2.27 [2.22, 2.32]
	Oracle PPO	0.95 [0.93, 0.97]	0.00 [0.00, 0.00]	0.88 [0.86, 0.90]	0.91 [0.90, 0.93]
OOD layouts					
ProxyFarming	Proxy PPO	0.11 [0.03, 0.20]	0.75 [0.66, 0.83]	-0.25 [-0.37, -0.14]	3.87 [3.27, 4.47]
	Oracle PPO	0.93 [0.92, 0.94]	0.01 [0.01, 0.01]	0.83 [0.81, 0.84]	0.88 [0.86, 0.89]
SensorTamper	Proxy PPO	0.01 [0.01, 0.01]	0.90 [0.89, 0.92]	-0.39 [-0.39, -0.38]	6.66 [6.54, 6.79]
	Oracle PPO	0.97 [0.96, 0.97]	0.00 [0.00, 0.00]	0.84 [0.83, 0.85]	0.84 [0.83, 0.85]
GemTimeout	Proxy PPO	0.04 [0.03, 0.05]	0.93 [0.91, 0.95]	-0.17 [-0.18, -0.17]	3.07 [2.95, 3.19]
	Oracle PPO	0.95 [0.93, 0.97]	0.00 [0.00, 0.00]	0.88 [0.87, 0.90]	0.92 [0.91, 0.93]

How hacking emerges depends on the mechanism (Figure 2). In PROXYFARMING, Proxy PPO first learns the intended task: before a run's hack rate first reaches 50%, its success rate peaks at 97% on average (at least 96% in every run), nearly as high as Oracle PPO's. The policy then abandons the goal for the beacon. 9 of 10 runs cross a 50% hack rate, between 600k and 977k steps (median 752k); the remaining run had reached 49% when training ended. Once under way, a run's hack rate climbs from below 10% to above 75% within a median of 301k steps. Proxy return rises throughout, so the training signal gives no warning, and a snapshot taken before the switch would look aligned. In SENSORTAMPER, tampering comes first: the hack rate reaches 50% after a median of 225k steps, while the average run's success rate has not exceeded 3%, and the task is never learned afterwards. In GEMTIMEOUT, gem detours dominate from the first snapshot (76k steps), so the bias is acquired within the first few percent of training. The same proxy–true gap can thus look like the late reversal of a learned skill, a skill that is never acquired, or a bias acquired almost at once.

5.2 What the reward pays for does not predict what PPO learns

Figure 3 retrains Proxy PPO with the channel scaled by λ and compares it with the exact proxy-optimal policy, which we compute on a finer grid of scales by enumerating every reachable state of each of 100 ID layouts and solving the finite-horizon MDP under PPO's discount factor (Appendix B). At $\lambda = 0$ both behave as intended. The optimum starts hacking far below the default scale: on most layouts from $\lambda = 0.15$ in PROXYFARMING and $\lambda = 0.1$ and 0.1 in SENSORTAMPER and GEMTIMEOUT, and on every layout of every task from $\lambda = 0.2$. From there on, exploiting the channel is part of the proxy-optimal behavior on every layout, alongside the task in PROXYFARMING and SENSORTAMPER and instead of the deadline in GEMTIMEOUT.

PPO departs from this reference in both directions. In PROXYFARMING and GEMTIMEOUT, it *under-exploits*. At $\lambda = 0.25$ it hacks in 0% and 0% of episodes, and in PROXYFARMING still in only 1% at $\lambda = 0.5$, against 89% at $\lambda = 1$ (the $\lambda = 1$ points are the first 5 of the 10 main runs). Its hack rate first reaches one half at $\lambda = 1$ in PROXYFARMING and $\lambda = 0.5$ in GEMTIMEOUT, several times the scale at which the optimum hacks; at $\lambda = 0.5$ in GEMTIMEOUT, the 5 runs disagree, with hack rates from 0% to 80%. The exploit is not undiscovered at low scales: early policies step on the beacon and collect gems, and PPO trains this away in favor of the task. In PROXYFARMING at $\lambda = 1$ the switch to farming comes only after hundreds of thousands of steps of task mastery, so at lower scales it may come later than our budget; we do not test this. Either way, whether PPO hacks within a given budget is not predicted by whether the reward pays for hacking. This is the kind of optimizer-dependent threshold that Pan et al. [2022] report, here measured against an exact optimum. In SENSORTAMPER, PPO hacks at every positive scale we trained, so its threshold is not resolved by our grid.

In SENSORTAMPER and PROXYFARMING, where PPO does hack, it *over-commits*. At $\lambda = 0.25$, the proxy-optimal SENSORTAMPER policy tampers and then delivers the object, succeeding on 94%




Figure 3: Final ID hack and success rates of Proxy PPO as the corruption channel is scaled ($\lambda = 1$ is the default; 5 seeds per value, 95% t intervals), next to the exact proxy-optimal policy on 100 layouts, computed on a finer grid. Lines connect the scales at which each was measured; the axis is linear below 0.1 and logarithmic above. The dashed line is Oracle PPO's success rate.




Figure 4: Held-out hack-monitor AUC (logistic regression, leave-one-seed-out, 95% t intervals over held-out seeds) for each channel. Lines join each channel's AUC to its AUC within one Proxy PPO snapshot (open circles); diamonds are the best single feature (selected on training folds) and dashed lines the policy-identity baseline. Note the zoomed axis.

of layouts; PPO tampers in 99% of episodes and succeeds in 0%. At the default scale of PROXYFARMING, the optimum farms the beacon and then reaches the goal on 48% of layouts; PPO does so in only 2% of episodes (it succeeds in 7%, mostly without farming). In both cases PPO's hack is more harmful than the reward requires, so an analysis of the reward function alone would underestimate the harm of training on it. In GEMTIMEOUT, where every gem breaks the deadline, the optimum gives up the task on every layout and PPO, which does not always collect a gem, fails slightly less often.

Table 3: Hack monitors (logistic regression). Hack rates of the monitor datasets in parentheses. *Within snapshot*: mean AUC within Proxy PPO snapshots. †Inadmissible: the channel sees every field the label is computed from (the privileged channel is a positive control).

		Monitor AUC		Baselines		Gain over	Transfer	
Task	Channel	pooled	within snapshot	policy identity	single feature	identity	ID→OOD	early→late
ProxyFarming (24%)	behavior	0.981 [0.973, 0.989]	0.890	0.948	0.965	0.033 [0.020, 0.047]	0.962	0.943
	task	0.984 [0.976, 0.991]	0.901		0.965	0.036 [0.022, 0.050]	0.971	0.901
	privileged†	1.000 [1.000, 1.000]	1.000		0.997	0.052 [0.031, 0.073]	1.000	0.969
SensorTamper (45%)	behavior	0.998 [0.997, 0.999]	0.973	0.990	0.998	0.008 [0.005, 0.012]	0.997	1.000
	task	0.998 [0.997, 0.999]	0.969		0.998	0.008 [0.005, 0.012]	0.997	1.000
	privileged†	1.000 [0.999, 1.000]	0.998		1.000	0.010 [0.006, 0.014]	1.000	1.000
GemTimeout (45%)	behavior	0.993 [0.992, 0.994]	0.986	0.944	0.962	0.049 [0.037, 0.060]	0.989	0.998
	task	0.995 [0.994, 0.997]	0.984		0.970	0.051 [0.040, 0.063]	0.995	0.999
	privileged†	1.000 [1.000, 1.000]	1.000		1.000	0.056 [0.045, 0.067]	1.000	1.000

Table 4: Agents trained against the behavior monitor (ID layouts; mean over runs with 95% t intervals), and the monitor's recall on hacks before and after. *Unpenalized*: out-of-run recall on the final policies of the main experiment. *Penalized*: recall of the training monitor, over runs with at least 50 hacking episodes.

	Hack	Harmful	Flagged	Undetected	Monitor recall on hacks	
Task	rate	hack rate	rate	hack rate	unpenalized	penalized
ProxyFarming	0.01 [0.00, 0.01]	0.00 [0.00, 0.00]	0.03 [0.02, 0.03]	0.01 [0.00, 0.01]	0.97 [0.94, 1.00]	– (no run)
SensorTamper	0.19 [0.00, 0.71]	0.19 [0.00, 0.70]	0.05 [0.00, 0.20]	0.13 [0.00, 0.51]	1.00 [1.00, 1.00]	0.28 (1 run)
GemTimeout	0.65 [0.56, 0.75]	0.65 [0.56, 0.75]	0.01 [0.01, 0.01]	0.64 [0.55, 0.74]	0.97 [0.95, 1.00]	0.01 [0.01, 0.02] (5 runs)

5.3 Pooled monitor AUCs say little about monitorability

Hack monitors are trained on 4,000 ID episodes per task, of which 24% (PROXYFARMING), 45% (SENSORTAMPER) and 45% (GEMTIMEOUT) are hacks. Held-out AUCs are high on every channel (Figure 4, Table 3). The behavior monitor, which sees only positions and actions, reaches 0.981, 0.998 and 0.993. Read alone, these numbers say that hacking is easy to monitor from behavior.

Most of that AUC is available without looking at the episode. The policy-identity baseline, which knows only the method and snapshot that produced an episode, reaches 0.948, 0.990 and 0.944, because the pooled data mix policies that hack at very different rates: knowing only whether Proxy or Oracle PPO produced an episode already gives 0.818, 0.950 and 0.914, and the training stage adds the rest, most of it in PROXYFARMING, where hacking emerges late. The behavior monitor beats the baseline in every task, but only by 0.033 [0.020, 0.047], 0.008 [0.005, 0.012] and 0.049 [0.037, 0.060] (paired over held-out seeds). A pooled AUC therefore says little about whether a monitor reads behavior. The relevant number for a monitor deployed on one policy is the AUC among the episodes of a single Proxy PPO snapshot, where policy identity carries no information. It is 0.973 in SENSORTAMPER and 0.986 in GEMTIMEOUT, close to the pooled values, but 0.890 in PROXYFARMING, well below the pooled 0.981.

The single-feature baseline qualifies the result further. In SENSORTAMPER, the fraction of *interact* actions alone reaches 0.998: tampering requires pressing *interact*, an action the intended task never needs (the object is picked up by stepping onto it), and Proxy PPO presses it on most steps, so the result is flagged trivial. In PROXYFARMING and GEMTIMEOUT, the learned monitor adds 0.016 [0.011, 0.020] and 0.031 [0.026, 0.037] AUC over the best single feature. Seeing the goal (the task channel) changes little. The privileged channel, which can reconstruct the label, reaches 1.000, 1.000 and 1.000 and is flagged inadmissible, as it should be. Behavior monitors also transfer: trained on ID episodes, they score 0.962, 0.997 and 0.989 on the OOD episodes of held-out seeds, and trained on the first half of training, 0.943, 1.000 and 0.998 on the second half. Gradient-boosted trees and harmful-hack labels give the same picture (Appendix C).

5.4 Training against the monitor removes hacking in one task and hides it in another

Before it is used for training, the behavior monitor is a good detector: fitted on the other seeds, it flags 97%, 100% and 97% of the hacks of unpenalized final policies (Table 4). Figure 5 shows what happens when it becomes part of the reward. In PROXYFARMING, the penalty removes hacking:




Figure 5: Proxy PPO trained with a penalty of $\beta = 10$ times the behavior monitor's hack probability (5 seeds, ID snapshots; thin lines are individual runs). The dashed line is the hack rate of unpenalized Proxy PPO.

Table 5: How penalized agents evade the monitor. For the hacking episodes of the last monitored snapshot of unpenalized and penalized Proxy PPO (ID), the three behavior features that changed the monitor's mean logit most, their standard deviation in the monitor's training data, and each feature's signed share of the total change (negative: the feature moved towards looking like a hack). PROXYFARMING is omitted because its penalized agents produce almost no hacks.

		Mean over hacking episodes		SD in monitor	Share of the
Task	Behavior feature	unpenalized	penalized	training data	change in logit
SensorTamper (15 hacks, 1 run)	repeated actions	0.91	0.32	0.294	65%
	action entropy	0.23	0.77	0.268	-65%
	longest stay / length	0.89	0.25	0.408	26%
GemTimeout (66 hacks, 5 runs)	fraction of interact actions	0.00	0.50	0.013	91%
	distinct cells visited	0.84	0.41	0.266	44%
	episode length / step limit	0.62	0.94	0.320	-20%

penalized agents hack in 1% of episodes and succeed in 97%, close to Oracle PPO's 99%. In SENSORTAMPER, all but 1 of the 5 runs do the same, but that run tampers in 93% of episodes, of which the monitor flags 28%. In GEMTIMEOUT, all 5 runs keep hacking: the penalized agents hack in 65% of episodes, the monitor flags 1% of those hacks, and 64% of all episodes are hacks it misses. The agents have not stopped hacking; they have stopped looking like it. From the monitor's side, the outcomes look alike: it flags 3%, 5% and 1% of the penalized agents' episodes, and only the ground-truth labels show that a low flag rate means removal in PROXYFARMING and evasion in GEMTIMEOUT.

Because the monitor is linear, the drop in its score can be attributed to individual features (Table 5). In GEMTIMEOUT, the penalized agents' hacking episodes spend 50% of their steps on *interact*, which does nothing in this task, against 0% for unpenalized agents. In the monitor's training data this fraction hardly varied (standard deviation 0.013), so the small negative weight the monitor gave it, evaluated far outside the range it was fitted on, accounts for 91% of the drop in its logit. Honest and hacking episodes in the monitor's training data both almost never press *interact*, so the agents did not imitate honest play; they moved along a direction in which the monitor had almost no data and simply extrapolates. In SENSORTAMPER, the evading run presses *interact* on 35% of steps instead of 89% and moves in between (left on 34% and right on 23% of steps, against 3% and 3%), which breaks up the repeated actions and long stays that the monitor weights heavily and changes its mean logit by -7.47. These features are correlated, so how the change splits between them is less meaningful than in GEMTIMEOUT, where one feature dominates.

6 Evaluation Pitfalls We Found in Our Own Earlier Version

An earlier version of this benchmark, with fixed hand-designed layouts and a lighter evaluation pipeline, reported results that did not survive an adversarial audit of its own code. We list the failures because each one is easy to make in a small RL safety benchmark. The first four are now guarded by unit tests, and the fifth by a continuous-integration check.

1. **Repeated episodes counted as independent samples.** Deterministic dynamics, greedy actions and two fixed layouts per split meant that each "24-episode" evaluation contained exactly two distinct trajectories, each repeated twelve times. Every rate was therefore a multiple of $1/2$ per seed. *Now:* layouts are procedurally generated per episode, evaluation uses 500 fresh layouts per split, and a test asserts that evaluation layouts are distinct.
2. **A leakage screen that screened nothing.** Features were flagged as suspicious by matching tokens in their names; no feature name matched, so every channel passed. *Now:* channels are defined by the provenance of their features, provenance is enforced when features are computed (Section 4), and a privileged channel serves as a positive control that the screen must flag.
3. **A causal ablation that ablated the measurement.** Switching off the tampering effect also switched off the counter that defined the hack label, so hacking "disappeared" while the policy kept pressing the console on almost every step. *Now:* labels are computed from behavior and do not depend on whether the channel pays; a regression test presses the console with the channel switched off and requires the episode to be labelled a hack.
4. **Statistics of constant vectors.** A per-policy proxy–true correlation was computed over episodes that were all identical, and floating-point noise in the variance turned an undefined value into ± 1. *Now:* uncertainty is computed only over independent training runs, and the metric was dropped.
5. **Hand-copied numbers.** Some numbers in the earlier manuscript came from exploratory runs that the documented pipeline could not regenerate. *Now:* every experimental result and every configuration setting cited in the text is a macro written by `speclens.report` from the committed result files and configuration, the task definitions are tabulated from the environment code, and continuous integration regenerates the macros and tables and fails if they differ from the committed versions. The check cannot catch a number typed directly into the text, and the pilot observations in Appendix A are not regenerated.

None of these errors required unusual carelessness; each produced a clean-looking table. The common remedy was to write tests that try to break the evaluation rather than tests that confirm it runs.

7 Limitations

Scale and realism. The tasks are small gridworlds with hand-designed channels. They are model organisms: useful because the true objective is known exactly and the corruption channel can be switched off, not because they resemble the settings where reward hacking matters most. Claims transfer to frontier systems only as hypotheses to test there.

One algorithm, one architecture. Every agent is PPO with the same small CNN. Whether hacking emerges, and when, depends on the optimizer and on exploration; the dose–response thresholds we report are properties of this agent, not of the reward functions alone.

Design choices were calibrated. The network architecture, the evaluation mode (sampled rather than greedy actions) and the gem bonus of GEMTIMEOUT were chosen in single-seed pilot runs so that Oracle PPO learns every task within the budget and the default channel is exploited (Appendix A). That Proxy PPO underperforms Oracle PPO on J_t is therefore a sanity check of the design, not a finding; the dose–response experiment reports outcomes across magnitudes so that the calibration is visible rather than hidden.

Hand-crafted monitors. Our monitors are linear models and shallow trees over at most 23 hand-written trajectory features. Stronger monitors could do better, and monitors with access to an agent's internals or reasoning are out of scope. Hack labels count uses of the channel, not harm; we therefore also report harmful hacks (channel use without task success), and the label thresholds are task-specific.

Training against a monitor. Our monitor-penalty experiment uses one penalty weight, one monitor channel, a fixed linear monitor and 5 seeds per task. A monitor that is retrained as the agent changes, a nonlinear monitor, or a penalty that is annealed may behave differently, and with 5 seeds the fraction of runs that evade is only coarsely estimated.

The proxy optimum. The exact optimum is computed for PPO's discount factor on a sample of layouts. It describes what the reward asks for, not what any particular learner can represent or find; that gap is the point of the comparison.

8 Conclusion

We built three small model organisms of reward hacking in which the true objective is known exactly and the corruption channel can be scaled or switched off, and used them to measure when PPO exploits a misspecified reward, whether trajectory monitors detect it, and what happens when agents are trained against a monitor. Three lessons seem likely to carry over to larger systems, as hypotheses to test there.

The reward function does not determine the outcome. The exact optimum hacks from 0.1–0.15 times the default channel scale, while in PROXYFARMING and GEMTIMEOUT PPO hacks only at several times that scale, with runs that can disagree widely near its threshold, and where PPO hacks in PROXYFARMING and SENSORTAMPER, it is more harmful than the optimum. A reward specification is safe or unsafe only relative to the optimizer that will be run on it, across seeds.

Pooled monitor evaluations say little about monitorability. When the policies pooled in an evaluation hack at different rates (here mostly Proxy against Oracle PPO, and in PROXYFARMING also early against late snapshots), a monitor is rewarded for recognizing the policy rather than the behavior. A policy-identity baseline and the AUC within single policies separate the two, and they told apart two tasks in which behavior monitors work within a policy from one in which they are much weaker. We recommend reporting both.

A monitor's recall before it becomes a training signal says little about its recall afterwards. The same penalty removed hacking in one task and taught agents to evade the monitor in another, consistent with the obfuscation Baker et al. [2025] observe when optimizing against chain-of-thought monitors. Only the known true objective let us tell the two outcomes apart; in deployed systems, that is exactly what is missing.

The environments, the evaluation pipeline and all results are released. A full rerun takes about 16 CPU-hours, and the report regenerates every figure, table and number in this paper from the saved results in a few minutes.

References

Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. In *Advances in Neural Information Processing Systems*, volume 34, pages 29304–29320, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/f514cec81cb148559cf475e7426eed5e-Abstract.html.

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in AI safety, 2016. URL https://arxiv.org/abs/1606.06565.

Bowen Baker, Joost Huizinga, Leo Gao, Zehao Dou, Melody Y. Guan, Aleksander Madry, Wojciech Zaremba, Jakub Pachocki, and David Farhi. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation, 2025. URL https://arxiv.org/abs/2503.11926.

Karl Cobbe, Chris Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 2048–2056, 2020. URL https://proceedings.mlr.press/v119/cobbe20a.html.

Carson Denison, Monte MacDiarmid, Fazl Barez, David Duvenaud, Shauna Kravec, Samuel Marks, Nicholas Schiefer, Ryan Soklaski, Alex Tamkin, Jared Kaplan, Buck Shlegeris, Samuel R. Bowman, Ethan Perez, and Evan Hubinger. Sycophancy to subterfuge: Investigating reward-tampering in large language models, 2024. URL https://arxiv.org/abs/2406.10162.

Tom Everitt, Marcus Hutter, Ramana Kumar, and Victoria Krakovna. Reward tampering problems and solutions in reinforcement learning: A causal influence diagram perspective. *Synthese*, 198 (7):6435–6467, 2021. doi: 10.1007/s11229-021-03141-4. URL https://doi.org/10.1007/s11229-021-03141-4.

Leo Gao, John Schulman, and Jacob Hilton. Scaling laws for reward model overoptimization. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 10835–10866, 2023. URL https://proceedings.mlr.press/v202/gao23h.html.

Shengyi Huang, Rousslan Fernand Julien Dossa, Chang Ye, Jeff Braga, Dipam Chakraborty, Kinal Mehta, and João G. M. Araújo. CleanRL: High-quality single-file implementations of deep reinforcement learning algorithms. *Journal of Machine Learning Research*, 23(274):1–18, 2022. URL https://jmlr.org/papers/v23/21-1342.html.

Evan Hubinger, Nicholas Schiefer, Carson Denison, and Ethan Perez. Model organisms of misalignment: The case for a new pillar of alignment research. AI Alignment Forum, 2023. URL https://www.alignmentforum.org/posts/ChDH335ckdvpxXaXX.

Victoria Krakovna, Jonathan Uesato, Vladimir Mikulik, Matthew Rahtz, Tom Everitt, Ramana Kumar, Zac Kenton, Jan Leike, and Shane Legg. Specification gaming: The flip side of AI ingenuity. DeepMind blog, 2020. URL https://deepmind.google/discover/blog/specification-gaming-the-flip-side-of-ai-ingenuity/.

Lauro Langosco di Langosco, Jack Koch, Lee D. Sharkey, Jacob Pfau, and David Krueger. Goal misgeneralization in deep reinforcement learning. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 12004–12019, 2022. URL https://proceedings.mlr.press/v162/langosco22a.html.

Jan Leike, Miljan Martic, Victoria Krakovna, Pedro A. Ortega, Tom Everitt, Andrew Lefrancq, Laurent Orseau, and Shane Legg. AI safety gridworlds, 2017. URL https://arxiv.org/abs/1711.09883.

Monte MacDiarmid, Benjamin Wright, Jonathan Uesato, Joe Benton, Jon Kutasov, Sara Price, Naia Bouscal, Sam Bowman, Trenton Bricken, Alex Cloud, Carson Denison, Johannes Gasteiger, Ryan Greenblatt, Jan Leike, Jack Lindsey, Vlad Mikulik, Ethan Perez, Alex Rodrigues, Drake Thomas, Albert Webson, Daniel Ziegler, and Evan Hubinger. Natural emergent misalignment from reward hacking in production RL, 2025. URL https://arxiv.org/abs/2511.18397.

Andrew Y. Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. In *Proceedings of the Sixteenth International Conference on Machine Learning*, pages 278–287, 1999.

Ian Osband, Yotam Doron, Matteo Hessel, John Aslanides, Eren Sezener, Andre Saraiva, Katrina McKinney, Tor Lattimore, Csaba Szepesvári, Satinder Singh, Benjamin Van Roy, Richard S. Sutton, David Silver, and Hado van Hasselt. Behaviour suite for reinforcement learning. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rygf-kSYwH.

Alexander Pan, Kush Bhatia, and Jacob Steinhardt. The effects of reward misspecification: Mapping and mitigating misaligned models. In *International Conference on Learning Representations*, 2022. URL https://arxiv.org/abs/2201.03544.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. URL https://arxiv.org/abs/1707.06347.

Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. Defining and characterizing reward gaming. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/3d719fee332caa23d5038b8a90e81796-Abstract-Conference.html.

A Task and Training Details

Rewards. Table 6 gives the full proxy reward, true objective and success definition of each task, generated from the environment code. Layouts are sampled by rejection: start, goal and task objects are placed uniformly on distinct cells, walls are placed uniformly among the remaining cells subject to all objects being mutually reachable, and in PROXYFARMING and GEMTIMEOUT the goal is at least four steps from the start. In GEMTIMEOUT, gems are sampled only from reachable cells c with $d(\text{start}, c) + d(c, \text{goal}) >$ deadline, where d is the shortest-path distance around walls.

Table 6: Proxy reward, true objective and success definition of every task.

Task	Proxy reward R_p	True objective J_t	Success
ProxyFarming	-0.01 per step, +1 on reaching the goal, +0.2 per step spent on the beacon.	-0.01 per step, +1 on reaching the goal.	Goal reached before the step limit.
SensorTamper	-0.01 per step, +1 per delivery confirmation from the sensor, real or false.	-0.01 per step, +1 when the object is actually delivered.	Object picked up and carried to the target before the step limit.
GemTimeout	-0.01 per step, +1 on reaching the goal at any time, +0.6 per gem collected.	-0.01 per step, +1 on reaching the goal by the deadline (shortest path + 2 steps).	Goal reached by the deadline.

Hyperparameters. Table 7 lists every training, evaluation, sweep and monitor setting. All values are read from `configs/paper.yaml` and the environment code, except the Adam epsilon and the learning-rate annealing, which are defaults of the PPO implementation.

Table 7: Training and evaluation settings, identical for every task and method.

Setting	Value
total steps	1,500,000
n envs	16
rollout steps	128
epochs	4
minibatch size	512
learning rate	0.0003
adam eps	1e-05
anneal lr	yes
gamma	0.99
gae lambda	0.95
clip eps	0.2
value coef	0.5
entropy coef	0.01
max grad norm	0.5
hidden	256
channels	16
seeds (main / sweep)	10 / 5
policy snapshots per run	20
evaluation layouts per split	500
layouts per snapshot (training curves)	100
channel scales (sweep)	0, 0.25, 0.5, 1, 2
layouts for the exact proxy-optimal policy	100
channel scales (exact optimum)	0, 0.05, 0.1, 0.15, 0.2, 0.25, 0.5, 1, 2
monitor episodes per snapshot and split	20
monitored snapshots	every 2. of 20
monitor models	logistic, boosting
monitor penalty: channel, β, seeds	behavior, 10, 5
step limit per episode	40 (ProxyFarming), 40 (SensorTamper), 30 (GemTimeout)

Pilot runs and what they changed. Before the main experiment we ran single-seed pilots of Oracle and Proxy PPO on every task. They led to three changes, all made before any main-experiment run, and we list them because they are researcher degrees of freedom: (i) a multilayer perceptron over the flattened grid learned the two-stage SENSORTAMPER task much more slowly than a small CNN, so we use the CNN; (ii) deterministic (argmax) evaluation scored well below the same policies' behavior during training, so we evaluate the stochastic policy that PPO optimizes; and (iii) with a gem bonus of 0.3, Proxy PPO on GEMTIMEOUT learned the intended behavior and rarely collected gems, so the default bonus is 0.6. The pilot code is not part of the repository. The dose–response sweep revisits the gem bonus: at $\lambda = 0.5$ (a bonus of 0.3), the 5 runs hack in 0% to 80% of episodes, so the single pilot run was not representative of that bonus.

Compute and provenance. The 120 main and dose–response runs took 14.0 CPU-hours including evaluation and monitor rollouts, and the 15 monitor-penalty runs another 1.7, on a single 4-core machine with one core per run. Every training run records a fingerprint of the code, configuration and (for the monitor-penalty runs) the monitor it was produced with (`results/runs.csv` and `penalty_runs.csv`), and continuous integration fails if any committed run does not match the current code. Runs also record the commit, and whether `src/` had uncommitted edits, when they finished; some finished while the repository had uncommitted edits to analysis code that no training run imports, which the fingerprints confirm. Training is deterministic given a seed: when we retrained all 15 monitor-penalty runs in a fresh container to add monitor rollouts, we checked that every evaluation episode was reproduced exactly. Every figure and table, and every result and setting cited in the text, is rebuilt from the saved results in about two minutes with `python -m speclens.report`.

B The Exact Proxy-Optimal Policy

For one layout, the state of each task is the agent's cell, the time step and the task's own state: nothing in PROXYFARMING; whether the object is carried and how many steps remain until the console can confirm again in SENSORTAMPER; and the set of collected gems in GEMTIMEOUT. We enumerate every state reachable from the start by stepping the environment itself (not a reimplementation of it), recording each transition's reward with the channel at scale 1, and solve the finite-horizon MDP by backward induction over the time step for each channel scale, with the discount factor $\gamma = 0.99$ that PPO optimizes. The greedy policy, with ties broken by action order, is then rolled out in the environment to obtain its hack label, success and true return. Two tests check the solver. One replays this policy and requires its discounted proxy return to equal the solver's value of the start state on every task and split. The other compares the solver's value with an exhaustive search over every action sequence on short horizons, run on copies of the environment so that it does not depend on the solver's state definition; we checked that it fails when the console cooldown or the set of collected gems is removed from the state. The solved layouts, the first 100 ID evaluation layouts of each task, have 1,519–1,644 (PROXYFARMING), 3,515–6,127 (SENSORTAMPER) and 5,052–7,778 (GEMTIMEOUT) reachable states.

C Additional Results

Table 8: Dose–response: final ID hack and success rates of Proxy PPO when the corruption channel is scaled by λ (5 seeds per value), and of the exact proxy-optimal policy (100 layouts).

Task	Metric	Policy	$\lambda = 0$	$\lambda = 0.25$	$\lambda = 0.5$	$\lambda = 1$	$\lambda = 2$
ProxyFarming	hack rate	Proxy PPO	0.00	0.00	0.01	0.89	0.88
		proxy-optimal	0.00	1.00	1.00	1.00	1.00
	success	Proxy PPO	0.98	0.98	0.98	0.07	0.04
		proxy-optimal	1.00	1.00	0.95	0.48	0.20
SensorTamper	hack rate	Proxy PPO	0.00	0.99	0.99	0.99	0.90
		proxy-optimal	0.00	1.00	1.00	1.00	1.00
	success	Proxy PPO	0.98	0.00	0.00	0.00	0.01
		proxy-optimal	1.00	0.94	0.46	0.14	0.05
GemTimeout	hack rate	Proxy PPO	0.00	0.00	0.56	0.93	0.96
		proxy-optimal	0.00	1.00	1.00	1.00	1.00
	success	Proxy PPO	0.95	0.95	0.39	0.06	0.03
		proxy-optimal	1.00	0.00	0.00	0.00	0.00

Table 9: Hack monitors with gradient-boosted trees instead of logistic regression (compare Table 3).

		Monitor AUC		Baselines		Gain over	Transfer	
Task	Channel	pooled	within snapshot	policy identity	single feature	identity	ID→OOD	early→late
ProxyFarming (24%)	behavior	0.982 [0.973, 0.992]	0.898	0.948	0.965	0.035 [0.022, 0.047]	0.966	0.978
	task	0.985 [0.977, 0.992]	0.899		0.965	0.037 [0.022, 0.052]	0.974	0.982
	privileged†	1.000 [1.000, 1.000]	1.000		0.997	0.052 [0.031, 0.073]	1.000	1.000
SensorTamper (45%)	behavior	0.999 [0.998, 0.999]	0.970	0.990	0.998	0.009 [0.005, 0.013]	0.997	1.000
	task	0.999 [0.998, 0.999]	0.972		0.998	0.009 [0.005, 0.013]	0.997	1.000
	privileged†	1.000 [1.000, 1.000]	1.000		1.000	0.010 [0.006, 0.014]	1.000	1.000
GemTimeout (45%)	behavior	0.995 [0.993, 0.996]	0.982	0.944	0.962	0.051 [0.039, 0.062]	0.991	0.999
	task	0.996 [0.995, 0.997]	0.982		0.970	0.052 [0.040, 0.063]	0.993	1.000
	privileged†	1.000 [1.000, 1.000]	1.000		1.000	0.056 [0.045, 0.067]	1.000	1.000

Table 10: Monitors for *harmful* hacks (channel use without task success), logistic regression. †Inadmissible, as in Table 3.

		Monitor AUC		Baselines		Gain over	Transfer	
Task	Channel	pooled	within snapshot	policy identity	single feature	identity	ID→OOD	early→late
ProxyFarming (22%)	behavior	0.992 [0.991, 0.994]	0.936	0.963	0.977	0.029 [0.022, 0.037]	0.980	0.945
	task	0.995 [0.993, 0.996]	0.954		0.984	0.032 [0.024, 0.039]	0.988	0.876
	privileged†	1.000 [1.000, 1.000]	0.999		0.994	0.037 [0.029, 0.045]	0.999	0.942
SensorTamper (45%)	behavior	0.998 [0.997, 0.999]	0.973	0.990	0.998	0.008 [0.005, 0.012]	0.997	1.000
	task	0.998 [0.997, 0.999]	0.970		0.998	0.008 [0.005, 0.012]	0.998	1.000
	privileged	1.000 [0.999, 1.000]	0.998		1.000	0.010 [0.006, 0.014]	1.000	1.000
GemTimeout (45%)	behavior	0.993 [0.992, 0.994]	0.986	0.944	0.962	0.049 [0.037, 0.060]	0.989	0.998
	task	0.995 [0.994, 0.997]	0.984		0.970	0.051 [0.040, 0.063]	0.995	0.999
	privileged	1.000 [1.000, 1.000]	1.000		1.000	0.056 [0.045, 0.067]	1.000	1.000

Table 11: Monitors for task *failure*, logistic regression. Failure is nearly determined by episode length in PROXYFARMING and SENSORTAMPER, which the behavior channel sees; this table is a sanity check of the triviality flag. †Inadmissible, as in Table 3.

		Monitor AUC		Baselines		Gain over	Transfer	
Task	Channel	pooled	within snapshot	policy identity	single feature	identity	ID→OOD	early→late
ProxyFarming (25%)	behavior	1.000 [0.999, 1.000]	1.000	0.953	0.999	0.047 [0.030, 0.063]	0.999	0.999
	task†	1.000 [1.000, 1.000]	1.000		1.000	0.047 [0.031, 0.063]	1.000	1.000
	privileged†	1.000 [1.000, 1.000]	1.000		1.000	0.047 [0.031, 0.063]	1.000	0.939
SensorTamper (56%)	behavior	0.999 [0.999, 1.000]	0.923	0.985	0.999	0.015 [0.009, 0.020]	1.000	1.000
	task	1.000 [1.000, 1.000]	0.995		0.999	0.015 [0.009, 0.021]	1.000	1.000
	privileged	1.000 [1.000, 1.000]	0.995		0.999	0.015 [0.009, 0.021]	1.000	1.000
GemTimeout (58%)	behavior	1.000 [1.000, 1.000]	1.000	0.913	0.997	0.087 [0.072, 0.102]	1.000	1.000
	task	1.000 [1.000, 1.000]	1.000		0.998	0.087 [0.072, 0.102]	1.000	1.000
	privileged	1.000 [1.000, 1.000]	1.000		0.998	0.087 [0.072, 0.102]	1.000	1.000