

Description Editorial Solutions Submissions

2756. Query Batching Premium

Solved 🟢

Hard

Batching multiple small queries into a single large query can be a useful optimization. Write a class `QueryBatcher` that implements this functionality.

The constructor should accept two parameters:

- An asynchronous function `queryMultiple` which accepts an array of string keys `input`. It will resolve with an array of values that is the same length as the input array. Each index corresponds to the value associated with `input[i]`. You can assume the promise will never reject.
- A throttle time in milliseconds `t`.

The class has a single method.

- `async getValue(key)`. Accepts a single string key and resolves with a single string value. The keys passed to this function should eventually get passed to the `queryMultiple` function. `queryMultiple` should never be called consecutively within `t` milliseconds. The first time `getValue` is called, `queryMultiple` should immediately be called with that single key. If after `t` milliseconds, `getValue` had been called again, all the passed keys should be passed to `queryMultiple` and ultimately returned. You can assume every key passed to this method is unique.

The following diagram illustrates how the throttling algorithm works. Each rectangle represents 100ms. The throttle time is 400ms.

Input Events



Throttled Events



Example 1:

Input:

```
queryMultiple = async function(keys) {
  return keys.map(key => key + '!');
}
t = 100
calls = [
  {"key": "a", "time": 10},
  {"key": "b", "time": 20},
  {"key": "c", "time": 30}
]
```

Output:

```
[
  {"resolved": "a!", "time": 10},
  {"resolved": "b!", "time": 110},
  {"resolved": "c!", "time": 110}
]
```

Explanation:

```
const batcher = new QueryBatcher(queryMultiple, 100);
setTimeout(() => batcher.getValue('a'), 10); // "a!" at t=10ms
setTimeout(() => batcher.getValue('b'), 20); // "b!" at t=110ms
setTimeout(() => batcher.getValue('c'), 30); // "c!" at t=110ms
```

`queryMultiple` simply adds an "!" to the key
At t=10ms, `getValue('a')` is called, `queryMultiple(['a'])` is immediately called and the result is immediately returned.
At t=20ms, `getValue('b')` is called but the query is queued
At t=30ms, `getValue('c')` is called but the query is queued.
At t=110ms, `queryMultiple(['a', 'b'])` is called and the results are immediately returned.

Example 2:

Input:

```
queryMultiple = async function(keys) {
  await new Promise(res => setTimeout(res, 100));
  return keys.map(key => key + '!');
}
t = 100
calls = [
  {"key": "a", "time": 10},
  {"key": "b", "time": 20},
  {"key": "c", "time": 30}
]
```

Output:

```
[
  {"resolved": "a!", "time": 110},
  {"resolved": "b!", "time": 210},
  {"resolved": "c!", "time": 210}
]
```

Explanation:

This example is the same as example 1 except there is a 100ms delay in `queryMultiple`. The results are the same except the promises resolve 100ms later.

Example 3:

Input:

```
queryMultiple = async function(keys) {
  await new Promise(res => setTimeout(res, keys.length * 100));
  return keys.map(key => key + '!');
}
t = 100
calls = [
  {"key": "a", "time": 10},
  {"key": "b", "time": 20},
  {"key": "c", "time": 30},
  {"key": "d", "time": 40},
  {"key": "e", "time": 250},
  {"key": "f", "time": 300}
]
```

Output:

```
[
  {"resolved": "a!", "time": 110},
  {"resolved": "e!", "time": 350},
  {"resolved": "b!", "time": 410},
  {"resolved": "c!", "time": 410},
  {"resolved": "d!", "time": 410},
  {"resolved": "f!", "time": 450}
]
```

Explanation:

`queryMultiple(['a'])` is called at t=10ms, it is resolved at t=110ms
`queryMultiple(['b', 'c', 'd'])` is called at t=110ms, it is resolved at 410ms
`queryMultiple(['e'])` is called at t=250ms, it is resolved at 350ms
`queryMultiple(['f'])` is called at t=350ms, it is resolved at 450ms

Constraints:

</> Code

JavaScript • Auto

```
1 /**
2  * @param {Function} queryMultiple
3  * @param {number} t
4  * @return {void}
5  */
6  var QueryBatcher = function(queryMultiple, t) {
7
8      this.t = t;
9      this.qmt = 0;
10     this.queries = [];
11
12     this.queryMultiple = (...args) => {
13         this.qmt = Date.now()
14         return queryMultiple(...args);
15     };
16
17 };
18
19 /**
20  * @param {string} key
21  * @return {Promise<string>}
22  */
23  QueryBatcher.prototype.getValue = async function(key) {
24
25     const elapsed = Date.now() - this.qmt
26     if (elapsed > this.t) {
27         return (await this.queryMultiple([key]))[0]
28     }
29
30     return new Promise(resolve => {
31         if (this.queries.push({ key, resolve }) === 1) {
32             setTimeout(async () => {
33                 const queries = this.queries
34                 this.queries = []
35                 const values = await this.queryMultiple(queries.map(query => query.key))
36                 queries.forEach(({ resolve }, i) => resolve(values[i]))
37             }, this.t - elapsed)
38         }
39     });
40 }
```

🔄 Saved

Ln 23, Col 56

- `0 <= t <= 1000`
- `0 <= calls.length <= 10`
- `1 <= key.length <= 100`
- All keys are unique

Seen this question in a real interview before? 1/5

Yes No

Accepted 254 | Submissions 415 | Acceptance Rate 61.2%

Discussion (0)

Copyright © 2024 LeetCode All rights reserved

12 0

Testcase Test Result