

Problem List

RunSubmit

882

DescriptionEditorialSolutionsSubmissions

2776. Convert Callback Based Function to Promise Based Function

Solved

Premium

Medium

Write a function that accepts another function `fn` and converts the callback-based function into a promise-based function.

The function `fn` takes a callback as its first argument, along with any additional arguments `args` passed as separate inputs.

The `promisify` function returns a new function that should return a promise. The promise should resolve with the argument passed as the first parameter of the callback when the callback is invoked without error, and reject with the error when the callback is called with an error as the second argument.

The following is an example of a function that could be passed into `promisify`.

```
function sum(callback, a, b) {
  if (a < 0 || b < 0) {
    const err = Error('a and b must be positive');
    callback(undefined, err);
  } else {
    callback(a + b);
  }
}
```

This is the equivalent code based on promises:

```
async function sum(a, b) {
  if (a < 0 || b < 0) {
    throw Error('a and b must be positive');
  } else {
    return a + b;
  }
}
```

Example 1:

Input:

```
fn = (callback, a, b, c) => {
  callback(a * b * c);
}
args = [1, 2, 3]
```

Output: {"resolved": 6}

Explanation:

```
const asyncFunc = promisify(fn);
asyncFunc(1, 2, 3).then(console.log); // 6
```

fn is called with a callback as the first argument and args as the rest. The promise based version of fn resolves a value of 6 when called with (1, 2, 3).

Example 2:

Input:

```
fn = (callback, a, b, c) => {
  callback(a * b * c, "Promise Rejected");
}
args = [4, 5, 6]
```

Output: {"rejected": "Promise Rejected"}

Explanation:

```
const asyncFunc = promisify(fn);
asyncFunc(4, 5, 6).catch(console.log); // "Promise Rejected"
```

fn is called with a callback as the first argument and args as the rest. As the second argument, the callback accepts an error message, so when fn is called, the promise is rejected with a error message provided in the callback. Note that it did not matter what was passed as the first argument into the callback.

Constraints:

- `1 <= args.length <= 100`
- `0 <= args[i] <= 104`

Seen this question in a real interview before? 1/5

Yes

No

Accepted 563 | Submissions 615 | Acceptance Rate 91.5%

Discussion (2)

Copyright © 2024 LeetCode All rights reserved

</> Code

TypeScriptAuto

```
1 type CallbackFn = (
2   next: {data: number, error: string} => void,
3   ...args: number[]
4 ) => void
5 type Promified = (...args: number[]) => Promise<number>
6
7 function promisify(fn: CallbackFn): Promified {
8
9   return async (...args) => new Promise((resolve, reject) => {
10     const callback = (data: number, err: string | Error) => {
11       if (err) {
12         reject(err);
13       } else {
14         resolve(data);
15       }
16     };
17     return fn(callback, ...args);
18   });
19 };
20
21 /**
22  * const asyncFunc = promisify(callback => callback(42));
23  * asyncFunc().then(console.log); // 42
24  */
```

SavedLn 17, Col 38

TestcaseTest Result

AcceptedRuntime: 54 ms

Case 1

Case 2

Input

(callback, a, b, c) => { callback(a \* b \* c) }

152

[1, 2, 3]