```
♦ E Problem List 〈 > 💢
                                                                                                                                       © ► Run 	 Submit 	 □
🖪 Description | 🛄 Editorial | 🚨 Solutions | 🤊 Submissions
                                                                                                                                                 TypeScript ∨ • Auto
2691. Immutability Helper Premium
 Hard ♥ Hint
Creating clones of immutable objects with minor alterations can be a tedious process. Write a class ImmutableHelper that serves as
a tool to help with this requirement. The constructor accepts an immutable object obj which will be a JSON object or array.
The class has a single method produce which accepts a function mutator. The function returns a new object which is similar to the
original except it has those mutations applied.
                                                                                                                                                   11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
 mutator accepts a proxied version of obj. A user of this function can (appear to) mutate this object, but the original
object obj should not actually be effected.
                                                                                                                                                            return this.assemble(draft);
For example, a user could write code like this:
  const originalObj = {"x": 5};
const helper = new ImmutableHelper(originalObj);
const newObj = helper.produce((proxy) => {
    proxy.x = proxy.x + 1;
});
   console.log(originalObj); // {"x": 5}
console.log(newObj); // {"x": 6}
Properties of the mutator function:
• It will always return undefined.

    It will never access keys that don't exist.

. It will never delete keys (delete obi.key)
                                                                                                                                                                  return true;

    It will never call methods on a proxied object (push, shift, etc).

• It will never set keys to objects (proxy.x = {})
Note on how the solution will be tested: the solution validator will only analyze differences between what was returned and the
original obj. Doing a full comparison would be too computationally expensive. Also, any mutations to the original object will result
in a wrong answer
                                                                                                                                                 ☑ Testcase 🔝 Test Result
                                                                                                                                                  Accepted Runtime: 80 ms
Example 1:
   Input:
   Input:
obj = {"val": 10},
mutators = [
    proxy => { proxy.val += 1; },
    proxy => { proxy.val -= 1; }
   Output:
     {"val": 11},
{"val": 9}
   Explanation:
const helper = new ImmutableHelper({val: 10});
helper.produce(proxy => { proxy.val += 1; }); // { "val": 11 }
helper.produce(proxy => { proxy.val -= 1; }); // { "val": 9 }
   Input:
   proxy.arr[0] = 5;
proxy.newVal = proxy.arr[0] + proxy.arr[1];
   Output:
      {"arr": [5, 2, 3], "newVal": 7 }
   Explanation: Two edits were made to the original array. The first element in the array was to
   set 5. Then a new key was added with a value of 7.
 Example 3:
   Input:
   Input:

obj = {"obj": {"val": {"x": 10, "y": 20}}}

mutators = [

proxy => {
         let data = proxy.obj.val;
let temp = data.x;
data.x = data.y;
         data.y = temp;
   Output:
      {"obj": {"val": {"x": 20, "y": 10}}}
   Explanation: The values of "x" and "y" were swapped.
• [2 \le JSON.stringify(obj).length <= 4 * 10^5]

    mutators is an array of functions

• total calls to produce() < 105
```

```
Accepted 173 | Submissions 434 | Acceptance Rate 39.9%
```

Seen this question in a real interview before? 1/5

O Hint 1 O Hint 2 O Hint 3

₩ Similar Questions O Discussion (0)

```
E □ () □ ±
1 type InputObj = Record<any, any> | Array<any>;
2 type Mutations = Map<atring | symbol | number, unknown>;
3 type Nested = Map<atring | symbol | number, any>;
4 type OraffState = [Nested, Mutations, InputObj];
              constructor(private readonly obj: InputObj) {}
           public produce(mutator: (obj: any) => void): any {
  const draft = this.createDraft(this.obj);
  mutator(draft);
             private draftStates = new WeakMap<object, DraftState>();
           private createBraft = (obj: any): InputObj => {
    // Mutated values
    const mutations: Mutations = new Map();
    // Nested darfst for nested objects
    const nested = new Map(string | symbol | number, any>();
    const draft = new Proxy(obj, {
    set: (_, p, v) => {
        mutations.set(p, v);
    if (mutations.set(p) == obj[p]) {
        // remove useless mutation
        mutations.delete(p);
    }
}
```

28 😥 🍐 2 💽

Copyright © 2024 LeetCode All rights reserved

159 P D 0 1 ☆ C 3

• Case 1 • Case 2 • Case 3