

Module 36

Partha Pratin Das

Objective & Outline

Exception Fundamental

Types of Exceptions

Exceptions in

C Language Features

RV & Param Local goto

C Standard Library Support

Termination

Conditional Termination

Signals

Shortcomings

Summary

Module 36: Programming C++

Exceptions (Error handling in C): Part 1

Partha Pratim Das

Department of Computer Science and Engineering Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ernet.in

Tanwi Mallick Srijoni Majumdar Himadri B G S Bhuyan



Module Objectives

Module 36

Partha Pratin Das

Objective & Outline

Exception
Fundamentals

Types of Exceptions

Exceptions i

Features
RV & Params
Local goto
C Standard
Library Support
Global Variabl

Terminatio Conditiona

Signals

Shortcoming

Summary

Understand the Error handling in C



Module Outline

Module 36

Partha Pratii Das

Objective & Outline

Fundamentals

Types of Exceptions Exception Stages

Exceptions in C

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal

Conditional Termination Non-Local go Signals Shortcomings

Summar

- Exception Fundamentals
 - Types of Exceptions
 - Exception Stages
- Exceptions in C
 - C Language Features
 - Return value & parameters
 - Local goto
 - C Standard Library Support
 - Global variables
 - Abnormal termination
 - Conditional termination
 - Non-local goto
 - Signal
 - Shortcomings
- Exceptions in C++
 - Exception Scope (try)
 - Exception Arguments (catch)
 - Exception Matching
 - Exception Raise (throw)
- Advantages
 NPTEL MOOCs Programming in C++



What are Exceptions?

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stages

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variable
Abnormal
Termination
Conditional
Termination
Non-Local goto
Signals

- Conditions that arise
 - Infrequently and Unexpectedly
 - Generally betray a Program Error
 - Require a considered Programmatic Response
 - Run-time Anomalies yes, but not necessarily
- Leading to
 - Crippling the Program
 - May pull the entire System down
 - Defensive Technique
 - Crashing Exceptions verses Tangled Design and Code



Exception Causes

Module 36

Partha Pratin Das

Objective & Outline

Exception Fundamentals

Exceptions
Exception Stages

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variables

Abnormal Termination Conditional Termination Non-Local goto Signals

Summar

Unexpected Systems State

- Exhaustion of Resources
 - Low Free Store Memory
 - Low Disk Space
- Pushing to a Full Stack
- External Events
 - Ĉ
 - Socket Event
- Logical Errors
 - Pop from an Empty Stack
 - Resource Errors like Memory Read/Write
- Run time Errors
 - Arithmetic Overflow / Underflow
 - Out of Range
- Undefined Operation
- Division by Zero NPTEL MOOCs Programming in C++



Exception Handling?

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variables
Abnormal
Termination
Conditional
Termination
Non-Local goto
Signals
Shortcomings

 Exception Handling is a mechanism that separates the detection and handling of circumstantial Exceptional Flow from Normal Flow

- Current state saved in a pre-defined location
- Execution switched to a pre-defined handler

Exceptions are C++'s means of separating error reporting from error handling

Bjarne Stroustrup



Types of Exceptions

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions i

C Standard Library Suppor Global Variab Abnormal Termination Conditional Termination Non-Local go Signals Shortcomings

Asynchronous Exceptions:

- Exceptions that come Unexpectedly
- Example an Interrupt in a Program
- Takes control away from the Executing Thread context to a context that is different from that which caused the exception

Synchronous Exceptions:

- Planned Exceptions
- Handled in an organized manner
- The most common type of Synchronous Exception is implemented as a throw



Exception Stages

Module 36

Partha Pratir Das

Objective Outline

Fundamentals
Types of
Exceptions
Exception Stages

Exceptions i

reatures
RV & Params
Local goto
C Standard
Library Support
Global Variable
Abnormal
Termination
Conditional
Termination
Non-Local got
Signals
Shortcomings

- Error Incidence
 - Synchronous (S/W) Logical Error
 - Asynchronous (H/W) Interrupt (S/W Interrupt)
- 2 Create Object & Raise Exception
 - An Exception Object can be of any Complete Type
 - An int to a full blown C++ class object
- Oetect Exception
 - Polling Software Tests
 - Notification Control (Stack) Adjustments
- 4 Handle Exception
 - Ignore: hope someone else handles it, that is, Do Not Catch
 - Act: but allow others to handle it afterwards, that is, Catch, Handle and Re-Throw
 - Own: take complete ownership, that is, Catch and Handle
- **Solution Solution Solution Solution**
 - Continue Execution: If handled inside the program
 - Abort Execution: If handled outside the program



Exception Stages

Module 36

Partha Pratir Das

Objective & Outline

Fundamentals

Types of

Exceptions
Exception Stages

Exceptions i C

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination Conditional Termination Non-Local goto Signals

```
int f() {
    int error:
    /* ... */
    if (error) /* Stage 1: error occurred */
        return -1; /* Stage 2: generate exception object */
    /* ... */
}
int main(void) {
    if (f() != 0) /* Stage 3: detect exception */
        /* Stage 4: handle exception */
    /* Stage 5: recover */
}
```



Support for Exceptions in C

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions in C

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal

Conditional Termination Non-Local go

Non-Local go Signals Shortcomings

Summary

Language Features

- Return Value & Parameters
- Local goto
- Standard Library Support
 - Global Variables
 - Abnormal Termination
 - Conditional Termination
 - Non-Local goto
 - Signals



Return Value & Parameters

Module 36

Partha Pratir Das

Objective & Outline

Fundamentals
Types of
Exceptions
Exception Stages

Exceptions in C

C Language Features RV & Params

C Standard Library Support Global Variables Abnormal

Conditional Termination Non-Local got Signals Function Return Value Mechanism

- Created by the Callee as Temporary Objects
- Passed onto the Caller
- Caller checks for Error Conditions
- Return Values can be ignored and lost
- Return Values are temporary
- Function (output) Parameter Mechanism
 - Outbound Parameters, bound to arguments, offer multiple logical Return Values



Example: Return Value & Parameters

Module 36

Partha Pratin Das

Objective & Outline

Exception Fundamentals

Exceptions
Exception Stages

Exceptions in C

C Language

RV & Params Local goto C Standard Library Support Global Variables

Abnormal Termination Conditional Termination

Non-Local gote Signals

Summary

```
int Push(int i) {
    if (top_ == size-1) // Incidence
        return 0; // Raise
    else
        stack_[++top_] = i;
    return 1;
}
int main() {
    int x:
    // ...
    if (!Push(x)) // Detect {
        // Handling
    // Recovery
}
```



Local goto

Module 36

Partha Pratir Das

Objective & Outline

Fundamentals
Types of
Exceptions

Exceptions in

C Language Features RV & Params Local goto C Standard Library Support Global Variable Abnormal Termination Conditional Local goto Mechanism

- (At Source) Escapes: Gets Control out of a Deep Nested Loop
- (At Destination) Refactors: Actions from Multiple Points of Error Inception
- A group of C Features
 - goto Label;
 - break; & continue;
 - default switch case



Module 36

Partha Pratir Das

Objective & Outline

Fundamentals
Types of
Exceptions

Exceptions in

C Language Features RV & Params Local goto C Standard Library Support Global Variable

Abnormal Termination Conditional Termination Non-Local goto Signals Shortcomings

```
_PHNDLR _cdecl signal(int signum, _PHNDLR sigact)
{ // Lifted from VC98\CRT\SRC\WINSIG.C
        /* Check for sigact support */
        if ((sigact == ...)) goto sigreterror;
        /* Not exceptions in the host OS. */
        if ((signum == ...) { ... goto sigreterror; }
    else { ... goto sigretok; }
        /* Exceptions in the host OS. */
        if ((signum ...)) goto sigreterror;
. . .
sigretok:
        return(oldsigact);
sigreterror:
        errno = EINVAL:
        return(SIG ERR):
}
```



PHNDLR cdecl signal (int signum, PHNDLR sigact)

if ((sigact == ...)) goto sigreterror;
/* Not exceptions in the host OS. */

if ((signum == ...) { ... goto sigreterror; }

else { ... goto sigretok; }

return (oldsigact);

errno = EINVAL;
return(SIG ERR);

/* Exceptions in the host OS. */
if ((signum ...)) goto sigreterror;

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Exceptions

Exception Stage

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variables

Conditional Termination Non-Local go

Signals
Shortcomings

NPTEL MOOCs Programming in C++

sigretok:

sigreterror:



Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Exceptions

Exception Stage

Exceptions in C

RV & Params
Local goto
C Standard
Library Support
Global Variables

Abnormal Termination Conditional Termination

Non-Local got

Summary

```
PHNDLR cdecl signal (int signum, PHNDLR sigact)
 // Lifted from VC98\CRT\SRC\WINSIG.C
        /* Check for sigact support */
        if ( (sigact == ...) ) goto sigreterror;
        /* Not exceptions in the host OS. */
        if ( (signum == ... ) { ... goto sigreterror; }
       else { ... goto sigretok; }
        /* Exceptions in the host OS. */
        if ( (signum ...) ) goto sigreterror;
sigretok:
        return (oldsigact);
sigreterror:
        errno = EINVAL:
        return (SIG ERR);
```



Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Exceptions

Exception Stage

Exceptions in C

RV & Params
Local goto
C Standard
Library Support
Global Variables

Abnormal Termination Conditional Termination

Non-Local got Signals

Summary

```
cdecl signal (int signum, PHNDLR sigact)
{ // Lifted from VC98\CRT\SRC\WINSIG.C
        /* Check for sigact support */
        if ( (sigact == ...) ) goto sigreterror;
        /* Not exceptions in the host OS. */
        if ( (signum == ... ) { ... goto sigreterror; }
       else { ... goto sigretok; }
        /* Exceptions in the host OS. */
             (signum ...) goto sigreterror;
sigretok:
        return (oldsigact);
sigreterror:
        errno = EINVAL;
        return (SIG ERR);
```



Global Variables

Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stages

Exceptions in C

RV & Params
Local goto
C Standard

Global Variables
Abnormal
Termination

Non-Local go Signals

Shortcomings

Summa

- GV Mechanism
 - Use a designated Global Error Variable
 - Set it on Error
 - Poll / Check it for Detection
- Standard Library GV Mechanism
 - < <errno.h > / <cerrno>



Example: Global Variables

```
Module 36
```

Global Variables

```
#include <errno.h>
#include <math.h>
#include <stdio.h>
int main() {
    double x, y, result;
    /*... somehow set 'x' and 'y'
    errno = 0;
    result = pow (x, y);
    if (errno == EDOM)
        printf("Domain error on x/y pair \n");
    else if (errno == ERANGE)
        printf("range error in result \n");
    else
        printf("x to the y = %d \n", (int) result);
    return 0;
}
```



Abnormal Termination

Module 36

Partha Pratii Das

Objective of Outline

Exception Fundamentals

Types of Exceptions
Exception Stages

Exceptions in C.

RV & Params
Local goto
C Standard
Library Support
Global Variable
Abnormal
Termination
Conditional
Termination
Non-Local got
Signals
Shortcomings

- Program Halting Functions provided by
 - o <stdlib.h> / <cstdlib>
- abort()
 - Catastrophic Program Failure
- exit()
 - Code Clean up via atexit() Registrations
- atexit()
 - Handlers called in reverse order of their Registrations



Example: Abnormal Termination

```
#include<stdio.h>
Module 36
            #include<stdlib.h>
             static void atexit_handler_1(void) {
                 printf("within 'atexit handler 1' \n"):
             }
            static void atexit handler 2(void) {
                printf("within 'atexit_handler_2' \n");
             }
             int main(){
                 atexit(atexit_handler_1);
                 atexit(atexit handler 2):
                 exit(EXIT_SUCCESS);
                 printf("This line should never appear \n");
Abnormal
                return 0:
Termination
             /* On Execution Output: within 'atexit_handler_2'
                                      within 'atexit handler 1'
                and returns a success code to calling environment */
```

NPTEL MOOCs Programming in C++



Conditional Termination

Module 36

Partha Pratin Das

Objective of Outline

Fundamentals
Types of
Exceptions
Exception Stages

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variable
Abnormal
Termination
Conditional
Termination
Non-Local goto

- Diagnostic ASSERT macro defined in
 - <assert.h> / <cassert>
- Assertions valid when NDEBUG macro is not defined (debug build is done)
- Assert calls internal function, reports the source file details and then Terminates



Example: Conditional Termination

Module 36

Partha Pratir Das

Objective of Outline

Exception Fundamental

Exceptions
Exception Stage

Exceptions II

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination

Termination

Non-Local goto
Signals

Shortcomings

```
/* Debug version */
//#define NDEBUG
#include <cassert>
#include <cstdlib>
#include <cstdio>
using namespace std:
int main() {
   int i = 0:
    assert(++i == 0): // Assert 0 here
    printf(" i is %d \n", i);
   return 0;
/* When run - Asserts
void _assert(int test, char const * test_image,
    char const * file, int line) {
    if (!test){
        printf("assertion failed: %s , file %s , line %d\n",
            test image, file, line):
        abort();
```



Module 36

Example: Conditional Termination

o 6 6 6 76 1 16 16 D:\ My Courses\Software Engineering [CS20006]\2016.H1.Sp... Assertion failed: ++i == 0, file d:_my courses\software engineering [cs20006]\2 15% Stack Frame: main 16.hl.spring\codes\moocs - programming in c++\module 36\assertion.cpp, line 10 Set.h Template Ptr Ref.cpp Exception bas Microsoft Visual C++ Runtime Library Debug Error! Program: ...1.Spring\Codes\MOOCs - Programming in C++\Debug\Module 36.exe R6010 return 0; - abort() has been called /* When run vields 'i' is 0 (Press Retry to debug the application) -------------Abort Retry Ignore



Example: Conditional Termination

Module 36

Partha Pratin Das

Objective Outline

Exception Fundamental

Exception Stage

Exceptions ii

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination

Conditional Termination Non-Local goto Signals Shortcomings /* Release version */ #define NDEBUG #include <cassert> #include <cstdlib> #include <cstdio> using namespace std: int main(){ int i = 0: assert(++i == 0): // Assert 0 here printf(" i is %d \n", i); return 0; /* When run vields 'i' is 0 */ void _assert(int test, char const * test_image, char const * file, int line) { if (!test){ printf("assertion failed: %s , file %s , line %d\n", test image, file, line): abort();



Non-Local goto

Module 36

Partha Pratii Das

Objective & Outline

Fundamental

Exceptions
Exception Stage

Exceptions in C

RV & Params
Local goto
C Standard
Library Support
Global Variables
Abnormal
Termination
Conditional
Termination
Non-Local goto
Signals
Shortcomings

- setjmp() and longjmp() functions provided in <setjmp.h> Header along with collateral type jmp_buf
- setjmp(jmp_buf)
 - Sets the Jump point filling up the jmp_buf object with the current program context
- longjmp(jmp_buf, int)
 - \bullet Effects a Jump to the context of the ${\tt jmp_buf}$ object
 - Control return to setjmp call last called on jmp_buf



Example: Non-Local goto: The Dynamics

Module 36

Partha Pratin Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions in C

C Language Features RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination

Non-Local goto Signals

Summary

```
Caller
```

er

```
void f() {
    A a;
    if (setjmp(jbuf) == 0)
    {
        B b;
        g();
        h();
    }
    else {
        cout << ex.what();
    }
    return ;
}</pre>
```

Callee

```
jmp_buf jbuf;

void g(){
    A a;
    UsrExcp ex ("From g()");

    longjmp(jbuf, 1);

    return;
}
```



Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variables

Abnormal Termination Conditional

Non-Local goto Signals

-

```
void f() {
       A a:
        if (setjmp(jbuf) == 0)
                                           jmp buf jbuf;
                                         void g()
                B b;
                a();
               h();
                                               A a;
                                               UsrExcp ex("From q()");
       else {
                cout <<
                                               longjmp(jbuf, 1);
                ex.what();
                                               return:
       return;
```

• g() called



Module 36

Partha Pratir Das

Objective & Outline

Exception Fundamentals

Types of Exceptions Exception Stage

Exceptions in C

Features
RV & Params
Local goto
C Standard
Library Support
Global Variables

Abnormal Termination Conditional Termination

Non-Local goto Signals

Summary

```
void f() {
       A a:
                                           jmp buf jbuf;
        if (setjmp(jbuf) == 0)
                                         void g()
                B b;
                a();
                h();
                                               A a;
                                               UsrExcp ex("From q()");
       else {
                cout <<
                                               longjmp(jbuf, 1);
                ex.what();
                                               return;
       return;
```

• g() successfully returns



Module 36

Non-Local goto

```
void f() {
       A a:
                                           jmp buf jbuf;
        if (setjmp(jbuf) == 0)
                                         void g()
                B b;
                a();
               h();
                                              A a;
                                               UsrExcp ex("From q()");
       else
                cout <<
                                               longjmp(jbuf, 1);
                ex.what();
                                               return:
       return;
```

- g() called and longjmp() executed
- setjmp() takes to exception part



Module 36

Partha Pratin Das

Objective & Outline

Fundamentals
Types of
Exceptions
Exception Stages

Exceptions in C

RV & Params
Local goto
C Standard
Library Support
Global Variables
Abnormal
Termination
Conditional

Non-Local goto Signals Shortcomings

Summary

```
#include<setjmp.h>
#include<stdio.h>
jmp_buf j ;
void raise_exception(){
    printf("Exception raised \n");
    longjmp(j, 1); /* Jump to exception handler */
   printf("This line should never appear \n");
}
int main(){
    if (setimp == 0) {
        printf(" 'setjmp' is intializing j \n ");
        raise_exception();
        printf("This line should never appear \n"):
    else
        printf(" 'setjmp' was just jumped into \n")
       /* This code is the exception handler */
    return 0 ;
  On execution : 'setjmp' is intializing
   exception raised and 'setjmp' was just jumped into */
```



Signals

Module 36

Partha Pratii Das

Objective Outline

Types of Exceptions

Exceptions in

RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination Conditional Termination Non-Local goto Signals

- Header <signal.h>
- raise()
 - Sends a signal to the executing program
- signal()
 - Registers interrupt signal handler
 - Returns the previous handler associated with the given signal
- Converts h/w interrupts to s/w interrupts



Example: Signals

Module 36

Signals

```
// Use signal to attach a signal
// handler to the abort routine
#include <stdio.h>
#include <stdlib.h>
#include <signal.h>
#include <tchar.h>
void SignalHandler(int signal) {
    printf("Application aborting...\n");
}
int main() {
    typedef void (*SignalHandlerPointer)(int);
    SignalHandlerPointer previousHandler;
    previousHandler = signal(SIGABRT, SignalHandler);
    abort();
    return 0;
NPTEL MOOCs Programming in C++
                                          Partha Pratim Das
```



Shortcomings

Module 36

Partha Pratir Das

Objective & Outline

Fundamentals

Exceptions
Exception Stage

Exceptions in C

RV & Params Local goto C Standard Library Support Global Variables Abnormal Termination Conditional Termination Non-Local goto

• Destructor-ignorant:

Cannot release Local Objects i.e. Resources Leak

Obtrusive:

Interrogating RV or GV results in Code Clutter

Inflexible:

Spoils Normal Function Semantics

Non-native:

Require Library Support outside Core Language



Module Summary

Module 36

Partha Pratii Das

Objective & Outline

Fundamentals
Types of
Exceptions

Exceptions i

RV & Params
Local goto
C Standard
Library Support
Global Variables
Abnormal
Termination

Non-Local go Signals Shortcomings

Summary

- Introduced the concept of exceptions
- Discussed exception (error) handling in C
- Illustrated various language features and library support in C for handling errors
- Demonstrated with examples



Instructor and TAs

Module 36

Partha Prati Das

Objective of Outline

Exception Fundamenta

Types of Exceptions Exception Stage

Exceptions in C.

C Language Features RV & Params Local goto C Standard Library Support Global Variabl Abnormal Termination Conditional Termination Non-Local got Signals

Name	Mail	Mobile
Partha Pratim Das, Instructor	ppd@cse.iitkgp.ernet.in	9830030880
Tanwi Mallick, <i>TA</i>	tanwimallick@gmail.com	9674277774
Srijoni Majumdar, <i>TA</i>	majumdarsrijoni@gmail.com	9674474267
Himadri B G S Bhuyan, <i>TA</i>	himadribhuyan@gmail.com	9438911655