Project Design Blueprint: Telehealth Hypertension Predictive Analytics System

Executive Summary

This design blueprint establishes the technical architecture and engineering specifications for the **Telehealth Hypertension Predictive Analytics System**. Transitioning from initial conceptual scoping into concrete technical design, this document details our data collection strategies, data management and governance protocols, machine learning model architectures, and strategies for overcoming implementation bottlenecks. The platform employs a decoupled microservice architecture consisting of a FastAPI backend, a PostgreSQL relational persistence layer, and a React clinician dashboard. By integrating supervised classification for hypertension staging, unsupervised anomaly detection for continuous telemetry, and a dual-layer explainable AI (XAI) interpretation pipeline, the system bridges the gap between raw home-monitoring data and clinical triage workflows.

1. Data Collection Strategy

1.1 Data Sources and Hybrid Collection Plan

The platform relies on a hybrid data collection strategy combining empirical public health baselines with continuous physiological telemetry:

- **Empirical Demographic & Clinical Baselines**: Cross-sectional clinical data is sourced from the Centers for Disease Control and Prevention (CDC) **National Health and Nutrition Examination Survey (NHANES)**. NHANES provides gold-standard epidemiological data spanning multiple biennial cycles (2017–2020), including verified demographic markers (age, biological sex, race/ethnicity), anthropometric measurements (Body Mass Index, waist circumference), dietary sodium intake, and resting blood pressure measurements.
- **Continuous Longitudinal Telemetry**: Because real-world ambulatory blood pressure monitoring (ABPM) feeds contain sensitive Protected Health Information (PHI) subject to strict regulatory barriers, the platform uses a parameterized synthetic telemetry generator for time-series modeling. This generator simulates high-frequency blood pressure recordings across multi-week monitoring windows, explicitly modeling circadian rhythms, morning blood pressure surges, and nighttime physiological dipping patterns informed by American Heart Association (AHA) clinical guidelines (Whelton et al., 2018).

1.2 Access, Format, and Quality Challenges

Integrating these data streams presents three distinct engineering challenges:

- **Format Heterogeneity & Missingness**: NHANES data files are distributed as disparate SAS transport files (.XPT) requiring extraction, harmonization, and joining across demographic, examination, and

dietary questionnaires. Clinical records frequently exhibit missing values in optional dietary fields or lab panels.

- **Synthetic Distribution Realism**: Unconstrained synthetic time-series generation risks producing mathematically impossible blood pressure readings or non-physical joint feature distributions that distort machine learning convergence.
- **Observational Noise in Home Monitoring**: Commercial home blood pressure cuffs introduce patient-dependent measurement errors, such as talking during inflation or inconsistent cuff placement, producing isolated extreme outliers that must be differentiated from true clinical crises.

1.3 Pre-Training Statistical Validation Gates

To prevent model corruption without compromising patient privacy, synthetic telemetry must pass five quantitative validation threshold gates prior to being ingested by the machine learning pipeline:

Univariate Distribution Matching: Two-Sample Kolmogorov-Smirnov (K-S) tests across systolic (SBP) and diastolic (DBP) distributions must fail to reject the null hypothesis ($p > 0.05$), proving statistical parity with empirical NHANES cohorts.

Information-Theoretic Divergence: The Jensen-Shannon Divergence (JSD) across binned probability density distributions must satisfy $JSD < 0.05$.

Physiological Boundary Enforcement: 100% of generated records must fall within medically viable boundaries for derived cardiovascular metrics: Mean Arterial Pressure ($70 <= MAP <= 110$ mmHg) and Pulse Pressure ($30 <= PP <= 80$ mmHg).

Circadian Dipping Validation: Longitudinal patient trajectories must demonstrate an average 10% to 20% nocturnal drop in systolic blood pressure to replicate healthy physiological dipping, while preserving blunted dipping (<10%) in designated high-risk synthetic cohorts.

Discriminator Classifier Test: A binary gradient-boosted discriminator trained to classify records as real vs. synthetic must yield an ROC-AUC between 0.45 and 0.55, confirming that synthetic records cannot be readily separated from empirical baselines.

1.4 Preprocessing and Feature Engineering Pipeline

The ingestion pipeline executes a four-stage preprocessing workflow essential for model accuracy and training stability:

- **Median Imputation**: Missing continuous variables are imputed using demographic sub-group medians. Median imputation is selected over mean imputation because clinical distributions are frequently skewed by extreme values, and medians preserve distribution centers without inflating variance.
- **Feature Scaling**: Continuous features undergo MinMax normalization ([0, 1] range) and standard Z-score scaling. Normalization prevents high-magnitude blood pressure values (e.g., SBP up to 200 mmHg) from overwhelming lower-magnitude continuous features (such as BMI or daily dietary sodium ratios) during gradient descent optimization.
- **Physiological Feature Engineering**: Rather than relying solely on raw systolic and diastolic readings, the pipeline derives established cardiovascular markers:

- Mean Arterial Pressure: MAP = DBP + 1/3(SBP - DBP)
- Pulse Pressure: PP = SBP - DBP
- Circadian Dipping Ratio: (Daytime Mean SBP - Nighttime Mean SBP) / Daytime Mean SBP

These derived features explicitly model vascular resistance and arterial stiffness, giving the tree-based models direct representations of clinical pathology.

- **Streaming Batch Chunking**: To process large multi-gigabyte telemetry uploads without incurring Out-Of-Memory (OOM) exceptions on cloud servers, the ingestion engine uses streaming batch iterators (chunksize = 5000) within Pandas, maintaining a low, constant memory footprint.

2. Blueprint for Data Management

2.1 Storage Architecture and Relational Schema

Data storage is managed using a PostgreSQL relational database structured to decouple authentication credentials, clinical demographics, telemetry logs, and analytical inference outputs.

```
-- Core Relational Database Entities:
-- 1. users: Authentication credentials, hashed passwords, and system roles
(Clinician, Analyst, Admin).
-- 2. patients: Demographic profiles, assigned physician IDs, and encrypted
identifiers.
-- 3. telemetry_records: Time-series SBP, DBP, heart rate, timestamps, and measurement
context.
-- 4. model_predictions: Historical model outputs, risk classifications, and SHAP
attribution vectors.
-- 5. audit_logs: Immutable records of every read, write, and export event for
compliance auditing.
```

To maintain high query velocity across hundreds of thousands of longitudinal telemetry rows, the database implements compound B-tree indexing on `(patient_id, recorded_at)`. This ensures that dashboard time-series queries execute in sub-10ms intervals without table scans.

2.2 Security Architecture and HIPAA Safeguard Alignment

Security is integrated directly into the application layers, strictly aligned with federal HIPAA Security Rule technical safeguards:

- **Access Control (§ 164.312(a))**: Authentication is managed via OAuth2 with JSON Web Tokens (JWT) signed using HMAC-SHA256. API routes enforce role-based access control (RBAC) via FastAPI dependency injection (`verify_role_access`), ensuring clinicians only view their assigned patients while data analysts have access only to de-identified aggregate tables.
- **Data Encryption at Rest and in Transit (§ 164.312(c/e))**: All network traffic is encrypted using Transport Layer Security (TLS 1.3). Within the PostgreSQL database, direct patient identifiers (names, contact details) are encrypted at rest using column-level symmetric encryption via the `pgcrypto` extension (`pgp_sym_encrypt`), with cryptographic keys isolated in secure environment variables.

- **Audit Controls & Traceability (§ 164.312(b))**: The platform generates structured, append-only audit logs capturing the authenticated user ID, client IP address, timestamp, action taken, and target resource ID for every sensitive API transaction.
- **Cloud Infrastructure Attestation & BAA Roadmap**: Cloud infrastructure is deployed across Render (backend container services and PostgreSQL) and Vercel (frontend client hosting). Both vendors operate on AWS physical data centers holding SOC 2 Type II certifications. In our production roadmap, enterprise tier subscriptions will be executed to sign formal Business Associate Agreements (BAAs) pursuant to 45 CFR § 164.502(e).

2.3 Management Tools, Versioning, and Documentation

- **Version Control & Auditable Project Record**: All source code is version-controlled in a private GitHub repository, maintaining an auditable project record through meaningful, descriptive commit histories. The repository includes a comprehensive README, strict environment requirements (`requirements.txt`), and clear data documentation linking the implemented code directly to this architectural blueprint.
- **Continuous Integration & Testing Evidence**: GitHub Actions run automated linting, security scans (`Bandit`), and execution of the `pytest` suite on every pull request, providing formal testing evidence before code merges into the main branch.
- **Data Versioning & Contracts**: Datasets and synthetic generator configurations are tracked using Git LFS (Large File Storage) and deterministic random seeds (`seed = 42`). API payloads are strictly validated using **Pydantic** models, establishing immutable data contracts between frontend and backend services.

3. Model Architecture and Selection

3.1 Model Architecture and Analytical Engine

The analytical engine is designed as a multi-tier machine learning pipeline that combines supervised multi-class risk classification, unsupervised time-series anomaly detection, and an explainable AI translation layer.




Figure 1: Telehealth Hypertension Predictive Analytics System Architecture Blueprint

3.2 Algorithm Selection and Project Alignment

Each algorithmic component serves a specific clinical objective:

Supervised Risk Classification (XGBoost & Random Forest):

- *Role*: Evaluates patient baseline records and historical telemetry to classify individuals into American Heart Association hypertension stages: **Normal**, **Elevated**, **Stage 1 Hypertension**, **Stage 2 Hypertension**, and **Hypertensive Crisis** (Whelton et al., 2018).
- *Justification*: Extreme Gradient Boosting (XGBoost) and Random Forest algorithms excel at modeling non-linear physiological interactions and tabular data with missing values. The models are evaluated using an 80/20 train-test split with 5-fold cross-validation. Hyperparameter tuning specifically optimizes **Recall and Sensitivity** (>= 0.90) for Stage 2 and crisis cases, reflecting the medical reality that a false negative (failing to identify an acute crisis) is vastly more hazardous than a false positive triage alert.

Unsupervised Anomaly Detection (Isolation Forest):

- *Role*: Continuously scans longitudinal time-series telemetry streams to identify anomalous blood pressure spikes, acute pulse pressure widening, or sudden loss of nocturnal dipping (Sylligardos et al., 2023).
- *Justification*: Unsupervised Isolation Forests isolate anomalous observations by randomly partitioning feature spaces. Because hypertensive crises and acute cardiac events are rare in ambulatory data, Isolation Forests effectively flag deviations from a patient's personal diurnal baseline without requiring manual anomaly labeling.

Dual-Layer Explainable AI (TreeSHAP + Plain-Language Clinical Translation):

- *Role*: Translates complex algorithmic predictions into intuitive, actionable clinical insights.
- *Justification*: Standard TreeSHAP (SHapley Additive exPlanations) algorithms compute mathematically rigorous feature attribution values based on cooperative game theory (Lundberg & Lee, 2017). However, raw mathematical plots can cause confusion during rapid clinical workflows. Our dual-layer architecture pairs interactive SHAP visual waterfall plots with an automated natural language translation module that renders a plain-language summary directly on the clinician interface:

  > *"Patient Risk Rating: Elevated (Stage 2). Primary drivers: Sustained 30-day average sodium intake (contributing +24% to risk score) and elevated BMI of 31.4 (+19%). Anomaly alert: Absence of nocturnal systolic dipping (<4% decrease between 23:00 and 06:00)."*

4. Implementation Challenges and Solutions

4.1 Processing Power and Latency Optimization

- **Challenge**: Real-time SHAP explanation calculations and matrix transformations can introduce significant latency (> 1.5 seconds), degrading dashboard responsiveness during patient consultations.
- **Solution**: The architecture implements an **asynchronous caching and precomputation strategy**. Baseline risk scores are calculated in under 50ms upon telemetry ingestion. SHAP feature attributions and anomaly scoring are dispatched as asynchronous background tasks using FastAPI background workers, with computed results cached in PostgreSQL. When a clinician opens a patient chart, precomputed explanations load instantaneously (< 100 ms).

4.2 System Scalability and Memory Limits

- **Challenge**: Cloud server memory exhaustion when ingesting large CSV telemetry files from multiple concurrent patient uploads.
- **Solution**: The backend runs as a stateless containerized service on Render, managed by Uvicorn worker processes behind an asynchronous event loop. Stateless routing allows horizontal scaling across container instances, while streaming chunk iterators ensure memory consumption remains bounded regardless of input file size.

4.3 Methodological Adjustments & Architecture Decision Records (ADRs)

In accordance with professional software engineering standards, major design adjustments driven by faculty review and technical feasibility are formalized as **Architecture Decision Records (ADRs)**:

- **ADR-001: Transition to Dual-Layer XAI**: Shifted from raw SHAP plots to dual-layer visual and narrative explanations based on faculty recommendations to eliminate clinical adoption barriers.
- **ADR-002: Pre-Training Synthetic Validation Gate**: Replaced ad-hoc data simulation with formal statistical gates (K-S tests, JSD < 0.05, and MAP/PP boundary checks) to guarantee model validity without compromising patient privacy.

- **ADR-003: Scope Refactoring for HIPAA Security Matrix**: Reframed compliance claims from generalized organizational certification to an explicit technical alignment matrix mapped directly to HIPAA Security Rule standards (§ 164.308, § 164.310, § 164.312).

References

Lundberg, S. M., & Lee, S.-I. (2017). A unified approach to interpreting model predictions. *Advances in Neural Information Processing Systems*, 30, 4765–4774.

Saltz, J., & Krasteva, I. (2022). Current approaches for executing big data science projects: A systematic literature review. *PeerJ Computer Science*, 8, e942. https://doi.org/10.7717/peerj-cs.942

Spector, A., Norvig, P., Wiggins, C., & Wing, J. M. (2022). *Data science in context: Foundations, challenges, opportunities*. Cambridge University Press. https://doi.org/10.1016/9781009272230

Sylligardos, M., Paul, A., Mercer, B., & Palpanas, T. (2023). Choose wisely: An extensive evaluation of model selection for anomaly detection in time series. *Proceedings of the VLDB Endowment*, 16(11), 3326–3339. https://doi.org/10.14778/3611479.3611536

Tsao, C. W., Aday, A. W., Almarzooq, Z. I., Anderson, C. A., Arora, P., Avery, C. L., ... & Martin, S. S. (2023). Heart disease and stroke statistics—2023 update: A report from the American Heart Association. *Circulation*, 147(8), e93–e621. https://doi.org/10.1161/CIR.0000000000001123

Whelton, P. K., Carey, R. M., Aronow, W. S., Casey, D. E., Collins, K. J., Himmelfarb, C. D., ... & Wright, J. T. (2018). 2017 ACC/AHA/AAPA/ABC/ACPM/AGS/APhA/ASH/ASPC/NMA/PCNA guideline for the prevention, detection, evaluation, and management of high blood pressure in adults. *Journal of the American College of Cardiology*, 71(19), e127–e248. https://doi.org/10.1016/j.jacc.2017.11.006