

Tidal: A Deadline-Contracted Batch Tier for Unmodified LLM Serving Engines*

Gurunath Lunkupali Venugopal

Abstract

A serving node sized for interactive traffic spends most of its life well below its throughput ceiling. On our GPU testbed, a vLLM node serving only online chat traffic emitted about a third of the output tokens per second that the same node sustains when saturated with offline work — and capacity left unspent in one scheduler iteration cannot be banked for the next. Commercial providers sell exactly this slack as a second product: a batch API at half the online price with a 24-hour completion window. A self-hosted deployment has no equivalent product. vLLM’s own batch tooling can drain an offline workload at full speed, but only by dedicating the machine to it, and the research systems that do harvest slack behind live traffic (HyGen, ConServe) fork the engine and promise no completion time — no deadline a customer could plan around. Tidal supplies the missing product over unmodified vLLM: an OpenAI-compatible `/v1/batches` front end, an admission test that *refuses* any deadline window the system’s own observed completion rate cannot meet, and per-job escalation governed by laxity — the classical real-time measure of how much time a job can still afford to lose before its deadline is at risk. On RTX A6000 nodes serving Qwen2.5-7B under a flat 20 req/s online load, a gateway sidecar recovers **69.3%** of the node’s steady-state offline ceiling while online request latency rises to $1.18\times$ a matched node’s online-only baseline at the median and $1.23\times$ at the 99th percentile; under a diurnal trace at 12.1 req/s mean offered load it recovers 78.1%. We also implement the identical policy *inside* the engine as a scheduler plugin and compare the two placements of one policy — outside the engine versus inside it — as an explicit design axis. Code and evidence are open source.

1 Introduction

A vLLM engine serves requests in a loop: the scheduler assembles the work for one step, the model runs that forward step, and the loop repeats. Nothing fixes the pace of that loop — each iteration takes as long as its forward step takes, which for a 7B-class model on server GPUs is typically some tens of milliseconds — but what an iteration may do is capped by a token budget, written τ throughout this paper: the number of tokens the engine will schedule into one step while keeping that step short enough for interactive latency. The budget’s value is a deployment choice that scales with the hardware and the model being served; both our testbeds pin it at 2,048. An engine serving only online traffic rarely comes close to spending it. A few dozen live conversations each decode one token per iteration, so the overwhelming share of the budgeted tokens goes unused — and budget unused in one iteration cannot be saved for the next. That slack is the margin commercial providers monetize as a second product: submit a file of requests, receive results within 24 hours, pay half the online price. Three gaps keep a self-hosted vLLM deployment from selling the same product:

- **The budget is perishable and mostly unspent.** Our in-engine instrumentation shows online-only traffic on the CPU testbed leaving nearly the whole budget idle in a typical iteration (Section 5.6), and the GPU baseline tells the same story at larger scale (Section 2.1). vLLM itself can batch: its offline entrypoints drain a list of requests at the engine’s full throughput. But that path assumes the machine is dedicated to it — it offers no way to sell the *remainder* of a node that is also serving online users — and an SLA-tier proposal for the scheduler was closed without adoption [26].

*Code, receipts, and raw evidence: github.com/rajagurunath/tidal

- **Best-effort co-location is not a product.** The harvesting systems that come closest — HyGen [8] and ConServe [9], which recover 78–88% of dedicated-offline throughput behind online traffic — expose no per-job deadline, no admission decision, and no promise a customer can plan around (no SLA); both are forks of the engine. Deadline-aware schedulers (Niyama [11]) target second-to-minute horizons and degrade under overload rather than refuse work at submission.
- **The naive path is catastrophic.** vLLM already ships a per-request priority field, and simply marking batch work low-priority sounds sufficient. It is not: on our CPU testbed that alone multiplied online median latency by 27.3 (22.6× at the 99th percentile; Section 5.4). Priority decides who is served *first*, but it does not bound how many batch requests become resident in the engine and dilute every subsequent iteration. Something must meter how much batch work exists at all.

The missing piece is not a better preemption mechanism — ConServe’s layer-wise safe-points already yield in single-digit milliseconds — but a *contract*: a specific job, a specific deadline, admission that refuses infeasible work, and scheduling that spends exactly as much online headroom as that deadline requires. The contract is what makes the tier sellable. A customer submits an overnight batch because “done by morning” is dependable enough to plan around; our motivating client, lazycode [28, 29] — a coding agent that plans work with a realtime model and executes it on provider batch APIs at the discount — exists only because that window is dependable. And the contract changes what the scheduler may do: where disaggregation separates prefill from decode in *space*, a deadline-contracted tier may separate work in *time* (Section 6).

Tidal implements the contract with deliberately classical machinery. The central quantity is *laxity*, an idea from hard-real-time scheduling [21] with a one-sentence intuition: *how much time can this job still afford to lose?* Concretely, laxity is the time remaining until the deadline minus the time the remaining work will take at the observed completion rate; a job with five hours of laxity could be starved for five hours before its deadline came under threat. (Section 3.2 gives the definitions and a worked example.) The same arithmetic serves twice. At admission, a job whose projected completion already exceeds its window is refused outright, with an error that shows the numbers. During execution, a job’s scheduling urgency ramps up only once its laxity falls inside a short escalation horizon: a job that is on track stays at the lowest priority no matter how long it has been running, a job at risk escalates early, continuously, and independently of other jobs, and a token-bucket floor guarantees a minimum rate of progress at maximum urgency — progress that feeds back into the laxity calculation and settles the job at the floor instead of oscillating around it.

The same policy can live in two different places, and we implement both — this comparison is the axis the paper turns on, so we name the placements here and keep the names throughout. *Technique A* places the policy *outside* the engine: a sidecar gateway submits batch items to a stock vLLM as low-priority requests and throttles how many are in flight, once per second, with a TCP-style feedback rule driven by the engine’s public metrics (Section 3.3). *Technique B* places the identical policy *inside* the engine, through vLLM’s pluggable scheduler interface: a subclass wraps the stock scheduler and caps the batch tokens admitted to each iteration against a latency model fitted continuously from the engine’s own step timings (Section 3.4). Neither placement forks the engine, and no prior co-serving system evaluates this choice — each evaluates only its own placement.

Terminology. “Batch” is overloaded in this domain, so we fix our words here and hold to them for the rest of the paper. An *online request* is a latency-sensitive request from a live user; it reaches the engine directly and runs at priority 0, and we call this traffic as a whole the *online tier*. A *batch job* is the customer-facing unit of the product: one file of requests submitted to `/v1/batches` under one deadline window, and the unit to which laxity, admission, and escalation apply. The lines of that file are *batch items*; when the dispatcher submits an item to the engine it becomes a *batch request*, distinguished from an online request only by its non-zero priority. *Offline* always names a regime rather than a request class: a machine dedicated to draining batch work with no online tier present — the regime that defines the throughput ceiling we normalize against. Finally, when we mean vLLM’s per-iteration grouping of work

(continuous batching), we say *iteration* or *decode batch*, never bare “batch.”

Contributions:

1. **A customer-facing batch contract for self-hosted serving** (Section 3.2): OpenAI-wire /v1/batches with durable per-job state, laxity-based admission refusal, horizon-scaled escalation, and a progress floor — semantics neither the co-serving nor the deadline-scheduling literature exposes. One caveat, stated here and examined in Section 5.5: the contract’s machinery demonstrably operates — escalation engages, admission refuses, the progress floor holds — but we have not yet constructed a load regime in which the contract makes a deadline that best-effort scheduling would have missed. The mechanism is validated; the end-to-end outcome is not yet demonstrated.
2. **The measured price of the no-fork placement at GPU scale** (Section 5.3): 69.3% of a same-node steady-state offline ceiling at $1.18\times/1.23\times$ online p50/p99 under flat load, 78.1% under a diurnal trace at 12.1 req/s mean offered load — inside the 78–88% band the fork-based literature reports, over an engine we never modified.
3. **Placement as an empirical design axis** (Section 5.4): the same policy outside versus inside the engine on identical traces is a throughput/latency *frontier*, not a ranking — at capacity on the CPU testbed the gateway holds online p99 to $1.97\times$ where the in-engine scheduler reaches $9.9\times$ while harvesting 26 more points of ceiling; the one GPU point shows the frontier moves with hardware (the $2.54\times$ CPU median tax is $1.18\times$ on the A6000).
4. **An audited measurement discipline for co-serving harvest** (Section 5.1): normalize to a *steady-state-tail* offline denominator, and treat any harvest above 100% of a claimed ceiling as a failed ceiling, not a system win. This rule changed our own reported result.

2 Motivation

2.1 One budget, two products

The token budget the introduction sketched has an exact form: a vLLM V1 iteration schedules up to `max_num_batched_tokens` (τ) tokens across running and waiting requests, with τ sized so an iteration’s latency fits the inter-token target. A running decode consumes one token per iteration, a prefill up to a chunk; the KV cache separately bounds how many requests may be resident. The token budget is the perishable good.

Two distinct mechanisms make the slack harvestable, and they spend different idle resources. The first spends idle *compute*: batch *prefill* chunks can fill whatever budget online work leaves in an iteration, because prefill is compute-bound and chunked-prefill schedulers already know how to interleave it under a latency budget [1]. The second spends idle *memory bandwidth*: batch *decodes* ride alongside online decodes. During decode, every iteration must stream the model’s weight matrices out of GPU memory, and with B requests decoding concurrently that single traversal serves all B tokens at once. A thicker decode batch therefore moves the projection and MLP multiplies from thin matrix–vector shapes (GEMV, one token per traversal) toward genuine matrix–matrix work (GEMM, higher arithmetic intensity), and throughput rises with B at nearly flat iteration latency. The free ride ends where compute saturates, or where the KV-cache reads become the binding cost — those do *not* amortize, because each request reads its own private history. Neither effect is monotonic or free; both are bounded by the online latency budget. Our GPU result — 1,408 batch output tokens/s added while online median latency rose to $1.18\times$ baseline — is *consistent with* this arithmetic, but we have not run the controlled batch-size sweep, with kernel-level profiling (e.g. NVIDIA Nsight) attributing the gain to the GEMV→GEMM transition, that would demonstrate the mechanism directly; Section 8 names that experiment as future work.

A roofline reading. The roofline model bounds attainable performance by the lower of a compute ceiling and a bandwidth ceiling selected by a kernel’s arithmetic intensity [2]. The GEMV→GEMM

effect above is exactly a move rightward along that intensity axis, and co-batching is the only lever an unmodified engine offers for making it. Roofline is therefore the frame, GEMV→GEMM the mechanism, and the following ordering the evidence:

$$\text{hardware roofline} \geq \text{engine offline ceiling} \geq \text{co-serving} \geq \text{online-only}.$$

We do not measure the leftmost term. That would require a validated compute-and-bandwidth model of the deployed A6000 at the engine’s precision, which we did not build, and we make no claim about it beyond the inequality. The second term we do measure: the same engine, model, and node saturated with offline work and nothing else sustains 2049.6, 2031.5, and 2057.0 output tok/s in steady state across our three nodes (Section 5.1). It is an operational stand-in — a measured lower bound sitting under the hardware roofline, and the only denominator we are entitled to divide by. The distance below it is what this paper is about. Online-only traffic at 20 req/s Poisson makes that distance concrete: over the baseline run’s 6-minute window the node emitted 687.6 output tokens/s — 33.5% of the 2,049.6 tok/s the same node sustains when saturated offline — while holding a mean of only 15.64 requests *resident* in the engine. (A request is resident while the engine holds its state and schedules it each iteration; residency, not arrival rate, is what fills or fails to fill the budget.) The CPU rig at chat-scale load is starker still, a mean of 0.41 resident requests (Figure 1). The gateway lifts harvested work to the 1,408 batch output tok/s the previous paragraph tied to the co-batching arithmetic, and to 1,607 under the diurnal trace at 12.1 req/s mean offered load (Section 5.3). The chain is an ordering of regimes, not an additive budget: each term is measured on its own request mix, so the online and batch token rates are not summable, and the online rate is set by offered load rather than by capacity — which is why co-serving’s price shows up in latency and not in online throughput.

2.2 Why best-effort is not a product

Best-effort co-location delivers whatever slack happens to exist; the customer learns at hour 24 how much that was. The obvious repair — “priority rises every hour, parity at hour 24” — fails twice: it escalates small on-track jobs pointlessly and escalates large at-risk jobs too late, with full service beginning exactly when time has run out. Feasibility is a relation between remaining work and remaining capacity — which is laxity, and which is why the same arithmetic serves as the admission test. We require of a contract: (R1) urgency is a function of remaining work versus remaining capacity, never of the clock alone; (R2) infeasible work is refused at submission, not accepted and missed; (R3) escalation is per-job and continuous, so at-risk jobs neither wait for a synchronized threshold nor flood the online tier together.

2.3 The placement question

Engine schedulers act per iteration (~10–100 ms) with exact visibility of the token budget and KV state; an external controller acts at 1 Hz on aggregate metrics. Intuition says in-engine must dominate. But the engine’s own priority preemption already covers token-granularity interference between controller ticks, and an external controller survives engine upgrades untouched. No prior co-location work isolates this variable; Section 5.4 measures it, and the intuition does not survive contact.

3 Design

3.1 Overview

Figure 2 shows the datapath. Batch jobs enter through an OpenAI-wire `/v1/files+/v1/batches` API (any OpenAI SDK works with a changed `base_url`), are validated line-by-line, checked for feasibility, and stored durably (SQLite WAL; the store is a repository interface, so Postgres is a DSN change). Items progress pending → inflight → succeeded/failed with idempotent terminal transitions. Online traffic never traverses the gateway. Technique A (the placement outside the engine) stops at the engine’s




Figure 1: The budget is mostly unspent — and spending it naively is catastrophic. Left: resident online requests ($\approx$ decode tokens per iteration) under online-only traffic on the CPU rig — mean 0.41, i.e. 0.02% of the $\tau = 2048$ budget (the GPU baseline’s mean of 15.64 resident is the same story at 0.8%). Right: the online latency price of naive co-location (vLLM’s priority field alone), $27.3\times/22.6\times$ p50/p99 on the CPU rig (Section 5.4) — admission priority does not bound resident-request contention, which is why something must meter how much batch work exists at all.

public API; technique B (the placement inside) adds a scheduler plugin. Both run the same contract arithmetic.

3.2 The contract: laxity at admission and in scheduling

The contract’s arithmetic is small enough to state in full. For each active batch job b the dispatcher tracks three quantities: the deadline D_b , the count of remaining items R_b , and the rate r_b at which the job’s items have recently been completing (a sliding-window estimate; while a job has no completion history the drain term is dropped entirely, so a job escalates on evidence or on deadline proximity, never on a missing denominator). From these it computes:

$$\text{laxity}(b) = (D_b - \text{now}) - R_b/r_b \quad (1)$$

$$\text{urgency}(b) = \text{clamp}\left(1 - \frac{\text{laxity}(b)}{H}, 0, 1\right) \quad H = \text{escalation horizon (6 h} \ll \text{24 h window)} \quad (2)$$

$$\text{priority}(b) = 100 \rightarrow 1 \text{ linearly with urgency} \quad (\text{online requests are 0; the opt-in } \texttt{sla_strict} \text{ tier may reach 0}) \quad (3)$$

A worked example. A batch of 9,000 items is submitted mid-flight with 10 hours left in its window, and the dispatcher has been observing $r_b = 0.5$ items/s for this job. Draining the remaining work needs $9,000/0.5 = 18,000$ s, five hours, so $\text{laxity}(b) = 10 - 5 = 5$ hours: this job could lose five whole hours to online bursts before its deadline came under threat. Five hours is inside the $H = 6$ -hour escalation horizon, so the job starts to escalate — mildly: $\text{urgency} = 1 - 5/6 \approx 0.17$, mapping to $\text{priority} \approx 83$, a step above the lowest band and still far from the online tier at 0. Had 20 hours remained, laxity (15 h) would sit beyond the horizon and the job would stay pinned at priority 100 no matter how long it had already run. Had only 5.5 hours remained, laxity (0.5 h) would drive urgency to 0.92 — past the 0.9 threshold where the token-bucket floor guarantees the job a minimum admission rate regardless of what else wants the node.

Admission (R2). The same arithmetic runs once more at `POST /v1/batches`: projected completion R/r_{global} is checked against the requested window with a configurable margin, and an infeasible job is




Figure 2: One policy, two placements. Batch jobs enter through an OpenAI-wire gateway that ① refuses infeasible windows at admission, ② stores jobs durably, ③ claims items in deadline order at their laxity priority, and ④ throttles dispatch by AIMD over the engine’s public metrics. Placement A stops there: the engine is stock vLLM, and online traffic never traverses the gateway. Placement B moves admission inside the engine ⑤ as a scheduler plugin that caps batch tokens per iteration against a self-calibrated latency model. Both are plugins; neither forks the engine.

rejected with an error naming the numbers. A system with no completion history yet accepts — it cannot judge what it has never measured.

What refusal means operationally (and what it does not). Refusal is a signal, not a dead end. The rejected submission carries the arithmetic — requested window, observed rate, projected completion — so a client can immediately resubmit with a window the node can honor, or split the job across nodes. Two further responses build naturally on the same signal, and we are explicit that Tidal implements neither today. First, an explicit best-effort tier: accept the job with no deadline and schedule it beneath every contracted job — precisely the service the harvesting literature already provides, and one that composes cleanly with the contracted tier. Second, refusals as an autoscaling signal: a run of infeasible submissions is a precise, deadline-denominated statement that demand has outgrown this node, which an operator or a serverless control plane can answer by adding capacity. Both are roadmap; the measured system refuses, reports the numbers, and stops there.

Scheduling (R1, R3). Figure 3 is the picture to hold onto; the rules below only formalize its three curves. A job that is on track — laxity at least the horizon H — stays pinned at priority 100, the lowest band, however deep into its window the clock has run: having been submitted eighteen hours ago is not, by itself, a reason to push ahead of anyone (R1). What moves a job is its own laxity falling inside the horizon; from there, urgency climbs continuously as laxity shrinks, each job independently of every other, which is what prevents a synchronized stampede of at-risk jobs into the online tier (R3). The horizon rather than the 24-hour window is the yardstick deliberately: scaling urgency by the window would make urgency grow with elapsed wall-clock time, which is exactly the aging rule Section 2.2 rejected, in disguise. Above urgency 0.9 a token bucket guarantees the job a minimum admission rate, and that assured progress feeds back into the laxity calculation, so the job settles at the floor instead of oscillating around it. One vLLM-specific consequence: the engine fixes a request’s priority at submission, so escalation acts on each newly submitted item, and the backlog that laxity governs is by construction the not-yet-submitted portion of the job. Co-location has a latency price even at the lowest band — Section 5 measures it. The contract’s property is never spending *more* online headroom than the deadline requires, not zero cost.




Figure 3: The contract in one picture. Wall-clock aging (gray dashes) escalates every job on the clock alone. Laxity escalation separates the cases: an on-track job (solid) stays at the lowest band for the entire window, while an at-risk job (dotted) ramps linearly over its last $H = 6$ h of *slack* — beginning when its laxity crosses H , not at any fixed hour — to one notch below online. Above urgency 0.9 (shaded) a token bucket guarantees a minimum admission rate, whose assured progress feeds back into laxity and stabilizes the job at the floor; `sla_strict` allows the dashed final step to priority 0 — parity — exactly at the deadline.

3.3 Technique A: external control

Technique A never touches the engine; it controls the one variable available from outside — how many batch requests exist in the engine at all. A loop wakes once per second, reads three metrics every vLLM already exports (queue depth, KV-cache usage, completion rate), smooths them, and adjusts a target for the number of batch items in flight by additive-increase/multiplicative-decrease (AIMD), the feedback rule that governs TCP congestion control [22]: while the engine shows headroom, raise the target by one; at the first sign of online queueing or a high KV watermark, cut it in half. The asymmetry is the point — probe upward gently, retreat drastically — and it keeps the controller hovering just below the level where batch work would start to interfere. One conservative twist: vLLM’s waiting-queue metric is not partitioned by priority, so the controller cannot tell whose requests are queued, and it halves as if every one of them were its own. Items are claimed in deadline order, grouped by shared prompt prefix so that arrival order recovers some prefix-cache locality (a heuristic we did not ablate against HyGen’s engine-side ordering [8]), and each item is submitted at its batch’s current laxity priority. If the engine becomes unreachable, a circuit opens and in-flight items re-queue idempotently. The cost of all of this is one metrics scrape and one $O(\text{jobs})$ laxity pass per second — negligible beside a single decode step.

3.4 Technique B: in-engine work conservation

`TidalScheduler` subclasses the V1 scheduler behind `--scheduler-cls` and wraps — never reimplements — the stock `schedule()` (Algorithm 1). The idea fits in one sentence: before each stock scheduling pass, decide how many batch requests that pass is allowed to see, and hide the rest. Requests with priority ≥ 1 are the batch class. The decision is a small feasibility problem solved each iteration: given the online work that must run — P_{on} prefill tokens against total attention context C — find the largest batch admission x such that the predicted step time still fits the inter-token latency budget, $\hat{T}(P_{\text{on}} + x, C) \leq \text{TBT}_{\text{budget}}$. The predictor is ConServe’s context-aware form $\hat{T}(P, C) = k_1 P + k_2 P(P+C) + k_4(P+C) + k_5$ [9], chosen because it prices the attention cost that a pure token count misses. Where ConServe fits its model in an offline profiling sweep, however, `TidalScheduler` fits the same form *continuously* from the engine’s own $(P, C, \text{step-time})$ stream — a ring buffer of recent observations, periodic least squares, non-negativity clamps, and an R^2 gate that falls back to a conservative static cap whenever the fit turns poor — which removes the profiling sweep HyGen and ConServe both require. With zero online requests resident the cap lifts entirely (offline mode: batch fills τ). Two protections

Algorithm 1 TidalScheduler pre-gate (one iteration)

- 1: $x \leftarrow \max\{x : \hat{T}(P_{\text{on}}+x, C) \leq \text{TBT}_{\text{budget}}\}$ $\triangleright x \leftarrow \infty$ if no online resident
 - 2: hide batch waiters beyond x ; hide all batch if $\text{KV} > 1 - H_{\text{kv}}$
 - 3: $\text{out} \leftarrow \text{stock_schedule}()$ $\triangleright$ unmodified upstream pass
 - 4: restore hidden waiters (exception-safe)
 - 5: if $\text{KV} > 1 - H_{\text{kv}}/2$: evict cheapest batch victim
 - 6: record $(P, C, \text{step time})$; periodically refit $\hat{T}$, gate on R^2
-

guard the KV cache: a guardband (an EWMA of online demand, clamped to 5–30%) stops batch admission before an online burst can be starved of cache space, and proactive eviction picks as its victim the batch request with the least non-prefix-cached work to lose. Enforcement is deliberately coarse — at chunk granularity, we bound which requests the stock scheduler may see, never its inner token loop — and that coarseness is what keeps the wrapper robust to upstream drift: it survived an upstream jump of roughly 1,700 commits during development, and porting to release v0.26.0 required one keyword argument. The price of the same coarseness is the interference Section 5.4 quantifies. Per-iteration overhead is one closed-form cap solve and two list partitions; the least-squares refit is periodic and off the step path.

3.5 Robustness

The failure paths are part of the design, consolidated here. *Model misfit*: if $\hat{T}$'s fit fails its R^2 gate, the cap falls back to a conservative static value. *Cold start*: with no completion history the laxity drain term is dropped — escalate on evidence, never on a missing denominator. *Engine loss*: the circuit opens, in-flight items re-queue idempotently, and a restarted dispatcher re-claims resultless items (re-execution rides the prefix cache). *Duplicate control*: a second dispatcher against one store is data-safe but duplicates work; there is no ownership lease (roadmap). *Late results* for cancelled or expired items are recorded-then-discarded without corrupting counts. *Non-stable interfaces*: `scheduler_cls` is not a stable vLLM interface; technique B pins a version and probes signatures. What we deliberately did not build: Con-Serve's layer-wise safepoint preemption and incremental KV checkpointing address unbounded iteration times; chunked prefill bounds ours to one τ -sized step, and Section 5.4 argues sub-iteration control is exactly what technique B lacks.

4 Implementation

Tidal is Python over unmodified upstream vLLM (v0.26 series): 424 tests including integration tests against a live engine, with the API layer wire-verified against the official OpenAI SDK. Item claims are single atomic updates; terminal transitions are idempotent, so duplicate or late results never drift `request_counts`; result-file attachment is first-writer-wins, so concurrent finalization cannot split a batch's outputs. Metering prices batch tokens at a configurable discount against an online price table; we make no claim about what discount a marginal-cost model would justify. The strongest wire-compatibility evidence is external: lazycode's Tidal adapter mirrors its Anthropic batch adapter nearly line-for-line — an existing batch-API client adopted the self-hosted tier as just another provider [29]. One obligation a fork never meets: vLLM attaches log handlers only to its own logger tree and runs the scheduler in a forked process, so an engine plugin injects logging configuration or runs blind. Operational semantics in full: Appendix B.

5 Evaluation

Five questions, in order of weight: **Q1** what does the no-fork gateway cost and recover at GPU scale (Section 5.3)? **Q2** does harvest follow the online tide (Section 5.3)? **Q3** how does placement change




Figure 4: Technique B: one engine iteration. `TidalScheduler` wraps rather than reimplements the stock `schedule()`. Before the stock pass it feeds the previous step’s $(P, C, \text{step_ms})$ to a continuously refitted latency model, solves that model for the largest batch-token cap X that keeps the step inside the guarded inter-token budget, and hides every waiting batch request beyond X — lifting the cap entirely when no online request is resident. A KV guardband stops batch admission before online bursts can be starved of blocks and evicts the cheapest batch victim under further growth. After the stock pass the held set is restored in a `finally` block. The side panel shows what X governs: online tokens occupy the bottom of the τ -token budget, batch work fills up to the cap, and whatever is left unfilled is reported as starved slack.

Table 1: Testbeds. The CPU rig is for controlled mechanism and placement comparisons only; the GPU rig carries the capacity and latency claims.

	CPU (mechanism/placement)	GPU (capacity/latency)
hardware	Apple M4 Pro, CPU-only build	RTX A6000 48 GB $\times$ 3 nodes (io.net)
model	Qwen2.5-0.5B-Instruct	Qwen2.5-7B-Instruct
engine	vLLM v0.26.1 @ e6d67fdd	vllm/vllm-openai:v0.26.0 image
budget, policy	$\tau=2048$, priority, eager	$\tau=2048$, priority
online load	Poisson, seeded, 1–3 req/s	Poisson, seeded, 20 req/s
windows	10 min	6 min flat; 20 min diurnal; warmup 45 s
metric	total request latency	total request latency (non-streaming)

Table 2: What each system exposes. *as reported by those papers, for forked engines, denominator methodology unreported; [†]steady-state-tail denominator (Section 5.1), unmodified engine, diurnal row at lower mean offered load (12.1 vs 20 req/s). BlendServe is offline-only; its number is % of a profiled practical optimum, and its only deadline notion is a pool-wide blending window.

	per-job deadline	admission refusal	online tier	engine change	placements evaluated / harvest
HyGen	—	—	✓	fork	1 / 78–88%*
ConServe	—	—	✓	fork (~9.2k LOC)	1 / 78–88%*
BlendServe	window only	—	—	modified backend	1 / 86.6–90.8% of T_o
Niyama	per-request (s–min)	degrades	QoS classes	fork	1 / —
Tidal	24 h, per job	refuses	✓	none (plugin/sidecar)	2 / 69.3%; 78.1%[†]

the price of the same policy (Section 5.4)? **Q4** does the contract machinery change deadline outcomes (Section 5.5)? **Q5** does the in-engine model calibrate itself (Section 5.6)?

5.1 Testbeds, and defining the ceiling

Table 1 fixes both rigs. Requests are short chat completions; we measure total non-streaming request latency (on these configurations a request is a short prefill plus a short decode; a TTFT/TPOT split is not measured here).

Defining the ceiling. Every “% of ceiling” below divides by the same node’s *dedicated-offline* rate — and how that denominator is measured decides the result. A burst probe’s whole-burst average is ramp-dominated: our probe drains 600 items at concurrency 512 with an 18.5 s makespan, so roughly half the window is pipeline fill, and the whole-burst figure (1438, 1427, and 1468 output tok/s across the three nodes) understates the node by 43%. The correct denominator is the probe’s **steady-state tail** (last 10 s): 2049.6, 2031.5, and 2057.0 tok/s, a $\pm 0.62\%$ cross-node band — a tighter instrument as well as a correct one. We learned this by being wrong: an independent numerical audit of our first draft rejected the whole-burst denominator, and the tell was in our own table — a diurnal run “harvesting” 109% of it. The rule this yields is free to apply and the field does not apply it: **any co-serving harvest above 100% of a claimed ceiling is proof the denominator is not a ceiling**. The prior literature does not report how its ceilings were measured (Section 7). Both denominators and the audit trail are archived in the repository. Throughput is normalized per node; **latency ratios are cross-node** (no within-node baseline/co-serving pair exists in the evidence) and are labeled as such throughout.

5.2 Comparison points

Table 2 makes the positioning checkable rather than asserted. Our evaluation arms: `online_only` (baseline), `naive` (vLLM priority field alone — the policy-free control), technique A, technique B, and `offline_only` (the ceiling probe).

Table 3: GPU results (A6000, Qwen2.5-7B, online 20 req/s Poisson). “% of ceiling” uses each node’s own steady-state-tail probe (Section 5.1). Latency ratios are cross-node. The diurnal row is a 20-minute run, peak 20 req/s, mean offered load 12.1 req/s ($n=14,498$, zero errors) — not directly comparable to the flat row.

condition	online p50	online p99	vs baseline	batch otok/s	% of ceiling
online_only (baseline)	0.753 s	1.570 s	1.00×	—	—
technique_a (flat)	0.886 s	1.927 s	1.18×/1.23×	1408	69.3%
technique_a (diurnal)	0.85 s	1.90 s	~1.13×/~1.21×	1607	78.1%




Figure 5: The headline trade at GPU scale. Left: online request-latency CDF, baseline versus technique A (cross-node). Right: batch harvest as a fraction of the node’s steady-state offline ceiling, with the band the fork-based literature reports shaded for reference.

5.3 Q1–Q2: the no-fork price at GPU scale

The gateway recovers **69.3% of the node’s steady-state offline ceiling** while holding the online tax to $1.18\times/1.23\times$ p50/p99 (Table 3, Figure 5) — inside the 78–88% band HyGen and ConServe report for forked engines, from a sidecar over a stock container image. Under the diurnal trace, harvest rises to 78.1% — but the diurnal run’s mean offered load is 12.1 req/s against the flat run’s 20 (completion lengths are nearly identical, 56.0 vs 54.8 mean output tokens), so the two rows are different regimes, not a dose-response, and we do not present 78.1% as evidence that diurnal load helps per se.

The tide (Q2). Per-minute batch completions anti-correlate with online load at $r = -0.85$ with the first-minute pipeline-fill bin excluded (minute 0 completes 771 items against 1667–1894 in every later minute; including it drags the correlation to -0.38 , a startup artifact). The GPU tide is in *phase* with the CPU tide (-0.85 vs -0.95 ; Figure 6) but much shallower: batch completions split -6.4% between above- and below-mean-load minutes on GPU against -22% on CPU — consistent with the GPU having more absolute headroom at the diurnal run’s 78.1% ceiling point (12.1 req/s mean offered load) than the CPU box had at 45%.

What the GPU campaign did not produce. Technique B’s compatibility canary passed on release v0.26.0 (one keyword-argument fix; 14 engine tests pass against both release and dev vLLM), but its matrix measurement — and the `offline_only` and `naive GPU` arms — were lost to a two-stage harness defect in the direct-submission path (Appendix A). The placement comparison therefore remains CPU-only, and the CPU naive arm stands as the policy-free control.




Figure 6: Batch fills the trough on both testbeds. Per-minute batch completions (bars) against online arrivals (line): CPU $r = -0.95$ (top), GPU $r = -0.85$ with the first-minute pipeline-fill bin shaded and excluded (bottom). On the CPU run the AIMD target never moved from its cap — the tide is produced entirely by engine-level priority scheduling, the two-level division of labor observed directly.

5.4 Q3: placement, and an inversion

Naive co-location is catastrophic despite correct priority ordering (Table 4, Figure 7): admission priority does not bound resident-request contention. Between the two placements the naive expectation — in-engine must dominate — is wrong on this hardware. Technique B’s cap and guardband address channels that never bind here: peak KV usage stayed below 0.5%, so eviction never fired, and a resident batch request decodes every iteration regardless of the admission cap. The binding channel is *resident-decode contention*, and only sub-iteration participation control — precisely ConServe’s layer-wise mechanism, which our no-fork constraint excludes — could bound it. Technique A holds latency in both regimes ($1.76\times$ vs $8.25\times$ p99 at equal work; $1.97\times$ vs $9.9\times$ at capacity) because its control point — how many batch requests exist at all — is upstream of residency. In the capacity regime, technique B converts that residency into 26 more points of ceiling (71.2% vs 45.1%). Placement is a frontier (Figure 8): the gateway buys latency protection with throughput, the in-engine scheduler the reverse. The comparison is of two placements of *one policy*, not of two systems — and the GPU crossover remains unmeasured because the direct-submission GPU arms failed (Section 5.3). The one GPU point shows the frontier moves: the median tax that costs $2.54\times$ on CPU costs $1.18\times$ on the A6000.

5.5 Q4: the contract, honestly

The honest headline of this subsection is a negative result, and we state it plainly before the numbers. We set out to construct the scenario in which the contract visibly changes an outcome: a feasible-but-tight job that best-effort co-location *misses* and laxity escalation *meets*. On this testbed we could not construct it: every load regime we tried left enough slack that both arms finished inside the window.

Table 4: CPU placement comparison, one table, two regimes: *equal-work* (all conditions complete the identical 1,200-item batch; 10-min windows, 1 req/s) and *capacity* (non-draining 3,000-item pool). Ceiling: 4.43 items/s (68.5 output tok/s), dedicated-offline.

condition	regime	online p50	online p99	vs baseline (p50/p99)	% of ceiling
online_only	equal-work	0.44 s	1.43 s	1.00×/1.00×	—
naive	equal-work	11.97 s	32.24 s	27.3×/22.6×	—
technique A	equal-work	1.12 s	2.52 s	2.54×/1.76×	—
technique B	equal-work	1.26 s	11.80 s	2.86×/8.25×	—
technique A	capacity	—	—	p99 1.97×	45.1%
technique B	capacity	—	—	p99 9.9×	71.2%




Figure 7: Online request-latency distribution under each CPU condition. The medians degrade more than the tails everywhere — co-serving adds a near-constant per-step cost that dominates fast requests — so p99-only reporting, common in this literature, flatters every technique, including ours.

Even at 3 req/s with a 900-item/15-minute job — the heaviest online load we could apply — the job completed with 3.5 minutes to spare, and at 2–2.6 req/s every configuration finished early for *both* arms (Table 5; full grid in Appendix D). **We therefore do not claim demonstrated deadline improvement.** What the runs do establish: the escalation machinery operates (per-tick priority traces show laxity bands engaging, minimum priority 66), the floor engages at its configured urgency, and admission refuses jobs the observed rate cannot serve. The A6000 runs validate slack harvesting under flat and diurnal load but still do not construct the discriminating regime; doing so — bursty load with genuinely scarce slack — remains the contract’s open experiment.

5.6 Q5: self-calibration

From cold start on the CPU rig, $\hat{T}$ passed its R^2 gate within the first capped phase of the integration run and settled at MAPE ≈ 0.11 on live traffic; the batch-token cap moved from the cold-start 40 to a converged 1 — correctly tight, since at a 60 ms budget with ~ 25 ms online-only steps this box has little slack to sell, and the model discovered that (Figure 9). The same trace shows the offline-mode transition: when online traffic stops, the held set empties and batch fills the whole budget. Regime-change adaptation (model swap, thermal drift) is untested.




Figure 8: Placement is a frontier, not a ranking. Online p99 ratio (log) against harvest, all measured arms, with the band the fork-based literature reports shaded. The same policy moves from the CPU point to the GPU point when the binding resource changes; technique B’s GPU point was not obtained (open marker).

Table 5: Deadline-stress runs (technique A, 15-minute windows). Every feasible configuration completed inside the window for both arms; escalation engaged but was never the difference-maker. Full five-row grid: Appendix D.

run	online load	items	completed	makespan	min. priority
saturated, best-effort	3.0 req/s	900	900/900	692 s	100
tight, best-effort	2.6 req/s	500	500/500	351 s	100
tight, laxity (+floor)	2.6 req/s	500	500/500	328 s	66




Figure 9: Technique B, step by step: online and batch tokens scheduled per iteration (top) and batch requests held back by the pre-gate (bottom). Online traffic stops near $t = 600$ s; the held set empties and batch takes the whole budget — offline mode.

6 Discussion: widening the control plane

Everything measured above places the batch tier against one aggregated engine. The same contract widens along three axes, and we are precise about the evidence each carries: local measurements for fleets and phase splitting, a design mapping only for disaggregation (details, tables, and figures in Appendix C). **Fleets:** with two phase-shifted replicas, placement that follows slack harvested +32% over pinning all batch to one replica, with per-replica batch completions anti-correlating with that replica’s own load ($r = -0.83, -0.56$) — mechanism proven on a CPU rig whose shared memory bus is a named confound on the latency side. **Disaggregation:** the three signals technique A scrapes have direct counterparts in NVIDIA Dynamo [20] (KVBM block metrics, router queue depth, per-worker throughput); the one non-rename nuance is that batch work is prefill-heavy, so the tier should target *prefill-worker* troughs. **Phase splitting:** a deadline legalizes an arbitrary gap between a request’s prefill and its decode. A freeze/thaw spike — prefill in one process, KV persisted to disk, process killed, a fresh process thaws — produced bit-identical greedy decode with TTFT $31.8\times$ faster than recomputing ($7.277 \rightarrow 0.229$ s, median of 5). Total FLOPs are unchanged; only their placement in time moves, and the bill moves to storage (12,288 B/token at 0.5B; ~ 2 orders worse at 70B-class). Disaggregation separates prefill from decode in space; a deadline-contracted batch tier separates them in time.

7 Related Work

Iteration-level scheduling. Orca introduced iteration-level batching [3]; Sarathi-Serve’s chunked prefill and token budget are the structure vLLM V1 inherits [1]; FastServe brought preemptive MLFQ to inference [4]; InferCept’s preemption taxonomy [24] underlies HyGen’s KV handling. DistServe and Splitwise disaggregate phases in space [6, 7]; Llumnix rebalances by live migration [5]; LMCACHE and Mooncake [18, 19] own the KV-persistence mechanics our freeze/thaw spike deliberately reuses rather than rebuilds.

Online/offline co-serving. ConServe [9] is the closest system and the strongest published harvest-interference frontier: an offline-profiled context-aware latency model, layer-wise safepoint preemption, and incremental KV checkpointing, at 78–88% of ceiling within 25% of online-only latency. We take its numbers as the target our in-engine placement should reach rather than a claim we contest, and we differ on exactly three axes, none of which is a better preemption mechanism. First, ConServe’s offline pool has no per-job identity: its only SLO is the online one, its offline metric is aggregate tokens per second, its s knob is an operator dial — nothing is ever refused. Tidal’s contribution sits there (per-job windows, admission refusal, horizon-scaled escalation, a floor with laxity feedback). Second, ConServe is a ~ 9.2 k-LOC fork including in-model instrumentation; both our placements are unforked, and we treat that as a measured cost/benefit — our wrapper survived an upstream jump of roughly 1,700 commits at the price of chunk-granular enforcement, which is one side of our placement frontier. Third, ConServe evaluates one placement; we compare two. HyGen [8] shares ConServe’s shape (profiled budget, prefix-aware offline order, starvation tempering) and the same three differences. OOCO [16] and Echo [17] are contemporaneous co-scheduling work, also contract-free.

Offline batch optimization. BlendServe [10] exploits the same physics from the opposite side: with *no online tier*, it reorders an offline pool so compute-heavy and memory-heavy requests overlap, reaching 86.6–90.8% of a profiled optimum. Tidal’s setting inverts the degrees of freedom: the memory-bound side of our blend is pinned by an exogenous arrival process we cannot reorder, our control variable is an admission rate under a live latency constraint rather than a one-time request order, and where BlendServe’s one deadline notion is a pool-wide blending window, our unit of promise is the individual job. The systems compose: BlendServe’s compute-density order is the right *intra-job* claim order for our dispatcher, and its density metric suggests selecting batch items whose resource shape complements the current online mix — neither system implements that today.

Deadline-aware serving. QLM [13] (ILP queue reordering), Ascendra [14], SCORPIO [15], and closest, Niyama [11]: per-request deadlines across QoS classes at second-to-minute horizons, degrading

under overload. None exposes day-scale per-job windows or admission refusal. FREESH [12] runs true LLF inside an engine for energy-aware scheduling of one request class — evidence the math runs in this setting, aimed at a different problem. Within vLLM itself: priority scheduling was motivated by batch/interactive co-location [25], an SLA-tier RFC was declined [26], and an online batch-API endpoint remains an open PR [27] — demand without an assembled answer. Every individual mechanism here is published; the contribution is the contract, the placement measurement, and the audited synthesis.

8 Limitations

Seven, one line each; full provenance in Appendix A. (1) Technique B’s admission gating does not bound resident-request inflation — the dominant residual interference channel on the CPU testbed; bounding it requires sub-iteration control. (2) The contract is mechanism-validated, not outcome-demonstrated (Section 5.5), and `sla_strict`’s latency price is unmeasured. (3) The placement inversion is CPU-only; technique B’s GPU arm was lost to a harness defect. (4) The GPU ceiling is a steady-state tail of a probe burst, not a 6-minute dedicated run, and GPU latency ratios are cross-node. (5) The fleet experiment’s latency side is confounded by shared memory bandwidth (thread-count isolation only). (6) Single engine, single model, one dispatcher per store (no lease); submission-time escalation cannot re-age already-queued items; `scheduler_cls` is not a stable interface. (7) The models measured (Qwen2.5-7B on GPU, Qwen2.5-0.5B on CPU) are a generation old; repeating the GPU campaign on a current model, and attributing the co-batching gain mechanistically with kernel-level profiling (NVIDIA Nsight), are the named next measurements.

9 Conclusion

The batch API is the rare product where the entire margin is scheduling. Tidal implements its contract — admission, escalation, floor — over an unmodified open-source engine with classical real-time machinery, prices the no-fork placement at GPU scale, and is explicit about what remains undemonstrated. We offer it as usable infrastructure, a baseline for deadline-contracted serving, and a placement study whose GPU evidence currently covers the gateway but not the in-engine scheduler. What is not measured here is equally specific: the in-engine GPU matrix, blocked by our harness defect; a load regime that discriminates escalation end-to-end; and a repeat of the campaign on a current-generation model with kernel-level attribution (Section 8).

A Artifact and provenance

Spend and teardown. Total GPU spend $\approx$ \$7.73: \$6.79 in archived price-quote receipts across six hires plus a one-hour extension ($\approx$ \$0.94) whose HTTP 200 was observed in-session but not archived. Three of six hires have archived DELETE receipts; two were expiry-reclaimed (DELETE returned 400 resource-not-found); the last was deleted manually with a receipt note in `evidence/TEARDOWN_NOTES.md`. A live check after close showed zero running deployments. \$1.98 of spend (the first two hires) produced no data — marketplace node failures — and an honest cost-per-datapoint includes it.

Harness defects. (1) The direct-submission path fails at GPU scale twice-over: an unbounded drain (fixed with bounded salvage, 12 tests) and a remaining stall-after-warmup mode; it cost the `offline_only`, `naive`, and `technique-B` GPU arms. (2) macOS fleet isolation is thread-count only. (3) Diurnal-B and B-matrix GPU numbers are absent, blocked by (1). (4) Metrics evidence is our own 1 Hz instrumentation plus archived CaaS API responses and engine logs (no production observability stack on the dev cluster). (5) Two analysis defects found by an independent audit, not by us: a ramp-dominated probe average used as a ceiling and a pipeline-fill bin left inside a correlation — both corrected in Section 5.1 and Section 5.3, both with tells we did not act on (a $>100\%$ harvest; a first bin completing 771 items against 1667–1894).

B Operational semantics and the client

A restarted dispatcher re-queues resultless in-flight items; re-execution rides vLLM’s prefix cache. Late results for cancelled or expired items are recorded-then-discarded without corrupting counts, and un-wedge finalization. One dispatcher per store is assumed; a second is safe for data, not for duplicated work (no ownership lease; roadmap). Figure 10 traces one batch through the gateway path end to end; Figure 11 closes the loop from client intent to applied code. The client’s architecture — the planning algebra, rewrite-rule optimizer, wave scheduler, and batch-vs-cached-realtime economics — is the companion paper’s subject [29].

C The A-ladder: fleets, disaggregation, phase splitting

Table 6 lays out the ladder; Figure 12 draws it. The ladder is the complement of technique B, not a competitor: B is maximum visibility over minimum scope (one engine’s iteration); the ladder trades coarser signals for widening scope, ending in a decision B cannot express — parking work in time.

Table 6: The A-ladder: widening the scope over which the deadline-contracted tier places work, with the evidence status of each rung.

rung	scope	status
A0	single aggregated engine	measured on GPU (Section 5.3)
A-F	fleet placement across replicas	mechanism proven locally (Table 7)
A-D	disaggregated-aware injection	design + Dynamo metric mapping (Table 8)
A-P	phase-split freeze/thaw	spike-proven locally (31.8× TTFT)

A-F: fleet placement. Two CPU replicas (Mac M4 Pro; thread-count isolation only — macOS cannot pin cores, so shared memory bandwidth is a named confound), phase-shifted diurnal load (period 600 s, phases $0/\pi$), 20-minute window, identical 4000-item pool. **This is not the GPU setup** (Qwen2.5-0.5B, peak 1 req/s, 16-token completions); its only job is the placement mechanism. Fleet placement (sticky prefix affinity + least-loaded + headroom filter, per-replica AIMD with replica-local circuits; 95 of the 424 tests) harvested 2494 in-window items versus pinned 1884 (+32%), with batch volume split nearly evenly (1239/1255) but *timed* into each replica’s trough — per-replica correlation $-0.83/-0.56$ (Figure 13). The cost is real: blended online p50 3.41 s vs 1.44 s, p99 12.1 vs 3.7 — attributed to the shared-substrate confound (spreading batch loads both replicas’ shared memory bus). GPU fleets with real isolation are where the latency side resolves; the mechanism claim is what this rig proves.

Table 7: A-F fleet versus pinned placement, two phase-shifted CPU replicas.

arm	batch items in-window	batch tok/s	blended online p50 / p99
pinned (all batch → replica 0)	1884	24.4	1.44 s / 3.7 s
fleet (placement follows slack)	2494	32.2	3.41 s / 12.1 s

A-P: freeze/thaw. vLLM CPU build, ExampleConnector (the renamed SharedStorageConnector), kv_role=kv_both, prefix caching disabled. Prefill in process 1 → KV persisted (23.6 MB for a 1973-token prompt: whole 128-token blocks only, 1920 cached tokens at exactly 12,288 B/token) → process killed → fresh process thaws → bit-identical greedy decode, TTFT 7.277 → 0.229 s = 31.8× (median of 5). A duplicate arm thawing from the in-engine prefix cache measured 48.2×; we quote the cross-process number because durability — surviving process death — is the property a deadline-deferred prefill needs.




Figure 10: Technique A: the batch request lifecycle, end to end. A client uploads a JSONL file and creates a batch; the gateway validates every line and applies the laxity admission test, refusing with `batch_infeasible` any job whose projected completion exceeds the window times a margin, and otherwise persisting `PENDING` items with a 24-hour `expires_at`. A 1 Hz dispatcher scrapes the engine’s public metrics, sets an AIMD in-flight target, computes each batch’s laxity-derived priority, claims items in deadline × prefix order and submits them to vLLM as ordinary low-priority chat completions — while online clients (thick arrow) reach the engine directly, never through the gateway. Results settle idempotently, are metered at the batch discount, and are assembled into the output and error files the client downloads.




Figure 11: The complete loop. A realtime model plans the work; the optimizer lowers the plan into barrier waves of rendered calls; the OpenAIBatchAdapter uploads a wave as JSONL and stamps a server-side idempotency key in the batch’s metadata, so a crashed run can adopt its own orphaned batch. Tidal admits, stores and dispatches the wave into a vLLM that is simultaneously serving online users; the adapter fetches the output and error files and reassembles the wave by union over custom_id; the verifier runs the results and applies what passes into a git worktree, which feeds the next wave. This is the request lifecycle from client intent to applied code, entirely on self-hosted capacity at batch pricing. The client-side stages (planner, optimizer, waves, verifier) are detailed in the companion paper [29]; this figure shows only their interface to the serving tier.

Short prompts (208 tokens) get 1.9 $\times$, so the $\approx 1\text{k}$ -token crossover is an interpolation between two measured points. Load-bearing caveats: debug-grade connector; all-or-nothing exact-prompt-hash keying (partial prefix reuse is LMCache/Mooncake territory [18, 19]); GPU KV-connector mode forces piecewise cudagraphs.

A-D: signal mapping. Table 8. A-D needs no new policy, only new signals; the non-rename nuance is targeting prefill-worker troughs.

Table 8: A-D signal mapping to a Dynamo-style disaggregated deployment.

tidal signal	Dynamo counterpart
kv_usage	KVBM block metrics
waiting	router queue depth
observed rate	per-worker throughput

D Full deadline-stress grid

References

- [1] A. Agrawal et al. Taming Throughput-Latency Tradeoff in LLM Inference with Sarathi-Serve. OSDI 2024. arXiv:2403.02310.




Figure 12: The A-ladder, drawn. The four rungs of Table 6, in order of widening scope: A0 places deferrable work inside one aggregated engine, A-F across the replicas of a fleet, A-D into the idle *phase pool* of a disaggregated deployment, and A-P across *time* itself, by freezing a finished prefill's KV to a durable store and thawing it into a decode worker hours later. Each panel carries the advantage that rung buys and the number that evidences it; A-D is drawn dimmed because it is design plus a metric mapping (Table 8) rather than a measurement. The last rung makes the section's one-liner literal: *disaggregation separates prefill from decode in space; a deadline-contracted batch tier separates them in time*.

Table 9: All deadline-stress runs (technique A, 15-minute windows).

run	online load	items	completed	makespan	min. priority
saturated, best-effort	3.0 req/s	900	900/900	692 s	100
easy, best-effort	2.0 req/s	350	350/350	204 s	100
easy, laxity	2.0 req/s	350	350/350	188 s	91
tight, best-effort	2.6 req/s	500	500/500	351 s	100
tight, laxity (+floor)	2.6 req/s	500	500/500	328 s	66




Figure 13: A-F mechanism, per replica: measured batch completions (bars) against each replica’s own analytic online rate (line). Volume splits evenly; *timing* follows each replica’s trough.

- [2] S. Williams, A. Waterman, D. Patterson. Roofline: An Insightful Visual Performance Model for Multicore Architectures. *Communications of the ACM* 52(4):65–76, 2009.
- [3] G.-I. Yu et al. Orca: A Distributed Serving System for Transformer-Based Generative Models. OSDI 2022.
- [4] B. Wu et al. Fast Distributed Inference Serving for Large Language Models. arXiv:2305.05920.
- [5] B. Sun et al. Llumnix: Dynamic Scheduling for Large Language Model Serving. OSDI 2024. arXiv:2406.03243.
- [6] Y. Zhong et al. DistServe: Disaggregating Prefill and Decoding for Goodput-optimized LLM Serving. OSDI 2024. arXiv:2401.09670.
- [7] P. Patel et al. Splitwise: Efficient Generative LLM Inference Using Phase Splitting. ISCA 2024. arXiv:2311.18677.
- [8] T. Sun, P. Wang, F. Lai. HyGen: Efficient LLM Serving via Elastic Online-Offline Request Co-location. arXiv:2501.14808.
- [9] Y. Qiao et al. ConServe: Fine-Grained GPU Harvesting for LLM Online and Offline Co-Serving. arXiv:2410.01228.
- [10] Y. Zhao et al. BlendServe: Optimizing Offline Inference for Auto-regressive Large Models with Resource-aware Batching. arXiv:2411.16102.
- [11] Niyama: Breaking the Silos of LLM Inference Serving. arXiv:2503.22562.
- [12] FREESH: Fair, Real-time, Energy-Efficient Scheduling for LLM Serving. arXiv:2511.00807.
- [13] QLM: Queue Management for SLO-Oriented Large Language Model Serving. SoCC 2024. arXiv:2407.00047.
- [14] Ascendra: Dynamic Request Prioritization for Efficient LLM Serving. arXiv:2504.20828.
- [15] SCORPIO: Serving the Right Requests at the Right Time. arXiv:2505.23022.

- [16] Online-Offline Co-location for LLM Serving. [arXiv:2511.21862](#).
- [17] Echo: Efficient Co-scheduling of Hybrid Online-Offline Tasks. [arXiv:2504.03651](#).
- [18] R. Qin et al. Mooncake: A KVCache-centric Disaggregated Architecture for LLM Serving. [arXiv:2407.00079](#).
- [19] LMCache: a KV-cache layer for LLM serving (prefix reuse, tiered storage, transfer engine). [github.com/LMCache/LMCache](#).
- [20] NVIDIA Dynamo: a datacenter-scale distributed inference serving framework, 2025. [github.com/ai-dynamo/dynamo](#).
- [21] A. K. Mok. Fundamental Design Problems of Distributed Systems for the Hard- Real-Time Environment. MIT, 1983.
- [22] D.-M. Chiu, R. Jain. Analysis of the Increase and Decrease Algorithms for Congestion Avoidance in Computer Networks. *Computer Networks and ISDN Systems* 17(1):1–14, 1989.
- [23] W. Kwon et al. Efficient Memory Management for Large Language Model Serving with PagedAttention. SOSP 2023. [arXiv:2309.06180](#).
- [24] R. Abhyankar et al. InferCept: Efficient Intercept Support for Augmented LLM Inference. ICML 2024. [arXiv:2402.01869](#).
- [25] vLLM RFC: Priority Scheduling. [github.com/vllm-project/vllm/issues/6077](#).
- [26] vLLM RFC: SLA-Tiered Scheduling (closed, not planned). [github.com/vllm-project/vllm/issues/30256](#).
- [27] vLLM PR: OpenAI-compatible online Batch and Files API (open). [github.com/vllm-project/vllm/pull/44445](#).
- [28] lazycode: plan with a realtime LLM, execute on batch APIs. [github.com/rajagurunath/lazycode](#).
- [29] G. Lunkupali Venugopal. LazyCode: Compiling Interactive Intent into Batch Execution — a Query-Optimizer Architecture, Its Economics, and the Limits of Overnight Coding Agents. Companion paper, 2026.