Does an Asymmetric-Reward E-DDQN Improve Safety-Prioritized Cybersickness Detection in Virtual Reality? A Leakage-Free Comparison with Standard DQN and Cost-Sensitive Baselines

Rajai Darabee, Manoranjitham Muniandy, Omar Shindi, Cheng Wai Khuen, and Ebrahim Hamid Sumiea

***Abstract*—Reinforcement-learning (RL) detectors with asymmetric rewards have been proposed for safety-prioritized detection, where a missed event costs more than a false alarm. We ask whether such a detector improves cybersickness detection in virtual reality (VR) once evaluation is free of data leakage. E-DDQN is a dueling Double Deep Q-Network whose reward penalizes a missed cybersickness event five times more than a false alarm. On the public UFFCSData gameplay dataset (35 sessions, 9,390 one-second samples), oversampling before a random row-level split placed exact copies of 92 % of the positive test rows in the training data and let an untuned classifier reach ROC-AUC 0.995; a session-grouped split of the same features gave 0.523. We prove that on logged data the alarm cannot affect future observations, so the task is a contextual bandit and the 5:1 reward induces exactly the decision rule of 5:1 cost-sensitive classification. Under a nested, session-grouped protocol fixed before testing, with equal tuning budgets for seven models, E-DDQN had a 5:1 expected cost of 0.663 and ROC-AUC 0.538. It did not outperform a standard DQN (0.584, 0.661) and had a higher cost than a cost-weighted random forest (0.491, 0.688; Holm-adjusted group-bootstrap $p = 0.006$). A logistic regression on elapsed time alone, added as a post-hoc baseline, reached the highest ROC-AUC of all models (0.704), statistically indistinguishable from the random forest. No model combined high recall with a controlled false-alarm rate: at the cost-optimal thresholds, 82–97 % of non-event seconds raised an alarm. Bounded perturbations of the logged telemetry changed ROC-AUC by at most 0.089. The asymmetric reward is a cost-sensitive operating point rather than a new learning objective, and RL detectors should be compared with cost-weighted and exposure-time baselines under participant-independent evaluation.**

***Index Terms*—Cybersickness, virtual reality, deep reinforcement learning, double deep Q-network, contextual bandit, cost-sensitive learning, data leakage, safety-critical detection.**

I. Introduction

Immersive virtual reality (VR) is used in clinical rehabilitation, industrial and defense training and human-performance assessment, where the headset shapes perception, balance and spatial orientation rather than merely presenting information. Cybersickness—nausea, disorientation, oculomotor strain and, in severe cases, postural instability—is a long-standing side effect of the sensory conflict that VR creates [1]. It can also be induced deliberately: an adversary who manipulates rendering parameters such as frame pacing, camera motion or field of view can make users sick or unsafe [2]–[4]. In both cases a detector that recognizes cybersickness during immersion, so that a mitigation can be triggered, is a safety function, and its two errors are not equally costly: a missed event leaves the user exposed to harm, whereas a false alarm causes a brief, recoverable interruption.

Detectors have progressed from post-exposure questionnaires to deep temporal and multimodal models of physiological, eye-tracking and gameplay data [5]–[10]. To encode unequal error costs, several authors have cast classification as a sequential decision problem and trained deep Q-networks with class-dependent rewards [11], [12]. E-DDQN follows this line for cybersickness: a dueling Double DQN [13], [14] whose reward penalizes a missed event five times more than a false alarm, trained with class-balanced replay and soft target updates.

Two questions must be answered before such a detector can be credited with a safety benefit. The first concerns evaluation. Gameplay telemetry is logged about once per second and self-reported discomfort changes rarely within a session, so any split that places seconds of the same session or participant in both training and test data rewards recognition of the session rather than detection of cybersickness. Oversampling before splitting is a known source of such leakage [15], and published results on the gameplay dataset used here were obtained by splitting samples rather than participants [16]. An earlier, unpublished version of the present study reported 96.88 % accuracy for E-DDQN under an oversampling-before-splitting protocol. The second question concerns the formulation. It is rarely made explicit what an asymmetric reward adds to classical cost-sensitive learning [17], and RL detectors are seldom compared with cost-weighted supervised models tuned and thresholded under the same rules.

We therefore address four research questions on the public UFFCSData dataset [18]:

- RQ1 How much does the split protocol change the measured performance?
- RQ2 What does the asymmetric reward add, formally, to cost-sensitive classification?
- RQ3 Under leakage-free evaluation, does E-DDQN outperform a standard DQN, cost-weighted supervised models and

R. Darabee, M. Muniandy, C. W. Khuen and E. H. Sumiea are with the Faculty of Science, Management & Computing, Universiti Teknologi PETRONAS, 32610 Seri Iskandar, Perak, Malaysia. O. Shindi is with the School of Information Technology, Crown Institute of Higher Education, Sydney, Australia. Corresponding author: R. I. A. Darabee (e-mail: rajai_24006920@utp.edu.my).

a minimal exposure-time baseline, and does any model meet a safety-prioritized operating target?

RQ4 How sensitive are the detectors to bounded manipulation of the telemetry channels that an adversary could influence?

The contributions are:

1) *Leakage audit.* We show that oversampling before a random row-level split places exact copies of 92 % of the positive test rows in the training data and lets an untuned classifier reach ROC-AUC 0.995, whereas a session-grouped split of the same features gives 0.523 (Section V-A).
2) *Formal link between RL and cost-sensitive learning.* We prove that, on logged data, the alarm cannot change future observations, so detection is a contextual bandit, and that the 5:1 reward induces exactly the Bayes decision rule $P(y = 1 \mid s) \geq 1/6$ of 5:1 cost-sensitive classification (Section III-D).
3) *A matched, leakage-free benchmark.* We compare E-DDQN with a standard DQN, a contextual-bandit variant and four cost-weighted supervised models under a nested, session-grouped protocol fixed before testing, with identical tuning budgets, checkpoint and threshold rules and paired statistics; two exposure-time baselines were added post hoc under the same protocol (Sections III-B–III-H).
4) *Findings.* E-DDQN does not outperform the standard DQN and has a higher cost than a cost-weighted random forest; elapsed time alone ranks seconds as well as any model; and no model combines high recall with a controlled false-alarm rate (Section V).
5) *Diagnosis and stress tests.* Bootstrapping and validation-based selection explain E-DDQN's under-performance (Section V-G); bounded telemetry perturbations show that all detectors rely mainly on exposure time and questionnaire answers (Section V-I).
6) *Reproducibility.* Code, the fixed protocol and per-sample predictions are released so that every number in the paper can be regenerated from the raw data.

Section II reviews related work, Section III presents the methods, Section IV the setup, Section V the results and Section VI the discussion; Section VII concludes.

II. Related Work

A. Cybersickness Detection and Its Evaluation

Questionnaires such as the Simulator Sickness Questionnaire [19] measure discomfort after exposure and cannot capture onset during immersion [1], which motivates sensor-driven detection. Dennison et al. [5] related physiological signals to cybersickness reports; Islam et al. detected and forecast severity from heart rate, breathing, heart-rate variability and skin conductance [6] and later fused eye- and head-tracking data [7]; Liu et al. used EEG with a CNN-ECA-LSTM network [8]; Yalcin et al. combined bidirectional LSTMs with GAN-based augmentation of consumer-grade physiological data [9]; and Jeong and Han applied transformers to multimodal time series [10]. Explainable models have been used to identify dominant features and to shrink detectors for deployment [16], [20], [21]. A systematic review notes that most detectors classify the current state rather than anticipating onset, and that evaluation protocols vary widely [22].

The gameplay data used here were collected by Porcino et al. [18], [23], who used symbolic machine learning to identify likely causes of discomfort such as rotation and acceleration [24]. The same gameplay data were used by TruVR, which reported 94.10 % accuracy with explainable boosting machines trained on 70 % of the samples and tested on the remaining 30 % [16], and in work on attacks against cybersickness detectors [4]. Splitting samples rather than participants has been used in this literature [16]; with 1-Hz samples and slowly changing labels, it allows a model to recognize sessions it has already seen [15], [25], [26]. We quantify this effect on the gameplay data in Section V-A; we do not re-evaluate the cited studies, whose exact pipelines are not available to us.

B. Adversarial Threats to VR Users and Detectors

VR mediates perception and balance and therefore exposes an attack surface distinct from conventional software [27], [28]. Tseng et al. showed that perceptual manipulations such as redirected walking can be repurposed to cause physical harm [2], and Cheng et al. studied user reactions to perceptual-manipulation attacks in mixed reality [29]. Odeleye et al. described frame-rate manipulation attacks that can induce VR sickness and detected them with an isolation forest [3]. Detectors themselves can be attacked: Kundu et al. crafted adversarial input perturbations that stop deep cybersickness detectors from triggering mitigation, evaluated them on two public datasets including the gameplay data used here, and proposed an XAI-guided attack detector [4]; Ahmed et al. built an open-source testbed in which gradient-based attacks (MI-FGSM, PGD, C&W) degrade deep detectors that drive a field-of-view mitigation in closed loop [30]. These works perturb detector inputs by optimization; the stress tests in this paper instead apply bounded, physically motivated manipulations to the logged telemetry channels (Section III-G), and neither approach measures what a manipulation would do to a participant.

C. Reinforcement Learning for Imbalanced or Cost-Sensitive Detection

Deep Q-networks [31] overestimate action values, which Double DQN reduces by decoupling action selection and evaluation [13]; dueling heads separate state value from action advantage [14]. Lin et al. cast imbalanced classification as a sequential decision process solved by DQN with larger rewards for minority-class samples [11], and Yang et al. combined dueling and double Q-learning with a custom reward for multi-class imbalanced clinical prediction [12]. E-DDQN applies the same ingredients to cybersickness. Safe-RL research shows that penalties shape how risk-averse a learned policy is [32], but the relation between asymmetric rewards and classical cost-sensitive thresholding [17] is rarely made explicit, and RL detectors are seldom compared with cost-weighted supervised models under the same tuning and threshold rules.

D. Gap Addressed

Table I summarizes the gaps this study addresses. The common thread is that a safety benefit can only be attributed to a detector design when the evaluation excludes leakage, the comparison is matched, and the decision rule is stated in terms of the costs it encodes.

III. Methods

Fig. 1 summarizes the procedure. The data are rebuilt from the original session exports; every split is made at the level of independent session-linkage groups *before* any feature is computed; all learned preprocessing is fitted on training groups only; the learning problem is formalized explicitly (Section III-D); and every model, including E-DDQN, is tuned, checkpointed and thresholded by one validation-only protocol fixed before testing (Section III-H).

A. Data, Provenance and Target

The experiments use UFFCSData [18], [23], [24], a public dataset in which volunteers played a race game and a flight game in a head-mounted display while the game logged, about once per second, the player's speed and acceleration, the camera orientation (quaternion components), the frame rate, the region of interest, session-configuration flags and the participant's self-reported discomfort level on a 0–3 scale; a Cybersickness Profile Questionnaire (CSPQ: gender, age band, VR experience, glasses, vision problems, eye dominance, flicker sensitivity) is stored with every session. We rebuilt every input from the original XML exports rather than from derived files. The dataset authors' curated release (35 seated sessions recorded in December 2019; 9,390 samples) is identical, sample by sample, to 35 of the raw exports and is our evaluation set. The 37 standing-posture sessions recorded in October 2019 are used *only* to debug code and calibrate training budgets; two further raw sessions that the dataset authors excluded are not used.

The binary target is $y_t = 1$ (*cybersickness event*) if the reported discomfort level at second t is at least 1, and $y_t = 0$ otherwise. The prevalence is 44.2 % (Flight 41.2 %, Race 48.1 %). Grades 2–3 occur in 1,450 of 3,993 Race samples but in only 41 of 5,397 Flight samples. Within a session the label changes rarely (on average about once), and 9 of the 35 sessions never report discomfort. We stress that y marks self-reported discomfort, *not* the presence of an attack: no session in the dataset was attacked.

B. Unit of Independence and Splits

The release contains no participant identifier, and sessions are not independent: some participants restarted after an aborted session (e.g., a 104-s session followed 108 s later by a full session with an identical nine-field CSPQ profile). We therefore form conservative *session-linkage groups*: sessions are linked if their CSPQ profiles are identical, or if a session follows an aborted one (< 200 samples) within 180 s with at most two differing questionnaire fields; connected components are groups. This yields 21 groups. The rule may merge different people who share a profile—which only makes evaluation more conservative—but it cannot reveal one person who answered the questionnaire differently in non-consecutive sessions; we report this residual risk as a limitation.

All splits are made at the group level. A nested design is used: 5 outer folds (stratified by game and label) provide test data, and within each outer development set 3 inner grouped folds provide validation data for hyper-parameter search, checkpoint selection and threshold selection. Every sample of the evaluation set is therefore predicted exactly once, by models that never saw its session, its linkage group or its exact questionnaire profile. Executable checks confirm zero session, group and profile overlap and zero duplicated feature rows between any development set and its test fold.

C. Causal Feature Engineering and Preprocessing

Features of second t use only seconds $0, \ldots, t$ of the same session (verified by recomputing features on sessions truncated at random t). They comprise the game indicator, elapsed time, instantaneous speed, acceleration and |acceleration|, the camera quaternion components, the per-second orientation change $\|q_t - q_{t-1}\|$, the frame rate (the logger writes 0 on the very first sample of some sessions; this artifact is imputed with the training median), the region of interest, trailing-window (5 s and 15 s) means, standard deviations, deltas, maxima, minima, acceleration-spike rates and frame-drop fractions, and cumulative exposure descriptors (cumulative orientation change, spike and frame-drop counts, running mean speed); 39 telemetry features in total, plus 14 CSPQ indicators. The spike threshold (90th percentile of |acceleration|) and the imputation value are learned on training rows only; the frame-drop threshold (80 fps, i.e. $> 11\%$ below the 90-Hz target) is fixed. Features are scaled with a median/IQR scaler fitted on training rows. Constant or redundant columns were removed: the field of view, the static-frame and auto-camera flags are constant within each game (pure game indicators), four configuration flags and posture are constant overall, and the absolute player position was excluded because it encodes elapsed course distance and is absent in the October wave. Which of four feature sets a model uses—*telemetry*, *telemetry+profile*, a small a-priori *exposure* set (game, elapsed time, cumulative orientation change, cumulative spikes, running and 15-s mean speed, 15-s mean rotation rate and |acceleration|), or *exposure+profile*—is a hyper-parameter chosen on validation folds. Two further sets, *time* (elapsed time only) and *time+game*, are used only by the post-hoc baselines of Section III-F. No oversampling or synthetic data are used anywhere; class imbalance is handled only inside training.

D. Decision Formulation: MDP or Contextual Bandit?

As in DQN-based detection [11], [12], detection is cast as a sequential decision process over each recorded session (an *episode*). The state $s_t \in \mathbb{R}^d$ is the causal feature vector at second t; the action $a_t \in \{0, 1\}$ is *stay silent* or *raise an alarm*; the reward is $r_t = R(a_t, y_t)$ with

$$\begin{aligned} R(1,1) &= +0.5, \quad R(0,0) = +0.1, \\ R(0,1) &= -0.5, \quad R(1,0) = -0.1; \end{aligned} \tag{1}$$

TABLE I
GAPS IN THE EVALUATION OF ASYMMETRIC-REWARD CYBERSICKNESS DETECTORS AND HOW THIS STUDY ADDRESSES THEM.

Gap	Evidence	This study
Sample-level splits of 1-Hz session data	Sample-level splits on the same gameplay data [16]; leakage literature [15], [25], [26]	Quantified leakage; session-linkage groups, nested grouped evaluation, train-only preprocessing, protocol fixed before testing
Relation of asymmetric rewards to cost-sensitive learning left implicit	[11], [12]	Proof that the 5:1 reward equals the 5:1 cost-sensitive Bayes threshold (Eq. 3); RL and cost-weighted models on one probability scale
RL detectors not compared with matched cost-sensitive or minimal baselines	–	Seven models with equal budgets and rules; two exposure-time baselines; group-bootstrap inference with multiplicity adjustment
Robustness assessed with optimization-based input attacks only	[4], [30]	Bounded, physically motivated telemetry perturbations with adaptive evasion and false-alarm worst cases




Fig. 1. Leakage-free evaluation pipeline. Blue: data construction (no step looks across a partition boundary); orange: model development using inner (validation) folds only; green: single evaluation of each outer-test fold with the frozen protocol.

the next state s_{t+1} is the next second *of the same session*, and the last sample of a session is terminal. No transition ever links two sessions.

Because the telemetry was logged while participants played, without any alarm in the loop, the action cannot influence later observations: $P(s_{t+1} \mid s_t, a_t) = P(s_{t+1} \mid s_t)$. For any discount $\gamma < 1$ the optimal action-value function then decomposes as

$$Q^*(s,a) = \mathbb{E}[R(a,y) \mid s] + \gamma\, \mathbb{E}[V^*(s_{t+1}) \mid s_t = s], \quad (2)$$

whose second term does not depend on a. Hence (i) the optimal policy is myopic for every γ, i.e. the logged-data problem is a *contextual bandit* [33] rather than a control problem in which actions steer future states; and (ii) with $p(s) = P(y = 1 \mid s)$,

$$Q^*(s,1) - Q^*(s,0) = p(s)\,\Delta_{\mathrm{FN}} - (1 - p(s))\,\Delta_{\mathrm{FP}}, \quad (3)$$

with regrets $\Delta_{\mathrm{FN}} = R(1,1) - R(0,1) = 1.0$ and $\Delta_{\mathrm{FP}} = R(0,0) - R(1,0) = 0.2$. The greedy policy alarms iff $p(s) \geq \Delta_{\mathrm{FP}}/(\Delta_{\mathrm{FN}}+\Delta_{\mathrm{FP}}) = 1/6$, which is exactly the Bayes-optimal decision of a cost-sensitive classifier with misclassification costs $C_{\mathrm{FN}} : C_{\mathrm{FP}} = 5 : 1$ [17]. The asymmetric reward is therefore not a different objective from cost-sensitive learning: it encodes the same 5:1 operating point. Bootstrapping with $\gamma > 0$ adds an action-independent term whose estimation noise enters both Q-values; it cannot improve the optimal policy and helps or hurts only through estimation effects. We therefore treat $\gamma \in \{0, 0.5, 0.9, 0.99\}$ as a hyper-parameter selected on validation data and also evaluate the $\gamma = 0$ special case as a separately tuned model (E-CB). A genuine MDP would require the alarm to change future rendering or symptoms (e.g., a mitigation in the loop); no such intervention exists in the data, so we make no claim that E-DDQN learns adaptive sequential control. Equation (3) also gives every Q-learner a calibrated-probability scale, $\hat{p}(s) = (\Delta Q + \Delta_{\mathrm{FP}})/(\Delta_{\mathrm{FN}} + \Delta_{\mathrm{FP}})$, used to place all models on a common score scale.

E. E-DDQN

Network. A multilayer trunk (width and depth tuned) with batch or layer normalization [34], ReLU and dropout [35] feeds a dueling head [14], $Q(s,a) = V(s) + A(s,a) - \frac{1}{2}\sum_{a'} A(s,a')$, with raw (unsquashed) Q-values. *Target.* The Double-DQN target [13] with terminal flags,

$$y_t = r_t + \gamma(1 - d_t)\, Q_{\theta^-}\big(s_{t+1}, \arg\max_{a'} Q_\theta(s_{t+1}, a')\big), \quad (4)$$

where the online arg-max is computed in evaluation mode, and the Huber loss [36] is minimized with Adam [37], weight decay, gradient clipping at 1.0 and a cosine learning-rate schedule [38]. *Target network.* Polyak averaging $\theta^- \leftarrow (1 - \tau)\theta^- + \tau\theta$ [39] after every update; the batch-normalization running statistics are copied as well. *Replay.* A circular buffer [40] from which minibatches are drawn with a fixed class composition ρ (Normal) and $1 - \rho$ (event). *Exploration and warm-up.* ε-greedy exploration decaying per epoch from 1.0 to 0.01; optional warm-up with uniformly random actions. *Full-information replay.* Because labels are available offline, the reward of *both* actions is known; E-DDQN may store the counterfactual action together with *its own* reward, a valid transition that turns Q-learning into cost-sensitive regression of $\mathbb{E}[R \mid s, a]$. Whether to use it is tuned. *Checkpointing.* Every second epoch the agent is scored on the inner validation groups; the epoch with the lowest achievable 5:1 cost (ties: higher PR-AUC) is kept. Algorithm 1 summarizes training. *Implementation pitfalls.* Three errors are easy to make when a

Algorithm 1 E-DDQN training for one inner split

Initialize θ, $\theta^- \leftarrow \theta$, buffer $\mathcal{D}$; optional warm-up with random actions on within-session transitions
for epoch $= 1, \ldots, E$ **do**
  Concatenate training sessions in random order, each in temporal order; mark the last second of each session terminal
  for each chunk of 256 consecutive transitions **do**
    $a_t \leftarrow \varepsilon$-greedy on $Q_\theta(s_t, \cdot)$; $r_t \leftarrow R(a_t, y_t)$
    store $(s_t, a_t, r_t, s_{t+1}, d_t, y_t)$; if full-information replay, also store $(s_t, 1 - a_t, R(1 - a_t, y_t), s_{t+1}, d_t, y_t)$
    every 2 chunks: k updates on class-balanced minibatches (Double-DQN target, Huber loss); Polyak update of θ^- and copy of BN statistics
  end for
  5 consolidation updates; decay ε; cosine LR step
  every 2 epochs: score inner-validation groups; keep θ if the achievable 5:1 cost improves
end for
return checkpoint; score $\hat{p}(s) = (\Delta Q + \Delta_{\mathrm{FP}})/(\Delta_{\mathrm{FN}} + \Delta_{\mathrm{FP}})$

classifier is trained as a Q-learner, and all three were present in an earlier implementation of this study: (i) building transitions across session boundaries, so that the next state of a session's last second is the first second of another session; (ii) storing the true label as the action while computing the reward of a different, exploratory action (a form of teacher forcing that trains the correct action toward the penalty of the wrong one); and (iii) averaging only the parameters into the target network, so that its batch-normalization statistics never leave their initial values. Executable unit tests guard against each of them and also verify the 5:1 regret ratio and bounded Q-values.

F. Matched Baselines

All models receive the same splits, the same four candidate feature sets, the same binary target, the same random-search budget (16 configurations; 12 for logistic regression), the same checkpoint rule (neural models), the same cross-fitted training recipe and the same threshold rules. **Standard DQN** [31]: symmetric ± 1 reward, single max-operator target, periodic hard target copies (every 10, 100 or 500 updates), uniform replay, plain (non-dueling) head, same episodes and transitions; γ is tuned as for E-DDQN. **E-CB**: E-DDQN with $\gamma = 0$ (contextual bandit; the target network and double estimator are then inactive by construction). **CS-MLP**: a cost-sensitive multilayer perceptron with the same trunk family and a positive-class-weighted cross-entropy ($w = 5$, i.e. the same 5:1 cost), uniform or class-balanced minibatches, checkpointed like the agents. **Logistic regression**, **histogram gradient boosting** and **random forest** [41] with class weight 5. For a weighted model the output p_w is mapped back to $\hat{p} = p_w/(5 - 4p_w)$, so that every model's score estimates $P(y = 1 \mid s)$ and the Bayes cut-off is $1/6$ for all of them. Two trivial references are reported: *always alarm* and *never alarm*. *Post-hoc exposure-time baselines.* Because the labels are close to step functions within a session and the primary analysis selected exposure features for most models, two minimal baselines were specified after the primary analysis and run under exactly the same splits, selection, checkpoint and threshold rules and seeds: **Time-LR**, a class-weighted logistic regression on elapsed time only (all six values of C), and **Time+game HGB**, gradient boosting on elapsed time and the game indicator (same search space and budget as HGB). Both are reported separately from the primary comparison.

G. Threat Model and Telemetry-Perturbation Stress Tests

The motivating threat is an adversary who controls the rendering or locomotion pipeline (e.g., a malicious modification or compromised runtime) degrades frame pacing [3], distorts camera or locomotion motion, or manipulates the field of view to induce or exploit cybersickness [2], [4]. The dataset contains *no attacked sessions* and no measurement of what any manipulation would do to a participant. We therefore evaluate only what the data support: *synthetic, bounded perturbations of the logged telemetry channels* of the outer-test sessions, after which the causal features are recomputed with the frozen, training-fitted featurizer—exactly as a deployed monitor would see manipulated telemetry. Labels are never changed; an indicator z marks perturbed seconds. Scenarios (frozen before evaluation): *frame-rate capping* to 72/60/45 fps (Type I); *camera-orientation jitter* $\pm 0.02/0.05/0.10$ per quaternion component (Type II); *speed up-scaling* by 10/25/50 % with acceleration recomputed (Type II); *acceleration-spike injection* of 10/20/40 units every 20 s (Type II); each over the whole session or a random 60-s window, all clipped to the ranges observed in the data. *Field-of-view manipulation (Type III) is not evaluated* because the field of view never varies in the data (it is constant within each game), so any perturbation would be pure extrapolation. Two adversarial goals are analyzed with a per-session worst case over the whole-session candidates plus three "hiding" manipulations (speed down-scaling, orientation smoothing, frame-rate restoration): *evasion* (minimize alarms on event seconds; the adversary is given the labels) and *false-alarm induction* (maximize alarms on non-event seconds). Because the adversary chooses among a fixed set of candidates rather than optimizing the input, the worst cases are lower bounds on vulnerability, weaker than the gradient-based attacks of [4], [30]. Labels are kept fixed, so these tests address evasion and false-alarm induction, not the scenario in which a manipulation induces sickness and thereby changes the label. They are feature-space stress tests of the detector, not demonstrations of physical rendering attacks.

H. Evaluation Protocol and Statistics

The protocol was written and committed before any model was trained on the evaluation sessions; the post-hoc analyses described at the end of this subsection were specified and committed after the primary results were known but before they were run. For every model family and outer fold, random search draws the family's configurations; each is trained on each inner split and the configuration with the lowest 5:1 expected cost on the pooled inner out-of-fold (OOF) predictions (at the cost-minimizing threshold; ties broken by PR-AUC) is selected. The selected configuration is then trained for five seeds; for each seed the 3 inner models are kept (each checkpointed on its own validation groups), the outer-test score is the mean of their scores, and the operating threshold is

chosen on the pooled inner-OOF scores of the development groups only. The primary operating rule (D1) minimizes the 5:1 expected cost $c = (5\,\mathrm{FN} + \mathrm{FP})/N$ on those OOF scores; secondary rules are the untuned Bayes cut-off $\hat{p} \geq 1/6$ (D0; for the asymmetric agents this is the greedy arg-max policy) and a validation recall constraint of 0.95. Matched operating points use validation-chosen thresholds for recall targets 0.80–0.99 and specificity targets 0.5 and 0.8. The outer-test folds are never used for any choice.

We report accuracy, precision, recall, specificity, F1, balanced accuracy, MCC [42], G-mean, false-positive and false-negative rates, missed events, the 5:1 expected cost, ROC-AUC and PR-AUC [43], exact confusion matrices, mean ± SD over the five seeds, and 95 % confidence intervals from a bootstrap that resamples linkage groups (2,000 replicates). Paired comparisons use the same test samples: McNemar's test [44], [45] (exact binomial and continuity-corrected χ^2; the contingency table is checked against the error counts, $b - c = \mathrm{err}_B - \mathrm{err}_A$) and a paired group bootstrap of the cost difference. Because consecutive seconds of a session are strongly dependent, the sample-level McNemar test overstates the evidence; the group bootstrap is the primary inference. Event-level metrics (sessions whose event is detected, detection delay after onset, alarm fraction before onset and in event-free sessions) complement the per-second metrics.

Post-hoc analyses. (i) Holm's step-down adjustment [46] of the six group-bootstrap p-values comparing E-DDQN with the other primary models, per operating rule. (ii) A paired group bootstrap of each model's cost against the always-alarm policy, Holm-adjusted over models. (iii) Two grouping sensitivity analyses: a bootstrap that resamples the 35 sessions instead of the 21 groups, and a leave-one-group-out jackknife of every cost and cost difference. (iv) Validation-chosen cost curves: for each false-negative to false-positive ratio $R \in \{1, \ldots, 20\}$ the threshold minimizing $R\,\mathrm{FN} + \mathrm{FP}$ on the pooled inner-OOF scores of each outer fold is applied to that fold's test data, and the test cost is divided by the cost of the better trivial policy at the same R. Bootstrap p-values are two-sided, $2\min\{\Pr(\Delta^* \leq 0), \Pr(\Delta^* \geq 0)\}$ over 2,000 replicates, so the smallest attainable value is about 0.001.

I. Explainability

SHAP values [47] are computed for the decision margin $\Delta Q(s) = Q(s,1) - Q(s,0)$ of E-DDQN (one model per outer fold—the first final model of that fold—with 200 background samples drawn from its training groups and attributions for 400 of its test samples). DeepExplainer [48] was attempted first with its additivity check enabled; it failed that check for the selected layer-normalized networks in every fold, so the expected-gradients estimator of the SHAP library (GradientExplainer) was used instead; the method used in each fold is recorded with the released results. Attributing a single Q-value such as $Q(s,1)$ would mix in the state value $V(s)$ shared by both actions, which does not explain the decision.

IV. Experimental Setup

A. Implementation

All models are implemented in PyTorch [49] and scikit-learn [41] and run on CPU with one thread per process. The data parser, grouping, causal features, agents, baselines, perturbation generator, protocol runner and statistics are released with the paper; one script regenerates every number from the raw XML files.

B. Search Spaces and Budgets

The search spaces (Supplementary Sec. S2.1) are shared wherever a hyper-parameter is common to several families. Neural models: feature set (four options), trunk (64–64, 128–128, 256–256 or 256–512–256), dropout (0–0.3), normalization (batch or layer), learning rate (3×10^{-4}–3×10^{-3}), weight decay (0–10^{-3}) and batch size (256 or 512). Agents additionally: ε decay per epoch (0.90–0.97), warm-up (0 or 4,000 random-action transitions) and updates per learning step (1, 2 or 4); E-DDQN: $\gamma \in \{0, 0.5, 0.9, 0.99\}$, $\tau \in \{0.005, 0.01, 0.05\}$, replay composition $\rho \in \{0.4, 0.5, 0.6\}$ and full-information replay (on/off); E-CB: ρ and full-information replay; DQN: γ and the hard-update period (10, 100 or 500 updates); CS-MLP: uniform or class-balanced minibatches. All agents are trained for 40 epochs (one epoch is one pass over every training session in temporal order), with chunks of 256 transitions, a learning step every two chunks, five consolidation updates per epoch, a 50,000-transition buffer and gradient clipping at 1.0; the CS-MLP is trained for 40 epochs. Validation-based checkpoints are taken every two epochs. These budgets were calibrated on the October-2019 development-only sessions, where validation cost plateaued after 20–30 epochs. Each family receives 16 random configurations (12 for logistic regression), drawn once with a fixed seed and evaluated on every inner split of every outer fold. Gradient boosting and random forests search learning rate, number of iterations, leaf counts, minimum leaf sizes, ℓ_2 regularization, depth and feature sub-sampling; logistic regression searches the inverse regularization strength $C \in [10^{-4}, 10]$. The configuration selected for each outer fold is listed in Supplementary Sec. S2.2.

C. Seeds and Repetitions

Final models are trained with five seeds per outer fold; for every seed the outer-test score is the average of the 3 cross-fitted inner models. We report mean ± SD over seeds and, for paired tests and confidence intervals, the *seed ensemble* (the mean score over the five seeds, with its threshold chosen on the mean OOF score). No seed was selected or discarded.

D. Leakage Audit

To quantify how the split protocol affects measured performance, we evaluated the same 21 raw columns of the curated release under three protocols with an untuned gradient-boosting classifier: (i) oversampling every discomfort grade to the size of grade 0 (5,243 samples) *before* a random 70/15/15 row-level split, the protocol of the earlier, unpublished version

of this study (it reproduces that version's partition sizes, 14,680 / 3,146 / 3,146, exactly); (ii) a row-level split without oversampling; and (iii) the grouped split of Section III-B. The earlier E-DDQN implementation was also run, unmodified, on partitions (i) and (iii). Because that version's 41-feature input files were not available, this is a reconstruction of its protocol rather than an exact reproduction.

V. Results

A. Effect of the Split Protocol (RQ1)

Table II evaluates the same 21 raw columns under three protocols. When every discomfort grade is oversampled to 5,243 samples before a 70/15/15 row split, an untuned gradient-boosting classifier reaches 97.6 % accuracy, 99.8 % recall, MCC 0.935 and ROC-AUC 0.995; 2,170 of the 2,359 positive test rows (92 %) have an exact duplicate in the training split, and every session contributes to both splits. Without oversampling, a row-level split still gives ROC-AUC 0.992 (accuracy 95.3 %), because adjacent seconds of the same session are nearly identical and carry the same label. With a session-grouped split, the same classifier falls to ROC-AUC 0.523 (MCC 0.005). The earlier E-DDQN implementation behaves the same way: 99.2 % recall and MCC 0.870 on the oversampled row-level partition, but MCC −0.004 on a grouped partition. Near-perfect scores on these data therefore measure the recognition of sessions seen during training, not the detection of cybersickness in new sessions, and they are obtained without any reinforcement learning. All results below use the leakage-free protocol of Section III-H.

B. Leakage-Free Comparison under the 5:1 Cost (RQ3)

Table III reports every model tuned, checkpointed and thresholded on validation groups only and scored once on the outer-test groups (all 9,390 samples, 35 sessions). Two facts dominate. First, the detection problem is hard once sessions and participants are not shared: among the primary models, the best ROC-AUC is 0.692 (HGB) and 0.688 (random forest), against a prevalence of 0.44. Second, under a 5:1 cost the cost-minimizing operating point of every model lies close to "always alarm" (cost 0.558): validation-selected thresholds yield high recall but false-positive rates of 82–97 %. The random forest has the lowest cost (0.491±0.003).

E-DDQN ranks last of the 7 primary models: recall 93.4±2.5 %, specificity 7.4±2.7 %, cost 0.663±0.048 (higher than always alarming), ROC-AUC 0.538±0.016 and MCC 0.016. The standard DQN reaches cost 0.584 and ROC-AUC 0.661, and the contextual-bandit variant E-CB cost 0.575 and ROC-AUC 0.653. E-DDQN therefore does not improve on the standard DQN in this controlled comparison.

C. Exposure-Time Baselines

The post-hoc baselines (Table III, Fig. 2) show what the primary models have learned. Time-LR, a logistic regression on elapsed time alone, reaches ROC-AUC 0.704 and PR-AUC 0.605, the highest values of all models. Its ranking performance is statistically indistinguishable from that of the random forest (difference in ROC-AUC +0.016, 95 % CI −0.071 to +0.102; group bootstrap). At the 5:1 operating point, however, the random forest has a lower cost than Time-LR (0.491 vs. 0.548; difference +0.063, CI +0.010 to +0.132, $p = 0.021$), so the additional inputs help the forest at the operating point (fewer missed events and fewer false alarms in the seed ensemble; Table III). Adding the game indicator (Time+game HGB) gives cost 0.517 and ROC-AUC 0.676, again indistinguishable from the random forest (cost difference +0.032, $p = 0.274$; ROC-AUC difference −0.012, $p = 0.760$). Both minimal baselines are better than E-DDQN in ROC-AUC (Time-LR by +0.163, CI +0.063 to +0.287). On these data, therefore, the discrimination available to every model is essentially that of a population onset curve: cybersickness becomes more likely the longer a session lasts.




Fig. 2. ROC curves of the seed-ensemble scores, pooled over the five outer-test folds, for the seven primary models and the two post-hoc exposure-time baselines (dashed and dash-dotted). The legend gives the ROC-AUC of the seed-ensemble score, which can differ slightly from the seed means in Table III.

D. Operating Points, Cost Ratios and the Asymmetric Reward

Table IV contrasts three operating rules. With the untuned Bayes cut-off $\hat{p} \geq 1/6$ (rule D0)—for the asymmetric agents this is the greedy policy $\arg\max_a Q(s,a)$—E-DDQN obtains recall 77.2 % at specificity 28.0 % (cost 0.905), whereas the random forest obtains recall 94.5 % at specificity 34.9 % (cost 0.486). When every model is held to a validation recall of at least 0.95, the random forest again has the lowest cost (0.483; E-DDQN 0.785). At validation-matched recall targets (Table V), the thresholds transfer worst for E-DDQN: at both recall targets it attains lower test recall than every supervised model, and at the 0.95 target it also has a higher false-positive rate than all of them. Reading the ROC curves at fixed recall (descriptive only), the false-positive rate at 95 % recall is 97.7 % for E-DDQN and 65.8 % for the random

TABLE II
EFFECT OF THE EVALUATION PROTOCOL ON THE SAME DATA (21 RAW COLUMNS OF THE CURATED RELEASE; TEST-SPLIT METRICS). "PROXY" MARKS THE RECONSTRUCTION OF THE EARLIER PROTOCOL, WHOSE 41-FEATURE INPUT FILES WERE NOT AVAILABLE.

Model	Evaluation protocol	Acc.	Recall	Spec.	MCC	ROC-AUC
HGB	Oversample to 5,243/grade, then 70/15/15 row split (earlier protocol)	97.6	99.8	91.0	0.935	0.995
HGB	Row-level random split, no oversampling	95.3	94.1	96.3	0.905	0.992
HGB	Grouped 5-fold split (session-linkage groups)	52.2	33.6	66.9	0.005	0.523
E-DDQN (earlier code)	Earlier script, earlier protocol (proxy)	95.2	99.2	83.1	0.870	–
E-DDQN (earlier code)	Earlier script, grouped split (proxy)	41.1	92.1	7.7	−0.004	–

TABLE III
LEAKAGE-FREE COMPARISON (RULE D1: THRESHOLD MINIMIZING THE 5:1 COST ON POOLED INNER-VALIDATION PREDICTIONS). MEAN ± SD OVER FIVE SEEDS OF THE POOLED OUTER-TEST METRICS (9,390 SAMPLES; RECALL, SPECIFICITY, PRECISION, F1 AND BALANCED ACCURACY IN %); FN AND FP ARE EXACT COUNTS OF THE SEED ENSEMBLE. BOLD: LOWEST COST AMONG THE PRIMARY MODELS. HGB, LOGISTIC REGRESSION AND THE POST-HOC BASELINES ARE DETERMINISTIC GIVEN THE DATA, HENCE SD = 0.

Model	Recall	Spec.	Prec.	F1	Bal. acc.	MCC	$\text{Cost}_{5:1}$	ROC-AUC	PR-AUC	FN	FP
E-DDQN	93.4±2.5	7.4±2.7	44.4±0.7	60.2±0.9	50.4±1.2	0.016±0.054	0.663±0.048	0.538±0.016	0.483±0.019	400	4,820
E-CB	97.1±2.9	8.4±2.8	45.6±0.6	62.1±1.0	52.8±1.2	0.122±0.052	0.575±0.055	0.653±0.011	0.562±0.006	140	4,480
DQN	95.2±2.7	14.5±4.9	46.8±1.0	62.8±0.8	54.8±1.6	0.158±0.038	0.584±0.040	0.661±0.013	0.595±0.022	129	4,391
CS-MLP	99.4±0.7	2.8±1.9	44.7±0.4	61.7±0.4	51.1±0.8	0.072±0.049	0.557±0.012	0.644±0.018	0.521±0.022	23	4,925
LogReg	99.1±0.0	8.1±0.0	46.0±0.0	62.9±0.0	53.6±0.0	0.167±0.000	0.532±0.000	0.626±0.000	0.576±0.000	36	4,817
HGB	97.0±0.0	14.6±0.0	47.3±0.0	63.6±0.0	55.8±0.0	0.197±0.000	0.543±0.000	0.692±0.000	0.593±0.000	124	4,479
RF	98.5±0.3	18.2±0.7	48.8±0.2	65.2±0.1	58.3±0.3	0.266±0.004	**0.491±0.003**	0.688±0.002	0.548±0.001	54	4,281
Post-hoc exposure-time baselines (added after the primary analysis)											
Time-LR (elapsed time)	96.7±0.0	15.0±0.0	47.4±0.0	63.6±0.0	55.8±0.0	0.194±0.000	0.548±0.000	0.704±0.000	0.605±0.000	138	4,457
Time+game HGB	97.4±0.0	17.6±0.0	48.3±0.0	64.6±0.0	57.5±0.0	0.239±0.000	0.517±0.000	0.676±0.000	0.550±0.000	107	4,319
Always alarm	100.0	0.0	44.2	61.3	50.0	0.000	0.558	–	–	0	5,243
Never alarm	0.0	100.0	–	–	50.0	0.000	2.208	–	–	4,147	0

TABLE IV
EXPECTED 5:1 COST (MEAN OVER SEEDS) UNDER THREE OPERATING RULES CHOSEN WITHOUT TEST DATA.

Model	D1: min cost	D0: $\hat{p} \geq 1/6$	val. recall ≥ 0.95
E-DDQN	0.663	0.905	0.785
E-CB	0.575	0.663	0.581
DQN	0.584	0.680	0.573
CS-MLP	0.557	0.731	0.544
LogReg	0.532	0.808	0.518
HGB	0.543	0.567	0.511
RF	0.491	0.486	0.483
Always alarm	0.558	0.558	0.558

forest. Because the reward encodes the same 5:1 operating point as a cost-weighted classifier (Eq. (3)), the asymmetric reward provides no advantage that cost-weighted training plus a validation-selected threshold does not already provide.

The cost curves of Fig. 3 show how much the choice of the 5:1 ratio matters. At ratios of 1.5–2, where the cost-optimal policy is not close to a trivial one, the relative costs of all models except E-DDQN lie between 0.72 and 0.91 (random forest: 0.773 at $R = 2$). As R grows, every curve approaches 1, because the Bayes cut-off $1/(1 + R)$ falls far below the prevalence and alarming almost always becomes optimal; at $R = 5$ the random forest's relative cost is 0.868. The random forest stays below the trivial policies at all 10 ratios, E-DDQN at 1 of them. The negative safety result is therefore not an artifact of the particular ratio: the models discriminate weakly at every ratio, and the 5:1 ratio places the operating point where that weakness is most visible.




Fig. 3. Validation-chosen cost curves (post hoc): for each false-negative to false-positive cost ratio R, the threshold minimizing $R\,\text{FN}+\text{FP}$ on the inner-validation predictions is applied to the outer-test fold; the pooled test cost of the seed ensemble is divided by the cost of the better trivial policy (always or never alarm). Values below 1 improve on the trivial policy; the dotted vertical line marks the 5:1 ratio.

E. Statistical Comparison

Table VI compares E-DDQN with every other primary model on identical test samples (seed ensembles, rule D1). Sample-level McNemar tests give $p < 0.001$ for every pair, but they treat 9,390 strongly autocorrelated seconds as independent and overstate the evidence; they are reported for com-

TABLE V
MATCHED OPERATING POINTS: THRESHOLDS CHOSEN ON VALIDATION PREDICTIONS TO REACH THE STATED RECALL OR SPECIFICITY; TEST RECALL (%), FALSE-POSITIVE RATE (%) AND FALSE-POSITIVE COUNT OF THE SEED ENSEMBLE.

	val. recall ≥ 0.90			val. recall ≥ 0.95			val. specificity ≥ 0.80		
Model	Rec.	FPR	FP	Rec.	FPR	FP	Rec.	FPR	FP
E-DDQN	81.7	77.0	4,036	84.5	86.6	4,539	25.2	18.6	974
E-CB	88.6	68.0	3,565	92.4	78.1	4,093	31.2	17.4	910
DQN	88.0	64.2	3,366	91.7	72.7	3,810	32.2	14.2	743
CS-MLP	94.1	78.4	4,111	97.5	85.1	4,463	24.2	12.7	666
LogReg	92.8	73.5	3,856	97.2	81.7	4,285	37.7	22.5	1,181
HGB	95.4	72.2	3,785	97.5	81.7	4,282	24.3	11.3	594
RF	93.7	64.0	3,358	96.9	74.3	3,896	21.0	13.3	695

pleteness, with the contingency identity $b - c = \mathrm{err}_B - \mathrm{err}_A$ checked and recomputed with an independent library. The primary inference is the group bootstrap, which resamples the 21 independent units. E-DDQN's cost exceeds that of every other primary model by +0.175 to +0.242; after Holm adjustment over the six comparisons, only the difference from the random forest remains significant (+0.242, 95 % CI +0.052 to +0.528; adjusted $p = 0.006$), whereas the adjusted p-values for the other five comparisons lie between 0.070 and 0.105. In particular, the difference from the standard DQN (+0.190) is not significant (unadjusted $p = 0.079$).

These conclusions are robust to the choice of resampling unit and to individual groups. Resampling the 35 sessions instead of the groups gives the same pattern (E-DDQN vs. random forest: CI +0.055 to +0.503, Holm-adjusted $p = 0.006$). In a leave-one-group-out jackknife over the 21 groups, the cost difference between E-DDQN and the random forest ranges from +0.137 to +0.284 and never changes sign; the same holds for every other comparison with E-DDQN. Compared with always alarming, the random forest's cost is lower by -0.074 (CI -0.135 to -0.019; unadjusted $p = 0.012$), but after Holm adjustment over the nine models this is not significant ($p = 0.108$); E-DDQN's cost is higher than always alarming by +0.168 (CI -0.024 to +0.466). No model is therefore shown to improve on the trivial policy at the 5:1 ratio.

F. Event-Level Behavior

At the cost-optimal operating points every model flags almost every session: E-DDQN raises an alarm on 96.6 % of the seconds of the 9 sessions in which no discomfort was ever reported and on 82.3 % of the seconds before onset in the 26 sessions with an event (random forest: 75.3 % and 61.3 %). Events are therefore "detected" with zero median delay by construction, not through discrimination.

G. Why E-DDQN Under-Performs: Bootstrapping and Selection Optimism

Validation selected $\gamma = 0.99, 0.99, 0.99, 0.99, 0.9$ for the five outer folds of E-DDQN, i.e. strong bootstrapping, and the exposure+profile feature set in 5 of 5 folds. Section III-D shows that bootstrapping cannot improve the optimal policy here and adds action-independent estimation noise to ΔQ. Two diagnostics agree. (i) The separately tuned $\gamma = 0$ variant (E-CB) ranks much better (ROC-AUC 0.653 vs. 0.538). (ii) Table VII compares, per family, the inner-validation cost of the configuration at the moment it was selected with its outer-test cost. The gap is +0.288 for E-DDQN but between -0.015 and +0.070 for all other models: noisy, high-variance training curves combined with validation checkpointing and selection let E-DDQN configurations look best on validation folds by chance [50]. Q-value estimates stay finite, so the failure is not numerical divergence, but they are poorly scaled. The largest magnitude over all E-DDQN runs is 61.78 (DQN 10.10, E-CB 0.95), and relative to the return bound $r_{\max}/(1-\gamma)$ of each fold's selected discount the largest estimates exceed the bound by up to a factor of 2.3 for E-DDQN (in 2 of 5 folds), 2.2 for DQN and 1.9 for E-CB, i.e. extrapolation on atypical states. The mean greedy-action Q-value differs from its realized discounted validation return by -2.900 for E-DDQN, +0.393 for DQN and +0.088 for E-CB.

H. Component Ablation and Reward-Ratio Sensitivity

Table VIII removes or changes one component of E-DDQN at a time while keeping the configuration selected for each outer fold fixed (five seeds; same protocol). Every variant ranks close to chance (ROC-AUC 0.529–0.576). No single change moves the cost by more than about one seed standard deviation of the full model (0.663 ± 0.048). The lowest cost is obtained by *replacing* the asymmetric reward with the symmetric ± 1 reward (0.625) and the highest ROC-AUC by switching off bootstrapping ($\gamma = 0$; 0.576); hard target copies (0.634), no dueling head (0.644), uniform replay (0.660), no warm-up (0.656) and toggling full-information replay (0.667) leave the cost essentially unchanged, and removing the double estimator slightly increases it (0.681). None of these components can be credited with a gain in safety or accuracy. Every variant is scored on the same implied-probability scale and thresholded with the same rules, so the reward table can act only through the learned scores; at the fixed cut-off $\hat{p} \geq 1/6$ (rule D0) the symmetric-reward variant is not worse either (cost 0.825 vs. 0.905).

Table IX varies the false-negative to false-positive regret of the reward from 1:1 to 10:1 (E-DDQN configuration per fold fixed; ratio 5:1 reproduces the main E-DDQN run bit for bit, which also confirms the determinism of the pipeline). The greedy policy moves along the trade-off exactly as Eq. (3) predicts: recall rises from 52.4 % (1:1) to 77.2 % (5:1) and 80.7 % (10:1), while specificity falls from 58.1 % to 28.0 % and 23.0 %. Once the threshold is chosen on validation data,

TABLE VI
PAIRED COMPARISONS WITH E-DDQN (A) ON THE SAME 9,390 TEST SAMPLES (SEED ENSEMBLES, RULE D1). b: A CORRECT, B WRONG; c: A WRONG, B CORRECT. ΔCOST, ITS CI AND p_{GROUP} COME FROM 2,000 GROUP-BOOTSTRAP REPLICATES (UNADJUSTED; HOLM-ADJUSTED VALUES IN THE TEXT); p_{EXACT} IS THE SAMPLE-LEVEL EXACT MCNEMAR TEST, WHICH IGNORES WITHIN-SESSION DEPENDENCE.

B (vs. A = E-DDQN)	b	c	err_A	err_B	χ^2_{cc}	p_{exact}	$\Delta\text{Cost}_{5:1}$ (A−B) [95% CI]	p_{group}
E-CB	299	899	5,220	4,620	299.5	<0.001	+0.175 [+0.016, +0.448]	0.014
DQN	297	997	5,220	4,520	377.6	<0.001	+0.190 [−0.017, +0.493]	0.079
CS-MLP	402	674	5,220	4,948	68.3	<0.001	+0.190 [+0.005, +0.485]	0.039
LogReg	389	756	5,220	4,853	117.0	<0.001	+0.194 [+0.011, +0.477]	0.026
HGB	203	820	5,220	4,603	370.9	<0.001	+0.183 [+0.011, +0.460]	0.035
RF	293	1,178	5,220	4,335	531.2	<0.001	+0.242 [+0.052, +0.528]	0.001

TABLE VII
SELECTION OPTIMISM: POOLED INNER-VALIDATION 5:1 COST OF THE SELECTED CONFIGURATION (HPO SEED) VERSUS ITS OUTER-TEST COST (MEAN OVER FOLDS AND SEEDS).

Model	Inner-OOF cost at selection	Outer-test cost	Gap
E-DDQN	0.467	0.754	+0.288
E-CB	0.488	0.557	+0.070
DQN	0.478	0.544	+0.065
CS-MLP	0.501	0.534	+0.033
LogReg	0.518	0.531	+0.014
HGB	0.518	0.539	+0.021
RF	0.495	0.481	−0.015

however, all ratios end at statistically indistinguishable costs (0.629–0.673) and similar ranking: the reward ratio sets the default operating point, but it does not create discrimination that a threshold cannot reproduce. The 5:1 ratio is therefore best understood as a declared safety preference whose operating point can equally be reached by cost-weighted training or threshold selection.

I. Robustness under Telemetry Perturbations (RQ4)

Table X reports threshold-free ranking performance under each perturbation fixed before evaluation. 87 % of the model–scenario combinations change the pooled ROC-AUC by less than 0.03 and none by more than 0.089 (the largest drops occur for acceleration-spike injection in E-CB and DQN and for speed down-scaling in gradient boosting), and several perturbations even raise it slightly. This insensitivity is not evidence of a robust safety monitor: it arises because the dominant inputs selected on validation data are exposure time, cumulative exposure and questionnaire answers rather than the manipulated channels, and the exposure-time baselines, whose inputs no perturbation touches, are perfectly insensitive by construction. At the cost-optimal operating points (Table XI), the per-session worst-case evasion adversary lowers recall on event seconds from 90.4 % to 82.9 % for E-DDQN, from 96.6 % to 78.0 % for E-CB and from 98.7 % to 90.5 % for the random forest, while the false-alarm adversary drives the false-positive rate of every model to 94.5–100 % (it is already 81.7–93.9 % without manipulation). These are lower bounds from a weak, candidate-selecting adversary on feature-space perturbations; they do not show what a real rendering attack would do to a participant, and field-of-view manipulation cannot be evaluated because the field of view never varies in the data.




Fig. 4. Mean absolute SHAP value of the E-DDQN decision margin ΔQ, averaged over the five outer folds (one model per fold; attributions on that fold's test groups).

J. Explainability

SHAP attributions of the E-DDQN decision margin ΔQ (Fig. 4) are dominated by *cum_rot*, *elapsed_s*, *speed_mean_sofar*, *CSPQ VR experience: some*, *cum_acc_spikes*. The decisions are driven mainly by exposure time, cumulative exposure and questionnaire answers rather than by instantaneous telemetry, consistent with the exposure-time baselines and with the insensitivity to telemetry perturbations. Because attributions are computed after the decision, they add no latency to detection.

VI. DISCUSSION

A. Answers to the Research Questions

RQ1. The split protocol dominates the measured performance on these data. Row-level splits—with or without oversampling—yield ROC-AUC above 0.99 because adjacent seconds of a session are near-duplicates with the same label; session-grouped evaluation of the same columns gives 0.523. Accuracy figures on gameplay cybersickness data should therefore be read together with the split protocol, and an earlier version of this study, which reported 96.88 % accuracy for E-DDQN, was affected in exactly this way. *RQ2.* On logged data the asymmetric reward encodes a cost-sensitive operating point: the greedy policy is the Bayes rule $P(y = 1 \mid s) \geq 1/6$

TABLE VIII
LEAVE-ONE-COMPONENT-OUT ABLATION OF E-DDQN (SELECTED CONFIGURATION PER OUTER FOLD HELD FIXED; RULE D1; MEAN OVER 5 SEEDS, COST ± SD).

Variant	Recall	Spec.	$\text{Cost}_{5:1}$	ROC-AUC	PR-AUC
Full E-DDQN (selected)	93.4	7.4	0.663±0.048	0.538	0.483
full-information replay toggled	93.7	5.4	0.667±0.106	0.563	0.500
symmetric ±1 reward instead of asymmetric	94.8	8.6	0.625±0.038	0.572	0.517
uniform instead of class-balanced replay	94.3	4.3	0.660±0.045	0.554	0.486
no double estimator (max-operator target)	93.1	5.3	0.681±0.086	0.543	0.491
no dueling head	94.6	5.8	0.644±0.059	0.559	0.494
hard target copy every 10 updates	94.9	6.5	0.634±0.043	0.529	0.472
no warm-up	93.8	7.1	0.656±0.049	0.547	0.497
$\gamma = 0$ (contextual bandit)	94.4	6.4	0.645±0.070	0.576	0.510

TABLE IX
REWARD-RATIO SENSITIVITY OF E-DDQN: OPERATING POINT OF THE GREEDY (ARG-MAX) POLICY, WHOSE IMPLIED CUT-OFF ON $P(y = 1 \mid s)$ IS $1/(1 + R)$, AND OF THE VALIDATION-TUNED THRESHOLD (RULE D1). MEAN (± SD) OVER FIVE SEEDS.

		Greedy policy ($\arg\max_a Q$)			Validation-tuned threshold (D1)			
FN:FP regret	implied cut-off	Recall	Spec.	$\text{Cost}_{5:1}$	Recall	Spec.	$\text{Cost}_{5:1}$	ROC-AUC
1:1	$1/2$	52.4±5.6	58.1±4.8	1.285	94.9	7.4	0.629±0.056	0.558
2:1	$1/3$	69.2±3.3	43.1±1.6	0.999	94.6	6.4	0.642±0.074	0.563
5:1	$1/6$	77.2±3.8	28.0±2.0	0.905	93.4	7.4	0.663±0.048	0.538
10:1	$1/11$	80.7±3.2	23.0±3.3	0.855	92.9	7.4	0.673±0.095	0.552

TABLE X
THRESHOLD-FREE ROBUSTNESS: POOLED OUTER-TEST ROC-AUC OF THE SEED-ENSEMBLE SCORE ON CLEAN TELEMETRY AND UNDER WHOLE-SESSION PERTURBATIONS (THE LAST COLUMN GIVES THE MOST NEGATIVE AND MOST POSITIVE CHANGE OVER ALL 21 WHOLE-SESSION VARIANTS).

Model	Clean	fps≤45	jitter 0.10	speed ×1.5	spikes 40	speed ×0.5	smooth 0.25	min / max Δ
E-DDQN	0.541	0.541	0.593	0.561	0.559	0.532	0.539	−0.008 / +0.053
E-CB	0.659	0.659	0.682	0.648	0.575	0.648	0.658	−0.089 / +0.052
DQN	0.665	0.665	0.677	0.680	0.605	0.632	0.676	−0.064 / +0.035
CS-MLP	0.654	0.649	0.654	0.630	0.652	0.629	0.646	−0.025 / +0.005
LogReg	0.626	0.677	0.639	0.620	0.629	0.608	0.639	−0.017 / +0.051
HGB	0.692	0.694	0.709	0.650	0.698	0.647	0.712	−0.068 / +0.019
RF	0.688	0.689	0.708	0.667	0.683	0.723	0.725	−0.021 / +0.037

of 5:1 cost-sensitive classification, and bootstrapping cannot improve it (Section III-D). *RQ3.* Under leakage-free, matched evaluation E-DDQN does not outperform the standard DQN, has a higher cost than a cost-weighted random forest, and ranks no better than elapsed time alone; no model meets a safety-prioritized target. *RQ4.* Bounded manipulation of the telemetry channels barely changes threshold-free ranking, because the detectors hardly use those channels, while an adaptive adversary with label knowledge can still lower recall by 4–19 percentage points.

B. Is E-DDQN Reinforcement Learning?

With logged data the alarm cannot influence the subsequent telemetry, so the decision problem is a contextual bandit. E-DDQN remains a valid value-based learner of a cost-sensitive detection policy, but (i) the asymmetric reward is mathematically equivalent to a 5:1 cost-sensitive Bayes threshold, so it is a statement about the operating point rather than a different learning objective; (ii) bootstrapping cannot improve the optimal policy, and empirically strong bootstrapping (γ close to 1) made the learned margins noisy and the validation-based selection over-optimistic; and (iii) under bandit feedback the agent observes the reward of one action only, although labels reveal both, which is why full-information replay is the principled way to use the labels. The same reasoning applies to other DQN-based classifiers trained on fixed datasets [11], [12]: unless actions change future observations, their benefit has to come from estimation effects, and they should be compared with cost-weighted supervised models at the same operating point. Adaptive sequential control would require an intervention in the loop—for example an alarm that triggers a rendering mitigation whose effect on later telemetry and symptoms is measured—which no public cybersickness dataset provides.

C. The Safety Objective

A 5:1 cost makes an alarm the cheaper decision whenever $P(y = 1 \mid s) \geq 1/6$. With a prevalence of 0.44 and weakly informative inputs, almost every second satisfies this, so the cost-optimal policy of every model is close to "always alarm": recall is high, but 82–97 % of non-event seconds also trigger an alarm. High recall alone is therefore not evidence of a useful safety monitor. Judged on cost, specificity at matched

TABLE XI
RECALL/FALSE-POSITIVE RATE (%) ON PERTURBED SECONDS AT THE D1 OPERATING POINT, AND PER-SESSION ADAPTIVE WORST CASES (EVASION: MINIMUM RECALL; FALSE-ALARM INDUCTION: MAXIMUM FPR) OVER ALL WHOLE-SESSION CANDIDATES.

Model	Clean Rec./FPR	fps≤45 Rec./FPR	jitter 0.10 Rec./FPR	speed ×1.5 Rec./FPR	spikes 40 Rec./FPR	Adaptive worst case Rec. (evasion)	Adaptive worst case FPR (false alarm)
E-DDQN	90.4/91.9	90.4/91.9	94.0/92.2	93.5/90.7	95.4/94.3	82.9	94.5
E-CB	96.6/85.4	96.6/85.4	96.1/88.2	98.7/95.9	99.3/97.7	78.0	98.9
DQN	96.9/83.7	96.9/83.7	94.8/83.5	97.8/91.8	97.9/95.4	87.3	97.5
CS-MLP	99.4/93.9	100.0/98.3	99.7/96.5	100.0/98.2	99.9/99.1	95.6	100.0
LogReg	99.1/91.9	97.0/86.3	99.2/92.7	99.7/94.9	99.9/96.7	95.4	96.7
HGB	97.0/85.4	97.0/85.9	96.3/82.7	98.2/91.7	98.1/95.7	81.0	96.1
RF	98.7/81.7	98.7/81.3	98.0/81.1	99.0/92.1	99.8/97.4	90.5	98.4

recall, threshold-free ranking and cost curves across ratios, the intended safety objective—near-complete detection with a controlled false-alarm rate—is not achieved by any model on these data. The exposure-time baselines locate the obstacle: once participants are not shared between training and test, the usable signal in game telemetry is mostly how long the session has lasted, which distinguishes individual susceptibility only coarsely.

D. The Adversarial Threat Model

Rendering manipulations that induce sickness are documented [2], [3], and optimization-based input attacks can disable deep cybersickness detectors [4], [30]. UFFCSData, however, contains no manipulated sessions, so its label marks cybersickness, not an attack. Our stress tests therefore answer a narrower question than the cited attack studies: how far bounded, physically motivated changes of the logged frame-rate, orientation and locomotion channels move the detectors' decisions. The small effect on ranking reflects detectors that rely on exposure and questionnaire inputs, not a robust design; a detector that used the telemetry more would also be easier to manipulate through it. Demonstrating detection of real rendering attacks requires data in which manipulations are applied to participants under ethical approval and their physiological effects are measured.

E. Limitations

(i) A single public dataset with 35 curated sessions and 21 independent groups; confidence intervals are wide and fold-to-fold variation is large. (ii) Participant identity cannot be verified; linkage groups are conservative but cannot exclude a participant who answered the questionnaire differently in non-consecutive sessions, and they may merge different people with identical profiles. (iii) The label is a coarse self-report sampled at 1 Hz that changes rarely within a session, and the binary threshold (discomfort $\geq$ 1) merges slight with severe discomfort; a safety monitor might target grades 2–3 only, which occur in just 41 Flight samples. (iv) The exposure-time baselines, the Holm adjustment, the grouping sensitivity analyses and the cost curves were specified after the primary results were known; they were committed before being run and use the same protocol, but they are post hoc. (v) Perturbations are synthetic and feature-space, their physiological effect is unknown, and the adversary is weaker than optimization-based attacks. (vi) Hyper-parameter search used an identical but modest budget (16 configurations per family); a larger budget could change the ranking of the neural models, although the selection-optimism analysis suggests that additional search would mostly increase optimism. (vii) The October-2019 sessions were used only for development and could not serve as an external test set because their camera-orientation channels were not logged.

F. Implications

For cybersickness detection from session data, results should be reported with participant- or session-grouped splits, alongside trivial policies and an exposure-time baseline, because elapsed time alone can match much more complex models. For safety-prioritized detection, an asymmetric reward should be treated as what it is—a cost-sensitive operating point—and RL detectors should be compared with cost-weighted supervised models at matched recall or cost. Claims of robustness to manipulation should state which inputs the detector actually uses, since insensitivity to a channel the detector ignores is not protection.

VII. CONCLUSION

We asked whether an asymmetric-reward dueling Double DQN (E-DDQN) improves safety-prioritized cybersickness detection in VR. On the public UFFCSData gameplay dataset the answer is no. Near-perfect accuracies on these data arise from splits that share sessions between training and test; with session-grouped evaluation the same features give ROC-AUC 0.523. On logged data the detection problem is a contextual bandit, and the 5:1 asymmetric reward induces exactly the Bayes threshold of 5:1 cost-sensitive classification. Under a nested, session-grouped protocol fixed before testing, E-DDQN reached cost 0.663 and ROC-AUC 0.538, did not outperform a standard DQN (cost 0.584, ROC-AUC 0.661) and had a higher cost than a cost-weighted random forest (cost 0.491, ROC-AUC 0.688; Holm-adjusted $p = 0.006$). A post-hoc logistic regression on elapsed time alone ranked seconds as well as any model (ROC-AUC 0.704), and no model combined high recall with a controlled false-alarm rate or was shown to improve on always alarming at the 5:1 ratio. Bounded telemetry perturbations changed ROC-AUC by at most 0.089, because the detectors rely on exposure time and questionnaire answers rather than on the manipulated channels.

Progress on this problem requires datasets with physiological or eye-tracking signals, verified participant identifiers and, for adversarial claims, manipulations applied to participants with measured effects, and evaluations that include grouped splits, trivial and exposure-time baselines, and cost-weighted comparators.

Data and Code Availability

The data are the publicly available UFFCSData release [18] (AGPL-3.0). All code, the evaluation protocol (`configs/protocol.json`, committed before any model was trained on the evaluation sessions), the specification of the post-hoc analyses (`configs/posthoc.json`, committed before those analyses were run), the split tables, the per-sample predictions of every model and the scripts that produce every number, table and figure of this paper are archived at [DOI to be added on deposit]. A single script regenerates everything from the raw XML files. Seeds are fixed for data splitting (20261012), hyper-parameter search (777; 801–802 for the post-hoc baselines) and final training (1000–1004); CPU execution with one thread per process was used, and minor floating-point differences across hardware are possible.

Acknowledgment

The authors thank Universiti Teknologi PETRONAS for institutional and computational support, and the authors of the UFFCSData dataset for making their data public.

Conflict of Interest

The authors declare no conflict of interest.

Funding

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors.

References

[1] P. Caserman, A. Garcia-Agundez, A. Gámez Zerban, and S. Göbel, "Cybersickness in current-generation virtual reality head-mounted displays: Systematic review and outlook," *Virtual Reality*, vol. 25, no. 4, pp. 1153–1170, 2021.

[2] W.-J. Tseng, E. Bonnail, M. McGill, M. Khamis, E. Lecolinet, S. Huron, and J. Gugenheimer, "The dark side of perceptual manipulations in virtual reality," in *Proc. CHI Conf. Human Factors in Computing Systems*, 2022.

[3] B. Odeleye, G. Loukas, R. Heartfield, and F. Spyridonis, "Detecting framerate-oriented cyber attacks on user experience in virtual reality," in *Proc. 1st Int. Workshop Security for XR and XR for Security (VR4Sec), held with SOUPS 2021*, 2021, pp. 1–5.

[4] R. K. Kundu, M. Denton, G. Mongalo, P. Calyam, and K. A. Hoque, "Securing virtual reality experiences: Unveiling and tackling cybersickness attacks with explainable AI," *IEEE Trans. Dependable Secure Comput.*, vol. 22, no. 6, pp. 6040–6057, 2025, arXiv:2503.13419.

[5] M. S. Dennison, A. Z. Wisti, and M. D'Zmura, "Use of physiological signals to predict cybersickness," *Displays*, vol. 44, pp. 42–52, 2016.

[6] R. Islam, Y. Lee, M. Jaloli, I. Muhammad, D. Zhu, P. Rad, Y. Huang, and J. Quarles, "Automatic detection and prediction of cybersickness severity using deep neural networks from user's physiological signals," in *Proc. IEEE Int. Symp. Mixed and Augmented Reality (ISMAR)*, 2020.

[7] R. Islam, K. Desai, and J. Quarles, "Cybersickness prediction from integrated HMD's sensors: A multimodal deep fusion approach using eye-tracking and head-tracking data," in *Proc. IEEE Int. Symp. Mixed and Augmented Reality (ISMAR)*, 2021, pp. 31–40, arXiv:2108.06437.

[8] M. Liu, B. Yang, M. Xu, P. Zan, L. Chen, and X. Xia, "Exploring quantitative assessment of cybersickness in virtual reality using EEG signals and a CNN-ECA-LSTM network," *Displays*, vol. 81, p. 102602, 2024.

[9] M. Yalcin, A. Halbig, M. Fischbach, and M. E. Latoschik, "Automatic cybersickness detection by deep learning of augmented physiological data from off-the-shelf consumer-grade sensors," *Frontiers in Virtual Reality*, vol. 5, p. 1364207, 2024.

[10] D. Jeong and K. Han, "PRECYSE: Predicting cybersickness using transformer for multimodal time-series sensor data," *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 2024.

[11] E. Lin, Q. Chen, and X. Qi, "Deep reinforcement learning for imbalanced classification," *Applied Intelligence*, vol. 50, pp. 2488–2502, 2020.

[12] J. Yang, R. El-Bouri, O. O'Donoghue, A. S. Lachapelle, A. A. S. Soltan, D. W. Eyre, L. Lu, and D. A. Clifton, "Deep reinforcement learning for multi-class imbalanced training: Applications in healthcare," *Mach. Learn.*, vol. 113, pp. 2655–2674, 2024.

[13] H. van Hasselt, A. Guez, and D. Silver, "Deep reinforcement learning with double Q-learning," in *Proc. AAAI Conf. Artificial Intelligence*, 2016, pp. 2094–2100.

[14] Z. Wang, T. Schaul, M. Hessel, H. van Hasselt, M. Lanctot, and N. de Freitas, "Dueling network architectures for deep reinforcement learning," in *Proc. Int. Conf. Machine Learning (ICML)*, 2016, pp. 1995–2003.

[15] S. Kapoor and A. Narayanan, "Leakage and the reproducibility crisis in machine-learning-based science," *Patterns*, vol. 4, no. 9, p. 100804, 2023.

[16] R. K. Kundu, R. Islam, P. Calyam, and K. A. Hoque, "TruVR: Trustworthy cybersickness detection using explainable machine learning," in *Proc. IEEE Int. Symp. Mixed and Augmented Reality (ISMAR)*, 2022, pp. 777–786.

[17] C. Elkan, "The foundations of cost-sensitive learning," in *Proc. Int. Joint Conf. Artificial Intelligence (IJCAI)*, 2001, pp. 973–978.

[18] T. Porcino *et al.*, "UFFCSData: Raw and selected datasets with user tests reporting the level of discomfort during virtual experiments," https://github.com/tmp1986/UFFCSData, AGPL-3.0.

[19] R. S. Kennedy, N. E. Lane, K. S. Berbaum, and M. G. Lilienthal, "Simulator sickness questionnaire: An enhanced method for quantifying simulator sickness," *Int. J. Aviation Psychology*, vol. 3, no. 3, pp. 203–220, 1993.

[20] R. K. Kundu, R. Islam, J. Quarles, and K. A. Hoque, "LiteVR: Interpretable and lightweight cybersickness detection using explainable AI," in *Proc. IEEE Conf. Virtual Reality and 3D User Interfaces (VR)*, 2023.

[21] R. K. Kundu, O. Y. Elsaid, P. Calyam, and K. A. Hoque, "VR-LENS: Super learning-based cybersickness detection and explainable AI-guided deployment in virtual reality," 2023, arXiv:2302.01985.

[22] A. H. X. Yang, N. Kasabov, and Y. O. Cakmak, "Machine learning methods for the study of cybersickness: A systematic review," *Brain Informatics*, vol. 9, p. 24, 2022.

[23] T. Porcino, D. Trevisan, and E. Clua, "An experimental methodology to capture user and gameplay data tied to cybersickness," in *Proc. Workshop on Extended Reality in Games (XR in Games), SBGames*, 2021.

[24] T. Porcino, E. O. Rodrigues, F. Bernardini, D. Trevisan, and E. Clua, "Identifying cybersickness causes in virtual reality games using symbolic machine learning algorithms," *Entertainment Computing*, 2022, ScienceDirect PII S1875952121000707.

[25] S. Kaufman, S. Rosset, C. Perlich, and O. Stitelman, "Leakage in data mining: Formulation, detection, and avoidance," *ACM Trans. Knowl. Discov. Data*, vol. 6, no. 4, p. 15, 2012.

[26] D. R. Roberts *et al.*, "Cross-validation strategies for data with temporal, spatial, hierarchical, or phylogenetic structure," *Ecography*, vol. 40, no. 8, pp. 913–929, 2017.

[27] B. Odeleye, G. Loukas, R. Heartfield, G. Sakellari, E. Panaousis, and F. Spyridonis, "Virtually secure: A taxonomic assessment of cybersecurity challenges in virtual reality environments," *Computers & Security*, vol. 124, p. 102951, 2023.

[28] A. Giaretta, "Security and privacy in virtual reality: A literature survey," *Virtual Reality*, vol. 29, p. 10, 2025.

[29] K. Cheng, J. F. Tian, T. Kohno, and F. Roesner, "Exploring user reactions and mental models towards perceptual manipulation attacks in mixed reality," in *Proc. 32nd USENIX Security Symp.*, 2023.

[30] I. Ahmed, R. K. Kundu, and K. A. Hoque, "Adversarial-VR: An open-source testbed for evaluating adversarial robustness of VR cybersickness detection and mitigation," 2025, arXiv:2512.17029.

[31] V. Mnih *et al.*, "Human-level control through deep reinforcement learning," *Nature*, vol. 518, no. 7540, pp. 529–533, 2015.

[32] J. García and F. Fernández, "A comprehensive survey on safe reinforcement learning," *J. Machine Learning Research*, vol. 16, no. 42, pp. 1437–1480, 2015.

[33] T. Lattimore and C. Szepesvári, *Bandit Algorithms*. Cambridge University Press, 2020.

[34] S. Ioffe and C. Szegedy, "Batch normalization: Accelerating deep network training by reducing internal covariate shift," in *Proc. Int. Conf. Machine Learning (ICML)*, 2015, pp. 448–456.

[35] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: A simple way to prevent neural networks from overfitting," *J. Machine Learning Research*, vol. 15, pp. 1929–1958, 2014.

[36] R. Girshick, "Fast R-CNN," in *Proc. IEEE Int. Conf. Computer Vision (ICCV)*, 2015, pp. 1440–1448.

[37] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2015.

[38] I. Loshchilov and F. Hutter, "SGDR: Stochastic gradient descent with warm restarts," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2017.

[39] T. P. Lillicrap *et al.*, "Continuous control with deep reinforcement learning," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2016.

[40] L.-J. Lin, "Self-improving reactive agents based on reinforcement learning, planning and teaching," *Machine Learning*, vol. 8, no. 3–4, pp. 293–321, 1992.

[41] F. Pedregosa *et al.*, "Scikit-learn: Machine learning in Python," *J. Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.

[42] D. Chicco and G. Jurman, "The advantages of the Matthews correlation coefficient (MCC) over F1 score and accuracy in binary classification evaluation," *BMC Genomics*, vol. 21, p. 6, 2020.

[43] T. Saito and M. Rehmsmeier, "The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets," *PLoS ONE*, vol. 10, no. 3, p. e0118432, 2015.

[44] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947.

[45] T. G. Dietterich, "Approximate statistical tests for comparing supervised classification learning algorithms," *Neural Computation*, vol. 10, no. 7, pp. 1895–1923, 1998.

[46] S. Holm, "A simple sequentially rejective multiple test procedure," *Scand. J. Statist.*, vol. 6, no. 2, pp. 65–70, 1979.

[47] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017, pp. 4765–4774.

[48] A. Shrikumar, P. Greenside, and A. Kundaje, "Learning important features through propagating activation differences," in *Proc. Int. Conf. Machine Learning (ICML)*, 2017, pp. 3145–3153.

[49] A. Paszke *et al.*, "PyTorch: An imperative style, high-performance deep learning library," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[50] S. Varma and R. Simon, "Bias in error estimation when using cross-validation for model selection," *BMC Bioinformatics*, vol. 7, p. 91, 2006.