

Chapter 14

Installing and Updating Software Packages

Registration from the Command Line

A repository in RHEL is a storage location (on the internet or on a local network) that contains software applications and updates for Red Hat Enterprise Linux, allowing users to easily install and update programs using commands like **yum** or **dnf**. It works similarly to an app store but is designed specifically for Linux systems.

To Configure online Repos

To register your account

```
[user@host ~]$ subscription-manager register --username=yourusername \
--password=yourpassword
```

To Unregister your account

```
[user@host ~]$ subscription-manager unregister
```

To Configure Offline Repos\

NOTE :- **/etc/yum.repos.d/**

vi /etc/yum.repos.d/base.repo

[AppStream]

name=AppStream

baseurl=file:///run/media/root/RHEL-9-5-0-BaseOS-x86_64/AppStream

gpgcheck=0

[BaseOS]

name=BaseOS

baseurl=file:///run/media/root/RHEL-9-5-0-BaseOS-x86_64/BaseOS

gpgcheck=0

:wq! – To Save The File

```
[AppStream]
name=AppStream
baseurl=file:///run/media/root/RHEL-9-5-0-BaseOS-x86_64/AppStream
gpgcheck=0
[BaseOS]
name=BaseOS
baseurl=file:///run/media/root/RHEL-9-5-0-BaseOS-x86_64/BaseOS
gpgcheck=0
```

To Check

```
[root@localhost ~]# yum repolist
Updating Subscription Management repositories.
Unable to read consumer identity

This system is not registered with an entitlement server. You can use "rhc" or "subscription-ma
nager" to register.

repo id                                repo name
AppStream                              AppStream
BaseOS                                 BaseOS
[root@localhost ~]#
```

To Install any Package

```
[root@localhost ~]# yum install telnet* -y
```

To remove any Package

```
[root@localhost ~]# yum remove telnet* -y
```