

Overview

This report documents every field in the **directus_files** collection as currently implemented on staging, cross-referenced against the field sheet. Fields are organised into three groups:

1. **Directus Default Fields** — built-in system fields provided by Directus out of the box; cannot be renamed, moved into groups, or deleted.
2. **Custom Added Fields** — fields added to fulfil the media library requirements.
3. **Handled via Custom Extension** — items covered through custom-built UI extensions rather than native **directus_files** fields.

Where applicable, each field entry includes context notes, the Directus default it maps to (if any), flow changes made, and developer notes.

Section 1 — Master Data

1.1 Generated File Name

Attribute	Value
API Key	generated_filename
Type	String (varchar 255)
Category	Custom Added Field
Required	No (generated automatically)
Status in Sheet	Done

Formula: **[3L Destination Cluster]** + **[3L Country]** + **[YYYYMMDD]** + **[Editor Initials]** + **[_NNN]**. Numbering continues per editor/day/destination.

1.2 Unique Media ID (Media ID)

Attribute	Value
API Key	id
Type	UUID (Primary Key)
Category	Directus Default Field
Schema Key	media_id

Note: This maps directly to the Directus native **id** field (UUID primary key). It is a protected system field — it **cannot be renamed, re-keyed, or moved into an accordion group**. It is exposed as **id** in all API responses. For any integrations where the label "Media ID" is preferred, the **id** value should be referenced accordingly.

1.3 Upload Date

Attribute	Value
API Key	uploaded_on
Type	Timestamp
Category	Directus Default Field
Schema Key	upload_date

Note: Maps to the Directus native `uploaded_on` field. This is a protected system field — it **cannot be moved into an accordion group** in the UI. It is hidden by default in the Directus interface. Directus also has a separate `created_on` field (record creation timestamp); `uploaded_on` is specifically populated on file upload.

1.4 Uploaded By

Attribute	Value
API Key	uploaded_by
Type	UUID → M2O <code>directus_users</code>
Category	Directus Default Field
Fotoweb Key	metadata_361

Note: Directus native `uploaded_by` field — protected system field, **cannot be moved into a group**. Hidden by default in the UI but available via API.

1.5 Editor Initials

Attribute	Value
API Key	<code>initials</code> (on <code>directus_users</code>)
Type	String (2–3 chars)
Category	Custom Added Field — on <code>directus_users</code> collection (not <code>directus_files</code>)
Schema Key	<code>editor_initials</code>

Dev Note: This is not a standalone field on `directus_files`. It is sourced from the user profile — added to the `directus_users` collection where it is manually set per editor. It is consumed by the Flow that auto-generates the `generated_filename` on upload.

1.6 Last Modified

Attribute	Value
API Key	<code>modified_on</code>
Type	Timestamp (read-only)
Category	Directus Default Field
Fotoweb Key	<code>asset_modified</code>
Schema Key	<code>last_modified_at</code>

Note: Maps to Directus native `modified_on`. Protected system field — **cannot be moved into a group**. Auto-updated by Directus on every save.

1.7 Last Modified By

Attribute	Value
API Key	<code>modified_by</code>
Type	UUID → M2O <code>directus_users</code> (read-only)
Category	Directus Default Field
Schema Key	<code>last_modified_by</code>

Note: Maps to Directus native `modified_by`. Protected system field — **cannot be moved into a group**. Auto-updated by Directus on every save.

Section 2 — Geographies

All geography fields are implemented using a **cascading select interface** — selecting a Place auto-populates State/Region/Country/Destination in a cascading hierarchy. All geography fields live in the `geographies` accordion group.

2.1 Place (City)

Attribute	Value
API Key	<code>place</code>
Type	Integer → M2O <code>places</code>
Category	Custom Added Field
Interface	Cascading Individual Select
Fotoweb Key	<code>metadata_90</code>

2.2 State

Attribute	Value
API Key	state
Type	Integer → M2O states
Category	Custom Added Field
Interface	Cascading Individual Select (cascades from place)

2.3 Region

Attribute	Value
API Key	region
Type	Integer → M2O regions
Category	Custom Added Field
Interface	Cascading Individual Select (cascades from place)
Fotoweb Key	metadata_90

2.4 Country

Attribute	Value
API Key	country
Type	Integer → M2O countries
Category	Custom Added Field
Required	Yes
Interface	Cascading Individual Select (cascades from place)
Fotoweb Key	metadata_101

2.5 Destination

Attribute	Value
API Key	destination
Type	Integer → M2O destinations
Category	Custom Added Field
Interface	Cascading Individual Select (cascades from country)

2.6 Categories

Attribute	Value
API Key	— (no separate field)
Category	Covered by Geographies module

Note: This is fully covered by the cascading Place → State/Region → Country → Destination hierarchy. No separate **categories** field is needed.

2.7 Keywords

Attribute	Value
API Keys	keyword_ids (primary), keywords (legacy)
Type	JSON (tag input — stores array)
Category	Custom Added Field
Fotoweb Key	metadata_25
Status in Sheet	Done (with note)

Note: The field sheet outlines a relation to a dedicated Keywords collection (taxonomy-style). This is not directly achievable with the standard Directus files interface — **directus_files** cannot use M2M relations the same way as regular collections without significant custom work. **Current implementation:** **keyword_ids** stores keywords as a JSON tag array (free-text strings).

Two keyword fields currently exist — **keywords** and **keyword_ids**. **keyword_ids** is the primary field. The legacy **keywords** field can be removed once confirmed no longer needed.

Section 3 — Media Rights

All fields in this section are **custom added fields** in the **media_rights** accordion group.

3.1 Photographer

Attribute	Value
API Key	photographer
Type	String (varchar 255)
Required	Yes
Fotoweb Key	metadata_122
Status in Sheet	Done

Populated from IPTC/EXLIF on upload if available; otherwise manually entered.

3.2 Company Name

Attribute	Value
API Key	company_name
Type	String (varchar 255)
Required	Yes
Translations	de-DE, de-CH, en-GB, nl-NL
Status in Sheet	Done

3.3 Contact Email

Attribute	Value
API Key	contact_email
Type	String (varchar 255)
Required	Yes
Translations	de-DE, de-CH, en-GB, nl-NL
Status in Sheet	Done

3.4 Copyright

Attribute	Value
API Key	copyright
Type	String (varchar 255)
Required	Yes
Default Value	@
Fotoweb Key	metadata_116
Status in Sheet	Done

Dev Note: The current default value is @. As defined in the field sheet, when IPTC/EXLIF is empty the default should be © none, and the UI should always prefix ©. The default value should be updated to © none and the prefix display option confirmed.

3.5 Expiry Date

Attribute	Value
API Key	expiry_date

Attribute	Value
Type	Date
Required	Yes
Translations	en-GB, de-DE, nl-NL
Fotoweb Key	metadata_428
Status in Sheet	Done

Media approaching or past expiry will trigger editor warnings. Visual marker logic is handled by Flow/extension.

3.6 Original File Name

Attribute	Value
API Key	original_filename
Type	String (varchar 255)
Required	Yes
Translations	en-GB, de-DE, nl-NL
Fotoweb Key	metadata_21
Status in Sheet	Done

Note: Directus also stores `filename_disk` (system field — actual filename on storage) and `filename_download` (system field — filename presented on download). `original_filename` is a separate custom field capturing the user's original upload filename including extension, kept for auditing purposes.

Section 4 — Description

4.1 Media Description

Attribute	Value
API Key	description
Type	Text (unlimited)
Category	Directus Default Field
Schema Key	description

Note: Maps to the Directus native `description` field. It is a protected system field — **cannot be moved into a group or renamed**. It remains at the root level of the file record. AI-assisted description

generation (using the original filename as input) is noted as a possible future enhancement.

4.2 Alt Text

Attribute	Value
API Key	<code>alt_text</code>
Type	String (varchar 255)
Required	Yes
Category	Custom Added Field
Fotoweb Key	<code>builtin_description</code>
Group	<code>description_raw_group</code> (inside Description accordion)
Translations	de-DE, en-GB, nl-NL
Status in Sheet	Done
Flow Changes	Yes

Flow Change: On file upload, the Flow reads IPTC/EXLIF `builtin_description` and auto-populates `alt_text`. Editors can manually override.

4.3 Creation Date (IPTC)

Attribute	Value
API Key	<code>iptc_creation_date</code>
Type	Date
Category	Custom Added Field
Fotoweb Key	<code>metadata_55</code>
Group	<code>description_raw_group</code>
Flow Changes	Yes

Flow Change: Populated from IPTC/EXLIF `metadata_55` on upload.

4.4 Creation Time (IPTC)

Attribute	Value
API Key	<code>iptc_creation_time</code>
Type	Time

Attribute	Value
Category	Custom Added Field
Fotoweb Key	metadata_60
Group	description_raw_group
Translations	en-GB, de-DE, nl-NL
Flow Changes	Yes

Flow Change: Populated from IPTC/EXLIF `metadata_60` on upload. Stored as time (hh:mm:ss); source value may be in `HHMMSS` format — the Flow handles the conversion.

Section 5 — Curation

5.1 Folder (Destination)

Attribute	Value
API Key	folder
Type	UUID → M2O <code>directus_folders</code> (read-only)
Category	Directus Default Field
Schema Key	folder_destination_id

Note: Directus natively provides a `folder` field (read-only, M2O to `directus_folders`) which covers this requirement. No additional field was added. The folder value is set when a file is uploaded or moved, and is accessible via API as the `folder` property.

5.2 Assigned to ID(s)

Attribute	Value
API Key	<code>action</code> (custom extension display)
Category	Handled via Custom Extension
Schema Key	<code>assigned_entity_ids</code>
Status in Sheet	Done

Implementation Note: Covered by the custom `file-media-extras` interface on the `action` alias field, which displays reverse-link assignments via the `hotels_directus_files` junction. The "Hotels using this file" table is shown directly in the file detail view.

Dev Note: Population of hotel assignments via API uses a custom function — editors manage assignments through the hotel/entity records rather than directly on the file.

5.3 Album(s) / Lightbox

Attribute	Value
API Key	<code>album</code> (alias field)
Category	Handled via Custom Extension
Schema Key	<code>album_ids</code>
Status in Sheet	Done

Implementation Note: Covered by the custom `file-albums` interface connected to the `albums_directus` junction collection. Media can appear in multiple albums without physical duplication.

5.4 Caption (Multilingual)

Attribute	Value
API Key	<code>translations</code> (alias — translations relation)
Category	Custom Added Field
Schema Key	<code>caption_i18n</code>
Interface	<code>ai-translations</code>
Group	<code>curation</code>
Status in Sheet	Done
Flow Changes	Yes

Multilingual caption stored via Directus translations interface. Supports all configured languages (de-DE, de-CH, en-GB, nl-NL).

5.5 Is Map

Attribute	Value
API Key	<code>is_map</code>
Type	Boolean (default: <code>false</code>)
Category	Custom Added Field
Schema Key	<code>is_map</code>
Translations	de-DE, en-GB, nl-NL
Group	<code>curation</code>

Note: The field is present in `directus_files` on staging and functions as a data flag — the custom extension reads this value to trigger the sticky box behaviour in the frontend. Both the field and the extension work together.

5.6 Tour32 Export

Attribute	Value
API Key	<code>tour32_export</code>
Type	Boolean (default: <code>false</code>)
Category	Custom Added Field
Schema Key	<code>tour32_export</code>
Translations	de-DE, en-GB, nl-NL
Group	<code>curation</code>

Note: Similar to `is_map` — the boolean field is present in `directus_files` on staging and serves as the data store that the extension reads and writes. Both the field and the extension are required.

5.7 On-demand Formats

Attribute	Value
Category	Handled Natively by Directus
Schema Key	<code>files_on_demand</code>

Note: Directus natively handles on-demand format generation via its image transformation pipeline — formats are generated at request time and cached. No additional field is needed.

Section 6 — Media Data

6.1 Draft / Published Status

Attribute	Value
API Key	<code>draft_status</code>
Type	String → Dropdown
Default Value	<code>draft</code>
Category	Custom Added Field
Schema Key	<code>draft_status</code>
Group	<code>media_data</code>

Attribute	Value
Translations	de-DE, en-GB, nl-NL

Note: The field sheet describes this as a "Draft / Paused State" boolean. The implementation provides a dropdown with two states: **draft** and **published** — covering both states in a single field rather than a boolean. This aligns better with standard CMS patterns and leaves room for additional states if needed down the line.

6.2 Original Format (Saved)

Attribute	Value
Category	Handled Natively by Directus
Schema Key	file_original

Note: Directus always retains the original uploaded file. No additional field is needed.

6.3 Auto-generated Formats

Attribute	Value
Category	Handled Natively by Directus
Schema Key	files_auto_generated

Note: Directus handles image format transformations natively via its asset pipeline. No additional field is needed.

6.4 File Size

Attribute	Value
Directus Default	filesize (bigInteger, bytes, read-only, system field)
Custom Added Field	file_size_mb (float)
Fotoweb Key	asset_filesize
Group	media_data

Note: Directus natively stores **filesize** in bytes. **file_size_mb** (float) was added as a companion field storing the size in megabytes for editor display convenience. Both values are available — **filesize** remains the authoritative system value.

6.5 File Format / Type

Attribute	Value
Directus Default	<code>type</code> (MIME type string, read-only, system field)
Custom Added Field	<code>file_format</code> (string, group: <code>media_data</code>)

Note: Directus natively stores `type` as a MIME type (e.g. `image/jpeg`). `file_format` was added as a human-readable format label (e.g. `JPG`, `PNG`, `MP4`) for display in the media library UI.

6.6 Dimensions (px)

Attribute	Value
Directus Defaults	<code>width</code> (integer, read-only) + <code>height</code> (integer, read-only) — system fields
Custom Added Field	<code>dimensions_px</code> (string, group: <code>media_data</code>)

Note: Directus stores `width` and `height` as separate read-only system fields. `dimensions_px` was added as a combined display string (e.g. `3840 × 2160`) populated automatically.

6.7 Resolution (dpi)

Attribute	Value
API Key	<code>resolution_dpi</code>
Type	BigInteger
Category	Custom Added Field
Translations	de-DE, en-GB, nl-NL
Group	<code>media_data</code>
Status in Sheet	Done

6.8 Media Sizes in cm

Attribute	Value
API Key	<code>media_sizes_cm</code>
Type	String (varchar 255)
Category	Custom Added Field
Translations	de-DE, de-CH, en-GB, nl-NL
Group	<code>media_data</code>
Status in Sheet	Done

Calculated field — stores three print sizes (at 300 dpi, 150 dpi, 72 dpi) derived from pixel dimensions. Applies to images only.

6.9 Color Space

Attribute	Value
API Key	color_space
Type	String → Dropdown
Category	Custom Added Field
Fotoweb Key	attr_colorspace
Translations	de-DE, en-GB, nl-NL
Group	media_data
Status in Sheet	Done

Dropdown choices: RGB, CMYK, Grayscale, Lab, YCbCr, XYZ, HSV, HLS.

6.10 Direct / Share Link

Attribute	Value
API Key	share (alias field)
Category	Handled via Custom Extension
Schema Key	share_link_url
Interface	media-share-button
Status in Sheet	Done

Implementation Note: Covered by the custom `media-share-button` interface on the `share` alias field, which generates and displays the shareable direct link for the file. No separate URL string field is stored.

Summary Tables

A. Directus Default Fields (Cannot be moved/renamed/deleted)

Field	Directus API Key	Type	Notes
Unique Media ID	id	UUID	Primary key — exposed as <code>id</code> in API
Upload Date	uploaded_on	Timestamp	Hidden by default in UI

Field	Directus API Key	Type	Notes
Uploaded By	uploaded_by	UUID → User	Hidden by default in UI
Last Modified	modified_on	Timestamp	Read-only, auto-updated
Last Modified By	modified_by	UUID → User	Read-only, auto-updated
Media Description	description	Text	Cannot be grouped
Folder (Destination)	folder	UUID → Folder	Read-only, set on upload
File Size (bytes)	filesize	BigInteger	System value in bytes
Width	width	Integer	System read-only
Height	height	Integer	System read-only
MIME Type	type	String	e.g. image/jpeg
Filename on Disk	filename_disk	String	System read-only
Download Filename	filename_download	String	
Title	title	String	Native Directus field (not in use)
Location	location	Text	Native Directus field (not in use)
Tags (native)	tags	JSON	Native Directus field (not in use — see keywords)

B. Custom Added Fields

Field	API Key	Type	Group/Accordion	Required	Flow
Generated File Name	generated_filename	String	Root	No	—
Place (City)	place	Int → M2O places	Geographies	No	—
State	state	Int → M2O states	Geographies	No	—
Region	region	Int → M2O regions	Geographies	No	—
Country	country	Int → M2O countries	Geographies	No	—

Field	API Key	Type	Group/Accordion	Required	Flow
Destination	destination	Int → M2O destinations	Geographies	No	—
Keywords	keyword_ids	JSON (tags)	Geographies	No	—
Photographer	photographer	String	Media Rights	Yes	—
Company Name	company_name	String	Media Rights	Yes	—
Contact Email	contact_email	String	Media Rights	Yes	—
Copyright	copyright	String	Media Rights	Yes	—
Expiry Date	expiry_date	Date	Media Rights	Yes	—
Original File Name	original_filename	String	Media Rights	Yes	—
Alt Text	alt_text	String	Description	Yes	✓ IPTC auto-populate
Creation Date (IPTC)	iptc_creation_date	Date	Description	No	✓ IPTC auto-populate
Creation Time (IPTC)	iptc_creation_time	Time	Description	No	✓ IPTC auto-populate
Is Map	is_map	Boolean	Curation	No	—
Tour32 Export	tour32_export	Boolean	Curation	No	—
Caption (multilingual)	translations	Alias → Translations	Curation	No	✓
Draft/Published Status	draft_status	String (dropdown)	Media Data	No	—
File Size (MB)	file_size_mb	Float	Media Data	No	—
File Format	file_format	String	Media Data	No	—
Dimensions (px)	dimensions_px	String	Media Data	No	—
Resolution (dpi)	resolution_dpi	BigInteger	Media Data	No	—

Field	API Key	Type	Group/Accordion	Required	Flow
Media Sizes in cm	<code>media_sizes_cm</code>	String	Media Data	No	—
Color Space	<code>color_space</code>	String (dropdown)	Media Data	No	—

C. Covered via Custom Extension (no direct field)

Field	Extension	Notes
Assigned to ID(s)	<code>file-media-extras</code> (action field)	Shows hotel/entity assignments via reverse junction; API population via custom function
Album(s) / Lightbox	<code>file-albums</code> (album field)	Manages album membership via <code>albums_directus</code> junction
Direct / Share Link	<code>media-share-button</code> (share field)	Generates shareable link dynamically

D. Handled Natively by Directus (no field needed)

Field	How it is covered
Original Format (saved)	Directus always retains the original uploaded file
Auto-generated Formats	Directus asset transformation pipeline handles this natively
On-demand Formats	Directus generates formats on-demand via asset endpoint

E. Fields with Flow Changes

Field	API Key	Flow Action
Alt Text	<code>alt_text</code>	Auto-populated from IPTC/EXLIF <code>builtin_description</code> on upload
Creation Date	<code>iptc_creation_date</code>	Auto-populated from IPTC <code>metadata_55</code> on upload
Creation Time	<code>iptc_creation_time</code>	Auto-populated from IPTC <code>metadata_60</code> on upload; <code>HHMMSS</code> → time conversion
Caption (multilingual)	<code>translations</code>	AI-assisted translation flow