

SIMATS ENGINEERING

ASSESSMENT TOOL 1: Data Interpretation

COURSE NAME: COMPUTER VISION
NAME: RAJA RAJESHWARI M

COURSE CODE: ITA0517
REG.NO: 192421253

COURSE OUTCOME COVERED

CO4: *Compare object and pattern recognition techniques for interpreting visual data with spatial and motion characteristics. (BTL 5)*

Assessment Tool Weightage: 40%

Read the given data carefully and compare the techniques or results based on multiple factors such as accuracy, robustness, and computational constraints. Evaluate and justify your decision with appropriate reasoning considering the application context.

1. Real-Time System Design Trade-off

A surveillance system must operate under constraints:

- Viola-Jones: fast but less accurate (78%)
- YOLO: moderate speed, good accuracy (92%)
- Deep Learning: high accuracy (95%) but slow

Compare the techniques and evaluate which should be selected under strict latency constraints while maintaining acceptable accuracy. Justify your decision considering deployment conditions.

ANS :1. Real-Time System Design Trade-off

Technique	Speed	Accuracy	Suitability
Viola-Jones	Very fast	78%	Excellent for strict real-time
YOLO	Moderate	92%	Best balance
Deep Learning	Slow	95%	Better for offline/high-accuracy

Analysis:

Viola-Jones has the lowest accuracy but provides very fast detection, making it suitable when latency is the most critical requirement. Deep Learning provides the highest accuracy but requires more computational resources and introduces higher delay. YOLO provides a strong compromise between speed and accuracy.

Evaluation:

Under **strict latency constraints**, **Viola-Jones** should be selected if 78% accuracy is considered acceptable. It is suitable for low-power cameras, embedded devices, and systems where an immediate response is more important than maximum detection accuracy.

However, if the system can tolerate moderate latency, **YOLO is the preferred practical choice** because its 92% accuracy is significantly higher while still supporting real-time operation.

Conclusion:

- Strictest latency → **Viola-Jones**
- Real-time with better accuracy → **YOLO**
- Accuracy more important than speed → **Deep Learning**

2. Robust Detection under Environmental Variations

Detection accuracy across environments:

Compare the robustness of each method and evaluate which technique provides the best overall performance across varying conditions. Justify trade-offs.

ANS: Robust Detection under Environmental Variations

Method	Normal	Occlusion	Low Light	Average
Viola-Jones	80%	60%	55%	65%
YOLO	90%	75%	70%	78.3%

Deep Learning	95%	85%	80%	86.7%
----------------------	-----	-----	-----	--------------

Analysis:

Viola-Jones performs reasonably in normal conditions but its accuracy drops significantly under occlusion and low-light conditions. YOLO is more robust, with better performance under both difficult conditions. Deep Learning achieves the highest accuracy in every environment.

Evaluation:

The average accuracy shows that Deep Learning has the best overall robustness at **86.7%**. Its ability to handle occlusion and low-light conditions makes it suitable for challenging surveillance environments.

The main trade-off is computational cost and processing speed. YOLO provides a better balance between robustness and real-time performance.

Conclusion:

Deep Learning is the best choice when robustness and accuracy are the main priorities. **YOLO** is preferable when real-time performance and robustness must both be considered.

3. Optical Flow Reliability vs Noise Sensitivity

Two optical flow methods show:

- Method A: stable vectors but misses small motions
- Method B: detects fine motion but noisy vectors

Compare both methods and evaluate which is more suitable for motion tracking in dynamic scenes. Justify based on application requirements.

ANS: 3. Optical Flow Reliability vs Noise Sensitivity

Method	Advantage	Limitation	Suitable Application
Method A	Stable vectors	Misses small motions	General/stable tracking
Method B	Detects fine motion	Noisy vectors	Detailed motion analysis

Analysis:

Method A produces stable optical-flow vectors, making it reliable for tracking large and continuous movements. However, it may fail to detect small or subtle movements.

Method B is more sensitive and can detect fine movements, but the noisy vectors can lead to inaccurate tracking and false motion estimates.

Evaluation:

For a **dynamic scene**, Method A is generally more suitable when stable tracking is required, such as vehicle or person tracking. Method B is preferable for applications where small movements are important, such as gesture recognition or subtle object motion.

Method B can be improved using **noise filtering, smoothing, or outlier removal**.

Conclusion:

For reliable motion tracking → **Method A**.
For fine-motion detection → **Method B with noise reduction**.

4. Background Modeling Strategy (GMM)

A GMM-based system shows:

- High false positives in dynamic background
- Missed detections in static background

Compare GMM performance across scenarios and evaluate whether GMM alone is sufficient. Propose and justify improvements.

ANS:

Scenario	GMM Performance	Problem
Dynamic background	Poor	High false positives
Static background	Better	Missed detections may occur
Overall	Moderate	Not sufficient alone

Analysis:

Gaussian Mixture Model (GMM) separates foreground objects from the background by modeling multiple background distributions. It works well when the background is relatively stable.

In a dynamic environment, such as moving trees, rain, water, or waving objects, GMM may incorrectly classify background motion as foreground, resulting in **false positives**. In static scenes, missed detections can occur when an object becomes part of the learned background or when illumination changes.

Evaluation:

GMM alone is **not sufficient** for a robust detection system. Its performance can be improved using:

1. Adaptive learning rates.
2. Shadow detection and removal.
3. Morphological operations.
4. Noise filtering.
5. Combining GMM with optical flow.
6. Using YOLO/deep-learning-based object verification.

Conclusion:

GMM is computationally efficient and useful for basic background subtraction, but a **hybrid approach** is more reliable for real-world surveillance systems.

5. Motion Estimation vs Computational Cost

Two methods:

- Method A: low error (5%), high computation
- Method B: moderate error (10%), low computation

Compare the methods and evaluate their suitability for real-time vs offline applications. Justify your decision.

ANS: 5. Motion Estimation vs Computational Cost

Method	Error	Computation	Accuracy	Suitable For
Method A	5%	High	High	Offline/high-accuracy
Method B	10%	Low	Moderate	Real-time

Analysis:

Method A has only **5% error**, meaning it provides more accurate motion estimation. However, its high computational requirement can cause processing delays and may not be suitable for systems with limited hardware resources.

Method B has a higher **10% error**, but its low computational cost allows faster processing. This makes it more suitable for real-time applications where immediate results are important.

Real-Time vs Offline Evaluation:

- **Real-time application:** Method B is preferable because low computation reduces latency. The additional 5% error may be acceptable when fast response is the priority.
- **Offline application:** Method A is preferable because computation time is less critical and the lower error provides more accurate results.

Conclusion:

Method B → **Real-time systems** because of its low computational cost.

Method A → **Offline systems** because of its lower error and higher accuracy.

Overall trade-off: The choice depends on whether the application prioritizes **speed** or **accuracy**.