



VIT[®]
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)

FALL Semester 2022-23

**ITA5002 - Problem Solving with Data Structures and Algorithms
Lab**

LAB DIGITAL ASSESSMENT – II

Due Date: 05-12-2022

**Submitted By: Rajat Singh
Reg No.: 22MCA0139**

SOLVE THE PROBLEMS GIVEN BELOW

1. Try to create an array of N elements as input which consists of Positive, Negative numbers and also the duplicate values. Perform any sorting procedure to get output as two sorted array one with positive numbers and one with negative numbers and print the number of comparisons made for each sorted array and also the say count for the each the duplicate values.

Exapmle : input[15]= { 10,4,-3,-1,0,4,3,-15,-8,4,-1,9,3,1,7}

Output1[15]={-1,-1,-3,-8,-15} and print Number of Comparisons

Output2[15]={0,1,3,3,4,4,4,7,9,10} and print Number of Comparisons

-1 has been present twice
+ 3 has been present twice
+ 4 has been present thrice

Code:

```
#include<iostream>
#include<vector>
using namespace std;

int sortNow(int arr[], int n){
    int i, j;
    int c=0;
    for (i = 0; i < n - 1; i++){
        for (j = 0; j < n - i - 1; j++){
            c++;
            if (arr[j] > arr[j + 1]){
                swap(arr[j], arr[j + 1]);
            }
        }
    }
    return c;
}

void countFreq(int arr[], int n)
{
    vector<bool> visited(n, false);

    for (int i = 0; i < n; i++) {

        if (visited[i] == true)
```

```

        continue;

    int count = 1;
    for (int j = i + 1; j < n; j++) {
        if (arr[i] == arr[j]) {
            visited[j] = true;
            count++;
        }
    }
    if(count>1)
        cout << arr[i] << " (" << count << " times.)" <<endl;
}
}

int main(){
    int arr[15] = { 10,4,-3,-1,0,4,3,-15,-8,4,-1,9,3,1,7};
    int pos[15];
    int neg[15];

    int p=0; int q=0;
    for( int i : arr){
        if(i<0){
            neg[q] = i;
            q++;
        }
        else{
            pos[p] = i;
            p++;
        }
    }

    int pos_count = sortNow(pos, p);
    int neg_count = sortNow(neg, q);

    cout<<"Sorted Positives: ";
    for(int i=0; i<p; i++)
        cout<<pos[i]<<" ";

    cout<<"\tComparisons: "<<pos_count<<endl;

    cout<<"Sorted Negetives: ";
    for(int i=0; i<q; i++)
        cout<<neg[i]<<" ";

    cout<<"\tComparisons: "<<neg_count<<endl;
    cout<<"Duplicate elements are: "<< endl;
    countFreq(arr, 15);
}

```

```
    return 0;
}
```

Output:

```
Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +15 ~1 -0 !]> g++ .\labAssignment2Question1.cpp
D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +15 ~1 -0 !]> ./a
Sorted Positives: 0 1 3 3 4 4 4 7 9 10 Comparisons: 45
Sorted Negatives: -15 -8 -3 -1 -1 Comparisons: 10
Duplicate elements are:
4 (3 times.)
-1 (2 times.)
3 (2 times.)
D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +15 ~1 -0 !]> []
```

2. Perform Binary Search for the given input

$A[14] = \{11, 22, 33, 44, 55, 66, 77, 88, 99, 111, 222, 333, 444\}$

And try to print the position of the number present in the upper half starting from 1 to n. N is the middle element.

After middle element again the position should start from 1 to n. Here N is the last element.

Example $mid = (0 + 14) / 2 == 7$ middle element is 88

Numbers 33 present in the third position

88 is present in the ninth position

99 is present in first position

333 is present in fourth position

Code:

```
#include<iostream>
using namespace std;

int binSearch(int arr[], int k, int n){
    int start=0;
    int end = n;
```

```

    int mid = start + ((end-start)/2);

    while(start<end){
        if(arr[mid] == k)
            return mid;
        else if(arr[mid] > k)
            end = mid-1;
        else
            start = mid+1;
        mid = start + ((end-start)/2);
    }
    return -1;
}

int main(){
    int arr[13] = {11,22,33,44,55,66,77,88,99,111,222,333,444};

    int n=13;
    int k = 11;

    int pos = binSearch(arr, k, n);
    if(pos == -1)
        cout<<endl<<"Not Found!"<<endl;
    else
        cout<<endl<<"Found at index: "<<pos<<endl;
    return 0;
}

```

Output:

```

D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +15 ~1 -0 !]> g++ .\labAssignment2Question2.cpp
D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +16 ~1 -0 !]> ./a

Key = 11 Found at index: 0
D:\Backup_28Sep\Study Material\MCA\SEM_1\dsa_lab [main = +16 ~1 -0 !]>

```

