ECEN 5613 Fall 2021

Embedded System Design Lab #1 Signoff Sheet - Part 1 Elements

Week #1 8/23/2021

You will need to obtain the signature of your TA on the following items in order to receive credit.

The Part 1 & Part 2 Elements of Lab #1 should be completed and signed off by Friday, Sept. 10, 2021 in order to give you time to complete the Part 3 Elements upon receipt of your parts kit. All signoffs are due by Friday, Sept. 17, 2021. You need to submit both of your signoff sheets and other required elements by 11:59pm Saturday, Sept. 18, 2021. Labs completed after the signature due date or submitted after the submission due date will usually receive grade reductions, but there is leniency on Lab #1.

Print your name below and then demonstrate your working hardware/firmware in order to obtain the necessary signatures. All items must be completed to get a signature, but partial credit is given for incomplete labs. Receiving a signature on this signoff sheet does not mean that your work is eligible for any particular grade; it merely indicates that you have completed the work at an acceptable level.

Student Name: Dhiray	Benna	di	_								
Checklist											
Student demonstrates detailed knowledge of a simulator (including changing register values, editing data memory, using breakpoints, single stepping, uses /overlay option, etc.) Student assembly program works correctly Student demonstrates detailed knowledge of WinCUPL and WinSim, logic equations correct											
Student Answers to Lab Questions											
1. How many bytes of code space do (Show how you arrived at your ans Code Size? 37 bytes	swer.)			2 Assume an	11 0502 MU-						
2. How long did your program take to execute for X=0x10 and Y=0x0A? Assume an 11.0592 MHz clock and include the instructions executed from the beginning until you reach the ENDLOOP label. Show the TA your detailed calculations on the code listing during your signoff. Execution Time? 123 445.											
			QQ	y De	2 2V	21					
Instructor/TA Comments:	TA signatu	re and date		Ì							
FOR INSTRUCTOR USE ONLY SPLD code Assembly Language Code Style Required Elements functionality Sign-off done without excessive retries Student understanding and skills Overall Demo Quality	Not Applicable	Poor/Not Complete	Meets Requirements	Exceeds Requirements	Outstanding						
Comments: Could Shorten code, reduce # of MOV instructions ver neatly organized code!											

NOTE: This submission sheet should be the top/first sheet of your submission.

ECEN 5613 Fall 2021

Embedded System Design Lab #1 Signoff Sheet - Part 3 Elements

Week #1 8/23/2021

Print your name below, answer the questions, and then demonstrate your working hardware in order to obtain the necessary signatures. All items must be completed to get a signature.

Stu	dent Name: Dhiray Ber	madi								
Checklist Schematic of acceptable quality, Student name on board in permanent ink Pins and signals labeled, decoupling capacitors, and two 28-pin wire wrap sockets present on board: Mounting hardware present (e.g. standoffs or an enclosure) Power switch and LED, voltage regulator functional, power jack present Power-on Reset (RC) and Run-time Reset (pushbutton), 8051 bypass cap is present RS-232 connector mounted, 74LS373 transparent latch wired Logic outputs correct (e.g. SPLD generation of /READ and /CSPERIPH; view SPLD code) Student displays good knowledge of oscilloscope Peak to peak noise measured across processor VCC and GND is < 800mV Oscillator functional (check for correct ALE/XTAL2 signals after power on-off cycles) ARM development board functional, student can demonstrate the basic software.										
	dent Answers to Lab Questions					. /				
1.	 What voltage is present at the regulator input? Use a digital multimeter. What voltage is present at the regulator output? Use a digital multimeter. 									
2.	2. What voltage is present at the regulator output? Use a digital multimeter \(\frac{1}{2} \)									
3.										
	Measured value at processor package pins on top side of board:									
	Measured value at wire wrap socket pins on bottom side of board:									
4.	How long is the processor held in reset after the run-time reset pushbutton is released? Use an oscilloscope and try to measure the time between the release of the pushbutton and the time when noise from ALE is observed on the RST signal.									
	Measured value: 120 m8				0					
5.	What frequency is present at the	ALE pin? U	se an oscillo	oscope	08 MH3					
				ale	y Ball	- 1/3/	(2)			
Inst	tructor/TA Comments:			TA signatui	re and date					
FOF	R INSTRUCTOR USE ONLY	Not Applicable	Poor/Not Complete	Meets Requirements	Exceeds Requirements	Outstanding				
	ematics, SPLD code ware physical implementation				Ħ	Ħ				
	uired Elements functionality -off done without excessive retries									
	ent understanding and skills			M						
	all Demo Quality	1								
Col	mments: Schematic - GND	resistor	1							

Submission Sheet

Instructions: Print your name below and sign the honor code pledge. Separate the signoff and submission sheets from the rest of the lab and turn in a scan (or clear picture) of these signed forms, the items in the checklist below, and the answers to any applicable lab questions in order to receive credit for your work. No cover sheet please. Submit all items electronically via Canvas to reduce paper usage. Canvas is https://canvas.colorado.edu.

In addition to the items listed on the signoff checklist, be sure to review the lab for additional requirements for submission, including:

- Scan of signed and dated Part 1 signoff sheet as the top sheet (No cover sheet please)
- □ Scan of signed and dated Part 3 signoff sheet as the second sheet
- Scan of submission sheet with signed honor code pledge as the third sheet
- PDF of complete and accurate final schematic of acceptable quality (all components shown).
- ☐ Fully, neatly, and clearly commented assembly code.

Make copies of your code, SPLD code, and schematic files and save them as an archive.

Student Name: Dhiray Bernadi

Honor Code Pledge: "On my honor, as a University of Colorado student, I have neither given nor received unauthorized assistance on this work. I have clearly acknowledged work that is not my own."

Student Signature:

1. How much power is dissipated in the regulator, assuming a load current of 125mA? Assume that the regulator is drawing the max quiescent current shown in the data sheet (use the correct data sheet for the regulator you have on your board). Neatly show all your work.

Calculated value: 370 mW

Comments:

NOTE: This submission sheet should be the third sheet of your submission.