

ASSIGNMENT

NAME- RAJAT SINGH

ROLL NO.- 46

UNIV. ROLL NO.- 2215001414

SECTION- U

SUBJECT- PYTHON PROGRAMMING

Q-1. What Will Be The Output Of The Following Code Snippet?

```
a = {(1,2):1,(2,3):2}
print(a[1,2])
```

ANS- A. KEY ERROR

-2. What Will Be The Output Of The Following Code Snippet?

```
a = {'a':1,'b':2,'c':3}
print (a['a','b'])
print(a.get('a','b'))
```

ANS- A. KEY ERROR

Q-3. What Will Be The Output Of The Following Code Snippet?

```
fruit = {}
def addone(index):
if index in fruit:
fruit[index] += 1
else:
fruit[index] = 1
addone('Apple')
addone('Banana')
addone('apple')
print (len(fruit))
```

ANS- C. 3

Q-4. What Will Be The Output Of The Following Code Snippet?

```
arr = {}
arr[1] = 1
arr['1'] = 2
arr[1] += 1
sum = 0
```

```
for k in arr:  
    sum += arr[k]  
print (sum)
```

ANS- D. 4

Q-5. What Will Be The Output Of The Following Code Snippet?

```
my_dict = {}  
my_dict[1] = 1  
my_dict['1'] = 2  
my_dict[1.0] = 4  
sum = 0  
for k in my_dict:  
    sum += my_dict[k]  
print (sum)
```

ANS- A. 7

Q-6. What Will Be The Output Of The Following Code Snippet?

```
my_dict = {}  
my_dict[(1,2,4)] = 8  
my_dict[(4,2,1)] = 10  
my_dict[(1,2)] = 12  
sum = 0  
for k in my_dict:  
    sum += my_dict[k]  
print (sum)  
print(my_dict)
```

ANS- B. 30

{(1, 2): 12, (4, 2, 1): 10, (1, 2, 4): 8}

Q-7. What Will Be The Output Of The Following Code Snippet?

```
box = {}  
jars = {}  
crates = {}  
box['biscuit'] = 1  
box['cake'] = 3  
jars['jam'] = 4  
crates['box'] = box  
crates['jars'] = jars  
print (len(crates[box]))
```

ANS- D. TYPE ERROR

Q-8. What Will Be The Output Of The Following Code Snippet?

```
dict = {'c': 97, 'a': 96, 'b': 98}  
for _ in sorted(dict):  
    print (dict[_])
```

ANS- A. 96 98 97

Q-9. What Will Be The Output Of The Following Code Snippet?

```
rec = {"Name" : "Python", "Age": "20"}  
r = rec.copy()  
print(id(r) == id(rec))
```

ANS- **B. FALSE**

Q-10. What Will Be The Output Of The Following Code Snippet?

```
rec = {"Name" : "Python", "Age": "20", "Addr" : "NJ", "Country" : "USA"}  
id1 = id(rec)  
del rec  
rec = {"Name" : "Python", "Age": "20", "Addr" : "NJ", "Country" : "USA"}  
id2 = id(rec)  
print(id1 == id2)
```

ANS- **B. FALSE**

1. Write a Python script to sort (ascending and descending) a dictionary by value.

ANS-

```
my_dict = {"apple": 5, "banana": 10, "orange": 3, "pear": 8}  
asc_dict = dict(sorted(my_dict.items(), key=lambda x: x[1]))  
desc_dict = dict(sorted(my_dict.items(), key=lambda x: x[1], reverse=True))  
print("Ascending order:", asc_dict)  
print("Descending order:", desc_dict)
```

2. Write a Python script to add a key to a dictionary

Sample Dictionary : {0: 10, 1: 20}

Expected Result : {0: 10, 1: 20, 2: 30}

ANS-

```
sample_dict = {0: 10, 1: 20}  
key = 2  
value = 30  
sample_dict[key] = value  
print(sample_dict)
```

3. Write a Python script to concatenate following dictionaries to create a new one.

Sample Dictionary :

dic1={1:10, 2:20}

dic2={3:30, 4:40}

dic3={5:50,6:60}

Expected Result : {1: 10, 2: 20, 3: 30, 4: 40, 5: 50, 6: 60}

ANS-

```
dic1 = {1: 10, 2: 20}
dic2 = {3: 30, 4: 40}
dic3 = {5: 50, 6: 60}
result = {}
for d in (dic1, dic2, dic3):
    result.update(d)
print(result)
```

4. Write a Python script to check if a given key already exists in a dictionary.

ANS-

```
my_dict = {'apple': 2, 'banana': 4, 'orange': 6}
key = 'banana'
if key in my_dict:
    print(f"The key '{key}' exists in the dictionary.")
else:
    print(f"The key '{key}' does not exist in the dictionary.")
```

5. Write a Python program to iterate over dictionaries using for loops.

ANS-

```
my_dict = {"name": "John", "age": 30, "city": "New York"}
for key in my_dict:
    print(key, ":", my_dict[key])
```

6. Write a Python script to generate and print a dictionary that contains a number (between 1 and n) in the form (x, x*x)

Sample Dictionary (n = 5) :

Expected Output : {1: 1, 2: 4, 3: 9, 4: 16, 5: 25}

ANS-

```
n = 5
d = {}
for x in range(1, n+1):
    d[x] = x*x
print(d)
```

7. Write a Python script to print a dictionary where the keys are numbers between 1 and 15 (both included) and the values are square of keys.

Sample Dictionary

{1: 1, 2: 4, 3: 9, 4: 16, 5: 25, 6: 36, 7: 49, 8: 64, 9: 81, 10: 100, 11: 121, 12: 144, 13: 169, 14: 196, 15: 225}

ANS-

```
d = {}
for i in range(1, 16):
    d[i] = i ** 2

print(d)
```

8. Write a Python script to merge two Python dictionaries.

ANS-

```
dict1 = {'a': 1, 'b': 2}
dict2 = {'c': 3, 'd': 4}
dict1.update(dict2)
print(dict1) # {'a': 1, 'b': 2, 'c': 3, 'd': 4}
```

9. Write a Python program to iterate over dictionaries using for loops.

ANS-

```
dict = {'name': 'John', 'age': 25, 'country': 'USA'}
for key in dict:
    print(key, ': ', dict[key])
```

10. Write a Python program to sum all the items in a dictionary.

ANS-

```
my_dict = {'a': 10, 'b': 20, 'c': 30}
total = sum(my_dict.values())
print(total)
```

11. Write a Python program to multiply all the items in a dictionary

ANS-

```
def multiply_dict_items(dict):
    result = 1
    for key in dict:
        result *= dict[key]
    return result
```

12. Write a Python program to remove a key from a dictionary.

ANS-

```
my_dict = {'apple': 2, 'banana': 3, 'orange': 4}
print("Original dictionary:", my_dict)
```

13. Write a Python program to map two lists into a dictionary.

ANS-

```
keys = ['name', 'age', 'gender']
values = ['Alice', 25, 'Female']
my_dict = dict(zip(keys, values))
print(my_dict)
```

14. Write a Python program to sort a dictionary by key.

ANS-

```
my_dict = {'b': 2, 'c': 3, 'a': 1}
sorted_dict = {k: v for k, v in sorted(my_dict.items(), key=lambda x: x[0])}
print(sorted_dict)
```

15. Write a Python program to get the maximum and minimum value in a dictionary.

ANS-

```
my_dict = {'a': 10, 'b': 5, 'c': 20, 'd': 30}
max_val = max(my_dict.values())
min_val = min(my_dict.values())
print('Maximum value:', max_val)
print('Minimum value:', min_val)
```

16. Write a Python program to get a dictionary from an object's fields.

ANS-

```
class Person:
    def __init__(self, name, age):
        self.name = name
        self.age = age
```

```
person = Person("John", 30)
```

```
person_dict = vars(person)
```

```
print(person_dict)
```

17. Write a Python program to remove duplicates from Dictionary

ANS-

```
original_dict = {"a": 1, "b": 2, "c": 1, "d": 3, "e": 2}
new_dict = {value:key for key, value in original_dict.items()}
```

18. Write a Python program to check a dictionary is empty or not.

ANS-

```
my_dict = { }
```

```
if len(my_dict) == 0:
    print("The dictionary is empty")
else:
    print("The dictionary is not empty")
```

19. Write a Python program to combine two dictionary adding values for common keys.

```
d1 = {'a': 100, 'b': 200, 'c':300}
```



```
d2 = {'a': 300, 'b': 200, 'd':400}
```

```
Sample output: Counter({'a': 400, 'b': 400,  
'd': 400, 'c': 300})
```

ANS-

```
from collections import Counter
```

```
d1 = {'a': 100, 'b': 200, 'c': 300}
```

```
d2 = {'a': 300, 'b': 200, 'd': 400}
```

```
result = Counter(d1) + Counter(d2)
```

```
print(result)
```

20. Write a Python program to print all unique values in a dictionary. Sample Data :

```
[{"V": "S001"}, {"V": "S002"}, {"VI": "S001"},  
{"VI": "S005"}, {"VII": "S005"},  
{"V": "S009"}, {"VIII": "S007"}]
```

Expected Output : Unique Values: {'S005', 'S002', 'S007', 'S001', 'S009'}

ANS-

```
data = [{"V": "S001"}, {"V": "S002"}, {"VI": "S001"}, {"VI": "S005"}, {"VII": "S005"},  
{"V": "S009"}, {"VIII": "S007"}]
```

```
unique_values = set()
```

```
for d in data:
```

```
    for value in d.values():
```

```
        unique_values.add(value)
```

```
print("Unique Values:", unique_values)
```

21. Write a Python program to create and display all combinations of letters, selecting each letter from a different key in a dictionary.

Sample data : {'1':['a','b'], '2':['c','d']}

Expected Output:

ac

ad

bc

bd

ANS-

```
def generate_combinations(data):  
    combinations = []  
    keys = data.keys()  
    values = [data[key] for key in keys]  
    for i in range(len(values[0])):  
        for j in range(len(values[1])):  
            combination = values[0][i] + values[1][j]  
            combinations.append(combination)  
    return combinations
```

22. Write a Python program to find the highest 3 values in a dictionary.

ANS-

```
def find_highest_values(data):  
    sorted_values = sorted(data.values(), reverse=True)  
    return sorted_values[:3]
```

23. Write a Python program to combine values in python list of dictionaries.

Sample data: [{'item': 'item1', 'amount': 400}, {'item': 'item2', 'amount': 300}, {'item': 'item1', 'amount': 750}]

Expected Output: Counter({'item1': 1150, 'item2': 300})

ANS-

```
from collections import Counter
def combine_values(data):
    result = Counter()
    for d in data:
        result[d['item']] += d['amount']
    return result
```

24. Write a Python program to create a dictionary from a string.

Note: Track the count of the letters from the string.

Sample string : 'w3resource'

Expected output: {'3': 1, 's': 1, 'r': 2, 'u': 1, 'w': 1, 'c': 1, 'e': 2, 'o': 1}

ANS-

```
def create_dict_from_string(s):
    counts = {}
    for letter in s:
        if letter in counts:
            counts[letter] += 1
        else:
            counts[letter] = 1
    return counts
```

25. Write a Python program to print a dictionary in table format.

ANS-

```
def print_dict_table(data):
    keys = list(data.keys())
    values = list(data.values())
    max_key_length = max(len(str(key)) for key in keys)
    max_value_length = max(len(str(value)) for value in values)
    print('+ ' + '-' * (max_key_length + 2) + ' + ' + '-' * (max_value_length + 2) + ' +')
    print('| {:<{}} | {:>{}} |'.format('Key', max_key_length, 'Value', max_value_length))
    print('+ ' + '-' * (max_key_length + 2) + ' + ' + '-' * (max_value_length + 2) + ' +')
    for key, value in data.items():
        print('| {:<{}} | {:>{}} |'.format(key, max_key_length, value, max_value_length))
    print('+ ' + '-' * (max_key_length + 2) + ' + ' + '-' * (max_value_length + 2) + ' +')
```

26. Write a Python program to count the values associated with key in a dictionary.

Sample data: = [{'id': 1, 'success': True, 'name': 'Lary'}, {'id': 2, 'success': False, 'name': 'Rabi'}, {'id': 3, 'success': True, 'name': 'Alex'}]

Expected result: Count of how many dictionaries have success as True

ANS-

```
def count_dicts_with_value(data, key, value):
    count = 0
    for dictionary in data:
        if dictionary.get(key) == value:
            count += 1
    return count
```

27. Write a Python program to convert a list into a nested dictionary of keys.

ANS-

```
def list_to_nested_dict(lst):
    nested_dict = {}
    for item in reversed(lst):
        nested_dict = {item: nested_dict}
    return nested_dict
```

28. Write a Python program to sort a list alphabetically in a dictionary

ANS-

```
my_dict = {'fruit': ['apple', 'orange', 'banana', 'kiwi']}
my_dict['fruit'].sort()
print(my_dict)
```

29. Write a Python program to remove spaces from dictionary keys.

ANS-

```
my_dict = {'my key': 1, 'another key': 2, 'third key': 3}
new_dict = {key.replace(' ', ''): value for key, value in my_dict.items()}
print('Original dictionary:', my_dict)
print('New dictionary:', new_dict)
```

30. Write a Python program to get the top three items in a shop.

Sample data: {'item1': 45.50, 'item2': 35, 'item3': 41.30, 'item4': 55, 'item5': 24}

Expected Output:

item4 55

item1 45.5

item3 41.3

ANS-

```
shop_inventory = {'item1': 45.50, 'item2': 35, 'item3': 41.30, 'item4': 55, 'item5': 24}
```

```
top_three = sorted(shop_inventory.items(), key=lambda x: x[1], reverse=True)[:3]
```

```
for item, price in top_three:
```

```
    print(item, price)
```

31. Write a Python program to get the key, value and item in a dictionary.

ANS-

```
my_dict = {'apple': 2, 'banana': 3, 'orange': 4}
```

```
for key, value in my_dict.items():
```

```
    item = (key, value)
```

```
    print(f"Key: {key}, Value: {value}, Item: {item}")
```

32. Write a Python program to print a dictionary line by line.

ANS-

```
my_dict = {'apple': 2, 'banana': 3, 'orange': 4}
```

```
for key, value in my_dict.items():
```

```
    print(f"{key}: {value}")
```

33. Write a Python program to check multiple keys exists in a dictionary.

ANS-

```
my_dict = {'apple': 2, 'banana': 3, 'orange': 4, 'pear': 5}
keys_to_check = ['apple', 'banana', 'peach']
if all(key in my_dict for key in keys_to_check):
    print("All keys exist in the dictionary")
else:
    print("At least one key does not exist in the dictionary")
```

34. Write a Python program to count number of items in a dictionary value that is a list.

ANS-

```
my_dict = {'fruits': ['apple', 'banana', 'orange'], 'vegetables': ['carrot', 'celery']}
for key, value in my_dict.items():
    num_items = len(value)
    print(f"{key} has {num_items} items")
```

35. Write a Python program to sort Counter by value.

Sample data : {'Math':81, 'Physics':83, 'Chemistry':87}

Expected data: [('Chemistry', 87),
('Physics', 83), ('Math', 81)]

ANS-

```
from collections import Counter
my_counter = Counter({'Math':81, 'Physics':83, 'Chemistry':87})
sorted_counter = sorted(my_counter.items(), key=lambda x: x[1], reverse=True)
print(sorted_counter)
```

36. Write a Python program to create a dictionary from two lists without losing duplicate values.

Sample lists: ['Class-V', 'Class-VI', 'Class-VII', 'Class-VIII'], [1, 2, 2, 3]

Expected Output: defaultdict(<class 'set'>, {'Class-VII': {2}, 'Class-VI': {2}, 'Class-VIII': {3}, 'Class-V': {1}})

ANS-

```
from collections import defaultdict
keys = ['Class-V', 'Class-VI', 'Class-VII', 'Class-VIII']
values = [1, 2, 2, 3]
result = defaultdict(set)
for k, v in zip(keys, values):
```



```
result[k].add(v)
print(result)
```

37. Write a Python program to replace dictionary values with their sum.

ANS-

```
data = {'a': 10, 'b': 20, 'c': 30, 'd': 40}
total = sum(data.values())
for key in data:
    data[key] = total
print(data)
```

38. Write a Python program to match key values in two dictionaries.
Sample dictionary: {'key1': 1, 'key2': 3, 'key3': 2}, {'key1': 1, 'key2': 2}
Expected output: key1: 1 is present in both x and y

ANS-

```
x = {'key1': 1, 'key2': 3, 'key3': 2}
y = {'key1': 1, 'key2': 2}
for key in x:
    if key in y:
        if x[key] == y[key]:
            print(key + ": " + str(x[key]) + " is present in both x and y")
```