

```
1 package com.rkg.phase3;
2
3 import javax.persistence.Entity;
4 import javax.persistence.GeneratedValue;
5 import javax.persistence.GenerationType;
6 import javax.persistence.Id;
7
8 import lombok.Data;
9
10 @Data
11 @Entity
12 public class Buy {
13
14     @Id
15     @GeneratedValue(strategy = GenerationType.AUTO)
16     private int id;
17
18
19 }
20
```

```
1 package com.rkg.phase3;
2
3 import javax.persistence.Entity;
4 import javax.persistence.GeneratedValue;
5 import javax.persistence.GenerationType;
6 import javax.persistence.Id;
7
8 import lombok.Data;
9
10 @Data
11 @Entity
12 public class Cart {
13
14     @Id
15     @GeneratedValue(strategy = GenerationType.AUTO)
16     private int c_id;
17     private String pro_id;
18     private String pro_code;
19     private String pro_name;
20     private String pro_brand;
21     private String pro_price;
22
23     public int getC_id() {
24         return c_id;
25     }
26     public void setC_id(int c_id) {
27         this.c_id = c_id;
28     }
29     public String getPro_id() {
30         return pro_id;
31     }
32     public void setPro_id(String pro_id) {
33         this.pro_id = pro_id;
34     }
35     public String getPro_name() {
36         return pro_name;
37     }
38     public void setPro_name(String pro_name) {
39         this.pro_name = pro_name;
40     }
41     public String getPro_brand() {
```

```
42         return pro_brand;
43     }
44     public void setPro_brand(String pro_brand) {
45         this.pro_brand = pro_brand;
46     }
47     public String getPro_price() {
48         return pro_price;
49     }
50     public void setPro_price(String pro_price) {
51         this.pro_price = pro_price;
52     }
53     public String getPro_code() {
54         return pro_code;
55     }
56     public void setPro_code(String pro_code) {
57         this.pro_code = pro_code;
58     }
59     public Cart() {
60         super();
61         this.c_id = c_id;
62         this.pro_id = pro_id;
63         this.pro_code = pro_code;
64         this.pro_name = pro_name;
65         this.pro_brand = pro_brand;
66         this.pro_price = pro_price;
67     }
68     @Override
69     public String toString() {
70         return "Cart [c_id=" + c_id + ", pro_id=" +
71             + pro_id + ", pro_code=" + pro_code + ", pro_name =
72             + pro_name
73                 + ", pro_brand=" + pro_brand + ",
74             pro_price=" + pro_price + "]";
75     }
76 }
```

```
1 package com.rkg.phase3;
2
3 import javax.persistence.Entity;
4 import javax.persistence.GeneratedValue;
5 import javax.persistence.GenerationType;
6 import javax.persistence.Id;
7
8 import lombok.Data;
9
10 @Data
11 @Entity
12 public class User {
13     @Id
14     @GeneratedValue(strategy = GenerationType.AUTO)
15     private int user_id;
16     private String user_fname;
17     private String user_lname;
18     private String user_phone;
19     private String user_mail;
20     private String user_dob;
21     private String user_pass;
22     private String user_compass;
23     private String user_state;
24     private String user_dist;
25     private String user_taluka;
26     private String user_pin;
27     private String user_gender;
28     public int getUser_id() {
29         return user_id;
30     }
31
32     public void setUser_id(int user_id) {
33         this.user_id = user_id;
34     }
35
36     public String getUser_fname() {
37         return user_fname;
38     }
39
40     public void setUser_fname(String user_fname) {
41         this.user_fname = user_fname;
```

```
42     }
43
44     public String getUser_lname() {
45         return user_lname;
46     }
47
48     public void setUser_lname(String user_lname) {
49         this.user_lname = user_lname;
50     }
51
52     public String getUser_phone() {
53         return user_phone;
54     }
55
56     public void setUser_phone(String user_phone) {
57         this.user_phone = user_phone;
58     }
59
60     public String getUser_mail() {
61         return user_mail;
62     }
63
64     public void setUser_mail(String user_mail) {
65         this.user_mail = user_mail;
66     }
67
68     public String getUser_dob() {
69         return user_dob;
70     }
71
72     public void setUser_dob(String user_dob) {
73         this.user_dob = user_dob;
74     }
75
76     public String getUser_pass() {
77         return user_pass;
78     }
79
80     public void setUser_pass(String user_pass) {
81         this.user_pass = user_pass;
82     }
```

```
83
84     public String getUser_compass() {
85         return user_compass;
86     }
87
88     public void setUser_compass(String
89         user_compass) {
90         this.user_compass = user_compass;
91     }
92
93     public String getUser_state() {
94         return user_state;
95     }
96
97     public void setUser_state(String user_state) {
98         this.user_state = user_state;
99     }
100
101    public String getUser_dist() {
102        return user_dist;
103    }
104
105    public void setUser_dist(String user_dist) {
106        this.user_dist = user_dist;
107    }
108
109    public String getUser_taluka() {
110        return user_taluka;
111    }
112
113    public void setUser_taluka(String user_taluka
114    ) {
115        this.user_taluka = user_taluka;
116    }
117
118    public String getUser_pin() {
119        return user_pin;
120    }
121
122    public void setUser_pin(String user_pin) {
123        this.user_pin = user_pin;
```

```
122     }
123
124     public String getUser_gender() {
125         return user_gender;
126     }
127
128     public void setUser_gender(String user_gender)
129     {
130         this.user_gender = user_gender;
131     }
132
133     public User() {
134         super();
135         this.user_id = user_id;
136         this.user_fname = user_fname;
137         this.user_lname = user_lname;
138         this.user_phone = user_phone;
139         this.user_mail = user_mail;
140         this.user_dob = user_dob;
141         this.user_pass = user_pass;
142         this.user_conpass = user_conpass;
143         this.user_state = user_state;
144         this.user_dist = user_dist;
145         this.user_taluka = user_taluka;
146         this.user_pin = user_pin;
147         this.user_gender = user_gender;
148     }
149
150     @Override
151     public String toString() {
152         return "User [user_id=" + user_id + ", "
153         + user_fname + ", user_lname=" +
154         user_lname
155         + ", user_phone=" + user_phone +
156         ", user_mail=" + user_mail + ", user_dob=" +
157         user_dob + ", user_pass="
158         + user_pass + ", user_conpass=" +
159         user_conpass + ", user_state=" + user_state + ", "
160         + user_dist + ", user_taluka=" +
161         user_taluka + ", user_pin=" + user_pin + ", "
```

```
154 user_gender=" + user_gender  
155             + "]";  
156     }  
157 }  
158
```

```
1 package com.rkg.phase3;
2
3 import javax.persistence.Entity;
4 import javax.persistence.GeneratedValue;
5 import javax.persistence.GenerationType;
6 import javax.persistence.Id;
7
8 import lombok.Data;
9
10 @Data
11 @Entity
12 public class Admin {
13
14     @Id
15     @GeneratedValue(strategy = GenerationType.AUTO)
16     private int ad_id;
17     private String ad_fname;
18     private String ad_lname;
19     private String ad_phone;
20     private String ad_mail;
21     private String ad_dob;
22     private String ad_pass;
23     private String ad_con;
24     private String ad_state;
25     private String ad_dist;
26     private String ad_taluka;
27     private String ad_pin;
28     private String ad_gen;
29
30     public Admin() {
31         super();
32         this.ad_id = ad_id;
33         this.ad_fname = ad_fname;
34         this.ad_lname = ad_lname;
35         this.ad_phone = ad_phone;
36         this.ad_mail = ad_mail;
37         this.ad_dob = ad_dob;
38         this.ad_pass = ad_pass;
39         this.ad_con = ad_con;
40         this.ad_state = ad_state;
41         this.ad_dist = ad_dist;
```

```
42         this.ad_taluka = ad_taluka;
43         this.ad_pin = ad_pin;
44         this.ad_gen = ad_gen;
45         this.log_date = log_date;
46     }
47     @GeneratedValue(strategy = GenerationType.AUTO)
48     private String log_date;
49
50     public int getAd_id() {
51         return ad_id;
52     }
53
54     public void setAd_id(int ad_id) {
55         this.ad_id = ad_id;
56     }
57
58     public String getAd_fname() {
59         return ad_fname;
60     }
61
62     public void setAd_fname(String ad_fname) {
63         this.ad_fname = ad_fname;
64     }
65
66     public String getAd_lname() {
67         return ad_lname;
68     }
69
70     public void setAd_lname(String ad_lname) {
71         this.ad_lname = ad_lname;
72     }
73
74     public String getAd_phone() {
75         return ad_phone;
76     }
77
78     public void setAd_phone(String ad_phone) {
79         this.ad_phone = ad_phone;
80     }
81
82     public String getAd_mail() {
```

```
83         return ad_mail;
84     }
85
86     public void setAd_mail(String ad_mail) {
87         this.ad_mail = ad_mail;
88     }
89
90     public String getAd_dob() {
91         return ad_dob;
92     }
93
94     public void setAd_dob(String ad_dob) {
95         this.ad_dob = ad_dob;
96     }
97
98     public String getAd_pass() {
99         return ad_pass;
100    }
101
102    public void setAd_pass(String ad_pass) {
103        this.ad_pass = ad_pass;
104    }
105
106    public String getAd_con() {
107        return ad_con;
108    }
109
110    public void setAd_con(String ad_con) {
111        this.ad_con = ad_con;
112    }
113
114    public String getAd_state() {
115        return ad_state;
116    }
117
118    public void setAd_state(String ad_state) {
119        this.ad_state = ad_state;
120    }
121
122    public String getAd_dist() {
123        return ad_dist;
```

```
124     }
125
126     public void setAd_dist(String ad_dist) {
127         this.ad_dist = ad_dist;
128     }
129
130     public String getAd_taluka() {
131         return ad_taluka;
132     }
133
134     public void setAd_taluka(String ad_taluka) {
135         this.ad_taluka = ad_taluka;
136     }
137
138     public String getAd_pin() {
139         return ad_pin;
140     }
141
142     public void setAd_pin(String ad_pin) {
143         this.ad_pin = ad_pin;
144     }
145
146     public String getAd_gen() {
147         return ad_gen;
148     }
149
150
151     public void setAd_gen(String ad_gen) {
152         this.ad_gen = ad_gen;
153     }
154
155     public String getLog_date() {
156         return log_date;
157     }
158
159     public void setLog_date(String log_date) {
160         this.log_date = log_date;
161     }
162
163     @Override
164     public String toString() {
```

```
165     return "Admin [ad_id=" + ad_id + ",  
166         ad_fname=" + ad_fname + ", ad_lname=" + ad_lname  
167         + ", ad_phone=" + ad_phone  
168         + ", ad_mail=" + ad_mail + ",  
169         ad_dob=" + ad_dob + ", ad_pass=" + ad_pass + ",  
170         ad_con=" + ad_con  
171         + ", ad_state=" + ad_state + ",  
172         ad_dist=" + ad_dist + ", ad_taluka=" + ad_taluka  
173         + ", ad_pin=" + ad_pin  
174         + ", ad_gen=" + ad_gen + ",  
175         log_date=" + log_date + "]";  
176     }  
177 }  
178 }
```

```
1 package com.rkg.phase3;
2
3 import org.springframework.data.jpa.repository.
4 JpaRepository;
5
6 public interface BuyRepo extends JpaRepository<Buy
7 , Integer>{
8 }
```

```
1 package com.rkg.phase3;
2
3 import org.springframework.beans.factory.annotation.
4     Autowired;
4 import org.springframework.stereotype.Service;
5
6 @Service
7 public class CartDao {
8
9     @Autowired
10    CartRepo c_repo;
11
12    //USER INSERT ITEMS INTO CART'S
13    public Cart addcart(Cart c)
14    {
15        return c_repo.save(c);
16    }
17 }
18
```

```
1 package com.rkg.phase3;
2
3 import java.text.SimpleDateFormat;
4 import java.time.LocalDate;
5 import java.util.Date;
6
7 import javax.persistence.Entity;
8 import javax.persistence.GeneratedValue;
9 import javax.persistence.GenerationType;
10 import javax.persistence.Id;
11 import javax.servlet.jsp.tagext.TryCatchFinally;
12
13 import org.springframework.data.jpa.provider.HibernateUtils;
14
15 import lombok.Data;
16
17 @Data
18 @Entity
19 public class Product {
20
21     @Id
22     @GeneratedValue(strategy = GenerationType.AUTO)
23     private int pro_id;
24     private String pro_code;
25     private String pro_name;
26     private String pro_brand;
27     private String pro_price;
28     private String pro_about;
29     private String sell_date;
30
31     public Product() {
32         super();
33         this.pro_id = pro_id;
34         this.pro_code = pro_code;
35         this.pro_name = pro_name;
36         this.pro_brand = pro_brand;
37         this.pro_price = pro_price;
38         this.pro_about = pro_about;
39         this.sell_date = sell_date;
40     }
}
```

```
41 // String pattern = "dd/MM/yyyy";
42 // SimpleDateFormat simpleDateFormat = new
43 // SimpleDateFormat(pattern);
44 // String date = simpleDateFormat.format(new Date
45 // ());
46
47 // private Date timestamp = new Date(System.
48 // currentTimeMillis());
49
50     @Override
51     public String toString() {
52         return "Product [pro_id=" + pro_id + ",  

53             pro_code=" + pro_code + ", pro_name=" + pro_name +  

54             ", pro_brand=" +  

55                 pro_brand + ", pro_price=" +  

56                 pro_price + ", pro_about=" + pro_about + ",  

57                 sell_date=" + sell_date  

58                     + "]";
59     }
60
61     public int getPro_id() {
62         return pro_id;
63     }
64
65     public void setPro_id(int pro_id) {
66         this.pro_id = pro_id;
67     }
68
69     public String getPro_code() {
70         return pro_code;
71     }
72
73     public void setPro_code(String pro_code) {
74         this.pro_code = pro_code;
75     }
76
77     public String getPro_name() {
78         return pro_name;
79     }
80
81     public void setPro_name(String pro_name) {
82         this.pro_name = pro_name;
83     }
84 }
```

```
75      }
76
77      public String getPro_brand() {
78          return pro_brand;
79      }
80
81      public void setPro_brand(String pro_brand) {
82          this.pro_brand = pro_brand;
83      }
84
85      public String getPro_price() {
86          return pro_price;
87      }
88
89      public void setPro_price(String pro_price) {
90          this.pro_price = pro_price;
91      }
92
93      public String getPro_about() {
94          return pro_about;
95      }
96
97      public void setPro_about(String pro_about) {
98          this.pro_about = pro_about;
99      }
100
101     public String getSell_date() {
102         return sell_date;
103     }
104
105     public void setSell_date(String sell_date) {
106         this.sell_date = sell_date;
107     }
108 }
109
```

```
1 package com.rkg.phase3;
2
3 import java.util.List;
4
5 import org.springframework.beans.factory.annotation.Autowired;
6 import org.springframework.beans.factory.support.SecurityContextProvider;
7 import org.springframework.boot.autoconfigure.security.servlet.SecurityFilterAutoConfiguration;
8 import org.springframework.stereotype.Service;
9
10 @Service
11 public class UserDao {
12
13     @Autowired
14     UserRepo u_repo;
15
16     //USER-INSERTION-CODE
17     public User user_insert(User u)
18     {
19         return u_repo.save(u);
20     }
21
22     //GET-REGISTERED-USER'S-LIST
23     public List<User> user_get()
24     {
25         return u_repo.findAll();
26     }
27
28     //SEARCH USER BY FIRST NAME
29     public List<User> findByName(String user_fname)
30     {
31         return u_repo.findByName(user_fname);
32     }
33
34     //THIS CODE GIVES RETURN PASSWORD FOR USER
35     //USING PHONE NUMBER
36     public List<User> forget_pass(String user_phone
37     )
38     {
```

```
37         return u_repo.findByPhone(user_phone);
38     }
39
40     //SHOW LOGED USER DATA AS A PROFILE
41     public List<User> user_profile()
42     {
43         return u_repo.findAll();
44     }
45
46 }
```

```
1 package com.rkg.phase3;
2
3 import java.util.List;
4
5 import org.springframework.beans.factory.annotation.
6     Autowired;
6 import org.springframework.stereotype.Service;
7
8 @Service
9 public class AdminDao {
10
11     @Autowired
12     AdminRepo ad_repo;
13
14     //REGISTRATION-OF-ADMIN
15     public Admin ad_insert(Admin a)
16     {
17         return ad_repo.save(a);
18     }
19
20     //ADMIN LOGIN BY USER-NAME
21     public Admin ad_login(String ad_fname)
22     {
23         return ad_repo.findbyname(ad_fname);
24     }
25
26     //THIS CODE GIVES RETURN PASSWORD FOR ADMIN
27     // USING PHONE NUMBER
27     public List<Admin> forget_ad_pass(String
28     ad_phone)
29     {
30         return ad_repo.findByAdPhone(ad_phone);
31     }
32 }
```

```
1 package com.rkg.phase3;
2
3 import org.springframework.data.jpa.repository.
4 JpaRepository;
5
6 public interface CartRepo extends JpaRepository<
7     Cart, Integer>{
8 }
```

```
1 package com.rkg.phase3;
2
3 import java.util.List;
4
5 import org.springframework.data.jpa.repository.JpaRepository;
6 import org.springframework.data.jpa.repository.Query;
7
8 public interface UserRepo extends JpaRepository<User, Integer>{
9
10
11     @Query("select user from User user where user.
12         user_fname=?1")
13     public User findbyname(String user_fname);
14
15     @Query("select u from User u where u.user_fname
16         =?1")
17     public List<User> findByName(String user_fname
18 );
19 }
20
```

```
1 package com.rkg.phase3;
2
3 import java.util.List;
4
5 import org.springframework.data.jpa.repository.
JpaRepository;
6 import org.springframework.data.jpa.repository.
Query;
7
8 public interface AdminRepo extends JpaRepository<
Admin, Integer>{
9
10     @Query("select admin from Admin admin where
admin.ad_fname=?1")
11     public Admin findbyname(String ad_fname);
12
13     @Query("select ad from Admin ad where ad.
ad_phone=?1")
14     public List<Admin> findByAdPhone(String
ad_phone);
15 }
16
```

```
1 package com.rkg.phase3;
2
3 import java.util.Date;
4 import java.util.List;
5
6 import org.springframework.beans.factory.annotation
7 .Autowired;
7 import org.springframework.stereotype.Service;
8
9 @Service
10 public class ProductDao {
11
12     @Autowired
13     ProductRepo pro_repo;
14
15     //INSERT PRODUCT HERE
16     public Product insert_product(Product p)
17     {
18         return pro_repo.save(p);
19     }
20
21     //SHOW AVILIABLE PRODUCT LIST
22     public List<Product> aviliablePro()
23     {
24         return pro_repo.findAll();
25     }
26
27
28     //GET REPORT USING PRODUCT CODE
29 //     public List<Product> report(Date timestamp)
30 //     {
31 //         return pro_repo.findBypcode(timestamp);
32 //     }
33
34
35 }
```

```
1 package com.rkg.phase3;
2
3 import org.springframework.boot.SpringApplication;
4 import org.springframework.boot.autoconfigure.
5   SpringApplication;
6
7 @SpringBootApplication
8 public class Application {
9
10   public static void main(String[] args) {
11     SpringApplication.run(Application.class,
12       args);
13   }
14 }
```

```
1 package com.rkg.phase3;
2
3 import java.util.List;
4
5 import org.springframework.data.jpa.repository.
JpaRepository;
6 import org.springframework.data.jpa.repository.
Query;
7
8
9
10 public interface ProductRepo extends JpaRepository<
Product, Integer>{
11
12     @Query("select pr from Product pr where pr.
sell_date=?1")
13     public List<Product> findByDate(String
sell_date);
14 }
15
```

```
1 package com.rkg.phase3;
2
3 import java.util.Date;
4 import java.util.List;
5
6 import javax.servlet.http.HttpServletRequest;
7 import javax.servlet.http.HttpServletResponse;
8
9 import org.springframework.beans.factory.annotation.
10    Autowired;
11 import org.springframework.stereotype.Controller;
12 import org.springframework.web.bind.annotation.
13    PathVariable;
14 import org.springframework.web.bind.annotation.
15    RequestMapping;
16 import org.springframework.web.bind.annotation.
17    ResponseBody;
18 import org.springframework.web.servlet.ModelAndView
19 ;
20 import org.springframework.web.servlet.view.
21    RedirectView;
22
23 @Controller
24 public class AllController {
25
26     /*HERE WE CREATE REPOSITORY'S OBJECT'S*/
27     @Autowired
28     UserRepo u_repo;
29
30     @Autowired
31     AdminRepo a_repo;
32
33     @Autowired
34     ProductRepo pro_repo;
35
36     @Autowired
37     CartRepo c_repo;
38
39     /*HERE WE CREATE DAO OBJECT'S*/
40     @Autowired
41     AdminDao a_dao;
```

```
36
37     @Autowired
38     UserDao u_dao;
39
40     @Autowired
41     ProductDao pro_dao;
42
43     @Autowired
44     CartDao c_dao;
45
46     /*USER OPERETION'S START FROM HERE*/
47
48     //USER CAN REGISTER USING THIS CODE
49     @ResponseBody
50     @RequestMapping("/user_insert")
51     public ModelAndView user_insert(
52         HttpServletRequest req, HttpServletResponse res)
53     {
54         ModelAndView mv = new ModelAndView();
55         User u = new User();
56         u.setUser_fname(req.getParameter("user_fname"));
57         u.setUser_lname(req.getParameter("user_lname"));
58         u.setUser_phone(req.getParameter("user_phone"));
59         u.setUser_mail(req.getParameter("user_mail"));
60         u.setUser_dob(req.getParameter("user_dob"));
61         u.setUser_pass(req.getParameter("user_pass"));
62         u.setUser_conpass(req.getParameter("user_conpass"));
63         u.setUser_state(req.getParameter("user_state"));
64         u.setUser_dist(req.getParameter("user_dist"));
65         u.setUser_taluka(req.getParameter("user_taluka"));
66         u.setUser_pin(req.getParameter("user_pin"));
```

```
65 });
66         u.setUser_gender(req.getParameter("user_gender"));
67         User ss = u_dao.user_insert(u);
68         if(ss!=null)
69         {
70             mv.setViewName("user_reg_succ");
71         }
72         return mv;
73     }
74
75
76     //ADMIN CAN SEE LIST OF SIGN-UP USER'S USING
77     THIS CODE
78     @ResponseBody
79     @RequestMapping("/user_get")
80     public ModelAndView user_get(
81         HttpServletRequest req, HttpServletResponse res)
82     {
83         ModelAndView mv = new ModelAndView();
84         List<User> list = u_dao.user_get();
85         mv.setViewName("all_user_list");
86         mv.addObject("list", list);
87         return mv;
88     }
89
90     //USER LOGIN USING THIS CODE
91     @ResponseBody
92     @RequestMapping("/user_login")
93     public String user_login(HttpServletRequest req, HttpServletResponse res)
94     {
95         String user_fname = req.getParameter("user_fname");
96         String user_conpass = req.getParameter("user_conpass");
97
98         if(u_repo.findbyname(user_fname)!=null)
99         {
100             return "Welcome Back"+ " "+ user_fname;
101         }else {
```

```

100          return "Check Credential's or Register
101      " + " ";
102  }
103
104 //USER CAN FORGET HIS PASSWORD USING THIS CODE
105 @ResponseBody
106 @RequestMapping("/forget_pass")
107 public ModelAndView forget_pass(
    HttpServletRequest req, HttpServletResponse res)
108 {
109     ModelAndView mv = new ModelAndView();
110     String user_phone = req.getParameter(
        "user_phone");
111     List<User> u_pass = u_dao.forget_pass(
        user_phone);
112     mv.setViewName("get_user_pass");
113     mv.addObject("u_pass", u_pass);
114     return mv;
115 }
116
117 //USER PROFILE
118 @ResponseBody
119 @RequestMapping("/user_profile")
120 public ModelAndView user_profile(
    HttpServletRequest req, HttpServletResponse res)
121 {
122     ModelAndView mv = new ModelAndView();
123     List<User> user_list = u_dao.user_profile
        ();
124     mv.setViewName("get_user_profile");
125     mv.addObject("user_list", user_list);
126     return mv;
127 }
128
129 //SHOW ALL AVILIABLE PRODUCT'S TO USER
130 @ResponseBody
131 @RequestMapping("/aviliablePro")
132 public ModelAndView aviliablePro(
    HttpServletRequest req, HttpServletResponse res)
133 {

```

```

134         ModelAndView mv = new ModelAndView();
135         List<Product> avil_pro = pro_dao.
136             aviliablePro();
137         mv.setViewName("avil_product");
138         mv.addObject("avil_pro",avil_pro);
139         return mv;
140     }
141     /*USER OPERETION'S END HERE*/
142
143
144     /*ADMIN OPERATIONS START*/
145
146     //ADMIN CAN APPLY FOR LOGIN CREDENCAL'S HERE
147     @ResponseBody
148     @RequestMapping("/apply_admin")
149     public ModelAndView ad_insert(
150         HttpServletRequest req, HttpServletResponse res)
151     {
152         ModelAndView mv = new ModelAndView();
153         Admin A = new Admin();
154         A.setAd_fname(req.getParameter("ad_fname"));
155         A.setAd_lname(req.getParameter("ad_lname"));
156         A.setAd_phone(req.getParameter("ad_phone"));
157         A.setAd_mail(req.getParameter("ad_mail"));
158         A.setAd_pass(req.getParameter("ad_pass"));
159         A.setAd_con(req.getParameter("ad_con"));
160         A.setAd_state(req.getParameter("ad_state"));
161         A.setAd_dist(req.getParameter("ad_dist"));
162         A.setAd_taluka(req.getParameter("ad_taluka"));
163         A.setAd_pin(req.getParameter("ad_pin"));
164         A.setAd_gen(req.getParameter("ad_gen"));
165         Admin aa = a_dao.ad_insert(A);
166         if(aa!=null)
167         {
168             mv.setViewName("ad_reg_succ");

```

```

168         }
169         return mv;
170     }
171
172     //ADMIN LOGIN USING USER NAME
173     @ResponseBody
174     @RequestMapping("/ad_login")
175     public String ad_login(HttpServletRequest req
, HttpServletResponse res)
176     {
177         String ad_fname = req.getParameter("ad_fname");
178         String ad_con = req.getParameter("ad_con");
179
180         if(a_repo.findbyname(ad_fname)!=null)
181     }
182         return "Welcome Back "+ " "+ ad_fname;
183     }else
184     {
185         return "Check Credencial's" + " ";
186     }
187 }
188
189
190     //ADMIN SEARCH USER USING THIS CODE
191     @ResponseBody
192     @RequestMapping("/search_user")
193     public ModelAndView search_user(
HttpServletRequest req, HttpServletResponse res)
194     {
195         ModelAndView mv = new ModelAndView();
196         String user_fname = req.getParameter("user_fname");
197         List<User> u_list = u_dao.findByName(
user_fname);
198         mv.setViewName("search_user_list");
199         mv.addObject("u_list", u_list);
200         if(u_dao==null)
201     }

```

```

202             mv.setViewName("search_error");
203         }
204         return mv;
205     }
206
207     //ADMIN CAN GET REPORT USING THIS CODE
208     @ResponseBody
209     @RequestMapping("/get_report")
210     public ModelAndView report(HttpServletRequest
req, HttpServletResponse res)
211     {
212         ModelAndView mv = new ModelAndView
();
213         String sell_date = req.getParameter("sell_date");
214         List<Product> r_list = pro_repo.findByDate
(sell_date);
215         mv.setViewName("get_report_here");
216         mv.addObject("r_list",r_list);
217         if(pro_dao==null)
218         {
219             mv.setViewName("report_error");
220         }
221         return mv;
222     }
223
224     //ADMIN CAN FORGOT PASSWORD USING REGISTERED
MOBILE NUMBER ONLY
225     @ResponseBody
226     @RequestMapping("forget_ad_pass")
227     public ModelAndView forget_ad_pass(
HttpServletRequest req, HttpServletResponse res)
228     {
229         ModelAndView mv = new ModelAndView();
230         String ad_phone = req.getParameter("ad_phone");
231         List<Admin> pass_list = a_dao.
forget_ad_pass(ad_phone);
232         mv.setViewName("get_admin_pass");
233         mv.addObject("pass_list",pass_list);
234         return mv;

```

```

235 }
236
237     /*ADMIN OPERATIONS END HERE*/
238
239
240     /**> PRODUCT OPERATIONS START HERE <--*/
241
242     //INSERTING PRODUCT CODE
243     @ResponseBody
244     @RequestMapping("/insert_product")
245     public ModelAndView insert_product(
246         HttpServletRequest req, HttpServletResponse res)
247     {
248         ModelAndView mv = new ModelAndView();
249         Product p = new Product();
250         p.setPro_code(req.getParameter("pro_code"));
251         p.setPro_name(req.getParameter("pro_name"));
252         p.setPro_brand(req.getParameter("pro_brand"));
253         p.setPro_price(req.getParameter("pro_price"));
254         p.setPro_about(req.getParameter("pro_about"));
255         p.setSell_date(req.getParameter("sell_date"));
256         Product pp = pro_dao.insert_product(p);
257         if(pp!=null)
258         {
259             mv.setViewName("pro_reg_succ");
260         }
261         return mv;
262     }
263
264     @ResponseBody
265     @RequestMapping("/addcart/{pro_code}")
266     public RedirectView addCart(@PathVariable("pro_code") String pro_code, HttpServletRequest req, HttpServletResponse res)
267     {

```

```
267         RedirectView rv = new RedirectView();
268         Cart c = new Cart();
269         c.setPro_code(pro_code);
270         return rv;
271     }
272
273     /*--> PRODUCT OPERATIONS END HERE <---*/
274 }
275
```

```
1 package com.rkg.phase3;
2
3 import org.springframework.boot.builder.
4 SpringApplicationBuilder;
5 import org.springframework.boot.web.servlet.support
6 .SpringBootServletInitializer;
7
8 @Override
9 protected SpringApplicationBuilder configure(
10    SpringApplicationBuilder application) {
11     return application.sources(Application.
12         class);
13 }
14
```

```
1 <%@page import="com.fasterxml.jackson.annotation.  
    JsonInclude.Include"%>  
2 <%@ page language="java" contentType="text/html;  
    charset=ISO-8859-1"  
3     pageEncoding="ISO-8859-1"%>  
4     <meta name="viewport"  
5         content="width=device-width, initial-  
6             scale=1, shrink-to-fit=no">  
7             <%@page isELIgnored="false" %>  
8                 <%@taglib prefix="c" uri="http://java.sun  
9 .com/jsp/jstl/core" %>  
10  
9 <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/css/bootstrap.min.css"  
    integrity="sha384-Gn5384xqQ1aoWXA+  
058RXPxPg6fy4IWvTNh0E263XmFcJlSAwiGgFAW/dAiS6JXm"  
    crossorigin="anonymous">  
10  
11 <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/font-awesome@6.1.1/css/all.min.css"  
    integrity="sha512-KfkfwYDsLkIlwQp6LFnl8zNdLGxu9YAA1QvwINks4PhcElQSvqc  
yVLLD9aMhXd13uQjoXtEKNosOWaZqXgel0g==" crossorigin="anonymous" referrerPolicy="no-referrer" />  
12  
13 <script  
14     src="https://code.jquery.com/jquery-3.2.1.  
    slim.min.js"  
15     integrity="sha384-  
KJ3o2DKtIkYIK3UENzm7KCKRr/rE9/Qpg6aAZGJwFDMVNA/  
    GpGFF93hXpG5KkN"  
16     crossorigin="anonymous">  
17 </script>  
18  
19 <script  
20     src="https://cdn.jsdelivr.net/npm/popper.js  
    @1.12.9/dist/umd/popper.min.js"  
21     integrity="sha384-ApNbgh9B+  
Y1QKtv3Rn7W3mgPxhU9K/  
    ScQsAP7hUiBx39j7fakFPskvXusvfa0b4Q"  
22     crossorigin="anonymous">
```

```
23 </script>
24
25 <script
26     src="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/js/bootstrap.min.js"
27     integrity="sha384-JZR6Spejh4U02d8j0t6vLEHfe/JQGiRRSQxSfFWpi1MquVdAyjUar5+76PVCmYl"
28     crossorigin="anonymous">
29 </script>
30
31     <title><c:out value="${title }"></c:out>
32         SportyShoes RKG</title>
33
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 750px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30     padding: 5px;
31     width: 70px;
32     height: 30px;
33 }
34
35 .db{
36     cursor: pointer;
37 }
38
39 .head{
40     max-width: 300px;
```

```
41      border: 2px solid #FFFFAFA;
42      position: relative;
43      margin: auto;
44      padding: 2px;
45      padding-right: 2px;
46      font-size: 47px;
47 }
48
49 .sh{
50     font-family: Garamond;
51     font-size: 20px;
52     color: green;
53     padding: 1px;
54     padding-top: 1px;
55     max-width: 500px;
56     margin: 1%;
57 }
58
59 .err{
60     color: red;
61 }
62
63 .log{
64     color: blue;
65 }
66
67 .admin{
68     text-decoration: none;
69     color: blue;
70 }
71
72 .forget_pass{
73     color: blue;
74     text-decoration: none;
75 }
76 </style>
77 </head>
78 <h3 class="sh">SportyShoes.com</h3>
79 <hr>
80 <br><br>
81 <h1 class="head">Admin <a class="log">Log In</a></
```



```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .log{
10     text-decoration: none;
11     color: blue;
12 }
13
14 .insert{
15     text-decoration: none;
16     color: blue;
17 }
18
19 .main{
20     background-color: #FFFAFA;
21 }
22
23 .sh{
24     font-family: Garamond;
25     font-size:20px;
26     color: green;
27     padding:1px;
28     padding-top:1px;
29     max-width:500px;
30     margin: 1%;
31 }
32 </style>
33 </head>
34 <h3 class="sh">SportyShoes.com</h3>
35 <hr>
36 <img alt="" src="">
37 <body class="main">
38 <h1>No Data to Show.....!</h1>
39 <h2>Log in to my account<a class="log" href="
  user_login.jsp"> User</a> /<a class="log" href="
```

```
39 ad_login.jsp"> Admin</a></h2>
40 <h3>If you Don't have account then Create Here<a
  class="insert" href="insert_user.jsp"> For User</a
> & <a class="insert" href="apply_admin.jsp">For
  Admin</a></h3>
41 </body>
42 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=UTF-8"
2     pageEncoding="UTF-8"%>
3
4 <!DOCTYPE html>
5 <html>
6 <head>
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9
10 .main{
11     margin: 0;
12     padding: 0;
13     background:#FAF0E6;
14     font-family: Sul Sans,Helvetica Neue,Helvetica,
15     Roboto,Arial,sans-serif;
16     font-weight: 400;
17     line-height: 1.5;
18     color: #FFFAFA;
19     -webkit-font-smoothing: antialiased
20     background-color: #FFFAFA;
21 }
22
23 .bx {
24     padding: 0;
25     background-color: black;
26     overflow: hidden;
27     border-radius: 0;
28     height:150px;
29     max-height: 210px;
30     margin: auto;
31     padding-top: 20px;
32     border-bottom-left-radius: 20px;
33     border-bottom-right-radius: 20px;
34 }
35
36 .head{
37     font-family: Garamond;
38     font-size:30px;
39     color: green;
```

```
40     padding:1px;
41     max-width:500px;
42     padding-top: 100px;
43 }
44
45 .sh {
46     position: absolute;
47     top: 21%;
48     left: 9%;
49     transform: translate(-50%, -50%);
50     font-family: Garamond;
51     color: green;
52     font-size:27px;
53 }
54
55 .active{
56     display :block;
57     text-decoration: none;
58     float: right;
59     padding: 1%;
60     margin: auto;
61     margin-right : 1%;
62     margin-left : 1%;
63     font-size: 27px;
64     font-family: Garamond;
65     color: green;
66 }
67
68
69 .active a:hover {
70     background: gray;
71 }
72
73 .img{
74     position: absolute;
75     margin-left: 2%;
76     margin-right: 2%;
77     max-height: 200px;
78     max-width: 400px;
79 }
80
```

```
81 .info{
82     color: black;
83     font-family: Garamond;
84     float: right;
85     padding-right: 15px;
86 }
87 </style>
88 </head>
89
90 <body class="main">
91
92
93 <div class="bx">
94 <div class="container">
95 
96 <h3 class="sh"></h3>
97 </div>
98 <br><br>
99
100 <a class="active" href="HOME_SCREEN.jsp"><b>LOG-
    OUT</b></a>
101 <a class="active" href="user_login.jsp"><b>LOGIN</b></a>
102 <a class="active" href="insert_user.jsp"><b>
    REGISTER</b></a>
103 <a class="active" href="User_main.jsp"><b>HOME</b>
    </a>
104 </div>
105 <h4 class="info">User Page</h4>
106 <br>
107 </body>
108 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=UTF-8"
2     pageEncoding=UTF-8"%>
3
4 <!DOCTYPE html>
5 <html>
6 <head>
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9
10 .main{
11     margin: 0;
12     padding: 0;
13     background:#FAF0E6;
14     font-family: Sul Sans,Helvetica Neue,Helvetica,
15     Roboto,Arial,sans-serif;
15     font-weight: 400;
16     line-height: 1.5;
17     color: #FFFAFA;
18     -webkit-font-smoothing: antialiased
19     background-color: #FFFAFA;
20
21 }
22
23 .bx {
24     padding: 0;
25     background-color: black;
26     overflow: hidden;
27     border-radius: 0;
28     height:150px;
29     max-height: 210px;
30     margin: auto;
31     padding-top: 20px;
32     border-bottom-left-radius: 20px;
33     border-bottom-right-radius: 20px;
34 }
35
36 .head{
37     font-family: Garamond;
38     font-size:30px;
39     color: green;
```

```
40     padding:1px;
41     max-width:500px;
42     padding-top: 100px;
43 }
44
45 .sh {
46     position: absolute;
47     top: 21%;
48     left: 9%;
49     transform: translate(-50%, -50%);
50     font-family: Garamond;
51     color: green;
52     font-size:27px;
53 }
54
55 .active{
56     display :block;
57     text-decoration: none;
58     float: right;
59     padding: 1%;
60     margin: auto;
61     margin-right : 1%;
62     margin-left : 1%;
63     font-size: 27px;
64     font-family: Garamond;
65     color: green;
66 }
67
68
69 .active a:hover {
70     background: gray;
71 }
72
73 .img{
74     position: absolute;
75     margin-left: 2%;
76     margin-right: 2%;
77     max-height: 200px;
78     max-width: 400px;
79 }
80
```

```
81 .info{
82     color: black;
83     font-family: Garamond;
84     float: right;
85     padding-right: 15px;
86 }
87 </style>
88 </head>
89
90 <body class="main">
91
92
93 <div class="bx">
94 <div class="container">
95 
96 <h3 class="sh"></h3>
97 </div>
98 <br><br>
99
100 <a class="active" href="ad_login.jsp"><b>LOGIN</b></a>
101 <a class="active" href="apply_admin.jsp"><b>APPLY</b></a>
102 <a class="active" href="Admin_main.jsp"><b>HOME</b></a>
103 </div>
104 <h4 class="info">Admin Page</h4>
105 <br>
106 </body>
107 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 750px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30     padding: 5px;
31     width: 70px;
32     height: 30px;
33 }
34
35 .db{
36     cursor: pointer;
37 }
38
39 .head{
40     max-width: 300px;
```

```
41     border: 2px solid #FFFFAFA;
42     position: relative;
43     margin: auto;
44     padding: 2px;
45     padding-right: 2px;
46     font-size: 47px;
47 }
48
49 .sh{
50     font-family: Garamond;
51     font-size: 20px;
52     color: green;
53     padding: 1px;
54     padding-top: 1px;
55     max-width: 500px;
56     margin: 1%;
57 }
58
59 .err{
60     color: red;
61 }
62
63 .log{
64     color: blue;
65 }
66
67 .ac{
68     text-decoration: none;
69 }
70
71 .forget_pass{
72     color: blue;
73     text-decoration: none;
74 }
75
76 </style>
77 </head>
78 <h3 class="sh">SportyShoes.com</h3>
79 <hr>
80 <br><br>
81 <h1 class="head">User <a class="log">Log In</a></h1>
```



```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 750px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30 }
31
32 .db{
33     cursor: pointer;
34 }
35
36 .head{
37     max-width: 280px;
38     border: 2px solid #FFFAFA;
39     position: relative;
40     margin: auto;
```



```
1 <%@ page language="java" contentType="text/html;
  charset=UTF-8"
2     pageEncoding=UTF-8"%>
3
4 <!DOCTYPE html>
5 <html>
6 <head>
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9
10 .main{
11     margin: 0;
12     padding: 0;
13     background:#FAF0E6;
14     font-family: Sul Sans,Helvetica Neue,Helvetica,
15     Roboto,Arial,sans-serif;
15     font-weight: 400;
16     line-height: 1.5;
17     color: #FFFAFA;
18     -webkit-font-smoothing: antialiased
19     background-color: #FFFAFA;
20
21 }
22
23 .bx {
24     padding: 0;
25     background-color: black;
26     overflow: hidden;
27     border-radius: 0;
28     height:150px;
29     max-height: 210px;
30     margin: auto;
31     padding-top: 20px;
32     border-bottom-left-radius: 20px;
33     border-bottom-right-radius: 20px;
34 }
35
36 .head{
37     font-family: Garamond;
38     font-size:30px;
39     color: green;
```

```
40     padding:1px;
41     max-width:500px;
42     padding-top: 100px;
43 }
44
45 .sh {
46     position: absolute;
47     top: 21%;
48     left: 9%;
49     transform: translate(-50%, -50%);
50     font-family: Garamond;
51     color: green;
52     font-size:27px;
53 }
54
55 .active{
56     display :block;
57     text-decoration: none;
58     float: right;
59     padding: 1%;
60     margin: auto;
61     margin-right : 1%;
62     margin-left : 1%;
63     font-size: 22px;
64     font-family: Garamond;
65     color: green;
66 }
67
68
69 .active a:hover {
70     background: gray;
71 }
72
73 .img{
74     position: absolute;
75     margin-left: 2%;
76     margin-right: 2%;
77     max-height: 200px;
78     max-width: 400px;
79 }
80 </style>
```

```
81 </head>
82
83 <body class="main">
84
85
86 <div class="bx">
87 <div class="container">
88 
89 <h3 class="sh"></h3>
90 </div>
91 <br><br>
92 <a class="active" href="HOME_CART.jsp"><b>CART</b></a>
93 <a class="active" href="User_main.jsp"><b>USER</b></a>
94 <a class="active" href="Admin_main.jsp"><b>ADMIN</b></a>
95 <a class="active" href="HOME_SCREEN.jsp"><b>HOME</b></a>
96
97 </div>
98 </body>
99 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 750px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30 }
31
32 .db{
33     cursor: pointer;
34 }
35
36 .head{
37     max-width: 490px;
38     border: 2px solid #FFFAFA;
39     position: relative;
40     margin: auto;
```

```
41     padding:2px;
42     padding-right: 2px;
43 }
44
45 .sh{
46     font-family: Garamond;
47     font-size:20px;
48     color: green;
49     padding:1px;
50     padding-top:1px;
51     max-width:500px;
52     margin: 1%;
53 }
54
55 .reg{
56     color: blue;
57 }
58
59 .log-in{
60     cursor: pointer;
61     padding:15px;
62     width: 90px;
63     height: 30px;
64     text-decoration: none;
65 }
66
67 </style>
68 </head>
69 <h3 class="sh">SportyShoes.com</h3>
70 <hr>
71 <br>
72 <h1 class="head">USER <a class="reg">REGISTRATION
...!</a></h1><br>
73 <body class="main">
74 <div class="box">
75
76 <form action="user_insert">
77
78 &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<b>First Name
:</b>&nbsp;
79 <input type="text" name="user_fname" placeholder="
```



```
121
122 </form>
123 </div>
124 </body>
125 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <h1>collect report from here</h1>
10 <body>
11 <form action="get_report">
12 <input type="date" name="sell_date">
13 <input type="submit" value="Get Report">
14 </form>
15 </body>
16 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=UTF-8"
2     pageEncoding="UTF-8"%>
3
4 <!DOCTYPE html>
5 <html>
6 <head>
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9
10 .main{
11     margin: 0;
12     padding: 0;
13     background:#FAF0E6;
14     font-family: Sul Sans,Helvetica Neue,Helvetica,
15     Roboto,Arial,sans-serif;
15     font-weight: 400;
16     line-height: 1.5;
17     color: #FFFAFA;
18     -webkit-font-smoothing: antialiased
19     background-color: #FFFAFA;
20
21 }
22
23 .bx {
24     padding: 0;
25     background-color: black;
26     overflow: hidden;
27     border-radius: 0;
28     height:150px;
29     max-height: 210px;
30     margin: auto;
31     padding-top: 20px;
32     border-bottom-left-radius: 20px;
33     border-bottom-right-radius: 20px;
34 }
35
36 .head{
37     font-family: Garamond;
38     font-size:30px;
39     color: green;
```

```
40     padding:1px;
41     max-width:500px;
42     padding-top: 100px;
43 }
44
45 .sh {
46     position: absolute;
47     top: 21%;
48     left: 9%;
49     transform: translate(-50%, -50%);
50     font-family: Garamond;
51     color: green;
52     font-size:27px;
53 }
54
55 .active{
56     display :block;
57     text-decoration: none;
58     float: right;
59     padding: 1%;
60     margin: auto;
61     margin-right : 1%;
62     margin-left : 1%;
63     font-size: 22px;
64     font-family: Garamond;
65     color: green;
66 }
67
68
69 .active a:hover {
70     background: gray;
71 }
72
73 .img{
74     position: absolute;
75     margin-left: 2%;
76     margin-right: 2%;
77     max-height: 200px;
78     max-width: 400px;
79 }
80
```

```
81 .pro-img{  
82     float : right;  
83     margin-top : -2%;  
84     margin-left: 2%;  
85     margin-right: 2%;  
86     margin-bottom: 2%;  
87     max-height: 100px;  
88     max-width: 120px;  
89     cursor: pointer;  
90 }  
91 </style>  
92 </head>  
93  
94 <body class="main">  
95  
96  
97 <div class="bx">  
98 <div class="container">  
99   
100 <h3 class="sh"></h3>  
101 </div>  
102 <br><br>  
103 <a href="">  
104   
105 </a>  
106 <a class="active" href="HOME_SCREEN.jsp"><b>LOG  
OUT</b></a>  
107 <a class="active" href="ad_get_report.jsp"><b>  
REPORT</b></a>  
108 <a class="active" href="ad_search_users.jsp"><b>  
SEARCH USER</b></a>  
109 <a class="active" href="/user_get"><b>USER LIST</b  
></a>  
110 <a class="active" href="insert_product.jsp"><b>ADD  
PRODUCT</b></a>  
111  
112 </div>  
113 </body>  
114 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7     <%@include file=".base.jsp" %>
8 <style type="text/css">
9 .box {
10     max-width: 750px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30 }
31
32 .db{
33     cursor: pointer;
34 }
35
36 .head{
37     max-width: 300px;
38     border: 2px solid #FFFAFA;
39     position: relative;
40     margin: auto;
```

```
41     padding:2px;
42     padding-right: 2px;
43 }
44
45 .sh{
46     font-family: Garamond;
47     font-size:20px;
48     color: green;
49     padding:1px;
50     padding-top:1px;
51     max-width:500px;
52     margin: 1%;
53 }
54
55 .reg{
56     color: blue;
57 }
58
59 .log-in{
60     cursor: pointer;
61     padding:15px;
62     width: 90px;
63     height: 30px;
64     text-decoration: none;
65 }
66
67 </style>
68 </head>
69 <h3 class="sh">SportyShoes.com</h3>
70 <hr>
71 <br>
72 <h1 class="head">Insert <a class="reg">PRODUCT
...!</a></h1><br>
73 <body class="main">
74 <div class="box">
75
76 <form action="insert_product">
77
78 &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;<b>Product Code
:</b>&nbsp;
79 <input type="text" name="pro_code" placeholder="
```



```
103 <a href="after_ad_login.jsp" class="btn btn-
    outline-danger">Back</a>
104 <button type="submit" class="btn btn-primary">Add
    </button>
105 </div>
106 </form>
107 </div>
108 </body>
109 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 450px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30     padding: 5px;
31     width: 70px;
32     height: 30px;
33 }
34
35 .db{
36     cursor: pointer;
37 }
38
39 .head{
40     max-width: 475px;
```



```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 300px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30     padding: 5px;
31     width: 100px;
32     height: 30px;
33     margin: auto;
34     margin-right: 10%;
35     margin-left: 12%;
36 }
37
38 .db{
39     cursor: pointer;
40 }
```

```
41
42 .head{
43     max-width: 350px;
44     border: 2px solid #FFFFAFA;
45     position: relative;
46     margin: auto;
47     padding: 2px;
48     padding-right: 2px;
49     font-size: 47px;
50 }
51
52 .sh{
53     font-family: Garamond;
54     font-size: 20px;
55     color: green;
56     padding: 1px;
57     padding-top: 1px;
58     max-width: 500px;
59     margin: 1%;
60 }
61
62 .err{
63     color: red;
64 }
65
66 .log{
67     color: blue;
68 }
69
70 .ac{
71     text-decoration: none;
72 }
73
74 .forget_pass{
75     color: blue;
76     text-decoration: none;
77 }
78
79 </style>
80 </head>
81 <h3 class="sh">SportyShoes.com</h3>
```



```
1
2 <!DOCTYPE html>
3 <html>
4 <head>
5   <%@ page import="java.util.*" %>
6   <%@ page import="com.rkg.phase3.*" %>
7
8 <%@include file=".base.jsp" %>
9 <%@taglib prefix="c" uri="http://java.sun.com/jsp/
jstl/core" %>
10
11 <style type="text/css">
12
13 .main{
14   margin: 0;
15   padding: 0;
16   background:#FAF0E6;
17   font-family: Sul Sans,Helvetica Neue,Helvetica,
18   Roboto,Arial,sans-serif;
19   font-weight: 400;
20   line-height: 1.5;
21   color: #FFFAFA;
22   -webkit-font-smoothing: antialiased
23   background-color: #FFFAFA;
24 }
25
26 .bx {
27   padding: 0;
28   background-color: black;
29   overflow: hidden;
30   border-radius: 0;
31   height:150px;
32   max-height: 210px;
33   margin: auto;
34   padding-top: 20px;
35   border-bottom-left-radius: 20px;
36   border-bottom-right-radius: 20px;
37 }
38
39 .head{
```

```
40     font-family: Garamond;
41     font-size: 30px;
42     color: green;
43     padding: 1px;
44     max-width: 500px;
45     padding-top: 100px;
46 }
47
48 .sh {
49     position: absolute;
50     top: 21%;
51     left: 9%;
52     transform: translate(-50%, -50%);
53     font-family: Garamond;
54     color: green;
55     font-size: 27px;
56 }
57
58 .active{
59     display: block;
60     text-decoration: none;
61     float: right;
62     padding: 1%;
63     margin: auto;
64     margin-right: 1%;
65     margin-left: 1%;
66     font-size: 22px;
67     font-family: Garamond;
68     color: green;
69 }
70
71
72 .active a:hover {
73     background: gray;
74 }
75
76 .img{
77     position: absolute;
78     margin-left: -4%;
79     margin-right: 2%;
80     max-height: 200px;
```

```
81     max-width: 400px;
82 }
83
84 .pro-img{
85     float : right;
86     margin-top : -2%;
87     margin-left: 2%;
88     margin-right: 2%;
89     margin-bottom: 2%;
90     max-height: 100px;
91     max-width: 120px;
92     cursor: pointer;
93 }
94
95 .table{
96     color: black;
97     font-size: 130%;
98     font-family: times new roman;
99 }
100 </style>
101 </head>
102
103 <body class="main">
104 <div class="bx">
105 <div class="container">
106 
107 </div>
108 <br><br>
109 <a href="user_profile.jsp">
110 
111 </a>
112 <a class="active" href="HOME_SCREEN.jsp"><b>LOG
    OUT</b></a>
113 <a class="active" href="#"><b>MY CART</b></a>
114 <a class="active" href="#"><b>MY ORDER'S</b></a>
115 <a class="active" href="/availablePro"><b>PRODUCT
    S</b></a>
116 <a class="active" href="/after_user_login.jsp"><b>
    HOME</b></a>
117 </div>
118
```

```
119  
120 </body>  
121 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 <style type="text/css">
9 .box {
10     max-width: 300px;
11     margin: auto;
12     align-content: center;
13     border : 1px solid gray;
14     border-radius: 15px;
15     background-color: white;
16     border-width: 2px;
17     overflow: hidden;
18
19     padding : 60px;
20     padding-top: 35px;
21     padding-bottom : 35px;
22 }
23
24 .main{
25     background-color: #FFFAFA;
26 }
27
28 .btn{
29     cursor: pointer;
30     padding: 5px;
31     width: 100px;
32     height: 30px;
33     margin: auto;
34     margin-right: 10%;
35     margin-left: 12%;
36 }
37
38 .db{
39     cursor: pointer;
40 }
```

```
41
42 .head{
43     max-width: 350px;
44     border: 2px solid #FFFAFA;
45     position: relative;
46     margin: auto;
47     padding: 2px;
48     padding-right: 2px;
49     font-size: 47px;
50 }
51
52 .sh{
53     font-family: Garamond;
54     font-size: 20px;
55     color: green;
56     padding: 1px;
57     padding-top: 1px;
58     max-width: 500px;
59     margin: 1%;
60 }
61
62 .err{
63     color: red;
64 }
65
66 .log{
67     color: blue;
68 }
69
70 .ac{
71     text-decoration: none;
72 }
73
74 .forget_pass{
75     color: blue;
76     text-decoration: none;
77 }
78
79 </style>
80 </head>
81 <h3 class="sh">SportyShoes.com</h3>
```



```

1 <%@page import="com.fasterxml.jackson.annotation.
   JsonInclude.Include"%>
2 <%@ page language="java" contentType="text/html;
   charset=ISO-8859-1"
3     pageEncoding="ISO-8859-1"%>
4     <meta name="viewport"
5         content="width=device-width, initial-
   scale=1, shrink-to-fit=no">
6     <%@page isELIgnored="false" %>
7     <%@taglib prefix="c" uri="http://java.sun
   .com/jsp/jstl/core" %>
8
9 <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/css/bootstrap.min.css"
   integrity="sha384-Gn5384xqQ1aoWXA+
058RXPxPg6fy4IWvTNh0E263XmFcJlSAwiGgFAW/dAiS6JXm"
   crossorigin="anonymous">
10
11 <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/font-awesome@6.1.1/css/all.min.css"
    integrity="sha512-
KfkfwYDsLkIlwQp6LFnl8zNdLGxu9YAA1QvwINks4PhcElQSvqc
yVLLD9aMhXd13uQjoXtEKNosOWaZqXgel0g==" crossorigin=
    "anonymous" referrerPolicy="no-referrer" />
12
13 <script
14     src="https://code.jquery.com/jquery-3.2.1.
   slim.min.js"
15     integrity="sha384-
   KJ3o2DKtIkYIK3UENzm7KCKRr/rE9/Qpg6aAZGJwFDMVNA/
   GpGFF93hXpG5KkN"
16     crossorigin="anonymous">
17 </script>
18
19 <script
20     src="https://cdn.jsdelivr.net/npm/popper.js
   @1.12.9/dist/umd/popper.min.js"
21     integrity="sha384-ApNbgh9B+
   Y1QKtv3Rn7W3mgPxhU9K/
   ScQsAP7hUiBx39j7fakFPskvXusvfa0b4Q"
22     crossorigin="anonymous">

```

```
23 </script>
24
25 <script
26     src="https://cdn.jsdelivr.net/npm/bootstrap@4.0.0/dist/js/bootstrap.min.js"
27     integrity="sha384-JZR6Spejh4U02d8j0t6vLEHfe/JQGiRRSQxSfFWpi1MquVdAyjUar5+76PVCmYl"
28     crossorigin="anonymous">
29 </script>
30
31     <title><c:out value="${title }"></c:out> </
32 title>
33
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>Admin Inserted Sucessfully</h1>
11 </body>
12 </html>
```

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4 <%@page import="com.rkg.phase3.Product"%>
5 <%@page import="java.util.List"%>
6 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
7   pageEncoding="ISO-8859-1"%>
8 <%@include file=".base.jsp" %>
9 <%@taglib prefix="c" uri="http://java.sun.com/jsp/
  jstl/core" %>
10
11 <meta charset="ISO-8859-1">
12 <title>SportyShoes RKG</title>
13 </head>
14 <body>
15 <table class="table table-striped">
16   <thead>
17     <tr>
18       <th scope="col">Product ID</th>
19       <th scope="col">Product Code</th>
20       <th scope="col">Product Name</th>
21       <th scope="col">Brand Name</th>
22       <th scope="col">About Product</th>
23       <th scope="col">Product Price</th>
24       <th scope="col">Action</th>
25     </tr>
26   </thead>
27   <tbody>
28     <c:forEach items="${avail_pro }" var="p">
29       <tr>
30         <th scope="row" >#${p.pro_id }</th>
31         <td class="font-weight-bold">PB${p.pro_code }
SH</td>
32         <td>${p.pro_name }</td>
33         <td>${p.pro_brand }</td>
34         <td>${p.pro_about }</td>
35         <td class="font-weight-bold">&#x20B9; ${p.
pro_price }/-</td>
36         <td>
37           <a href="/addcart/${p.pro_code}/ "

```

```
37 class="outline-danger">><i class="fas fa-cart-plus"></i></a>
38           &nbsp;&nbsp;&nbsp;
39           <a href="" class="btn btn-outline-
danger">Buy</a>
40           </td>
41       </tr>
42   </c:forEach>
43 </tbody>
44 </table>
45 </body>
46 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>Product Inserted Sucessfully</h1>
11 </body>
12 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>We Can't Provide Report for Restricted ID</h1>
11 </body>
12 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>User List Is Empty</h1>
11 </body>
12 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3     %@ page import="java.util.*" %
4     %@ page import="com.rkg.phase3.*" %
5 <!DOCTYPE html>
6 <html>
7 <head>
8 <meta charset="ISO-8859-1">
9 <title>SportyShoes RKG</title>
10 </head>
11 <body>
12 <% List<User> u = (List<User>)request.getAttribute(
  "list"); %>
13
14
15 <table border="1">
16 <tr>
17     <th>User ID</th>
18     <th>First Name</th>
19     <th>Last Name</th>
20     <th>Phone Number</th>
21     <th>E-Mail</th>
22     <th>Date Of Birth</th>
23     <th>Password</th>
24     <th>State</th>
25     <th>District</th>
26     <th>Taluka</th>
27     <th>Pin Code</th>
28     <th>Gender</th>
29 </tr>
30
31 <% for(User uu : u ) { %>
32 <tr>
33     <td><%= uu.getUser_id() %></td>
34     <td><%= uu.getUser_fname() %></td>
35     <td><%= uu.getUser_lname() %></td>
36     <td><%= uu.getUser_phone() %></td>
37     <td><%= uu.getUser_mail() %></td>
38     <td><%= uu.getUser_dob() %></td>
39     <td><%= uu.getUser_conpass() %></td>
```

```
40      <td><%= uu.getUser_state() %></td>
41      <td><%= uu.getUser_dist() %></td>
42      <td><%= uu.getUser_taluka() %></td>
43      <td><%= uu.getUser_pin() %></td>
44      <td><%= uu.getUser_gender() %></td>
45  </tr>
46 <%} %>
47
48 </table>
49 </body>
50 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3     %@ page import="java.util.*" %
4     %@ page import="com.rkg.phase3.*" %
5 <!DOCTYPE html>
6 <html>
7 <head>
8 <meta charset="ISO-8859-1">
9 <title>SportyShoes RKG</title>
10 </head>
11 <body>
12 <% List<User> up = (List<User>)request.getAttribute(
  "u_pass"); %>
13
14
15 <table border="1">
16 <tr>
17     <th>Password</th>
18 </tr>
19
20 <% for(User uu : up ) { %>
21 <tr>
22     <td><%= uu.getUser_conpass() %></td>
23 </tr>
24 <%} %>
25
26 </table>
27 </body>
28 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>User Registered Successfully</h1>
11 <hr>
12 <a href="user_login.jsp"> Go for Log In</a>
13
14
15 </body>
16 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3     %@ page import="java.util.*" %
4     %@ page import="com.rkg.phase3.*" %
5 <!DOCTYPE html>
6 <html>
7 <head>
8 <meta charset="ISO-8859-1">
9 <title>SportyShoes RKG</title>
10 </head>
11 <body>
12 <% List<Admin> up = (List<Admin>)request.
  getAttribute("pass_list"); %>
13
14
15 <table border="1">
16 <tr>
17     <th>Password</th>
18 </tr>
19
20 <% for(Admin aa : up ) { %>
21 <tr>
22     <td><%= aa.getAd_con() %></td>
23 </tr>
24 <%} %>
25
26 </table>
27 </body>
28 </html>
```

```

1 <!DOCTYPE html>
2 <html>
3 <head>
4 <%@page import="com.rkg.phase3.Product"%>
5 <%@page import="java.util.List"%>
6 <%@include file=".base.jsp" %>
7 <%@taglib prefix="c" uri="http://java.sun.com/jsp/
jstl/core" %>
8
9 <meta charset="ISO-8859-1">
10 <title>SportyShoes RKG</title>
11 </head>
12 <body>
13 <table class="table table-striped">
14   <thead>
15     <tr>
16       <th scope="col"> Product ID </th>
17       <th scope="col">Product Code</th>
18       <th scope="col">Product Name</th>
19       <th scope="col">Brand Name</th>
20       <th scope="col">About Product</th>
21       <th scope="col">Product Price</th>
22       <th scope="col">Purchased Date</th>
23     </tr>
24   </thead>
25   <tbody>
26   <c:forEach items="${r_list }" var="r">
27     <tr>
28       <th scope="row" >PRAJ${r.pro_id }SH</th>
29       <td class="font-weight-bold">${r.pro_code }</
30       <td>${r.pro_name }</td>
31       <td>${r.pro_brand }</td>
32       <td>${r.pro_about }</td>
33       <td class="font-weight-bold">&#x20B9; ${r.
34         pro_price }/-</td>
35       <td class="font-weight-bold">${r.sell_date }<
36         i class='fas fa-stopwatch'></td>
37     </tr>
38   </c:forEach>
39 </tbody>

```

```
38 </table>
39 </body>
40 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10 <h1>THIS IS USER PROFILE</h1>
11 </body>
12 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3     %@ page import="java.util.*" %
4     %@ page import="com.rkg.phase3.*" %
5 <!DOCTYPE html>
6 <html>
7 <head>
8 <meta charset="ISO-8859-1">
9 <title>SportyShoes RKG</title>
10 </head>
11 <body>
12 <% List<User> u = (List<User>)request.getAttribute(
  "u_list"); %>
13
14
15 <table border="1">
16 <tr>
17     <th>User ID</th>
18     <th>First Name</th>
19     <th>Last Name</th>
20     <th>Phone Number</th>
21     <th>E-Mail</th>
22     <th>Date Of Birth</th>
23     <th>Password</th>
24     <th>State</th>
25     <th>District</th>
26     <th>Taluka</th>
27     <th>Pin Code</th>
28     <th>Gender</th>
29 </tr>
30
31 <% for(User uu : u ) { %>
32 <tr>
33     <td><%= uu.getUser_id() %></td>
34     <td><%= uu.getUser_fname() %></td>
35     <td><%= uu.getUser_lname() %></td>
36     <td><%= uu.getUser_phone() %></td>
37     <td><%= uu.getUser_mail() %></td>
38     <td><%= uu.getUser_dob() %></td>
39     <td><%= uu.getUser_conpass() %></td>
```

```
40      <td><%= uu.getUser_state() %></td>
41      <td><%= uu.getUser_dist() %></td>
42      <td><%= uu.getUser_taluka() %></td>
43      <td><%= uu.getUser_pin() %></td>
44      <td><%= uu.getUser_gender() %></td>
45  </tr>
46 <%} %>
47
48 </table>
49 </body>
50 </html>
```

```
1 <%@ page language="java" contentType="text/html;
  charset=ISO-8859-1"
2     pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 <title>SportyShoes RKG</title>
8 </head>
9 <body>
10
11 </body>
12 </html>
```

```
1 #view resolver
2 spring.mvc.view.prefix=/pages/
3 spring.mvc.view.suffix=.jsp
4
5 #datasource
6 spring.datasource.driver-class-name=com.mysql.cj.
  jdbc.Driver
7 spring.datasource.url=jdbc:mysql://localhost:3306/
  sportyShoesDB
8 spring.datasource.username=root
9 spring.datasource.password=9899Raj@Cisco
10
11 #spring.port = 8080
12
13 #jpa-hibernate
14 spring.jpa.hibernate.ddl-auto=update
15 spring.jpa.hibernate.dialect=org.hibernate.dialect.
  MySQLDialect
16 spring.jpa.show-sql=true
```

```
1 package com.rkg.phase3;
2
3 import org.junit.jupiter.api.Test;
4 import org.springframework.boot.test.context.
5 SpringBootTest;
6
7 @SpringBootTest
8 class ApplicationTests {
9
10     @Test
11     void contextLoads() {
12
13 }
14
```