

Building Defensive Design Instead of Writing Defensive Code



Zoran Horvat


PRINCIPAL CONSULTANT AT CODING HELMET

@zoranh75 csharpmentor.com




Encapsulation and Defense

Good encapsulation



**Not many things
to defend from**

Poor encapsulation



**Lots of defensive code
everywhere around**

Encapsulation defined

- A language mechanism for restricting direct access to some of the object's components.

State

- A language construct that facilitates the bundling of data with the methods (or other functions) operating on that data.

**Operations
(methods)**

[https://en.wikipedia.org/wiki/Encapsulation_\(computer_programming\)](https://en.wikipedia.org/wiki/Encapsulation_(computer_programming))



Encapsulating State

```
class Student
{
    private string lastName;

    public string LastName
    {
        get { return lastName; }
        set
        {
            if (string.IsNullOrEmpty(value))
                throw new ArgumentException();
            lastName = value;
        }
    }
}
```

Caller will get the student's last name and then do all the work itself!

Invalid state cannot find its way to the private field



Encapsulating State

```
class Student
{
    private string lastName;

    public string LastName
    {
        get { return lastName; }
        set
        {
            if (string.IsNullOrEmpty(value))
                throw new ArgumentException();
            lastName = value;
        }
    }
}
```

Consequence

When only **state** is encapsulated, then **behavior** is put far away from the data.



Encapsulating State

```
class Student
{
    private string lastName;

    public string LastName
    {
        get { return lastName; }
        set
        {
            if (string.IsNullOrEmpty(value))
                throw new ArgumentException();
            lastName = value;
        }
    }
}
```

Example

LINQ query to filter
students by their initial

```
students.Where(student =>
    student.LastName.StartsWith('S'));
```

Sample data	
Last name	Initial letter
Smith	S
Simpson	S
O'Sullivan	O or S?
de Smedt	D or S?
De Smedt	D or S?



Encapsulating Behavior

```
class Student
{
    ...
    public bool LastNameStartsWith(char letter)
    {
        int index = 0;

        if (this.lastName.StartsWith("O'"))
            index = 2;

        if (this.lastName.ToLower().StartsWith("de "))
            index = 3;

        return
            this.lastName[index].ToLower() ==
            letter.ToLower();
    }
}
```

Support for traditional family names is encapsulated


Case-insensitiveness is encapsulated



Encapsulating State vs. Encapsulating Behavior

With encapsulated state:











```
students.Where(student => student.LastName.StartsWith('S'));
```



With encapsulated behavior:

```
students.Where(student => student.LastNameStartsWith('S'));
```




Last name	Initial (encapsulated state)		Initial (encapsulated behavior)	
Smith	S		S	
Simpson	S		S	
O'Sullivan	O		S	
de Smedt	D		S	
De Smedt	D		S	

Encapsulating State vs. Encapsulating Behavior

With encapsulated state:

```
students.Where(student => student.LastName.StartsWith('S'));
```



With encapsulated behavior:

```
students.Where(student => student.LastNameStartsWith('S'));
```



Encapsulation defined

A language construct that facilitates the bundling of data with the methods (or other functions) operating on that data.

[Wikipedia](#)



Encapsulating State vs. Encapsulating Behavior

```
class Student
{
    private string LastName { get; }
    public bool LastNameStartsWith(char letter);
    public bool LastNameContains(string part);
    public int CompareLastNameWith(Student other);
    public bool IsMultipartLastName();
}
```



Encapsulating State vs. Encapsulating Behavior

```
class Student
{
    private string LastName { get; }
    public bool LastNameStartsWith(char letter);
    public bool LastNameContains(string part);
    public int CompareLastNameWith(Student other);
    public bool IsMultipartLastName();
    ...
}
```

Encapsulation defined

A language mechanism for restricting direct access to some of the object's components.

[Wikipedia](#)



Encapsulating State vs. Encapsulating Behavior

```
class Student
{
  private string LastName { get; }
  public char LastNameInitial { get { ... } }
}
```

Raw, unprocessed state
remains *private*

New property is a *projection*
of the encapsulated state!

Behavior is encapsulated
in the feature provider

Encapsulation defined

A language mechanism for restricting direct access to some of the object's components.

Wikipedia



Encapsulating State vs. Encapsulating Behavior

```
class Student
{
  private string LastName { get; }
  public char LastNameInitial { get { ... } }
}
```

Raw, unprocessed state
remains *private*

New property is a *projection*
of the encapsulated state!

Behavior is encapsulated
in the feature provider

```
students.Where(student => student.LastNameInitial.ToLower() == 'S')...
```

Producer tells the initial

Consumer says letter
casing is not important

Good separation
of responsibilities



Encapsulating State vs. Encapsulating Behavior

```
class Student
{
    private string LastName { get; }
    public char LastNameInitial { get { ... } }
    public int CompareLastNameWith(Student other);
}
```

Keep raw data private

Expose processed data only

Project state into a generally useful form

Method returning a value is also projecting private state, in a way

Advice

Strike the right balance between only exposing *state* and only exposing *behavior*



Encapsulation and Cohesion



```
class Student
{
    private string LastName { get; }
    public char LastNameInitial
    {
        get
        {
            Logic is encapsulated here
        }
    }
}
```

Encapsulation and Cohesion



Definition of cohesion

- Keeping related things together

Student's class responsibilities

- Enlist for semesters
- Take labs and exams
- Collect grades
- Know traditional family names

Cohesion in the Student Class

```
class Student
{
    private string lastName;
    public char LastNameInitial
    {
        get
        {
            int index = 0;
            if (this.lastName.StartsWith("0'"))
                index = 2;
            if (this.lastName.ToLower().StartsWith("de "))
                index = 3;
            return this.lastName[index];
        }
    }
}
```

False assumption

Defensive code

Concrete cases



Cohesion in the Student Class


```
class Student
{
    private string lastName;
    public char LastNameInitial
    {
        get
        {
            int index = 0;
            if (this.lastName.StartsWith("O'"))
                index = 2;
            if (this.lastName.ToLower().StartsWith("de "))
                index = 3;
            return this.lastName[index];
        }
    }
}
```

Encapsulates access
to private state



Cohesion in the Student Class

```
class Student
{
    private string lastName;
    public char LastNameInitial { get { ... } }
    public void SetGrade(Grade grade) { ... }
    public void Enlist(Semester semester) { ... }
    public void TakeExamOn(Subject subject) { ... }
    ...
}
```



Unrelated members can access this field as if it were public!

Low cohesion:

Class breaks its own encapsulation.



Cohesion in the Student Class

```
class Student
{
    private string lastName;
    private Semester enlisted;
    private List<Grade> grades;
    private List<Subject> takenExams;

    public char LastNameInitial { get { ... } }

    public void SetGrade(Grade grade) { ... }
    public void Enlist(Semester semester) { ... }
    public void TakeExamOn(Subject subject) { ... }
    ...
}
```

Advice

Class with low cohesion should be split into two.



Introducing the Chain of Responsibility

```
public char LastNameInitial
{
    get
    {
        int index = 0;
        if (this.LastName.StartsWith("O' "))
            index = 2;
        if (this.LastName.ToLower().StartsWith("de "))
            index = 3;
        return this.LastName[index];
    }
}
```

Issue #1:

Adding more cases requires code change

Issue #2:

Incomplete branching logic causes bugs

Issue #3:

Branching can easily be misunderstood, causing bugs




Introducing the Chain of Responsibility

```
public char LastNameInitial  
{  
    get  
    {  
        int index = 0;  
  
        prefix O' → index 2  
  
        prefix de/De → index 3  
  
        return this.LastName[index];  
    }  
}
```



Introducing the Chain of Responsibility



Chain of Responsibility

Request is passed down the chain until served.


Catch-all element

Terminates the chain and processes all requests.



Introducing the Chain of Responsibility

Constructed at run time




Constructed at compile time

```
if (n.StartsWith("O"))  
    index = 2;  
else if (n.ToLower().StartsWith("de "))  
    index = 3;  
else  
    index = 0;
```



Introducing the Chain of Responsibility

Constructed at run time




Constructed at compile time

```
if (n.StartsWith("O"))
    index = 2;
else if (n.ToLower().StartsWith("de "))
    index = 3;
else if (n.StartsWith("la "))
    index = 3;
else if (n.StartsWith("le "))
    index = 3;
else if (n.StartsWith("da "))
    index = 3;
else if (n.StartsWith("di "))
    index = 3;
else
    index = 0;
```



Introducing the Chain of Responsibility



Benefits of Using Regular Expressions

Expressions, not code

Domain-Specific
Language (DSL)

Configurable

Testable

Expressions are not executable

Expressions are plain text



Benefits of Using Regular Expressions

Expressions, not code

Domain-Specific
Language (DSL)

Configurable

Testable

Serve as text processing language

No need for general-purpose code



Benefits of Using Regular Expressions

Expressions, not code

Domain-Specific
Language (DSL)

Configurable

Testable

Keep expressions separate from code

Pull them from configuration,
database, file, etc.



Benefits of Using Regular Expressions

Expressions, not code

Domain-Specific Language (DSL)


Configurable

Testable

Try them in a stand-alone emulator

Plenty of online testers available

<https://regex101.com>



Summary



Encapsulation

- Validation before modifying state
- Keeping operations close to data

Encapsulating behavior

- Domain rules and logic located together with the affected data

Operations have nothing to defend from when located close to correct data

- There will be no exceptions at run time



Summary



Alternative computation models

- Rules instead of step-by-step process

Dealing with rules

- Externalize them into a separate type
- Hosting object only triggers the rules
- Rules become an object's dependency



Summary



Chain of Responsibility pattern

- Refer to *Tactical Design Patterns in .NET: Managing Responsibilities* course

Regular expressions

- Organized into a list to form a Chain
- Great match for text processing tasks

After externalizing rules

- Class has nothing to defend from (except against null references)

Next module

Working with Objects, Not with Nulls

