IPL Data Analysis – DAX Formula Documentation

1.Season Result Metrics

- **Season Winner Measure**

Purpose: Returns the winning team of the selected season final match.

Dax formula:

```
Season Winner =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )   --2025
VAR FinalMatchDate =
   CALCULATE (
      MAX ( ipl_matches_data[match_date] ),
      ipl_matches_data[season] = SelectedSeason   --Max Date = 3 June
   )
VAR FinalMatchWinner =
   CALCULATE (
      MAX ( ipl_matches_data[match_winner] ),     -- Winner Team
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_date] = FinalMatchDate
   )
RETURN
   FinalMatchWinner
```

- ## Season Winner logo

Purpose: Displays the logo of the winning team for the selected season

DAX Formula:

```
Season Winner Logo =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR FinalMatchDate =
   CALCULATE (
      MAX ( ipl_matches_data[match_date] ),
      ipl_matches_data[season] = SelectedSeason
   )

VAR FinalMatchWinner =
   CALCULATE (
      MAX ( ipl_matches_data[match_winner] ),
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_date] = FinalMatchDate
   )

RETURN
   LOOKUPVALUE(
      teams_data[image_url],
      teams_data[team_name],
      FinalMatchWinner
   )
```

- ## Runner-Up Team

Purpose: Returns the team that lost in the final match of the selected season.

DAX Formula:

```
Runner Up =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR FinalMatchDate =
   CALCULATE (
      MAX ( ipl_matches_data[match_date] ),
      ipl_matches_data[season] = SelectedSeason
   )

VAR FinalMatchWinner =
```

```
    CALCULATE (
        MAX ( ipl_matches_data[match_winner] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

VAR Team1 =
    CALCULATE (
        MAX ( ipl_matches_data[team1] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

VAR Team2 =
    CALCULATE (
        MAX ( ipl_matches_data[team2] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

RETURN
    IF ( FinalMatchWinner = Team1, Team2, Team1 )
```

- ## Runner-Up Logo

Purpose: Displays the logo of the team that lost in the final match of the selected season.

DAX Formula:

```
Runner Up Logo =
VAR SelectedSeason =
    SELECTEDVALUE ( ipl_matches_data[season] )

VAR FinalMatchDate =
    CALCULATE (
        MAX ( ipl_matches_data[match_date] ),
        ipl_matches_data[season] = SelectedSeason
    )

VAR FinalMatchWinner =
    CALCULATE (
        MAX ( ipl_matches_data[match_winner] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

VAR Team1 =
```

```
    CALCULATE (
        MAX ( ipl_matches_data[team1] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

VAR Team2 =
    CALCULATE (
        MAX ( ipl_matches_data[team2] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_date] = FinalMatchDate
    )

RETURN
    LOOKUPVALUE(
        teams_data[image_url],
        teams_data[team_name],
        [Runner Up]
    )
```

2. Orange Cap Metrics (Season Top Scorer)

- **Orange Cap Holder**

Purpose: Returns the batter with the highest total runs in the selected season.

DAX Formula:

```
Orange Cap Holder =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonDataOnly =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
    )

VAR RunSummary =
    SUMMARIZE (
        SeasonDataOnly,
        'ball_by_ball_data'[batter],
        "Total Runs", SUM ( 'ball_by_ball_data'[batter_runs] )
    )

VAR MaxRuns =
    MAXX ( RunSummary, [Total Runs] )
```

```
VAR TopScorer =
   CALCULATETABLE (
      VALUES ( 'ball_by_ball_data'[batter] ),
      FILTER ( RunSummary, [Total Runs] = MaxRuns )
   )

RETURN
   MAXX ( TopScorer, 'ball_by_ball_data'[batter] )
```

- ## Orange Cap Runs

Purpose: Returns the total runs scored by the highest-scoring batter in the selected season.

DAX Formula:

```
Orange Cap Runs =
VAR SelectedSeason =
   SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonDataOnly =
   FILTER (
      'ball_by_ball_data',
      RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
   )

VAR RunSummary =
   SUMMARIZE (
      SeasonDataOnly,
      'ball_by_ball_data'[batter],
      "Total Runs", SUM ( 'ball_by_ball_data'[batter_runs] )
   )

VAR MaxRuns =
   MAXX ( RunSummary, [Total Runs] )

RETURN
   MaxRuns
```

- ## Orange Cap Team Name

Purpose: Returns the team of the highest-scoring batter in the selected season.

DAX Formula:

```
Orange Cap Team Name =
VAR SelectedSeason =
```

```
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonDataOnly =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
    )

VAR RunSummary =
    SUMMARIZE (
        SeasonDataOnly,
        'ball_by_ball_data'[batter],
        "Total Runs", SUM ( 'ball_by_ball_data'[batter_runs] )
    )

VAR MaxRuns =
    MAXX ( RunSummary, [Total Runs] )

VAR TopScorer =
    CALCULATETABLE (
        VALUES ( 'ball_by_ball_data'[batter] ),
        FILTER ( RunSummary, [Total Runs] = MaxRuns )
    )

VAR FullTeamName =
    CALCULATE (
        MAX ( 'ball_by_ball_data'[team_batting] ),
        FILTER (
            SeasonDataOnly,
            'ball_by_ball_data'[batter]
                = MAXX ( TopScorer, 'ball_by_ball_data'[batter] )
        )
    )

RETURN
    FullTeamName
```

- ## Orange Cap Player Image

Purpose: Displays the image of the highest-scoring batter in the selected season.

DAX Formula:

```
Orange Cap Image =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonDataOnly =
```

```
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
    )

VAR RunSummary =
    SUMMARIZE (
        SeasonDataOnly,
        'ball_by_ball_data'[batter],
        "Total Runs", SUM ( 'ball_by_ball_data'[batter_runs] )
    )

VAR MaxRuns =
    MAXX ( RunSummary, [Total Runs] )

VAR TopScorer =
    CALCULATETABLE (
        VALUES ( 'ball_by_ball_data'[batter] ),
        FILTER ( RunSummary, [Total Runs] = MaxRuns )
    )

RETURN
    LOOKUPVALUE (
        'players_data_updated'[player_image],
        'players_data_updated'[player_name],
        MAXX ( TopScorer, 'ball_by_ball_data'[batter] )
    )
```

3. Purple Cap Metrics (Season Top Wicket-Taker)

- **Purple Cap Holder**

Purpose: Returns the bowler with the highest number of wickets in the selected season, excluding non-bowler dismissals.

DAX Formula:

```
PurpleCapHolder =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

-- Filter wickets in selected season, exclude non-bowler dismissals
VAR SeasonWickets =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
```

```
        && 'ball_by_ball_data'[is_wicket] = TRUE ()
        && NOT (
            'ball_by_ball_data'[wicket_kind]
                IN {
                    "run out",
                    "retired hurt",
                    "obstructing the field",
                    "retired out"
                }
        )
    )

-- Summarize bowler and count wickets
VAR WicketSummary =
    SUMMARIZE (
        SeasonWickets,
        'ball_by_ball_data'[bowler],
        "WicketCount",
        COUNTROWS (
            FILTER (
                SeasonWickets,
                'ball_by_ball_data'[bowler]
                    = EARLIER ( 'ball_by_ball_data'[bowler] )
            )
        )
    )

-- Find highest wicket count
VAR MaxWickets =
    MAXX ( WicketSummary, [WicketCount] )

-- Get the bowler(s) with that wicket count
VAR TopBowler =
    CALCULATETABLE (
        VALUES ( 'ball_by_ball_data'[bowler] ),
        FILTER ( WicketSummary, [WicketCount] = MaxWickets )
    )

-- Return the name (if multiple, picks one alphabetically)
RETURN
    MAXX ( TopBowler, 'ball_by_ball_data'[bowler] )
```

- ## Purple Cap Wicket Count

Purpose: Returns the total number of wickets taken by the highest-wicket bowler in the selected season.

DAX Formula:

```
PurpleCapWicketCount =
VAR SelectedSeason =
   SELECTEDVALUE ( 'ipl_matches_data'[season] )

-- Step 1: Filter valid bowler wickets in selected season
VAR SeasonWickets =
   FILTER (
      'ball_by_ball_data',
      RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
         && 'ball_by_ball_data'[is_wicket] = TRUE ()
         && NOT (
            'ball_by_ball_data'[wicket_kind]
               IN {
                  "run out",
                  "retired hurt",
                  "retired out",
                  "obstructing the field"
               }
         )
   )

-- Step 2: Summarize wickets per bowler
VAR WicketSummary =
   SUMMARIZE (
      SeasonWickets,
      'ball_by_ball_data'[bowler],
      "WicketCount",
         COUNTROWS (
            FILTER (
               SeasonWickets,
               'ball_by_ball_data'[bowler]
                  = EARLIER ( 'ball_by_ball_data'[bowler] )
            )
         )
   )

-- Step 3: Get the highest wicket count
```

```
VAR MaxWickets =
   MAXX ( WicketSummary, [WicketCount] )

RETURN
   MaxWickets
```

- ## Purple Cap Team

Purpose: Returns the team of the highest-wicket bowler in the selected season.

DAX Formula:

```
PurpleCapTeam =
VAR SelectedSeason =
   SELECTEDVALUE ( 'ipl_matches_data'[season] )

-- Step 1: Filter valid bowler wickets for the selected season
VAR SeasonWickets =
   FILTER (
      'ball_by_ball_data',
      RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
         && 'ball_by_ball_data'[is_wicket] = TRUE ()
         && NOT (
            'ball_by_ball_data'[wicket_kind]
               IN {
                  "run out",
                  "retired hurt",
                  "retired out",
                  "obstructing the field"
               }
         )
   )

-- Step 2: Summarize bowler and team, count wickets per bowler
VAR WicketSummary =
   ADDCOLUMNS (
      SUMMARIZE (
         SeasonWickets,
         'ball_by_ball_data'[bowler],
         'ball_by_ball_data'[team_bowling]
      ),
      "WicketCount",
         COUNTROWS (
            FILTER (
               SeasonWickets,
               'ball_by_ball_data'[bowler]
                  = EARLIER ( 'ball_by_ball_data'[bowler] )
```

```
            )
        )
    )

-- Step 3: Get maximum wickets
VAR MaxWickets =
    MAXX ( WicketSummary, [WicketCount] )

-- Step 4: Return team name of the top wicket-taker
RETURN
    MAXX (
        FILTER ( WicketSummary, [WicketCount] = MaxWickets ),
        'ball_by_ball_data'[team_bowling]
    )
```

- ## Purple Cap Player Image :

Purpose: Displays the image of the highest-wicket bowler in the selected season.

DAX Formula:

```
PurpleCapImage =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

-- Step 1: Filter valid bowler wickets for the selected season
VAR SeasonWickets =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
            && 'ball_by_ball_data'[is_wicket] = TRUE ()
            && NOT (
                'ball_by_ball_data'[wicket_kind]
                    IN {
                        "run out",
                        "retired hurt",
                        "retired out",
                        "obstructing the field",
                        "hit wicket"
                    }
            )
    )

-- Step 2: Summarize bowler-wise wicket count
VAR WicketSummary =
    SUMMARIZE (
        SeasonWickets,
```

```
        'ball_by_ball_data'[bowler],
        "WicketCount",
          COUNTROWS (
            FILTER (
              SeasonWickets,
              'ball_by_ball_data'[bowler]
                = EARLIER ( 'ball_by_ball_data'[bowler] )
            )
          )
    )

-- Step 3: Get the maximum wicket count
VAR MaxWickets =
    MAXX ( WicketSummary, [WicketCount] )

-- Step 4: Get the bowler with maximum wickets
VAR TopBowler =
    CALCULATETABLE (
        VALUES ( 'ball_by_ball_data'[bowler] ),
        FILTER ( WicketSummary, [WicketCount] = MaxWickets )
    )

-- Step 5: Return image using LOOKUP from player table
RETURN
    LOOKUPVALUE (
        'players_data_updated'[player_image],
        'players_data_updated'[player_name],
        MAXX ( TopBowler, 'ball_by_ball_data'[bowler] )
    )
```

4. Top Fours Metrics (Season Boundary Leader – 4's)

- **Top Fours Player Name**

Purpose: Returns the batter who hit the most fours in the selected season

DAX Formula:

```
Top Fours Player Name =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonFours =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
          && 'ball_by_ball_data'[batter_runs] = 4
```

```
    )

VAR FourSummary =
    SUMMARIZE (
        SeasonFours,
        'ball_by_ball_data'[batter],
        "FoursCount",
            COUNTROWS (
                FILTER (
                    SeasonFours,
                    'ball_by_ball_data'[batter]
                        = EARLIER ( 'ball_by_ball_data'[batter] )
                )
            )
    )

VAR MaxFours =
    MAXX ( FourSummary, [FoursCount] )

VAR TopFoursPlayer =
    CALCULATETABLE (
        VALUES ( 'ball_by_ball_data'[batter] ),
        FILTER ( FourSummary, [FoursCount] = MaxFours )
    )

RETURN
    MAXX ( TopFoursPlayer, 'ball_by_ball_data'[batter] )
```

- ## Top Fours Count

Purpose: Returns the highest number of fours hit by a batter in the selected season.

DAX Formula:

```
Top Fours Count =
VAR SelectedSeason =
    SELECTEDVALUE ( 'ipl_matches_data'[season] )

VAR SeasonFours =
    FILTER (
        'ball_by_ball_data',
        RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
            && 'ball_by_ball_data'[batter_runs] = 4
    )
VAR FourSummary =
    SUMMARIZE (
        SeasonFours,
```

```
      'ball_by_ball_data'[batter],
      "FoursCount",
         COUNTROWS (
            FILTER (
               SeasonFours,
               'ball_by_ball_data'[batter]
                  = EARLIER ( 'ball_by_ball_data'[batter] )
            )
         )
   )

VAR MaxFours =
   MAXX ( FourSummary, [FoursCount] )

RETURN
   MaxFours
```

- ## Top Fours Player Team Name

Purpose: Returns the team of the batter who hit the most fours in the selected season.

DAX Formula:

```
Top Fours Player Team Name =
VAR SelectedSeason = SELECTEDVALUE(ipl_matches_data[season])

VAR SeasonFours = FILTER(
   ball_by_ball_data,
   RELATED(ipl_matches_data[season]) = SelectedSeason
      && ball_by_ball_data[batter_runs] = 4
)

VAR FourSummary = SUMMARIZE(
   SeasonFours,
   ball_by_ball_data[batter],
   "FoursCount",
      COUNTROWS(
         FILTER(
            SeasonFours,
            ball_by_ball_data[batter] = EARLIER(ball_by_ball_data[batter])
         )
      )
)

VAR MaxFours = MAXX(FourSummary, [FoursCount])

VAR TopFoursPlayer = CALCULATETABLE(
   VALUES(ball_by_ball_data[batter]),
```

```
    FILTER(FourSummary, [FoursCount] = MaxFours)
)

VAR BatterTeam =
    CALCULATE(
        MAX(ball_by_ball_data[team_batting]),
        FILTER(
            SeasonFours,
            ball_by_ball_data[batter] = MAXX(TopFoursPlayer, ball_by_ball_data[batter])
        )
    )

RETURN BatterTeam
```

- **Top Fours Player Image**

Purpose: Displays the image of the batter who hit the most fours in the selected season.

DAX Formula:

```
Top Fours Player Image =
VAR SelectedSeason = SELECTEDVALUE(ipl_matches_data[season])

VAR SeasonFours = FILTER(
    ball_by_ball_data,
    RELATED(ipl_matches_data[season]) = SelectedSeason &&
    ball_by_ball_data[batter_runs] = 4
)

VAR FourSummary = SUMMARIZE(
    SeasonFours,
    ball_by_ball_data[batter],
    "FoursCount", COUNTROWS(
        FILTER(SeasonFours, ball_by_ball_data[batter] = EARLIER(ball_by_ball_data[batter]))
    )
)

VAR MaxFours = MAXX(FourSummary, [FoursCount])

VAR TopFoursPlayer = CALCULATETABLE(
    VALUES(ball_by_ball_data[batter]),
    FILTER(FourSummary, [FoursCount] = MaxFours)
)

RETURN
    LOOKUPVALUE(
        'players_data_updated'[player_image],
```

```
    'players_data_updated'[player_name],
    MAXX(TopFoursPlayer, ball_by_ball_data[batter])
  )
```

5. Top Sixes Metrics (Season Boundary Leader – 6's)

- **Top Sixes Player Name**

Purpose: Returns the batter who hit the most sixes in the selected season.

DAX Formula:

```
Top Sixes Player Name =
VAR SelectedSeason = SELECTEDVALUE ( 'ipl_matches_data'[season] )

// 1. Create a table of batters and their total sixes for the season
VAR SixesSummary =
  SUMMARIZE (
    FILTER (
      'ball_by_ball_data',
      RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
        && 'ball_by_ball_data'[batter_runs] = 6
    ),
    'ball_by_ball_data'[batter],
    "SixesCount", COUNTROWS ( 'ball_by_ball_data' )
  )

// 2. Identify the maximum number of sixes hit
VAR MaxSixes = MAXX ( SixesSummary, [SixesCount] )

// 3. Get the name of the player(s) who achieved that maximum
VAR TopSixesPlayer =
  FILTER ( SixesSummary, [SixesCount] = MaxSixes )

// 4. Return the name (MAXX handles ties by picking the last name alphabetically)
RETURN
  MAXX ( TopSixesPlayer, 'ball_by_ball_data'[batter] )
```

- **Top Sixes Count**

Purpose: Returns the highest number of sixes hit by a batter in the selected season.

DAX Formula:

```
Top Sixes Count =
VAR SelectedSeason = SELECTEDVALUE ( 'ipl_matches_data'[season] )
```

```
// Create a summary table of batters and their total sixes for the season
VAR SixesSummary =
   SUMMARIZE (
      FILTER (
         'ball_by_ball_data',
         RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
            && 'ball_by_ball_data'[batter_runs] = 6
      ),
      'ball_by_ball_data'[batter],
      "SixesCount", COUNTROWS ( 'ball_by_ball_data' )
   )

// Extract the highest number of sixes from that list
VAR MaxSixes = MAXX ( SixesSummary, [SixesCount] )

RETURN
   MaxSixes
```

- ## Top Sixes Player Team Name

Purpose: Returns the team of the batter who hit the most sixes in the selected season.

DAX Formula:

```
Top Sixes Player Team Name =
VAR SelectedSeason = SELECTEDVALUE('ipl_matches_data'[season])

// 1. Filter ball-by-ball data for the selected season and sixes only
VAR SeasonSixes =
   FILTER(
      'ball_by_ball_data',
      RELATED('ipl_matches_data'[season]) = SelectedSeason &&
      'ball_by_ball_data'[batter_runs] = 6
   )

// 2. Summarize to find total sixes per batter
VAR SixesSummary =
   SUMMARIZE(
      SeasonSixes,
      'ball_by_ball_data'[batter],
      "SixesCount", COUNTROWS('ball_by_ball_data')
   )

// 3. Find the maximum number of sixes hit
VAR MaxSixes = MAXX(SixesSummary, [SixesCount])
```

```
// 4. Get the player name who hit the max sixes
VAR TopSixesPlayerName =
   MAXX(
      FILTER(SixesSummary, [SixesCount] = MaxSixes),
      'ball_by_ball_data'[batter]
   )

// 5. Get the team name for that player in that season
VAR BatterTeam =
   CALCULATE(
      MAX('ball_by_ball_data'[team_batting]),
      FILTER(
         SeasonSixes,
         'ball_by_ball_data'[batter] = TopSixesPlayerName
      )
   )

RETURN
   BatterTeam
```

- ## Top Sixes Player Image

Purpose: Displays the image of the batter who hit the most sixes in the selected season.

DAX Formula:

```
Top Sixes Player Image =
VAR SelectedSeason = SELECTEDVALUE('ipl_matches_data'[season])

// 1. Create a virtual table of batters and their sixes count
VAR SixesSummary =
   SUMMARIZE (
      FILTER (
         'ball_by_ball_data',
         RELATED ( 'ipl_matches_data'[season] ) = SelectedSeason
            && 'ball_by_ball_data'[batter_runs] = 6
      ),
      'ball_by_ball_data'[batter],
      "SixesCount", COUNTROWS ( 'ball_by_ball_data' )
   )
// 2. Identify the Top 1 player name from that summary
VAR TopPlayerName =
   SELECTCOLUMNS (
      TOPN ( 1, SixesSummary, [SixesCount], DESC ),
      "PlayerName", 'ball_by_ball_data'[batter]
   )
// 3. Fetch the image URL from the player details table
```

```
RETURN
   LOOKUPVALUE (
      'players_data_updated'[player_image],
      'players_data_updated'[player_name],
      TopPlayerName
   )
```

6. Season Summary Metrics

- **Total 6's**

Purpose: Counts the total number of sixes hit in the selected season.

DAX Formula:

```
Total 6's =
CALCULATE(
   COUNTROWS(ball_by_ball_data),
   ball_by_ball_data[batter_runs] = 6,
   KEEPFILTERS(VALUES(ipl_matches_data[season]))
)
```

- **Total 4's**

Purpose: Counts the total number of fours hit in the selected season.

DAX Formula:

```
Total 4's =
CALCULATE(
   COUNTROWS(ball_by_ball_data),
   ball_by_ball_data[batter_runs] = 4,
   KEEPFILTERS(VALUES(ipl_matches_data[season]))
)
```

- **Total Matches**

Purpose: Counts the total number of matches played in the selected season.

DAX Formula:

```
Total Matches =
CALCULATE(
   DISTINCTCOUNT(ipl_matches_data[match_id])
)
```

- **Total Teams**

Purpose: Counts the total number of unique teams that played in the selected season.

DAX Formula:

```
Total Teams =
CALCULATE(
```

```
   DISTINCTCOUNT(ipl_matches_data[team1])
)
```

- ## Total Venues

Purpose: Counts the total number of unique venues used in the selected season.

DAX Formula:

```
Total Venues =
CALCULATE(
   DISTINCTCOUNT(ipl_matches_data[venue])
)
```

- ## Total Centuries

Purpose: Counts the total number of centuries scored by all batters in the selected season.

DAX Formula:

```
Centuries =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR SeasonData =
   FILTER (
      ball_by_ball_data,
      RELATED ( ipl_matches_data[season] ) = SelectedSeason
   )

VAR BatterRuns =
   SUMMARIZE (
      SeasonData,
      ball_by_ball_data[match_id],
      ball_by_ball_data[batter],
      "TotalRuns", SUM ( ball_by_ball_data[batter_runs] )
   )

VAR CenturyCount =
   FILTER ( BatterRuns, [TotalRuns] >= 100 )

RETURN
   COUNTROWS ( CenturyCount )
```

- ## Total Half-Centuries

Purpose: Counts the total number of innings where a batter scored 50–99 runs in the selected season.

DAX Formula:

```
Half Centuries =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR SeasonData =
   FILTER (
      ball_by_ball_data,
      RELATED ( ipl_matches_data[season] ) = SelectedSeason
   )

VAR BatterRuns =
   SUMMARIZE (
      SeasonData,
      ball_by_ball_data[match_id],
      ball_by_ball_data[batter],
      "TotalRuns", SUM ( ball_by_ball_data[batter_runs] )
   )

VAR HalfCenturyCount =
   FILTER ( BatterRuns, [TotalRuns] >= 50 && [TotalRuns] < 100 )

RETURN
   COUNTROWS ( HalfCenturyCount )
```

7. Team Performance Metrics

- **Matches Played**

Purpose: Counts the total number of T20 matches played by a team in the selected season.

DAX

```
Matches Played =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR Team1Matches =
   CALCULATE (
      COUNTROWS ( ipl_matches_data ),
      USERELATIONSHIP ( ipl_matches_data[team1], teams_data[team_name] ),
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_type] = "T20"
   )

VAR Team2Matches =
   CALCULATE (
      COUNTROWS ( ipl_matches_data ),
      USERELATIONSHIP ( ipl_matches_data[team2], teams_data[team_name] ),
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_type] = "T20"
   )
```

```
RETURN
   Team1Matches + Team2Matches
```

- ## Matches Won

Purpose: Counts the total T20 matches won by a team in the selected season.

DAX:

```
Matches Won =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season] )

VAR CurrentTeam =
   SELECTEDVALUE ( teams_data[team_name] )

RETURN
CALCULATE (
   COUNTROWS ( ipl_matches_data ),
   ipl_matches_data[season] = SelectedSeason,
   ipl_matches_data[match_winner] = CurrentTeam,
   ipl_matches_data[match_type] = "T20"
)
```

- ## Matches Lost

Purpose: Counts the total T20 matches lost by a team in the selected season**.**

DAX:

```
Matches Lost =
VAR SelectedSeason =
   SELECTEDVALUE ( ipl_matches_data[season])
VAR Team1LostMatches =
   CALCULATE (
      COUNTROWS ( ipl_matches_data ),
      USERELATIONSHIP ( ipl_matches_data[team1], teams_data[team_name]),
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_type] = "T20",
      NOT ISBLANK ( ipl_matches_data[match_winner]),
      ipl_matches_data[match_winner] <> ipl_matches_data[team1]
   )

VAR Team2LostMatches =
   CALCULATE (
      COUNTROWS ( ipl_matches_data ),
      USERELATIONSHIP ( ipl_matches_data[team2], teams_data[team_name]),
      ipl_matches_data[season] = SelectedSeason,
      ipl_matches_data[match_type] = "T20",
```

```
    NOT ISBLANK ( ipl_matches_data[match_winner]),
    ipl_matches_data[match_winner] <> ipl_matches_data[team2]
  )

RETURN
  Team1LostMatches + Team2LostMatches
```

- ## No Result Played

Purpose: Counts the number of T20 matches with “No Result” for a team in the selected season.

DAX:

```
No Result Played =
VAR SelectedSeason =
  SELECTEDVALUE ( ipl_matches_data[season] )

VAR Team1Matches =
  CALCULATE (
    COUNTROWS ( ipl_matches_data ),
    USERELATIONSHIP ( ipl_matches_data[team1], teams_data[team_name] ),
    ipl_matches_data[season] = SelectedSeason,
    ipl_matches_data[match_type] = "T20",
    ipl_matches_data[result]="no result"
  )

VAR Team2Matches =
  CALCULATE (
    COUNTROWS ( ipl_matches_data ),
    USERELATIONSHIP ( ipl_matches_data[team2], teams_data[team_name] ),
    ipl_matches_data[season] = SelectedSeason,
    ipl_matches_data[match_type] = "T20",
    ipl_matches_data[result]="no result"
  )
RETURN
  Team1Matches + Team2Matches
```

- ## Tie Played

Purpose: Counts the number of tied T20 matches for a team in the selected season.

DAX:

```
Tie Played =
VAR SelectedSeason =
  SELECTEDVALUE ( ipl_matches_data[season] )

VAR Team1Matches =
  CALCULATE (
    COUNTROWS ( ipl_matches_data ),
    USERELATIONSHIP ( ipl_matches_data[team1], teams_data[team_name] ),
```

```
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_type] = "T20",
        ipl_matches_data[result]="tie"
    )

VAR Team2Matches =
    CALCULATE (
        COUNTROWS ( ipl_matches_data ),
        USERELATIONSHIP ( ipl_matches_data[team2], teams_data[team_name] ),
        ipl_matches_data[season] = SelectedSeason,
        ipl_matches_data[match_type] = "T20",
        ipl_matches_data[result]="tie"
    )

RETURN
    Team1Matches + Team2Matches
```

- ## Total Points

Purpose: Calculates total points for a team in the selected season (2 points per win + 1 per no result).

DAX:

```
TotalPoints =
VAR Win = [Matches Won]
VAR NR = [No Result Played]
RETURN (Win * 2) + NR
```