

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets



LangChain Docs

☰ Monitoring & alerting > Alerts in LangSmith

Monitoring & alerting

Alerts in LangSmith

 Copy page



 **Self-hosted version requirement:** Access to alerts requires Helm chart version **0.10.3** or later.

Effective observability in LLM applications requires proactive detection of failures, performance degradations, and regressions. LangSmith's alerts feature helps identify critical issues such as:

- API rate limit violations from model providers.
- Latency increases for your application.
- Application changes that affect feedback scores reflecting end-user experience.
- Unexpected cost spikes from LLM usage.

Alerts in LangSmith are project-scoped, requiring separate configuration for each monitored project.

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets →



Step 1: Navigate to create alert

In the UI, navigate to the Tracing project that you would like to configure alerts for. Click the **Alerts** icon on the top right-hand corner of the page to view existing alerts for that project and set up a new alert.

Step 2: Select metric type

LangSmith provides threshold-based alerting on the following metrics:

Metric Type	Description	Use Case
Run Count	Tracks the total number of <u>runs</u> over a time window.	Monitor whether a pipeline is producing runs at the expected volume and alert when it drops unexpectedly.
Cost	Tracks the total cost of runs over a time window.	Monitor LLM spending to alert when costs exceed expected thresholds. Requires <u>cost tracking</u> to be configured.
Errors	Tracks runs with an error status. Alert on total error count or error percent (rate of errored runs out of all runs).	Monitor for failures in an application, or alert when the error rate exceeds an acceptable threshold.

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets



Additionally, for **Errors** and **Latency**, you can use the filter builder to stack conditions on fields such as **Status**, **Run Type**, **Tag**, and **Error**. For example, you can scope an error alert to runs where **Status** is `error`, **Run Type** is `llm`, **Tag** is `support_agent`, and **Error** matches `RateLimitExceeded`.

Step 3: Define alert conditions

Alert conditions consist of several components:

- **Aggregation Method:** Average, Percentage, or Count.
- **Comparison Operator:** `>=`, `<=`, or exceeds threshold.
- **Threshold Value:** Numerical value triggering the alert.
- **Aggregation Window:** Time period for metric calculation (choose between 5 or 15 minutes).
- **Feedback Key** (Feedback Score alerts only): Specific feedback metric to monitor.

Define Conditions

Define the threshold that will trigger the alert.

Errored runs Count Percent exceeds 5 % in the last 5 15 minutes.

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets



Alert Preview

See how the metric configured has performed over the time frame selected.



Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets

→



❗ The native Slack notification type is available on LangSmith Cloud only. For self-hosted deployments, use the [webhook Slack recipe](#) in the **Webhook** tab instead.

Prerequisites

- A Slack workspace connected to your LangSmith organization. If you haven't connected one yet, LangSmith will prompt you to do so inline when you configure this notification type.

1. Configure the Slack notification

1. In the **Notification Settings** section of your alert setup, select **Slack**.
2. Click the channel selector. If no Slack workspace is linked yet, click **Connect Slack** and complete the OAuth flow to authorize LangSmith.
3. Add the `@LangSmith` app to the channel you want to receive notifications in. The app must be a member of the channel — type `/invite @LangSmith` in the channel to add it.
4. Select the workspace and channel from the dropdown. Click the refresh icon if the channel does not appear immediately.
5. Click **Save** to save the notification configuration.

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets



When an alert triggers, LangSmith posts a structured Slack message that includes:

- **Headline:** The alert name and your LangSmith workspace name.
- **Detail line:** The metric attribute, triggered value, comparison operator, configured threshold, aggregation method, and time window — for example: `Total Cost: $12.50 ≥ $5.00 · avg · 30 min`.
- **Action buttons:** **View Alert** (links to the alert preview in LangSmith) and **View Runs** (links to the filtered runs that triggered the alert).

Best practices

- Adjust sensitivity based on application criticality
- Start with broader thresholds and refine based on observed patterns
- Ensure alert routing reaches appropriate on-call personnel

 [Connect these docs](#) to Claude, VSCode, and more via MCP for real-time answers.

Interrupt is coming to NYC and London this fall. Join the builders, engineers, and teams shaping what's next for agents. Get your tickets



Resources

[Forum](#)

[Changelog](#)

[LangChain Academy](#)

[Contact Sales](#)

Company

[Home](#)

[Trust Center](#)

[Careers](#)

[Blog](#)