

AWS DynamoDB – Create Table using CloudShell and Perform CRUD Operations

Task:

Create a DynamoDB table using AWS CloudShell and perform CRUD operations using AWS CLI.

(a) Open AWS CloudShell:

Login to AWS Management Console → Click CloudShell icon → Wait for terminal to open

(b) Create DynamoDB Table:

```
aws dynamodb create-table \  
--table-name StudentTable \  
--attribute-definitions AttributeName=StudentID,AttributeType=S \  
--key-schema AttributeName=StudentID,KeyType=HASH \  
--billing-mode PAY_PER_REQUEST
```

(c) Check Table Created:

```
aws dynamodb list-tables
```

(d) Insert Data (Create Operation):

```
aws dynamodb put-item \  
--table-name StudentTable \  
--item '{  
  "StudentID": {"S": "101"},  
  "Name": {"S": "Rahul"},  
  "Department": {"S": "CSE"}  
}'
```

(e) Read Data (Get Operation):

```
aws dynamodb get-item \  
--table-name StudentTable \  
--key '{"StudentID": {"S": "101"}}'
```

(f) Update Data:

```
aws dynamodb update-item \  
--table-name StudentTable \  
--key '{"StudentID": {"S": "101"}}' \  
--update-expression "SET Department = :d" \  
--expression-attribute-values '{":d":{"S":"IT"}}'
```

(g) Delete Data:

```
aws dynamodb delete-item \  
--table-name StudentTable \  
--key '{"StudentID": {"S": "101"}}'
```

(h) Verify Data:

```
aws dynamodb scan --table-name StudentTable  
Result:
```

DynamoDB table created successfully using AWS CloudShell and all CRUD operations (Create, Read,