HTML Canvas – 50 MCQs (Answers with Reasons)

Section 1: Basics & Paths

Q1. What does `beginPath()` do?

A. Ends drawing

B. Starts a new path

C. Fills shape

D. Clears canvas

Answer: B

Reason: Starts a fresh path and resets previous drawing path.

Q2. What is the purpose of `moveTo(x, y)`?

A. Draws rectangle

B. Sets starting point

C. Fills color

D. Ends path

Answer: B

Reason: Moves cursor without drawing.

Q3. `lineTo(x, y)` is used to:

A. Move cursor

B. Draw line

C. Fill text

D. Clear path

Answer: B

Reason: Draws a line from current point.

Q4. Which method actually draws the path?

A. moveTo()

B. lineTo()

C. stroke()

D. fillText()

Answer: C

Reason: Renders the outline.

Q5. Default coordinate origin is:

A. Center

B. Bottom-left

C. Top-left

D. Top-right

Answer: C

Reason: Canvas starts from top-left.

Section 2: Drawing Logic

Q6. Canvas draws in which order?

A. Random

B. Last to first

C. Code order

D. Circular

Answer: C

Reason: Executes top to bottom.

Q7. Overlap means:

A. Deleting shapes

B. Same area covered

C. Resizing shapes

D. Rotating shapes

Answer: B

Reason: Multiple drawings share same region.

Q8. Which appears on top?

A. First drawn

B. Last drawn

C. Both equal

D. None

Answer: B

Reason: Latest drawing overwrites visually.

Q9. What does `strokeStyle` define?

A. Fill color

B. Border color

C. Font size

D. Gradient

Answer: B

Reason: Controls outline color.

Q10. A closed shape is formed by:

A. stroke()

B. beginPath()

C. Connecting last to first

D. fillText()

Answer: C

Reason: Completes the shape loop.

Section 3: Text on Canvas

Q11. `ctx.font` is used to:

A. Set color

B. Set font and size

C. Draw line

D. Clear text

Answer: B

Reason: Defines text style.

Q12. Which method draws filled text?

A. strokeText()

B. fillText()

C. drawText()

D. textFill()

Answer: B

Reason: Creates solid text.

Q13. `strokeText()` creates:

A. Filled text

B. Outlined text

C. Gradient text

D. Shadow text

Answer: B

Reason: Only border is drawn.

Q14. Coordinates in `fillText()` represent:

A. Center

B. Top-right

C. Starting point

D. End point

Answer: C

Reason: Text begins from this point.

Q15. Example font format:

A. Arial 50px

B. 50px Arial

C. px50 Arial

D. Arial size 50

Answer: B

Reason: Uses CSS format.

Section 4: Rectangles

Q16. `fillRect()` does:

A. Draw outline

B. Draw filled rectangle

C. Draw line

D. Draw text

Answer: B

Reason: Creates solid rectangle.

Q17. `strokeRect()` does:

A. Fill rectangle

B. Outline rectangle

C. Clear rectangle

D. Rotate rectangle

Answer: B

Reason: Draws border only.

Q18. Rectangles can:

A. Only be filled

B. Only be outlined

C. Overlap

D. Cannot overlap

Answer: C

Reason: Shapes can share space.

Q19. Default canvas size is:

A. 500×500

B. 300×150

C. 100×100

D. Full screen

Answer: B

Reason: Default HTML size.

Q20. Overlapping depends on:

A. Color

B. Drawing order

C. Size

D. Font

Answer: B

Reason: Order controls visibility.

Section 5: Gradients

Q21. `createLinearGradient()` creates:

A. Circle

B. Line

C. Gradient

D. Text

Answer: C

Reason: Defines linear color transition.

Q22. Parameters of linear gradient represent:

A. Width & height

B. Start and end points

C. Color

D. Radius

Answer: B

Reason: Defines gradient direction.

Q23. `addColorStop()` is used to:

A. Add border

B. Define colors

C. Draw shape

D. Clear gradient

Answer: B

Reason: Sets gradient colors.

Q24. Offset range is:

A. 0–100

B. 1–10

C. 0–1

D. 0–255

Answer: C

Reason: Uses normalized values.

Q25. Gradient is applied using:

A. strokeStyle

B. fillStyle

C. font

D. lineTo

Answer: B

Reason: Fill style controls color.

Section 6: Radial Gradient

Q26. `createRadialGradient()` creates:

A. Square

B. Circle gradient

C. Line

D. Path

Answer: B

Reason: Creates circular gradient.

Q27. Number of parameters required:

A. 2

B. 4

C. 6

D. 8

Answer: C

Reason: Two circles need center and radius.

Q28. `r0` represents:

A. Outer radius

B. Inner radius

C. Width

D. Height

Answer: B

Reason: Starting circle radius.

Q29. Gradient moves from:

A. Left to right

B. Inner to outer

C. Top to bottom

D. Random

Answer: B

Reason: Color spreads outward.

Q30. Middle color uses offset:

A. 0

B. 0.5

C. 1

D. 2

Answer: B

Reason: Middle of gradient.

Section 7: Advanced Concepts

Q31. Canvas uses which coordinate system?

A. Cartesian

B. Polar

C. 3D

D. Matrix

Answer: A

Reason: Uses x and y axes.

Q32. Increasing x moves:

A. Up

B. Down

C. Right

D. Left

Answer: C

Reason: X increases horizontally.

Q33. Increasing y moves:

A. Up

B. Down

C. Left

D. Right

Answer: B

Reason: Y increases downward.

Q34. `stroke()` draws:

A. Fill

B. Outline

C. Text

D. Gradient

Answer: B

Reason: Draws border.

Q35. Multiple `lineTo()` create:

A. Circles

B. Polygons

C. Text

D. Gradients

Answer: B

Reason: Forms shapes.

Section 8: Mixed Concepts

Q36. Canvas is part of:

A. CSS

B. HTML

C. Python

D. SQL

Answer: B

Reason: HTML element.

Q37. JavaScript is used to:

A. Style canvas

B. Draw on canvas

C. Create HTML

D. Store data

Answer: B

Reason: Used for drawing.

Q38. Without `stroke()` lines will:

A. Show

B. Not appear

C. Turn red

D. Fill

Answer: B

Reason: Not rendered.

Q39. Without `beginPath()` shapes may:

A. Clear

B. Mix with previous paths

C. Delete

D. Resize

Answer: B

Reason: Path continues.

Q40. `fillStyle` affects:

A. Borders

B. Fill color

C. Font

D. Size

Answer: B

Reason: Controls fill.

Section 9: Final Questions

Q41. Canvas element is:

A. `<div>`

B. `<canvas>`

C. `<draw>`

D. `<svg>`

Answer: B
Reason: Correct HTML tag.

Q42. Canvas requires:
A. CSS
B. JavaScript
C. SQL
D. Python
Answer: B
Reason: Used for drawing.

Q43. Path must start with:
A. stroke()
B. beginPath()
C. fillText()
D. font
Answer: B
Reason: Initializes path.

Q44. Shape edges use:
A. fill()
B. stroke()
C. font()
D. style()
Answer: B
Reason: Draws outline.

Q45. Gradient colors defined by:
A. addColorStop()
B. fillRect()
C. moveTo()

D. strokeText()

Answer: A

Reason: Sets color stops.

Q46. Canvas supports:

A. Only shapes

B. Only text

C. Both

D. None

Answer: C

Reason: Supports both.

Q47. Coordinates format:

A. (y, x)

B. (x, y)

C. (z, x)

D. (a, b)

Answer: B

Reason: Standard format.

Q48. Overlapping depends on:

A. Speed

B. Drawing order

C. Color

D. Size

Answer: B

Reason: Later covers earlier.

Q49. `moveTo()` draws:

A. Line

B. Nothing

C. Text

D. Rectangle

Answer: B

Reason: Only moves cursor.

Q50. Canvas is used for:

A. Database

B. Graphics

C. Networking

D. Storage

Answer: B

Reason: Used for drawing visuals.