



Git Restore Command

Learn how to use the `git restore` command to undo changes in your working directory and safely recover files in Git.

 **Watch the Video:**

https://youtu.be/9NcXOSXIOOQ?si=hLDpEJhmQv_ozdv-

 **Recommended:** Learn `git restore` after understanding basic Git commands to manage and undo file changes safely.

Git Restore Command

What is `git restore` ?

The `git restore` command is used to discard changes in your working directory and restore files to their previous state. It is commonly used to undo accidental modifications before committing changes.

Common Commands

Restore a Single File

```
git restore <file-name>
```

Example:

```
git restore index.html
```

Restores the file to its last committed state.

Restore All Modified Files

```
git restore .
```

Restores all modified files in the current directory.

Restore a File from the Latest Commit

```
git restore --source=HEAD <file-name>
```

Example:

```
git restore --source=HEAD app.js
```

Restores the specified file from the latest commit (HEAD).

Unstage a File

```
git restore --staged <file-name>
```

Example:

```
git restore --staged app.js
```

Removes the file from the staging area while keeping the changes in your working directory.

When to Use `git restore`

- Undo accidental changes in a file.
- Restore a file to its last committed version.
- Remove files from the staging area.
- Recover files before creating a commit.

Key Points

- `git restore` only affects your local repository.
- It does not modify the commit history.
- It is safe to use before committing changes.
- Once local changes are restored, they cannot be recovered unless they were committed or backed up.