

Understanding and Removing Noisy Data

A comprehensive guide to data smoothing techniques for data preprocessing

Made with GAMMA

What is Noisy Data?

Noise represents random errors or variance in measured variables that can obscure meaningful patterns in your data. These unwanted fluctuations can arise from various sources including measurement errors, data entry mistakes, or natural variability in the data collection process.

In data mining, noise can significantly impact the quality of your analysis and the accuracy of your predictive models. Identifying and removing noise is a crucial preprocessing step that helps reveal the underlying patterns and relationships in your dataset.

Why Noise Matters

Noise can lead to misleading conclusions and reduce model performance. Cleaning your data improves analysis reliability.



Made with GAMMA

Detecting Outliers and Noise



Statistical Visualization

Boxplots effectively identify outliers by displaying quartiles and whiskers, making extreme values immediately visible in the distribution.



Scatter Plots

Two-dimensional scatter plots reveal unusual patterns and data points that deviate significantly from the general trend.



Distribution Analysis

Histograms show the frequency distribution of values, helping identify values that fall outside expected ranges.

These basic statistical description techniques provide the foundation for identifying potential noise in your dataset. Once outliers are detected, you can apply appropriate smoothing techniques to clean your data.

Made with GAMMA



Binning: Local Neighborhood Smoothing

Binning methods smooth data by consulting the "neighborhood" of values around each data point. The sorted values are distributed into a number of buckets, or bins. Since binning consults neighboring values, it performs local smoothing that preserves the overall data structure while reducing random fluctuations.

Equal-Frequency Bins

Each bin contains the same number of values, ensuring balanced distribution across all bins.

Equal-Width Bins

The interval range of values in each bin is constant, creating uniform value ranges.

Made with GAMMA

Smoothing by Bin Means

Before Smoothing

Sorted Data for Price:

4, 8, 15, 21, 21, 24, 25, 28, 34

Partition into Bins (size 3):

- Bin 1: 4, 8, 15
- Bin 2: 21, 21, 24
- Bin 3: 25, 28, 34

After Smoothing

Smoothing by Bin Means:

- Bin 1: 9, 9, 9 (mean = 9)
- Bin 2: 22, 22, 22 (mean = 22)
- Bin 3: 29, 29, 29 (mean = 29)

In smoothing by bin means, each value in a bin is replaced by the mean value of the bin. For example, the mean of values 4, 8, and 15 in Bin 1 is 9, so each original value is replaced by 9. This technique effectively reduces noise by averaging neighboring values.

Made with GAMMA

Smoothing by Bin Boundaries

1

Identify Boundaries

Find minimum and maximum values in each bin, which become the bin boundaries.

2

Replace Values

Each bin value is replaced by the closest boundary value (minimum or maximum).

3

Result

Values are pulled toward bin edges, creating a different smoothing effect.

Example: In Bin 1 (4, 8, 15), the boundaries are 4 (minimum) and 15 (maximum). The value 4 stays 4, 8 is replaced by 4 (closer to minimum), and 15 stays 15.

Smoothing by bin boundaries creates a different effect compared to bin means. While bin means pull all values toward the center, bin boundaries push values toward the edges of each bin. This can be useful when you want to preserve the range of values while still reducing noise.

Made with GAMMA



Regression-Based Smoothing

Regression is a powerful technique that conforms data values to a mathematical function. Instead of local neighborhood smoothing, regression performs global smoothing by fitting the data to a curve or surface.

01

Linear Regression

Finds the best line to fit two attributes so one can predict the other. This creates a smooth relationship between variables.

02

Multiple Linear Regression

Extends linear regression to more than two attributes, fitting data to a multidimensional surface.

03

Application

Replace original values with predicted values from the regression function to smooth the data.

Made with GAMMA

Outlier Detection Through Clustering

Clustering organizes similar values into groups or "clusters." Intuitively, values that fall outside these cluster sets can be considered outliers and potential noise.

Cluster Formation

Similar data points are grouped together based on distance or similarity measures.

Outlier Identification

Points that don't fit well into any cluster are flagged as potential outliers.

Smoothing Decision

Outliers can be removed, adjusted, or investigated further depending on context.

Chapter 12 provides detailed coverage of outlier analysis techniques and their applications in data mining.



Made with GAMMA

Beyond Smoothing: Additional Applications

Data Discretization

Binning reduces distinct values per attribute, acting as data discretization. For example, price values can map to inexpensive, moderately priced, and expensive categories.

Data Reduction

Reducing distinct values serves as data reduction for logic-based mining methods like decision tree induction, which repeatedly compares sorted values.

Classification Methods

Some classification techniques, such as neural networks, have built-in data smoothing mechanisms that automatically handle noise during the learning process.

Many data smoothing methods serve multiple purposes in the data mining pipeline, making them efficient tools for preprocessing.



Made with GAMMA

Key Takeaways

1 Choose the Right Technique

Different smoothing methods work best in different scenarios. Binning is great for local smoothing, regression for global patterns, and clustering for outlier detection.

2 Balance Smoothing and Information

While larger bin widths increase smoothing effect, they may also remove valuable information. Find the right balance for your analysis goals.

3 Consider Multiple Applications

Smoothing techniques often serve as data discretization and reduction methods, providing multiple benefits from a single preprocessing step.

4 Validate Your Results

Always verify that smoothing hasn't removed meaningful patterns. Compare results before and after smoothing to ensure data integrity.

