

CU-DTSA-530 - NYPD Shooting Incident Report

Rajesh Kutti, Student - University of Colorado, Boulder

2024-02-24

Important Note

- **Libraries Required:** Please plan to install the libraries (**ltidyverse**, **lhubridate**, **lusmap**, **lstringr**)
- **PDF Document:** A PDF version of this report is available in GitHub.

Executive Summary

Gun violence has been one of the most sensitive and debated topics in USA for years and it has been used by politicians in every election for their own gains. In this report, we will keep our biases aside and try to look at the facts by analyzing the real cases that are available to us from the catalog.data.gov website.

- We will follow a step by step and iterative Data Science process to analyze and generate insights.
- **Goal** - Analyze and build a Quantitative model to predict Gun violence in NYC.
- **Benefits** - By exploring the nature of shooting/criminal activity, we can help the Law Enforcement Agencies to minimize crime. We can help the public to stay informed and We can help to Government to create a safe neighborhood.
- **Objectives** - To achieve our goal, we must continue to ask questions (as follows) to gain more insights into the problem until all our objectives are met.
 - How many incidents are happening across New York City?
 - * What location and at what time are these incidents more common?
 - * How fatal are these incidents?
 - * Can we understand the demographics of the perpetrators?
 - What is their race, age group and gender?
 - * Can we understand the demographics of the victims?
 - What is their race, age group and gender?
 - Can we narrow down into the top 2 precinct and get some insights?
- Finally, we want to train and test a predictive model to predict future shooting incidents to help law enforcement.
- For those who want a summarized view of this report, please start from **Section 3: Visualizations**. The observations and insights are articulated in that section.

Data Science Process - An iterative approach. Reference: *DTSA-530 by Prof. Jane Wall*)

- We will follow a well-defined process that we learned in DTSA-5301 for doing our analysis. During this process we will document our observations and share insights that will help the team and the key stakeholders.
- **Import data** from catalog.data.gov
- **Tidy data** by removing unwanted rows, then formatting the data so that each row is an observation and finally null imputation or null value replacements.
- **Transform data** - Here we change numbers to categorical variables, rename columns or we add new columns as needed.
- **Analyze and Visualize** - We then go through iterative process of analyzing, visualizing, asking questions then going back to prior steps and repeating the process until we have good understanding of the answers to the questions we started with, (until our goal is met).
- For analyzing, we will do Univariate analysis by looking at distributions for single variable, Bivariate analysis by looking at correlations between two variables and Multivariate analysis by checking relationship between multiple predictors and our target variables.
- **Model** - We will build a quantitative model for our data and observations. During this phase we will try to check if our assumptions are accurate by running the predictions.
- **Communicate** - Finally, we will communicate our results in a reproducible way so that the report can be improved in future or can be leveraged by others to do more analysis.

References:

- University of Colorado, Boulder - DTSA-530
 - CSSE Johns Hopkins University
 - Coursera, CU Boulder
-

Section 1A: Common Functions:

- In this section we will add all the common functions used.
- Each function is well-documented.
 - Data can come from various sources, and it could be various types, size and shapes.
 - There could be null values, unknown values, NA, etc. To do good analysis we need to tidy/clean the data.
 - Common and reusable functions will help all the team members (like Airbnb approach for Data Science).

```
# function to format large numbers
formatNumber <- function(x) {
  format( x, digits = 2, scientific=FALSE, big.mark = ",",
)
}

# Tidy dataset: Remove unwanted columns - select only the columns needed for analysis.
tdRemoveCols <- function(ds_nyc_sh) {
  cols <- c("INCIDENT_KEY", "OCCUR_DATE", "OCCUR_TIME", "BORO", "LOC_OF_OCCUR_DESC", "PRECINCT", "JURISDICTION")
  result <- ds_nyc_sh %>% select(all_of(cols))
  result
}
```

```

# Tidy dataset - Fix/substitute nulls with appropriate values
# Lump bad PERP_AGE_GROUP into one category - unknown
# Lump bad VIC_AGE_GROUP into one category - unknown
# Furthermore, move bad/unknown values for PERP_SEX, VIC_SEX, PERP_RACE, LOCATION_DESC, under one category

tdDatasetFixColValues <- function(ds_nyc_sh) {

  # We will replace all null and unknown into one bucket called unknown
  ds_nyc_sh$PERP_AGE_GROUP[ds_nyc_sh$PERP_AGE_GROUP %in% c("(null)", "1020", "224", "940")] <- "UNKNOWN"

  ds_nyc_sh$VIC_AGE_GROUP[ds_nyc_sh$VIC_AGE_GROUP %in% c("1022")] <- "UNKNOWN"

  # Fix PERP_SEX cols
  ds_nyc_sh$PERP_SEX[ds_nyc_sh$PERP_SEX %in% c("(null)", "NA")] <- "U"
  ds_nyc_sh <- ds_nyc_sh %>% replace_na(list(PERP_SEX="U"))

  # Fix VIC_SEX cols
  ds_nyc_sh$VIC_SEX[ds_nyc_sh$VIC_SEX %in% c("(null)", "NA")] <- "U"
  ds_nyc_sh <- ds_nyc_sh %>% replace_na(list(VIC_SEX="U"))

  # Fix Race cols
  ds_nyc_sh$PERP_RACE[ds_nyc_sh$PERP_RACE %in% c("(null)", "NA")] <- "UNKNOWN"
  ds_nyc_sh <- ds_nyc_sh %>% replace_na(list(PERP_RACE="UNKNOWN"))

  # Fix LOCATION_DESC cols
  ds_nyc_sh$LOCATION_DESC[ds_nyc_sh$LOCATION_DESC %in% c("(null)", "NA")] <- "UNKNOWN"
  ds_nyc_sh <- ds_nyc_sh %>% replace_na(list(LOCATION_DESC="UNKNOWN"))

  # replace all nulls with "unknown"
  ds_nyc_sh <- ds_nyc_sh %>% replace_na(list(PERP_AGE_GROUP="UNKNOWN"))
  ds_nyc_sh
}

# Tidy dataset:
# In this method we will create date type, then year, month, dayofweek columns for our analysis using m
tdAugmentDates <- function(df_nyc_sh) {
  result <- df_nyc_sh %>%
    mutate(
      OCCUR_DATE = mdy(OCCUR_DATE),
      syear = year(OCCUR_DATE),
      smonth = month(OCCUR_DATE, label = TRUE),
      sday_of_week = wday(OCCUR_DATE, label = TRUE),
      shour = hour(hms(as.character(OCCUR_TIME)))
    ) %>%
    mutate(hour_bucket = case_when(
      (shour >= 5 & shour < 12) ~ "Morning 5AM-12PM",
      (shour >= 12 & shour < 16) ~ "Afternoon 12PM-4PM",
      (shour >= 16 & shour < 20) ~ "Evening 4PM-8PM",
      (shour >= 20 & shour <= 24) ~ "Night 8PM-12AM",
      (shour >= 0 & shour < 5) ~ "Midnight 12AM-5AM",
    ))
  result
}

```

```

# Create Categorical columns - Categorical functions are very useful while doing grouping or drawing graphs
# In our use case, here are all columns that need to be transformed to categorical.
tdChangeColTypesForCategoricalCols <- function(ds_nyc_sh) {
  ds_nyc_sh$BORO = as.factor(ds_nyc_sh$BORO)
  # replace PERP_AGE_GROUP with factors
  ds_nyc_sh$PERP_AGE_GROUP = as.factor(ds_nyc_sh$PERP_AGE_GROUP)
  ds_nyc_sh$PRECINCT = as.factor(ds_nyc_sh$PRECINCT)

  ds_nyc_sh$PERP_AGE_GROUP = as.factor(ds_nyc_sh$PERP_AGE_GROUP)
  ds_nyc_sh$VIC_AGE_GROUP = as.factor(ds_nyc_sh$VIC_AGE_GROUP)
  ds_nyc_sh$PERP_SEX = as.factor(ds_nyc_sh$PERP_SEX)
  ds_nyc_sh$VIC_SEX = as.factor(ds_nyc_sh$VIC_SEX)
  ds_nyc_sh$PERP_RACE = as.factor(ds_nyc_sh$PERP_RACE)
  ds_nyc_sh$VIC_RACE = as.factor(ds_nyc_sh$VIC_RACE)
  ds_nyc_sh
}

# Plot US Map
# This function uses the map api to plot some cool graphs.
# https://cran.r-project.org/web/packages/usmap/vignettes/usmap3.html
plotMapForUSACounties <- function(df, region_type, state_code, column_name,
                                  color1, color_low, color_high, plot_name, plot_title) {
  plt <- plot_usmap(regions = region_type, include=state_code,data=df,
                    values=column_name, color = color1, labels=TRUE) +
    scale_fill_continuous(low=color_low, high=color_high, na.value="white", name=plot_name) +
    theme(legend.position = "right")
  plt$layers[[2]]$aes_params$size <- 2.5
  plt <- plt + ggtitle(plot_title)
  plt
}

```

Section 1B: Import the datasets and cache locally:

- We will first load the data from its SOR :
 - URL : <https://data.cityofnewyork.us/api/views/833y-fsy8/rows.csv?accessType=DOWNLOAD>
- We will cache the data locally for future analysis.

```

DOWNLOAD_URL <- "https://data.cityofnewyork.us/api/views/833y-fsy8/rows.csv?accessType=DOWNLOAD"
LOCAL_FILE = "cached_data/NYPD_Shooting_Incident_Data_Historic_.csv"
if (!file.exists("cached_data")) {
  dir.create("cached_data")
  print(str_c("Please wait .. Downloading the data from :", DOWNLOAD_URL))
  download.file(DOWNLOAD_URL, destfile=LOCAL_FILE)
}
nyc_raw_data <- read_csv(LOCAL_FILE)
records <- nyc_raw_data %>% summarize(ct = n())
columns <- length(colnames(nyc_raw_data))
print(str_c("Datafile loaded. Rows:", records, ", Columns:", columns))

```

```
## [1] "Datafile loaded. Rows:27312, Columns:21"
```

```
# We will create a fips dataset to create some cool maps. Please review fips code from:-
# https://en.wikipedia.org/wiki/List_of_counties_in_New_York
# New York County (Manhattan), Kings County (Brooklyn), Bronx County (The Bronx),
# Richmond County (Staten Island), and Queens County (Queens)
fips_df <- df <- data.frame(BORO=c("BRONX", "BROOKLYN", "MANHATTAN", "QUEENS", "STATEN ISLAND"),
                           fips=c("36005", "36047", "36061", "36081", "36085"))
```

Section 1C: Prepare the NYC incident dataset

- Tidy the NYC incident datasets.
- Join with the FIPS for NYC Boros

```
# Total incidents
total_no_of_incidents_fl <- (nyc_raw_data %>% summarize(ct = n()))$ct
total_no_of_incidents <- formatNumber(total_no_of_incidents_fl)

# Get the incidents by Boro and join with FIPS dataset
nyc_inc_by_boro_df <- nyc_raw_data %>%
  group_by(BORO) %>%
  summarise(inc_ct = n()) %>%
  ungroup() %>%
  full_join(fips_df, by = c("BORO")) %>%
  mutate(BORO = factor(BORO))

# remove unwanted cols
nyc_dataset_df <- tdRemoveCols(nyc_raw_data)

# fix field values
nyc_dataset_df <- tdDatasetFixColValues(nyc_dataset_df)

# Augment Date time
nyc_dataset_df <- tdAugmentDates(nyc_dataset_df)

# Prepare categorical columns
nyc_dataset_df <- tdChangeColTypesForCategoricalCols(nyc_dataset_df)
```

Section 1D: Summarize: Summarize the NYC incident datasets

- Two datasets were prepared:
 - nyc_dataset_df : Tidy'd data for detail analysis.
 - nyc_inc_by_boro_df : For high level stats of the incidents.
- From the summary, we noticed the following
 - OCCUR_DATE is a date column.
 - Factor variables are PRECINCT, STATISTICAL_MURDER_FLAG, PERP_AGE_GROUP, PERP_SEX.
 - PERP_RACE, VIC_AGE_GROUP, VIC_SEX, VIC_RACE.
 - Transformations: We added columns:- syear, smonth, sday_of_week, shour.

```
# Display summary for the nyc_dataset_df dataset.
summary(nyc_dataset_df)
```

```

## INCIDENT_KEY OCCUR_DATE OCCUR_TIME
## Min. : 9953245 Min. :2006-01-01 Length:27312
## 1st Qu.: 63860880 1st Qu.:2009-07-18 Class1:hms
## Median : 90372218 Median :2013-04-29 Class2:difftime
## Mean :120860536 Mean :2014-01-06 Mode :numeric
## 3rd Qu.:188810230 3rd Qu.:2018-10-15
## Max. :261190187 Max. :2022-12-31
##
## BORO LOC_OF_OCCUR_DESC PRECINCT JURISDICTION_CODE
## BRONX : 7937 Length:27312 75 : 1557 Min. :0.0000
## BROOKLYN :10933 Class :character 73 : 1452 1st Qu.:0.0000
## MANHATTAN : 3572 Mode :character 67 : 1216 Median :0.0000
## QUEENS : 4094 44 : 1020 Mean :0.3269
## STATEN ISLAND: 776 79 : 1012 3rd Qu.:0.0000
## 47 : 953 Max. :2.0000
## (Other):20102 NA's :2
## LOC_CLASSFCTN_DESC LOCATION_DESC STATISTICAL_MURDER_FLAG PERP_AGE_GROUP
## Length:27312 Length:27312 Mode :logical <18 : 1591
## Class :character Class :character FALSE:22046 18-24 : 6222
## Mode :character Mode :character TRUE :5266 25-44 : 5687
## 45-64 : 617
## 65+ : 60
## UNKNOWN:13135
##
## PERP_SEX PERP_RACE VIC_AGE_GROUP VIC_SEX
## F: 424 AMERICAN INDIAN/ALASKAN NATIVE: 2 <18 : 2839 F: 2615
## M:15439 ASIAN / PACIFIC ISLANDER : 154 18-24 :10086 M:24686
## U:11449 BLACK :11432 25-44 :12281 U: 11
## BLACK HISPANIC : 1314 45-64 : 1863
## UNKNOWN :11786 65+ : 181
## WHITE : 283 UNKNOWN: 62
## WHITE HISPANIC : 2341
## VIC_RACE syear smonth
## AMERICAN INDIAN/ALASKAN NATIVE: 10 Min. :2006 Jul : 3238
## ASIAN / PACIFIC ISLANDER : 404 1st Qu.:2009 Aug : 3156
## BLACK :19439 Median :2013 Jun : 2829
## BLACK HISPANIC : 2646 Mean :2013 Sep : 2572
## UNKNOWN : 66 3rd Qu.:2018 May : 2571
## WHITE : 698 Max. :2022 Oct : 2279
## WHITE HISPANIC : 4049 (Other):10667
## sday_of_week shour hour_bucket
## Sun:5452 Min. : 0.00 Length:27312
## Mon:3883 1st Qu.: 3.00 Class :character
## Tue:3163 Median :15.00 Mode :character
## Wed:3000 Mean :12.22
## Thu:3034 3rd Qu.:20.00
## Fri:3585 Max. :23.00
## Sat:5195

```

```

# Display summary for the nyc_inc_by_boro_df dataset.
summary(nyc_inc_by_boro_df)

```

```

## BORO inc_ct fips
## BRONX :1 Min. : 776 Length:5

```

```
## BROOKLYN      :1  1st Qu.: 3572   Class :character
## MANHATTAN     :1  Median  : 4094   Mode  :character
## QUEENS        :1  Mean    : 5462
## STATEN ISLAND:1  3rd Qu.: 7937
##               Max.    :10933
```

- Display few rows.

```
# Display two rows for the nyc_dataset_df dataset.
nyc_dataset_df %>% head(n=2) %>% print(width=Inf)
```

```
## # A tibble: 2 x 21
##   INCIDENT_KEY OCCUR_DATE OCCUR_TIME BORO   LOC_OF_OCCUR_DESC PRECINCT
##   <dbl> <date>      <time>    <fct> <chr>              <fct>
## 1    228798151 2021-05-27  21:30    QUEENS <NA>              105
## 2    137471050 2014-06-27  17:40    BRONX  <NA>              40
##   JURISDICTION_CODE LOC_CLASSFCTN_DESC LOCATION_DESC STATISTICAL_MURDER_FLAG
##   <dbl> <chr>              <chr>          <lgl>
## 1      0 <NA>              UNKNOWN        FALSE
## 2      0 <NA>              UNKNOWN        FALSE
##   PERP_AGE_GROUP PERP_SEX PERP_RACE VIC_AGE_GROUP VIC_SEX VIC_RACE syear smonth
##   <fct>          <fct>    <fct>    <fct>      <fct> <fct>   <dbl> <ord>
## 1 UNKNOWN      U      UNKNOWN  18-24      M      BLACK   2021 May
## 2 UNKNOWN      U      UNKNOWN  18-24      M      BLACK   2014 Jun
##   sday_of_week shour hour_bucket
##   <ord>        <dbl> <chr>
## 1 Thu         21 Night 8PM-12AM
## 2 Fri         17 Evening 4PM-8PM
```

```
# Display two rows for the nyc_inc_by_boro_df dataset.
nyc_inc_by_boro_df %>% head(n=2) %>% print(width=Inf)
```

```
## # A tibble: 2 x 3
##   BORO   inc_ct fips
##   <fct>   <int> <chr>
## 1 BRONX     7937 36005
## 2 BROOKLYN 10933 36047
```

Section 2A: Analyze and Prepare the graphs for the NYC incident datasets Analyze and prepare stats for **State, Counties & Counts** for Visualization

```
# ----- NYC Counties
# County label and fips code for NYC as found from wiki page. https://en.wikipedia.org/wiki/List\_of\_counties\_in\_New\_York\_City
counties_lbl <- "Shooting incidents in NYC BORO's: \nKings County (Brooklyn), \nBronx County (The Bronx)"
NYC_BORO_CODES <- c("36005", "36047", "36061", "36081", "36085");

# Display the map of NYC
nyc_inc_by_boro_vz1 <- plotMapForUSACounties(
  nyc_inc_by_boro_df, "county", c("NY", NYC_BORO_CODES), "inc_ct",
  "coral", "yellow", "coral3", "Shooting Incidents",
  str_c("New York City - Shooting Incidents. Total incidents:", total_no_of_incidents))
```

```

# Display only the Boros and concentration of incidents
nyc_inc_by_boro_vz2 <- plotMapForUSACounties(
  nyc_inc_by_boro_df, "county", NYC_BORO_CODES, "inc_ct",
  "coral", "yellow", "coral3", "Shooting Incidents",
  counties_lbl)

# Create a new dataset for display labels with counts
# We want the legends to display labels, hence we need to create a dataframe and join the counts for th
nyc_dataset_df1 <- nyc_dataset_df %>%
  group_by(syear, BORO) %>% summarize(ct = n()) %>%
  ungroup() %>%
  full_join(nyc_inc_by_boro_df) %>%
  # reorder the data so that it can appear sequentially on the facet grid
  mutate(boro_with_inc = paste0(BORO, '-', formatNumber(inc_ct))) %>%
  mutate(BORO = reorder(BORO, -inc_ct),
         boro_with_inc = reorder(boro_with_inc, -inc_ct)) %>%
  select(syear, BORO, ct, boro_with_inc)

# Create the visualization for cases per boro.
# The legends will include the counts
# the facet wrap will be by Boro. It helps to see the data for each Boro independantly.
nyc_incidents_ts_vz <- nyc_dataset_df1 %>%
  ggplot(aes(x=syear, y=ct, fill=boro_with_inc)) +
  geom_bar(stat='identity', aes(color=boro_with_inc), alpha=0.8, width = 0.5) +
  facet_wrap(~BORO, scales="free_y", nrow=3) +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("Shooting incidents in NYC Boros. Total incidents:", total_no_of_incidents)
  )

```

Analyze and prepare stats for **Location and Hours** for Visualization

```

# ----- NYC incidents by Location
# Prepare the location stats dataframe by grouping by LOCATION_DESC
nyc_incidents_by_loc_df <- nyc_dataset_df %>%
  group_by(LOCATION_DESC) %>% summarize(inc_ct = n()) %>%
  filter(inc_ct > 70)

# How many other location exists -- todo try fct_lump
other_locations_ct <- (nyc_dataset_df %>%
  group_by(LOCATION_DESC) %>% summarize(inc_ct = n()) %>%
  filter(inc_ct <= 70) %>%
  summarize(inc_ct = n())
)$inc_ct

# All other locations since fct_lump is not working
# Any locations with fewer counts will be lumped together with locations

```



```

other_locations_df <- data.frame(LOCATION_DESC=c("Other-Known-Locations-Grouped"),
                                inc_ct=c(other_locations_ct))

# Merge two datasets - append operation :- nyc_incidents_by_loc_df, other_locations_df
nyc_incidents_by_loc_df <- rbind(nyc_incidents_by_loc_df, other_locations_df)

# Sort the dataframe and add more informative labels
nyc_incidents_by_loc_df <- nyc_incidents_by_loc_df %>%
  mutate(LOCATION_DESC = paste0(LOCATION_DESC, ' - ', formatNumber(inc_ct))) %>%
  mutate(LOCATION_DESC = reorder(LOCATION_DESC, -inc_ct)) %>%
  ungroup()

# Prepare the graph for location display
nyc_incidents_by_loc_vz <- nyc_incidents_by_loc_df %>%
  ggplot(aes(x="", y=inc_ct, fill=LOCATION_DESC)) +
  geom_bar(stat="identity", width=1) +
  coord_polar("y", start=0) +
  xlab("") + ylab("") + ggtitle(str_c("S-Inc by Location. Total incidents:", total_no_of_incidents)) +
  theme(legend.direction="vertical")

# ----- NYC incidents by Day of Week and Hours
# Compute Weekly and Hourly incidents
nyc_incidents_by_week_hour_df <- nyc_dataset_df %>%
  group_by(sday_of_week, hour_bucket) %>% count()

# get the bucket wise count
nyc_incidents_hour_buc_df <- nyc_incidents_by_week_hour_df %>%
  group_by(hour_bucket) %>%
  summarize(bucket_ct = sum(n)) %>%
  ungroup()

# join two datasets to get count and labels together
nyc_incidents_by_week_hour_df <- nyc_incidents_by_week_hour_df %>%
  full_join(nyc_incidents_hour_buc_df, by = c("hour_bucket"))

nyc_incidents_by_week_hour_df <- nyc_incidents_by_week_hour_df %>%
  mutate(hour_bucket = paste0(hour_bucket, '.....', formatNumber(bucket_ct)))

# Prepare graph for incidents by week.
nyc_incidents_by_week_hour_vz <- nyc_incidents_by_week_hour_df %>%
  ggplot(aes(x=sday_of_week, y=n, fill=hour_bucket), label=hour_bucket) +
  geom_bar(stat="identity") +
  scale_fill_manual(values=c("tomato", "lightcyan", "lightsteelblue", "khaki1", "gray49", "snow2")) +
  #scale_fill_viridis_c(option="H") +
  xlab("") + ylab("") + ggtitle(str_c("S-Inc by Week and hour. Total incidents:", total_no_of_incidents)) +
  theme_classic()

```

Analyze and prepare stats for **Boro wise fatal flags** for Visualization

```

colors_fatal <- c("orange", "red")

```

```

# Create new dataset by aggregating data by Boro and STATISTICAL_MURDER_FLAG
nyc_dataset_byfatal_df <- nyc_dataset_df %>%
  group_by(BORO, STATISTICAL_MURDER_FLAG) %>%
  summarise(inc_ct = n()) %>%
  ungroup()

# Create new dataset by aggregating data by STATISTICAL_MURDER_FLAG
stat_flag_df <- nyc_dataset_df %>%
  group_by(STATISTICAL_MURDER_FLAG) %>%
  summarise(flag_ct = n()) %>%
  ungroup()

# Create new dataset by aggregating data by BORO, STATISTICAL_MURDER_FLAG and creating new columns for
nyc_dataset_byfatal_df2 <- nyc_dataset_df %>%
  group_by(BORO) %>%
  summarise(boro_ct = n(),
            true_ct = sum(STATISTICAL_MURDER_FLAG == TRUE),
            false_ct = sum(STATISTICAL_MURDER_FLAG == FALSE)
            ) %>%
  ungroup()

# Join the two datasets to create new dataset with good labels.
nyc_dataset_byfatal_df <- nyc_dataset_byfatal_df %>%
  full_join(nyc_dataset_byfatal_df2, by = c("BORO")) %>%
  full_join(stat_flag_df, by = c("STATISTICAL_MURDER_FLAG")) %>%
  mutate(pct = paste0(round(100 * (inc_ct / boro_ct), 2), "%"),
         fatal_flag = paste0(STATISTICAL_MURDER_FLAG, " - ", formatNumber(flag_ct)))

# Prepare graph for murder flag view.
nyc_dataset_byfatal_vz <- nyc_dataset_byfatal_df %>%
  ggplot(aes(x=BORO, y=inc_ct, fill=fatal_flag)) +
  scale_fill_manual(values=colors_fatal) +
  geom_bar(stat="identity", position=position_dodge()) +
  geom_text(aes(label=pct), color="navy", hjust=-0.06,
            position = position_dodge(0.9), size=3)+
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Fatal flag. Total incidents:", total_no_of_incidents)
  ) +
  coord_flip()

```

Analyze and prepare stats for **Age Groups** for Visualization

```

# ----- NYC incidents by perpetrators age group
# Timeseries data : NYC incidents by perpetrators age group

```

```

colors_age_grp1 <- c("red" ,"orange", "purple", "limegreen", "blue", "snow2")

# Create dataset for age-group, aggregating by syear, BORO, PERP_AGE_GROUP
nyc_incidents_by_perp_age_group_df <- nyc_dataset_df %>%
  group_by(syear, BORO, PERP_AGE_GROUP) %>% summarize(ct = n()) %>%
  ungroup()

# Create dataset for age-group, aggregating by PERP_AGE_GROUP
nyc_incidents_age_grp_ct_df1 <- nyc_incidents_by_perp_age_group_df %>%
  group_by(PERP_AGE_GROUP) %>% summarize(bucket_ct = sum(ct)) %>%
  ungroup()

# Merge the two datasets to get all the columns from both.
nyc_incidents_by_perp_age_group_df <- nyc_incidents_by_perp_age_group_df %>%
  full_join(nyc_incidents_age_grp_ct_df1, by = c("PERP_AGE_GROUP")) %>%
  mutate(age_grp_ct = paste0(PERP_AGE_GROUP, '.....', formatNumber(bucket_ct)))

# Prepare graph using merged dataset. The graph will be wrapped by Boro
nyc_incidents_by_perp_age_group_ts_vz <- nyc_incidents_by_perp_age_group_df %>%
  ggplot(aes(x=syear, y=ct, fill=age_grp_ct)) +
  geom_bar(stat='identity', alpha=0.8, width = 0.5) +

  facet_wrap(~PERP_AGE_GROUP, scales="free_y") +
  scale_fill_manual(values=colors_age_grp1) +
  facet_wrap(~BORO, scales="free_y") +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Perpetrator age group. Total incidents:", total_no_of_incidents)
  )

# ----- NYC incidents by Victims age group
colors_age_grp2 <- c("red" ,"orange", "purple", "limegreen", "blue", "snow2")
# Timeseries data : NYC incidents by Victims Age group

# Create dataset for age-group, aggregating by syear, BORO, VIC_AGE_GROUP
nyc_incidents_by_vic_age_group_df <- nyc_dataset_df %>%
  group_by(syear, BORO, VIC_AGE_GROUP) %>% summarize(ct = n()) %>%
  ungroup()

# Create dataset for age-group, aggregating by VIC_AGE_GROUP
nyc_incidents_age_grp_ct_df2 <- nyc_incidents_by_vic_age_group_df %>%
  group_by(VIC_AGE_GROUP) %>% summarize(bucket_ct = sum(ct)) %>%
  ungroup()

```

```

# merge wo datasets
nyc_incidents_by_vic_age_group_df <- nyc_incidents_by_vic_age_group_df %>%
  full_join(nyc_incidents_age_grp_ct_df2, by = c("VIC_AGE_GROUP")) %>%
  mutate(age_grp_ct = paste0(VIC_AGE_GROUP, '.....', formatNumber(bucket_ct)))

# Prepare graph using merged dataset. The graph will be wrapped by Boro
nyc_incidents_by_vic_age_group_ts_vz <- nyc_incidents_by_vic_age_group_df %>%
  ggplot(aes(x=syear, y=ct, fill=age_grp_ct)) +
  geom_bar(stat='identity', alpha=0.8, width = 0.5) +

  facet_wrap(~VIC_AGE_GROUP, scales="free_y") +
  scale_fill_manual(values = colors_age_grp2) +
  facet_wrap(~BORO, scales = "free_y") +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Victims age group. Total incidents:", total_no_of_incidents)
  )

```

Analyze and prepare stats for **Age Groups and Race** for Visualization

```

# ----- NYC incidents by Perpetrator age group and race

rc_colors1 <- c("blue", "darkslategrey", "rosybrown3", "snow2", "orchid", "skyblue", "red" )
rc_colors2 <- c("blue", "orchid", "darkslategrey", "rosybrown3", "snow2", "gold", "skyblue", "cyan", "red" )

# Create dataset for age-group and race, aggregating by syear, BORO, PERP_AGE_GROUP, PERP_RACE
nyc_incidents_by_perp_age_group_race_ts_df <- nyc_dataset_df %>%
  group_by(syear, BORO, PERP_AGE_GROUP, PERP_RACE) %>%
  summarize(ct_inc = n()) %>% filter(PERP_AGE_GROUP != "(null)" & ct_inc > 1) %>%
  ungroup()

# Create dataset for age-group and race, aggregating by PERP_RACE
nyc_race_ct_df <- nyc_incidents_by_perp_age_group_race_ts_df %>%
  group_by(PERP_RACE) %>%
  summarize(ct_rc = sum(ct_inc)) %>%
  ungroup()

# Merge two datasets for providing label ct views.
nyc_incidents_by_perp_age_group_race_ts_df <- nyc_incidents_by_perp_age_group_race_ts_df %>%
  full_join(nyc_race_ct_df) %>%
  mutate(race_with_inc = paste0(PERP_RACE, '-', formatNumber(ct_rc)))

# Prepare the graph for age group and race
nyc_incidents_by_perp_age_group_race_ts_vz <- nyc_incidents_by_perp_age_group_race_ts_df %>%
  ggplot(aes(x=PERP_AGE_GROUP, y=ct_inc, fill=race_with_inc)) +
  geom_bar(stat="identity") +
  facet_wrap(~PERP_AGE_GROUP, scales="free_y") +

```

```

scale_fill_manual(values=rc_colors1) +
facet_wrap(~BORO, scales="free_y") + # nrow=3
theme_light() +
theme(
  strip.background = element_rect(fill = "peachpuff"),
  strip.text = element_text(colour = "navy", size = rel(1.0)),
  plot.title = element_text(hjust = 0.5),
  plot.subtitle = element_text(hjust = 0.97),
  axis.text.x = element_text(angle = 45, hjust = 1)
) +
labs(
  title = str_c("S-Inc by Perpetrator age group and race. \nTotal incidents:", total_no_of_incidents)
)

# ----- NYC incidents by Victims age group and race

# Create dataset for age-group and race, aggregating by syear, BORO, VIC_AGE_GROUP, VIC_AGE_GROUP
nyc_incidents_by_vic_age_group_race_ts_df <- nyc_dataset_df %>%
  group_by(syear, BORO, VIC_AGE_GROUP, VIC_RACE) %>%
  summarize(ct_inc = n()) %>% filter(VIC_AGE_GROUP != "(null)" & ct_inc > 1) %>%
  ungroup()

# Create dataset for age-group and race, aggregating by VIC_RACE
nyc_vic_race_ct_df <- nyc_incidents_by_vic_age_group_race_ts_df %>%
  group_by(VIC_RACE) %>%
  summarize(ct_rc = sum(ct_inc)) %>%
  ungroup()

# join both datasets just above.
nyc_incidents_by_vic_age_group_race_ts_df <- nyc_incidents_by_vic_age_group_race_ts_df %>%
  full_join(nyc_vic_race_ct_df) %>%
  mutate(race_with_inc = paste0(VIC_RACE, '-', formatNumber(ct_rc)))

# Prepare graphs for displaying info by age-group and race
# use facet wrap to show each Boro separately with the info above.
nyc_incidents_by_vic_age_group_race_ts_vz <- nyc_incidents_by_vic_age_group_race_ts_df %>%
  ggplot(aes(x=VIC_AGE_GROUP, y=ct_inc, fill=race_with_inc)) +
  geom_bar(stat="identity") +
  facet_wrap(~VIC_AGE_GROUP, scales="free_y") +
  scale_fill_manual(values=rc_colors2) +
  facet_wrap(~BORO, scales="free_y") + # nrow=3
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Victims age group and race. \nTotal incidents:", total_no_of_incidents)
  )

```

Analyze and prepare stats for **Sex** for Visualization

```
# ----- NYC incidents by perpetrators gender
# Prepare visualization by Sex
x_colors <- c("deeppink", "slategray3", "snow2")
# Timeseries data : NYC incidents by Perpetrators Age group
# Create dataset for perpetrators gender, aggregating by syear, BORO, PERP_SEX
nyc_dataset_by_sex_df <- nyc_dataset_df %>%
  group_by(syear, BORO, PERP_SEX) %>% summarize(ct = n()) %>%
  ungroup()

# Create dataset for perpetrators gender, aggregating by PERP_SEX
nyc_dataset_by_sex_df2 <- nyc_dataset_by_sex_df %>%
  group_by(PERP_SEX) %>%
  summarize(sex_ct = sum(ct)) %>%
  ungroup()

# join the two datasets to get all cols
nyc_dataset_by_sex_df <- nyc_dataset_by_sex_df %>%
  full_join(nyc_dataset_by_sex_df2, by = c("PERP_SEX")) %>%
  mutate(sex_ct = str_c(PERP_SEX, '-', formatNumber(sex_ct)))

# Prepare graph for perpetrators gender stats display
nyc_incidents_by_perp_sex_ts_vz <- nyc_dataset_by_sex_df %>%
  ggplot(aes(x=syear, y=ct, fill=sex_ct)) +
  geom_bar(stat='identity', aes(fill=sex_ct), alpha=0.8, width = 0.5) +

  facet_wrap(~PERP_SEX, scales="free_y") +
  scale_fill_manual(values=x_colors) +
  facet_wrap(~BORO, scales="free_y") +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Perpetrator sex: Total incidents:", total_no_of_incidents)
  )

# ----- NYC incidents by victims sex
# Timeseries data
# Create dataset for victims gender, aggregating by syear, BORO, VIC_SEX
nyc_dataset_by_vic_sex_df <- nyc_dataset_df %>%
  group_by(syear, BORO, VIC_SEX) %>% summarize(ct = n()) %>%
  ungroup()

# Create dataset for victims gender, aggregating by VIC_SEX
nyc_dataset_by_vic_sex_df2 <- nyc_dataset_by_vic_sex_df %>%
  group_by(VIC_SEX) %>%
  summarize(sex_ct = sum(ct)) %>%
  ungroup()
```

```

# Merge the two datasets
nyc_dataset_by_vic_sex_df <- nyc_dataset_by_vic_sex_df %>%
  full_join(nyc_dataset_by_vic_sex_df2, by = c("VIC_SEX")) %>%
  mutate(sex_ct = str_c(VIC_SEX, '-', formatNumber(sex_ct)))

# Prepare graph for victims gender stats display
nyc_incidents_by_vic_sex_ts_vz <- nyc_dataset_by_vic_sex_df %>%
  ggplot(aes(x=syear, y=ct, fill=sex_ct)) +
  geom_bar(stat='identity', aes(fill=sex_ct), alpha=0.8, width = 0.5) +

  facet_wrap(~VIC_SEX, scales="free_y") +
  scale_fill_manual(values=x_colors) +
  facet_wrap(~BORO, scales="free_y") +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = str_c("S-Inc by Victims sex: Total incidents:", total_no_of_incidents)
  )

```

Analyze and prepare stats for **Precinct** for Visualization

```

# ----- NYC incidents for Brooklyn Precinct
# Create dataset for Brooklyn precinct, aggregating by PRECINCT
nyc_dataset_brooklyn_df <- nyc_dataset_df %>% filter(BORO == "BROOKLYN") %>%
  group_by(PRECINCT) %>% summarize(ct = n()) %>% arrange(desc(ct))

total_no_of_incidents_in_brooklyn <- (nyc_dataset_brooklyn_df %>% summarize(total=sum(ct)))$total
brooklyn_pct <- round((total_no_of_incidents_in_brooklyn/total_no_of_incidents_fl) * 100,2)
total_no_of_incidents_in_brooklyn <- formatNumber(total_no_of_incidents_in_brooklyn)

# -----
# Slice and dice Top 10
# Get the top 10 precinct in Brooklyn using the rank function and desc order of shooting counts
bk_top10_precinct_df <- nyc_dataset_brooklyn_df %>%
  mutate(rnk = min_rank(desc(ct))) %>%
  filter(rnk <=10)

# Get total no of shooting incidents in Brooklyn
bk_total_inc <- (nyc_dataset_brooklyn_df %>% summarize(tot = sum(ct)))$tot

# Which were the top 10 precincts in terms of no of shootings
top10_precinct <- paste(bk_top10_precinct_df$PRECINCT, collapse=', ')

# What was the share of top 10 precincts
bk_top10_share <- (bk_top10_precinct_df %>% summarize(tot = sum(ct)))$tot

bk_top10_global_pct <- str_c(round((bk_top10_share/total_no_of_incidents_fl) * 100,2), "%")

```

```

# What was the percentage of top 10 precincts
bk_top10_share_pct <- str_c(round((bk_top10_share/bk_total_inc) * 100,2), "%")

bk_inference1 <- str_c("\n NYC: ", total_no_of_incidents, ", Brooklyn: ", total_no_of_incidents_in_brooklyn)
bk_top10_inference1 <- str_c("\nTop 10 Brooklyn precincts with the most incidents were :\n", top10_precincts)
bk_top10_inference2 <- str_c("\nIncidents in the Top 10 precincts was ", formatNumber(bk_top10_share), "%")
bk_top10_inference3 <- str_c("\nTop 10 precincts overall share: ", bk_top10_global_pct)

display_label <- str_c("Shooting incidents in Brooklyn precincts. ", bk_inference1, bk_top10_inference3)

# -----

# Prepare graph for Brooklyn precinct
nyc_dataset_brooklyn_vz <- ggplot(nyc_dataset_brooklyn_df, aes(x=PRECINCT, y=ct)) +
  geom_bar(stat='identity', fill="coral") +
  xlab("Brooklyn precincts") + ylab("Brooklyn shooting counts") + ggtitle(display_label) +
  theme_light() +
  coord_flip() +
  theme(
    plot.title = element_text(hjust = 0.5, colour = "tomato", size=11),
    plot.subtitle = element_text(hjust = 0.97)
  )


```

Section 3: Visualizations


Section 3A: Big picture: - Shooting Incidents across New York City

- How many incidents are happening across New York City?
 - The total no of incidents was: **27,312**.
 - The incidents only impacted the 5 Boro's of NYC
 - NYC Boro names and FIPS codes can be found here - [List_of_counties_in_New_York](#)

New York City – Shooting Incidents. Total incidents:27,312




Shooting incidents in NYC BORO's:
Kings County (Brooklyn),
Bronx County (The Bronx),
Queens County (Queens),
New York County (Manhattan),
Richmond County (Staten Island)



- There were more incidents in Brooklyn and Bronx when compared with others.
 - Brooklyn started with 800+ incidents in 2005, then the incidents slowed down until *2019*.
 - After 2019, the incidents are again on rise in Brooklyn.
 - We observed a similar pattern in cases in Bronx where incidents are on the rise after 2019.


Shooting incidents in NYC Boros. Total incidents:27,312



Section 3B: Location & Time: Shooting Incidents across New York City


- Can we look at the location and time of the incident? What can we conclude?
 - Incidents were more frequent in the following locations. There were many unknowns too due to data collection issues.
 - We lumped few locations that had fewer than 70 incidents into **Other-known-locations**.
 - From these insights, we can warn people in the top 5 locations to be careful.
 - We can also ask Government to put more law enforcement surveillance in the top 3 areas.

S-Inc by Location. Total incidents:27,312 LOCATION_DESC




- **What time during the week do these incidents happen?**
 - On a Weekday basis, we get to know when these incidents are happening.
 - We can infer that most of the incidents are happening during the Night and Midnight time in general.
 - This info should help Law Enforcement and the public for safety purposes.

S-Inc by Week and hour. Total incidents:27,312



Section 3C: Incident Fatality: Shooting Incidents across New York City

- Were the incidents Fatal?
 - Between **17% to 20%** of the incidents resulted in a murder.




Demographics - Perpetrators

Section 3D: Perpetrators Demographics: Shooting Incidents across New York City


- Can we understand the demographics of the perpetrators?
- What were the age-group of the perpetrators?
 - Throughout the years, we noticed that the perpetrators of the age groups 18 to 44 committed the most crimes.
 - A large section of the age group is unknown to us, hence it is lightly shaded.
 - The cops couldn't figure out the ages for some reasons.

S-Inc by Perpetrator age group. Total incidents:27,312




- What are the race and age-group of the perpetrators in each Boro?
 - Based on our data, Black and Black Hispanic between ages 18-44 committed most crimes.

S-Inc by Perpetrator age group and race.
Total incidents:27,312



- What were the gender of the perpetrators?
 - We can conclude that amongst this group, Men are more involved in crimes than women.
 - There are many unknowns too, since data is missing.
 - Also, men shop for firearms more than women.

S-Inc by Perpetrator sex: Total incidents:27,312




Demographics - Victims

Section 3E: Victims Demographics: Shooting Incidents across New York City


- Can we understand the demographics of the victims?
- **What was the age-group of the victims?**
 - Based on our data, ages between 18-44 were victims.

S-Inc by Victims age group. Total incidents:27,312




- What are the race and age-group of the victims in each Boro?
 - Based on our data, Black and Black Hispanic between ages 18-44 were the victims.

S-Inc by Victims age group and race.
Total incidents:27,312



- What were the gender of the Victims?
 - We can conclude that amongst this group, Men are more targeted in crimes than women.
 - It is possible that Men are out most of the time than women during night hours in these areas.


S-Inc by Victims sex: Total incidents:27,312



Section 3F: Closer look: Shooting Incidents in Brooklyn, New York City

- Which precinct in Brooklyn had the most incidents? What could be the reasons?
 - There are few precincts that need more attention from Law Enforcement
 - With limited data we cannot do the root cause analysis for the shootings in this location.
 - Government needs to understand the cause of shooting in these precincts.

Shooting incidents in Brooklyn precincts.
 NYC: 27,312, Brooklyn: 10,933 (40.03%)
 Top 10 precincts overall share: 32.35%
 Top 10 Brooklyn precincts with the most incidents were :
 75, 73, 67, 79, 81, 77, 71, 83, 69, 70
 Incidents in the Top 10 precincts was 8,835, which was about 80.81% of below.



Section 4: Model Training and Prediction

Section 4: Model Building: Build Quantitative model for shooting incidents in New York City

- Train and test a model for NYC Shooting incident

Section 4A: Prepare model data and Train a linear model:

- Prepare the data and train model

```
nyc_ct_by_year_mdl_df <- nyc_dataset_df %>%
  group_by(BORO, syear) %>%
  summarise(inc_ct = n()) %>%
  ungroup()

nyc_ct_by_year_mdl = lm(inc_ct ~ syear + BORO, data = nyc_ct_by_year_mdl_df)
```

Section 4B: Run predictions on the model and prepare the Visualizations:

- We ran the predictions on the model and created `nyc_ct_by_year_pred_df`
- Prepare the visualizations for the predicted model.

```
nyc_ct_by_year_pred_df = nyc_ct_by_year_md1_df %>% mutate(pred=predict(nyc_ct_by_year_md1)) %>%
  mutate(BORO = factor(BORO))

nyc_ct_by_year_pred_vz <- ggplot(nyc_ct_by_year_pred_df) +
  geom_point(aes(x = syear, y = inc_ct, color = "Actual")) +
  geom_point(aes(x = syear, y = pred, color = "Predicted")) +
  facet_wrap(~BORO, scales="free_y") +
  theme_light() +
  theme(
    strip.background = element_rect(fill = "peachpuff"),
    strip.text = element_text(colour = "navy", size = rel(1.0)),
    plot.title = element_text(hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.97),
    axis.text.x = element_text(angle = 45, hjust = 1)
  ) +
  labs(
    title = "Predictions by NYC Boros. "
  )
```

```
# Formula is
summary(nyc_ct_by_year_md1)[1]
```


```
## $call
## lm(formula = inc_ct ~ syear + BORO, data = nyc_ct_by_year_md1_df)
```

```
# summarize the champion model
summary(nyc_ct_by_year_md1$coefficients)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## -421.2  -249.1  -116.4  2236.1   130.5 14151.2
```

- How close are we with respect to Boro wise yearly predictions? will this help NYPD or others?
 - The future predictions, if accurate, will help the law enforcement to stop the crime before it happens.
 - In the prediction's dataset, we noticed that the incidents are decreasing over time in our model. This is a good starting point.
 - However, this model is not accurate. There are more improvements needed to gain accuracy.
 - Perhaps some other model or new variables may yield better results. We must continue doing the experiments

Predictions by NYC Boros.



Section 5A: Bias Identification & Elimination: Professor Jane Wall rightly mentioned that Biases are natural. Everyone falls into their trap. While looking at the initial data I might have some implicit bias such as stereotypes.

Implicit bias refers to the attitudes or stereotypes that affect our understanding, actions, and decisions in an unconscious manner. An implicit bias can make us susceptible to unintentionally acting in ways that are inconsistent with our values. Implicit bias can be based on stereotypes.

A **stereotype** is a generalized belief about a particular category of people. It is an expectation that people might have about every person of a particular group. The type of expectation can vary; it can be, for example, an expectation about the group's personality, preferences, appearance or ability. Stereotypes are sometimes overgeneralized, inaccurate, and resistant to new information, but can sometimes be accurate.

Biases - How to overcome: To overcome implicit biases, we need to thoroughly analyze the data and our report must be based on facts in the data and not based on our emotions and biases.

Section 5B: Conclusion:

- After downloading and cleaning up the data for NYPD shooting, we went through an iterative Data science process of Asking questions, preparing data, analyzing, visualizing the data and drawing conclusions. We eliminated the Biases - stereotype, emotional and other biases - by gleaning valuable information from the data to make inferences.
- We reported our observations at each step. Our key observations were:

- Between **2005** and **2020**, there were **27,312** shooting incidents in the **five** Boro's and **Brooklyn 40%** and **Bronx** were the areas with most crimes. **Approx. 17% to 20%** of the incidents resulted in a murder. We also noticed that the incident was concentrated in few Precincts within these Boro's.
 - The incidents mostly occurred in the multi-dwell, apt, grocery, bar/night club, and commercial buildings during the night and the midnight hours and mostly men were involved in crime.
 - The race, sex and age-group of most of the perpetrators were - Black Male between **ages 18 to 44** years. The race, sex and age-group of most of the victims were - Black and Black Hispanic and white Hispanic male between **ages 18 to 44** years.
 - The top 10 precincts in Brooklyn resulted in a crime rate of **32.35%** of the NYC shootings. These precincts : **75, 73, 67, 79, 81, 77, 71, 83, 69, 70** had total **8,835** shooting incidents and hence they really need attention. Crime rate can be cut into more than 1/2 if we can help these precincts.
 - We built a model to predict the shootings in each Boro for the future. We noticed that our model is good, but not 100% accurate. A linear model in this case might not yield good accuracy. We need to run various experiments - try new variables, try new models, etc. to fine tune our model.
 - With the **limited amount** of data, we cannot do provide justifications to the causes of these crimes. It could be late night street fights, drug abuse, etc. It could be related to unemployment and theft. Government should investigate the root cause of crime in the key precincts.
 - We **recommend** that Law Enforcement should deploy more cops in the high-risk region that was highlighted in the report for the safety of the public during night hours. The public should be extra careful during the high-risk hours.
-