```c
#include <stdio.h>
#include <stdlib.h>

#define MIN(x, y) (x > y ? y : x)

int main()
{
   int orate, cap, x, count = 0, i = 0, nsec, ch;
   int inp[100] = {0};

   printf("\n Enter bucket size : ");
   scanf("%d", &cap);

   printf("\n Enter output rate : ");
   scanf("%d", &orate);

   do
   {
      if(i >= 100)
      {
         printf("Maximum number of input seconds reached. Exiting input loop.\n");
         break;
      }

      printf("Enter number of packets coming at second %d : ", i + 1);
      scanf("%d", &inp[i]);
      i++;

      printf("Enter 1 to continue or 0 to quit: ");
      scanf("%d", &ch);
   } while(ch == 1);

   nsec = i;

   printf("Second \t Received \t Sent \t Dropped \t Remaining");

   for(i = 0; count > 0 || i < nsec; i++)
   {
      int current_received = (i < nsec) ? inp[i] : 0;
      int sent = MIN(current_received + count, orate);

      x = current_received + count - sent;

      int dropped = 0;

      if(x > cap)
      {
         dropped = x - cap;
         count = cap;
      }
      else
      {
         count = x;
      }

      printf("%d\t %d\t %d\t %d\t %d", i + 1, current_received, sent, dropped, count);
   }

   return 0;
}
```