```html
<!DOCTYPE html>
<html lang="en">
<head>
<title>Simple Music Player</title>
<!-- Load FontAwesome icons -->
<link rel="stylesheet"
        href=
"https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.13.0/css/all.min.css">

<!-- Load the custom CSS style file -->
<link rel="stylesheet" type="text/css" href="style.css">
</head>
<body>
<div class="player">

    <!-- Define the section for displaying details -->
    <div class="details">
    <div class="now-playing">PLAYING MAGIC SHOP OF
BTS</div>
    <div class="track-art"></div>
    <div class="track-name">MAGIC SHOP</div>
    <div class="track-artist">BTS</div>
    </div>
```

```html
<!-- Define the section for displaying track buttons -->
<div class="buttons">
<div class="prev-track" onclick="prevTrack()">
    <i class="fa fa-step-backward fa-2x"></i>
</div>
<div class="playpause-track" onclick="playpauseTrack()">
    <i class="fa fa-play-circle fa-5x"></i>
</div>
<div class="next-track" onclick="nextTrack()">
    <i class="fa fa-step-forward fa-2x"></i>
</div>
</div>


<!-- Define the section for displaying the seek slider-->
<div class="slider_container">
<div class="current-time">00:00</div>
<input type="range" min="1" max="100"
    value="0" class="seek_slider" onchange="seekTo()">
<div class="total-duration">00:00</div>
</div>


<!-- Define the section for displaying the volume slider-->
<div class="slider_container">
<i class="fa fa-volume-down"></i>
<input type="range" min="1" max="100"
```

```html
            value="99" class="volume_slider"
onchange="setVolume()">
        <i class="fa fa-volume-up"></i>
        </div>
</div>


<!-- Load the main script for the player -->
<script src="main.js"></script>
</body>
</html>
```