



Culture and  
Methodologies  
(/culture-and-  
methodologies)

Data  
Engineering  
(/data-  
engineering)

Software Design and  
Architecture (/software-  
design-and-architecture)

Coding  
(/coding)

Testing, Deployment, and  
Maintenance (/testing-  
deployment-and-  
maintenance)

Partner  
Zones

## Partner Resources



Culture and  
Methodologies  
(/culture-and-  
methodologies)

Data  
Engineering  
(/data-  
engineering)

Software Design and  
Architecture (/software-  
design-and-architecture)

Coding  
(/coding)

Testing, Deployment, and  
Maintenance (/testing-  
deployment-and-  
maintenance)

Partner  
Zones



# Top 20 Git Commands With Examples

Now that you (presumably) know what Git is and how it works, take a look at examples of how to use the top 20 Git commands.



by Sahiti Kappagantula (/users/3288749/sahiti-k.html) MVB · Jun. 21, 22 · Tutorial

👍 Like (111) 💬 Comment (8) ☆ Save 🐦 Tweet in Share 👁 2.10M Views

In the previous blog, you got an understanding of what git is (https://www.edureka.co/blog/what-is-git/). In this blog, I will talk about the Top 20 Git Commands that you will be using frequently while you are working with Git (https://dzone.com/refcardz/getting-started-git).

Here are the Git commands which are being covered:

- **git config**
- **git init**
- **git clone**
- **git add**
- **git commit**
- **git diff**
- **git reset**
- **git status**
- **git rm**
- **git log**
- **git show**
- **git tag**
- **git branch**



git checkout

**DZone**

(/)

REFCARDS (/refcards)

REPORTS (/reports)

TESTS (/tests)

DEVELOPS (/develop)

SEARCH (\$search)

## ABOUT US

About DZone (/pages/about)

Send Feedback (mailto:support@dzone.com)

Careers (/careers)

Sitemap (/sitemap)

Culture and Data

Software Design and

Coding

Testing, Deployment, and

Partner

Methodologies (/methodologies)

Engineering (/engineering)

Architecture (/software-  
(/coding)

Maintenance (/testing-  
deployment-and-

Zones  
maintenance)

## ADVERTISE

Advertise with DZone (https://advertise.dzone.com)

## CONTRIBUTE ON DZONE

Article Submission Guidelines (/articles/dzones-article-submission-guidelines)

Become a Contributor (/pages/contribute)

Visit the Writers' Zone (/writers-zone)

## LEGAL

Terms of Service (/pages/tos)

Privacy Policy (/pages/privacy)

## CONTACT US

600 Park Offices Drive

Suite 300

Durham, NC 27709

support@dzone.com (mailto:support@dzone.com)

Let's be friends:



(/pages/lets-be-friends) (https://www.dzone.com/dzonecompany/dzone/)

~

Usage: git init [repository name]

This command is used to start a new repository.

```
edureka@master:~$ git init /home/edureka/Documents/DEMO
Initialized empty Git repository in /home/edureka/Documents/DEMO/.git/
```

## git clone

Usage: git clone [url]

This command is used to obtain a repository from an existing URL.

```
edureka@master:~$ git clone https://github.com/sahitikappagantula/gitexample.git
Cloning into 'gitexample'...
remote: Counting objects: 28, done.
remote: Compressing objects: 100% (16/16), done.
remote: Total 28 (delta 5), reused 28 (delta 5), pack-reused 0
Unpacking objects: 100% (28/28), done.
```

## git add

Usage: git add [file]

This command adds a file to the staging area.

```
edureka@master:~/Documents/DEMO$ git add project_1
```

Usage: git add \*

This command adds one or more to the staging area.

```
edureka@master:~/Documents/DEMO$ git add *
```

## git commit

Usage: git commit -m "[ Type in the commit message]"

This command records or snapshots the file permanently in the version history.

```
edureka@master:~/Documents/DEMO$ git commit -m "First Commit"
[master (root-commit) aff3269] First Commit
9 files changed, 200 insertions(+)
create mode 100644 project_1/css/site.css
create mode 100644 project_1/fonts/segoeui.ttf
create mode 100644 project_1/img/cloneWhite.svg
create mode 100644 project_1/img/deployWhite.svg
create mode 100644 project_1/img/lightbulbWhite.svg
create mode 100644 project_1/img/stackWhite.svg
create mode 100644 project_1/img/successCloudNew.svg
create mode 100644 project_1/img/tweetThis.svg
create mode 100644 project_1/index.html
```

Usage: git commit -a

This command commits any files you've added with the git add command and also commits any files you've changed since then.

```
edureka@master:~/Documents/DEMO$ git commit -a
On branch master
nothing to commit, working tree clean
```

## git diff

Usage: git diff

This command shows the file differences which are not yet staged.

```
edureka@master:~/Documents/DEMO$ git diff
diff --git a/project_1/index.html b/project_1/index.html
index 8a985d9..94cfa0f 100644
--- a/project_1/index.html
+++ b/project_1/index.html
@@ -20,8 +20,8 @@
     </div>
     <div class="content-body">
       <div class="success-text">Success!</div>
-      <div class="description line-1"> AWS DevOps Project has been successfully setup</div>
-      <div class="description line-2"> Your HTML app is up and running on AWS</div>
+      <div class="description line-1"> Azure DevOps Project has been successfully setup</div>
```

```
+      <div class="description line-2"> Your HTML app is up and running on Azure</div>
      <div class="next-steps-container">
        <div class="next-steps-header">Next up</div>
        <div class="next-steps-body">
```

Usage: `git diff --staged`

This command shows the differences between the files in the staging area and the latest version present.

```
edureka@master:~/Documents/DEMO/project_1/css$ git diff --staged
diff --git a/project_1/css/site.css b/project_1/css/site.css
index 25606b6..fba307d 100644
--- a/project_1/css/site.css
+++ b/project_1/css/site.css
@@ -1,5 +1,5 @@
html,
/* This the css file for the web page */
/* This the css file for the web page we are using for our DEMO */
body {
  height: 100%;
  width: 100%;
```

Usage: `git diff [first branch] [second branch]`

This command shows the differences between the two branches mentioned.

```
edureka@master:~/Documents/DEMO/project_1$ git diff branch_2 branch_3
diff --git a/project_1/index.html b/project_1/index.html
index b567d94..94cfa0f 100644
--- a/project_1/index.html
+++ b/project_1/index.html
@@ -47,7 +47,7 @@
      <div class="step-icon">
        
      </div>
      <div class="step-text"><a href="https://go.microsoft.com/fwlink/?linkid=862126">Learn more about a
ll you can do with AWS & Google Cloud Platform projects by visiting the documentation</a></div>
+      <div class="step-text"><a href="https://go.microsoft.com/fwlink/?linkid=862126">Learn more about a
ll you can do with AWS & GCP projects by visiting the documentation</a></div>
      </div>
    </div>
  </div>
```

## git reset

Usage: `git reset [file]`

This command unstages the file, but it preserves the file contents.

```
edureka@master:~/Documents/DEMO/project_1/css$ git reset site.css
Unstaged changes after reset:
M   project_1/css/site.css
M   project_1/index.html
```

Usage: `git reset [commit]`

This command undoes all the commits after the specified commit and preserves the changes locally.

```
edureka@master:~/Documents/DEMO$ git reset 09bb8e3f996eaf9a68ac5ba8d8b8fceb0e8641e7
Unstaged changes after reset:
M   project_1/css/site.css
M   project_1/index.html
```

Usage: `git reset -hard [commit]` This command discards all history and goes back to the specified commit.

```
edureka@master:~/Documents/DEMO$ git reset --hard b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
HEAD is now at b01557d CHanges made in HTML file
```

## git status

Usage: `git status`

This command lists all the files that have to be committed.

```
edureka@master:~/Documents/DEMO$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

        modified:   project_1/css/site.css
        modified:   project_1/index.html

no changes added to commit (use "git add" and/or "git commit -a")
```

## git rm

Usage: `git rm [file]`

This command deletes the file from your working directory and stages the deletion.

```
edureka@master:~/Documents/DEMO/project_2$ git rm example.txt
rm 'project_2/example.txt'
```

## git log

Usage: `git log`

This command is used to list the version history for the current branch.

```
edureka@master:~/Documents/DEMO$ git log
commit 09bb8e3f996eaf9a68ac5ba8d8b8fceb0e8641e7 (HEAD -> master)
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:25:17 2018 +0530

    Changes made in HTML and CSS file

commit b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:13:29 2018 +0530

    CHanges made in HTML file

commit aff3269a856ed251bfdf7ef87acb1716a2a9527a
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:07:28 2018 +0530

    First Commit
```

Usage: `git log -follow[file]`



This command lists version history for a file, including the renaming of files also.

```
edureka@master:~/Documents/DEMO$ git log --follow project_1
commit 2b4c50431c127a0ae9ede4aace0b8dd1f9fcf2c5
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:50:08 2018 +0530

    New file added

commit 09bb8e3f996eaf9a68ac5ba8d8b8fceb0e8641e7
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:25:17 2018 +0530

    Changes made in HTML and CSS file

commit b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:13:29 2018 +0530

    CHanges made in HTML file

commit aff3269a856ed251bfdf7ef87acb1716a2a9527a
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:07:28 2018 +0530

    First Commit
```

## git show

Usage: git show [commit]

This command shows the metadata and content changes of the specified commit.

```
edureka@master:~/Documents/DEMO$ git show b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
commit b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
Author: sahitikappagantula <sahiti.kappagantula@edureka.co>
Date:   Fri Jul 20 12:13:29 2018 +0530

    Changes made in HTML file

diff --git a/project_1/index.html b/project_1/index.html
index 8a985d9..94cfa0f 100644
--- a/project_1/index.html
+++ b/project_1/index.html
@@ -20,8 +20,8 @@
     </div>
     <div class="content-body">
       <div class="success-text">Success!</div>
-      <div class="description line-1"> AWS DevOps Project has been successfully setup</div>
-      <div class="description line-2"> Your HTML app is up and running on AWS</div>
+      <div class="description line-1"> Azure DevOps Project has been successfully setup</div>
+      <div class="description line-2"> Your HTML app is up and running on Azure</div>
       <div class="next-steps-container">
         <div class="next-steps-header">Next up</div>
         <div class="next-steps-body">
```

## git tag

Usage: git tag [commitID]

This command is used to give tags to the specified commit.

```
edureka@master:~/Documents/DEMO$ git tag b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
edureka@master:~/Documents/DEMO$ git tag
aff3269a856ed251bfdf7ef87acb1716a2a9527a
b01557d80d5f53dcf0ebdde4d3f8b0d20d8b8c16
```



## git branch

Usage: git branch

This command lists all the local branches in the current repository.

```
edureka@master:~/Documents/DEMO$ git branch
* master
```

Usage: git branch [branch name]

This command creates a new branch.

```
edureka@master:~/Documents/DEMO$ git branch branch_1
```

Usage: git branch -d [branch name]

This command deletes the feature branch.

```
edureka@master:~/Documents/DEMO$ git branch -d branch_1
Deleted branch branch_1 (was be040cc).
```

## git checkout

Usage: git checkout [branch name]

This command is used to switch from one branch to another.

```
edureka@master:~/Documents/DEMO$ git checkout branch_2
Switched to branch 'branch_2'
```

Usage: git checkout -b [branch name]

This command creates a new branch and also switches to it.

```
edureka@master:~/Documents/DEMO$ git checkout -b branch_4
Switched to a new branch 'branch_4'
```

## git merge

Usage: git merge [branch name]

This command merges the specified branch's history into the current branch.

```
edureka@master:~/Documents/DEMO$ git merge branch_2
Merge made by the 'recursive' strategy.
 project_1/index.html | 2 +-
 1 file changed, 1 insertion(+), 1 deletion(-)
```

## git remote

Usage: git remote add [variable name] [Remote Server Link]

This command is used to connect your local repository to the remote server.

```
edureka@master:~/Documents/DEMO$ git remote add origin https://github.com/sahitikappagantula/GitDemo.git
```

## git push

Usage: git push [variable name] master

This command sends the committed changes of master branch to your remote repository.

```
edureka@master:~/Documents/DEMO$ git push origin master
Username for 'https://github.com': sahitikappagantula
Password for 'https://sahitikappagantula@github.com':
Counting objects: 42, done.
Delta compression using up to 2 threads.
Compressing objects: 100% (32/32), done.
Writing objects: 100% (42/42), 463.10 KiB | 3.62 MiB/s, done.
Total 42 (delta 9), reused 0 (delta 0)
remote: Resolving deltas: 100% (9/9), done.
To https://github.com/sahitikappagantula/GitDemo.git
 * [new branch]      master -> master
```

Usage: git push [variable name] [branch]

This command sends the branch commits to your remote repository.

```
edureka@master:~/Documents/DEMO$ git push origin master
Username for 'https://github.com': sahitikappagantula
Password for 'https://sahitikappagantula@github.com':
Counting objects: 42, done.
Delta compression using up to 2 threads.
Compressing objects: 100% (32/32), done.
Writing objects: 100% (42/42), 463.10 KiB | 3.62 MiB/s, done.
Total 42 (delta 9), reused 0 (delta 0)
remote: Resolving deltas: 100% (9/9), done.
To https://github.com/sahitikappagantula/GitDemo.git
 * [new branch]      master -> master
```

Usage: git push -all [variable name]

This command pushes all branches to your remote repository.

```
edureka@master:~/Documents/DEMO$ git push --all origin
Username for 'https://github.com': sahitikappagantula
Password for 'https://sahitikappagantula@github.com':
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/sahitikappagantula/GitDemo.git
 * [new branch]      branch_3 -> branch_3
 * [new branch]      branch_4 -> branch_4
```

Usage: git push [variable name] :[branch name]

This command deletes a branch on your remote repository.

```
edureka@master:~/Documents/DEMO$ git push origin :branch_2
Username for 'https://github.com': sahitikappagantula
Password for 'https://sahitikappagantula@github.com':
```

## git pull

Usage: `git pull [Repository Link]`

This command fetches and merges changes on the remote server to your working directory.

```
edureka@master:~/Documents/DEMO$ git pull https://github.com/sahitkappagantula/gitlearn.git
warning: no common commits
remote: Counting objects: 13, done.
remote: Compressing objects: 100% (8/8), done.
remote: Total 13 (delta 1), reused 10 (delta 1), pack-reused 0
Unpacking objects: 100% (13/13), done.
From https://github.com/sahitkappagantula/gitlearn
* branch      HEAD      -> FETCH_HEAD
fatal: refusing to merge unrelated histories
```

## git stash

Usage: `git stash save`

This command temporarily stores all the modified tracked files.

```
edureka@master:~/Documents/DEMO/project_1$ git stash save
Saved working directory and index state WIP on branch_2: 5152fcd Index.html updated
```

Usage: `git stash pop`

This command restores the most recently stashed files.

```
edureka@master:~/Documents/DEMO/project_1$ git stash pop
On branch branch_2
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git checkout -- <file>..." to discard changes in working directory)

        modified:   index.html

no changes added to commit (use "git add" and/or "git commit -a")
Dropped refs/stash@{0} (365fa2ef6ed4f1f8d7d406bd0abb205279aad0c5)
```

Usage: `git stash list`

This command lists all stashed changesets.

```
edureka@master:~/Documents/DEMO/project_1$ git stash list
stash@{0}: WIP on master: 5f6ba20 Merge branch 'branch_2'
```

Usage: `git stash drop`

This command discards the most recently stashed changeset.

```
edureka@master:~/Documents/DEMO/project_1$ git stash drop stash@{0}
Dropped stash@{0} (5e2cbcea1b37d4e5b88854964d6165e461e2309d)
```

Want to learn more about git commands? Here is a Git Tutorial (<https://www.edureka.co/blog/git-tutorial/>) to get you started. Alternatively, you can take a top-down approach and start with this DevOps Tutorial.

(<https://www.edureka.co/blog/devops-tutorial>)

---

Git    Command (Computing)

Opinions expressed by DZone contributors are their own.

---

## TRENDING

Batch Processing vs. Stream Processing: Why Batch Is Dying and Streaming Takes Over

---

Using Artificial Intelligence in Finance

---

A Developer's Dilemma: Flutter vs. React Native

---

What Is QA as a Service?