

* Servlet Configuration

There are two types of configuration in servlet

- configuration means settings or information that we provide to an application so it knows how to behave, without changing the Java code.

- We use configuration to separate configuration settings from application logic. Instead of hard-coding values like the database URL, username, password, or API keys inside the Java code, we store them in a configuration file such as web.xml.

This makes the application easier to maintain because if any setting changes, we only update the configuration file instead of modifying, recompiling and redeploying the Java code. It improves maintainability, flexibility & reusability.

- If we hardcode the configuration values inside the Java code, then whenever a value changes such as database URL, username, password we have to modify the Java source code, recompile it and redeploy the application. This takes extra time

and

- If we store the values in web.xml, we only change the configuration file. We don't need to modify or recompile the Java code because the servlet reads the configuration from web.xml. After the application reloads, the updated values are used. This saves time and makes the application easier to maintain.

① ServletConfig:

The first type of configuration in Servlet is Servlet configuration (ServletConfig).

Okay

- Now ServletConfig is an interface provided by the Servlet API. It is used to provide configuration information to a specific Servlet.
- The configuration values are written inside the `<init-param>` tag in `web.xml`
- and those values can be accessed using the ServletConfig object.
- each Servlet has its own separate ServletConfig object. So configuration is available only to that particular Servlet.

Syntax:

```

<web-app>
  <Servlet>
    <Servlet-name>
    <Servlet-class>
    <init-param>
      <param-name>
      <param-value>
    </init-param>
  </Servlet>
  <Servlet-mapping>
    <Servlet-name>
    <url-pattern>
  </Servlet-mapping>
</web-app>

```


Revision for servlet mapping

<web-app>

<servlet>

<servlet-name>

<servlet-class>

</servlet>

<servlet-mapping>

<servlet-name>

<url-pattern>

</servlet-mapping>

</web-app>