



Piscine

04

*Summary: this document is the subject for the unit C 04 of the C Piscine @ 42.*

*Version: 3*

# Contents

<b>I</b>	<b>Instructions</b>	<b>2</b>
<b>II</b>	<b>Foreword</b>	<b>4</b>
<b>III</b>	<b>Exercise 00 : ft_strlen</b>	<b>6</b>
<b>IV</b>	<b>Exercise 01 : ft_putstr</b>	<b>7</b>
<b>V</b>	<b>Exercise 02 : ft_putnbr</b>	<b>8</b>
<b>VI</b>	<b>Exercise 03 : ft_ toi</b>	<b>9</b>
<b>VII</b>	<b>Exercise 04 : ft_putnbr_base</b>	<b>10</b>
<b>VIII</b>	<b>Exercise 05 : ft_ toi_base</b>	<b>12</b>

# Chapter I

## Instructions

- Only this page will serve as reference: do not trust rumors.
- Watch out! This document could potentially change before submission.
- Make sure you have the appropriate permissions on your files and directories.
- You have to follow the submission procedures for all your exercises.
- Your exercises will be checked and graded by your fellow classmates.
- On top of that, your exercises will be checked and graded by a program called Moulinette.
- Moulinette is very meticulous and strict in its evaluation of your work. It is entirely automated and there is no way to negotiate with it. So if you want to avoid bad surprises, be as thorough as possible.
- Moulinette is not very open-minded. It won't try and understand your code if it doesn't respect the Norm. Moulinette relies on a program called `norminette` to check if your files respect the norm. TL;DR: it would be idiotic to submit a piece of work that doesn't pass `norminette`'s check.
- These exercises are carefully laid out by order of difficulty - from easiest to hardest. We **will not** take into account a successfully completed harder exercise if an easier one is not perfectly functional.
- Using a forbidden function is considered cheating. Cheaters get **-42**, and this grade is non-negotiable.
- You'll only have to submit a `main()` function if we ask for a program.
- Moulinette compiles with these flags: `-Wall -Wextra -Werror`, and uses `gcc`.
- If your program doesn't compile, you'll get 0.
- You cannot leave any additional file in your directory than those specified in the subject.
- Got a question? Ask your peer on the right. Otherwise, try your peer on the left.

- Your reference guide is called `Google / man / the Internet / ....`
- Check out the "C Piscine" part of the forum on the intranet, or the slack Piscine.
- Examine the examples thoroughly. They could very well call for details that are not explicitly mentioned in the subject...
- By Odin, by Thor ! Use your brain !!!



Norminette must be launched with the `-R CheckForbiddenSourceHeader` flag. Moulinette will use it too.

# Chapter II

## Foreword

Here are the lyrics for City Hunter's theme song "Moonlight Shadow":

The last time ever she saw him  
Carried away by a moonlight shadow  
He passed on worried and warning  
Carried away by a moonlight shadow.  
Lost in a riddle that Saturday night  
Far away on the other side.  
He was caught in the middle of a desperate fight  
and she couldn't find how to push through

The trees that whisper in the evening  
Carried away by a moonlight shadow  
Sing a song of sorrow and grieving  
Carried away by a moonlight shadow  
All she saw was a silhouette of a gun  
Far away on the other side.  
He was shot six times by a man on the run  
and she couldn't find how to push through

[Chorus]  
I stay, I pray  
See you in Heaven far away...  
I stay, I pray  
See you in Heaven one day.

Four .M. in the morning  
Carried away by a moonlight shadow  
I watched your vision forming  
Carried away by a moonlight shadow  
The star was glowing in the silvery night  
Far away on the other side  
Will you come to talk to me this night  
But she couldn't find how to push through


[Chorus]

Far away on the other side.  
Caught in the middle of a hundred and five  
The night was heavy and the air was alive  
But she couldn't find how to push through  
Carried away by a moonlight shadow  
Carried away by a moonlight shadow  
Far away on the other side.

Unfortunately, this topic has nothing to do with City Hunter.

# Chapter III

## Exercise 00 : ft\_strlen


	Exercise 00
ft_strlen	
Turn-in directory : <i>ex00</i>	
Files to turn in : <b>ft_strlen.c</b>	
Allowed functions : None	

- Create a function that counts and returns the number of characters in a string.
- Here's how it should be prototyped :

```
int ft_strlen(char *str);
```

# Chapter IV

## Exercise 01 : ft\_putstr

	Exercise 01
ft_putstr	
Turn-in directory : <i>ex01</i>	
Files to turn in : <b>ft_putstr.c</b>	
Allowed functions : <b>write</b>	


- Create a function that displays a string of characters on the standard output.
- Here's how it should be prototyped :

```
void    ft_putstr(char *str);
```



# Chapter V

## Exercise 02 : ft\_putnbr

	Exercise 02
	ft_putnbr
	Turn-in directory : <i>ex02</i>
	Files to turn in : <b>ft_putnbr.c</b>
	Allowed functions : <b>write</b>

- Create a function that displays the number entered as a parameter. The function has to be able to display all possible values within an `int` type variable.
- Here's how it should be prototyped :


```
void ft_putnbr(int nb);
```

- For example:

`ft_putnbr(42)` displays "42".

# Chapter VI

## Exercise 03 : ft\_atoi

	Exercise 03
	ft_atoi
	Turn-in directory : <i>ex03</i>
	Files to turn in : <b>ft_atoi.c</b>
	Allowed functions : None

- Write a function that converts the initial portion of the string pointed by str to its int representation
- The string can start with an arbitrary amount of white space (as determined by `isspace(3)`)
- The string can be followed by an arbitrary amount of + and - signs, - sign will change the sign of the int returned based on the number of - is odd or even.
- Finally the string can be followed by any numbers of the base 10.
- Your function should read the string until the string stop following the rules and return the number found until now.
- You should not take care of overflow or underflow. result can be undefined in that case.
- Here's an example of a program that prints the atoi return value:


```
$>./ .out " ----+---1234 b567"  
-1234
```

- Here's how it should be prototyped :

```
int      ft_atoi(char *str);
```

# Chapter VII

## Exercise 04 : ft\_putnbr\_base

	Exercise 04
	ft_putnbr_base
	Turn-in directory : <i>ex04</i>
	Files to turn in : <b>ft_putnbr_base.c</b>
	Allowed functions : <b>write</b>

- Create a function that displays a number in a base system in the terminal.
- This number is given in the shape of an **int**, and the radix in the shape of a **string** of characters.
- The base-system contains all useable symbols to display that number :

0123456789 is the commonly used base system to represent decimal numbers

01 is a binary base system ;

0123456789 BCDEF an hexadecimal base system ;

poneyvif is an octal base system.

- The function must handle negative numbers.
- If there's an invalid argument, nothing should be displayed. Examples of invalid arguments :

base is empty or size of 1;

base contains the same character twice ;


base contains + or - ;

- Here's how it should be prototyped :

```
void      ft_putnbr_base(int nbr, char *base);
```

# Chapter VIII

## Exercise 05 : ft\_toi\_base

	Exercise 05
	ft_atoi_base
	Turn-in directory : <i>ex05</i>
	Files to turn in : <b>ft_toi_base.c</b>
	Allowed functions : None

- Write a function that converts the initial portion of the string pointed by str to int representation.
- str is in a specific base given as a second parameter.
- excepted the base rule, the function should work exactly like ft\_atoi.
- If there's an invalid argument, the function should return 0. Examples of invalid arguments :

base is empty or size of 1;

base contains the same character twice ;

base contains + or - or whitespaces;

- Here's how it should be prototyped :

```
int ft_toi_base(char *str, char *base);
```