1. create database work;

use work;

create table workers (

workerid int Primary key,

Company name varchar(100) not null,

designation varchar(100) not null,

Salary decimal(10, 2) check (Salary > 0),

Experience int check (Experience > 0)

);

desc workers;

Insert into workers (work id, company name, designation, Salary, Experience)

Values :

(1, 'Zoho', 'Software Engineer', 50000, 2),

(2, 'amazon', 'Quality analyser', 30000, 3),

(3, 'HCl', 'developer', 45000, 1);

Scanned with OKEN Scanner

Select * From workers;

workerid	Companyname	designation	Salary	Expe
1	Zoho	Software Engineer	50,000	2
2.	amazon	Quality analyst	30,000	3
3	Hcl	developer	45,000	1

2.) create database work;

use work;

create table workers (

workersid int Primary key,

workername varchar(100) not null,

company name varchar(100) not null,

designation varchar(100) not null,

Salary Decimal(10,2) check (salary>0),

Experience int check (Experience>0)

);

dex workers;

workers values:

(1, 'Arun', 'zoho', 'Software Engineer', 50000, 2),

(2, 'Bala', 'amazon', 'Quality analyser', 80000, 5)

(3, 'Ajay', 'HCl', 'developer', 45000, 1);

Select * From workers;

worker Id	worker name	Company name	designation	Salary	Exper
1	Arun	zoho	Software Engineer	50000	2
2	Bala	amazon	Quality analyser	80000	5
3	Ajay	HCl	developer	45000	1

Select * from workers

where Salary = (select max(Salary) from

Select * From workers

where Salary = (select min (Salary) From workers)

Output :

highest salary

worker name	Salary
Bala	80000

lowest Salary

Ajay - 45000.

Scanned with OKEN Scanner

3. select student_id,

marks,

Sum(marks) over() AS total_marks,

AVG(marks) over() AS avg_marks

From ur

order By marks desc

limit 10;

student id	marks	total mark	avg marks
101	98	100	75
112	74	100	75
113	56	100	75
109	78	100	75
118	87	100	75
114	94	100	75
107	98	100	75
119	91	100	75
120	60	100	75
116	55	100	75
		100	75

Scanned with OKEN Scanner

4.)

<u>Inner join</u>: returns rows with matches in both tables.

```
Select column_names
From table1
inner join table2.
on table.common_column = table2.common_
                                column;
```

Left join:

returns all rows from the right table and matching rows from the left table, using null for non matches.

```
Select emp.name, departments.department_name
From employees
left join departments
on employees.department_id = departments.
                                department_id;
```

Scanned with OKEN Scanner

Right join:

returns all rows from the right table and matching rows from the left table, using null for non matches.

```
Sel emp.name, departments.dep_Name
From employees
right join departments
On employees.dep_id = dept.dept_id
```

Full outer join:

my sql does not have a native full outer join. can be simulate using left and right join with union.

```
Sel emp.name, depts.dept_name
From employees.
left join depts
Onemps.dep_id = deps.dept_id
union
```

Scanned with OKEN Scanner

Cross join: creates a cartesian product of all rows from both tables.

```
Sel.emps.name, depts.dept-name
From employees
cross join deptms;
```

Self join: joins a table to itself using aliases.

```
Select a.name as employee, b.name as manager
From employees a, employees b
where a.manager_id = b.employee_id;
```

Scanned with OKEN Scanner