Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

s1 =

1100

s2 =

1111

Your Output:

1

Expected Output:

1

Java (21) | Start Timer

```java
class Solution {
    public int minSwaps(String s1, String s2) {
        int count01 = 0, count10 = 0;

        for (int i = 0; i < s1.length(); i++) {
            if (s1.charAt(i) == '0' && s2.charAt(i) == '1')
                count01++;
            else if (s1.charAt(i) == '1' && s2.charAt(i) == '0')
                count10++;
        }

        // if total mismatches is odd, impossible
        if ((count01 + count10) % 2 != 0)
            return -1;

        return (count01 + count10) / 2;
    }
}
```

Custom Input | Compile & Run | Submit

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

s =

(()(

Your Output:

2

Expected Output:

2

Java (21) | Start Timer

```java
class Solution {
    public int minParentheses(String s) {
        int open = 0, add = 0;

        for (char ch : s.toCharArray()) {
            if (ch == '(') {
                open++;
            } else {
                if (open > 0) {
                    open--;
                } else {
                    add++;
                }
            }
        }
        return add + open;
    }
}
```

Custom Input | Compile & Run | Submit

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

s =

(()(()))

Your Output:

6

Expected Output:

6

Java (21) | Start Timer

```java
class Solution {
    public int scoreOfParentheses(String s) {
        int score = 0;
        int depth = 0;

        for (int i = 0; i < s.length(); i++) {
            if (s.charAt(i) == '(') {
                depth++;
            } else {
                depth--;
                if (s.charAt(i - 1) == '(') {
                    score += 1 << depth;
                }
            }
        }
        return score;
    }
}
```

Custom Input | Compile & Run | Submit

Search... | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

12:30:15 12:30:45

Your Output:

30

Expected Output:

30

Java (21) | Start Timer

```java
class Solution {
    public int minDifference(String[] arr) {
        int n = arr.length;
        int[] time = new int[n];

        // Convert HH:MM:SS to seconds
        for (int i = 0; i < n; i++) {
            String[] t = arr[i].split(":");
            int h = Integer.parseInt(t[0]);
            int m = Integer.parseInt(t[1]);
            int s = Integer.parseInt(t[2]);
            time[i] = h * 3600 + m * 60 + s;
        }

        Arrays.sort(time);

        int minDiff = Integer.MAX_VALUE;

        // Adjacent differences
        for (int i = 1; i < n; i++) {
            minDiff = Math.min(minDiff, time[i] - time[i - 1]);
        }

        // Circular difference (midnight wrap)
        int wrapDiff = 86400 - time[n - 1] + time[0];
        minDiff = Math.min(minDiff, wrapDiff);

        return minDiff;
    }
}
```

Search... | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

s =

geeksforgeeks

Your Output:

forggkksseeee

Expected Output:

forggkksseeee

Java (21) | Start Timer

```java
class Solution {
    public String frequencySort(String s) {

        int[] freq = new int[26];

        // Count frequency
        for (char c : s.toCharArray()) {
            freq[c - 'a']++;
        }

        // Store characters
        Character[] chars = new Character[s.length()];
        for (int i = 0; i < s.length(); i++) {
            chars[i] = s.charAt(i);
        }

        // Sort by frequency, then lexicographically
        Arrays.sort(chars, (a, b) -> {
            if (freq[a - 'a'] != freq[b - 'a'])
                return freq[a - 'a'] - freq[b - 'a'];
            return a - b;
        });

        // Build result
        StringBuilder sb = new StringBuilder();
        for (char c : chars) {
            sb.append(c);
        }

        return sb.toString();
    }
}
```

Custom Input | Compile & Run | Submit

Search... | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

GeeksforGeeeks I from am

Your Output:

["I", "am", "from", "GeeksforGeeeks"]

Expected Output:

["I", "am", "from", "GeeksforGeeeks"]

Java (21) | Start Timer

```java
import java.util.*;

class Solution {
    public void sortByLength(String[] arr) {

        Arrays.sort(arr, (a, b) -> a.length() - b.length());

    }
}
```

Custom Input | Compile & Run | Submit

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

def deg dmf xef dxg

Your Output:

4

Expected Output:

4

Java (21) | Start Timer

```java
import java.util.*;

class Solution {
    public int countPairs(String[] arr) {

        Map<String, Integer> map = new HashMap<>();
        int count = 0;

        for (String s : arr) {
            char[] ch = s.toCharArray();

            for (int i = 0; i < ch.length; i++) {
                char temp = ch[i];
                ch[i] = '*';

                String key = new String(ch);
                count += map.getOrDefault(key, 0);
                map.put(key, map.getOrDefault(key, 0) + 1);

                ch[i] = temp;
            }
        }

        return count;
    }
}
```

Ctrl + ·

Custom Input | Compile & Run | Submit

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

john johnny jackie johnny john jackie jamie jamie john johnny jamie johnny john

Your Output:

john 4

Expected Output:

john 4

Java (21) | Start Timer

```java
import java.util.*;

class Solution {
    public List<String> winner(List<String> arr) {

        Map<String, Integer> map = new HashMap<>();

        for (String name : arr) {
            map.put(name, map.getOrDefault(name, 0) + 1);
        }

        String winner = "";
        int maxVotes = 0;

        for (Map.Entry<String, Integer> entry : map.entrySet()) {
            String name = entry.getKey();
            int votes = entry.getValue();

            if (votes > maxVotes ||
               (votes == maxVotes && name.compareTo(winner) < 0)) {
                maxVotes = votes;
                winner = name;
            }
        }

        List<String> result = new ArrayList<>();
        result.add(winner);
        result.add(String.valueOf(maxVotes));

        return result;
    }
}
```

Ctrl + ·

Custom Input | Compile & Run | Submit

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

txt =

geeks

pat =

eke

Your Output:

true

Expected Output:

true

Java (21) | Start Timer

```java
class Solution {
    boolean search(String txt, String pat) {

        if (pat.length() > txt.length()) return false;

        int[] patFreq = new int[26];
        int[] winFreq = new int[26];

        // Frequency of pattern
        for (char c : pat.toCharArray()) {
            patFreq[c - 'a']++;
        }

        int k = pat.length();

        // First window
        for (int i = 0; i < k; i++) {
            winFreq[txt.charAt(i) - 'a']++;
        }

        if (matches(patFreq, winFreq)) return true;

        // Sliding window
        for (int i = k; i < txt.length(); i++) {
            winFreq[txt.charAt(i) - 'a']++;          // add new char
            winFreq[txt.charAt(i - k) - 'a']--;      // remove old char

            if (matches(patFreq, winFreq)) return true;
        }

        return false;
    }

    private boolean matches(int[] a, int[] b) {
        for (int i = 0; i < 26; i++) {
```

Custom Input | Compile & Run | Submit

Search...

2 Offers Ending

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

s =

ritz

k =

2

Your Output:

tz

Expected Output:

tz

Java (21) Start Timer

```java
class Solution {
    public static String maxSubseq(String s, int k) {

        StringBuilder stack = new StringBuilder();

        for (char c : s.toCharArray()) {
            while (stack.length() > 0 && k > 0 && stack.charAt(stack.length() - 1) < c) {
                stack.deleteCharAt(stack.length() - 1);
                k--;
            }
            stack.append(c);
        }

        // Remove remaining characters from end if k still > 0
        if (k > 0) {
            stack.setLength(stack.length() - k);
        }

        return stack.toString();
    }
}
```

Ctrl + '

Custom Input Compile & Run Submit