Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

```
3 3 2
1 2 3
4 5 6
7 8 9
0 0 2 2
1 0 2 1
```

Your Output:

```
45
24
```

Expected Output:

```
45
24
```

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    ArrayList<Long> submatrixSum(long[][] a, int n, int m, int[][] query, int q) {
        long[][] ps = new long[n][m];

        // build prefix sum
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {
                ps[i][j] = a[i][j]
                        + (i > 0 ? ps[i - 1][j] : 0)
                        + (j > 0 ? ps[i][j - 1] : 0)
                        - (i > 0 && j > 0 ? ps[i - 1][j - 1] : 0);
            }
        }

        ArrayList<Long> ans = new ArrayList<>();

        for (int i = 0; i < q; i++) {
            int r1 = query[i][0];
            int c1 = query[i][1];
            int r2 = query[i][2];
            int c2 = query[i][3];

            long sum = ps[r2][c2];
            if (r1 > 0) sum -= ps[r1 - 1][c2];
            if (c1 > 0) sum -= ps[r2][c1 - 1];
            if (r1 > 0 && c1 > 0) sum += ps[r1 - 1][c1 - 1];

            ans.add(sum);
        }
        return ans;
    }
}
```

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

```
3 3
1 2 3
4 5 6
7 8 9
1
2 2
```

Your Output:

```
20
```

Expected Output:

```
20
```

Java (21) Start Timer

```java
            int min3 = Integer.MAX_VALUE;
            int min4 = Integer.MAX_VALUE;

            // top-left
            for (int i = 0; i < r; i++)
                for (int j = 0; j < c; j++)
                    min1 = Math.min(min1, a[i][j]);

            // top-right
            for (int i = 0; i < r; i++)
                for (int j = c + 1; j < m; j++)
                    min2 = Math.min(min2, a[i][j]);

            // bottom-left
            for (int i = r + 1; i < n; i++)
                for (int j = 0; j < c; j++)
                    min3 = Math.min(min3, a[i][j]);

            // bottom-right
            for (int i = r + 1; i < n; i++)
                for (int j = c + 1; j < m; j++)
                    min4 = Math.min(min4, a[i][j]);

            int sum = 0;
            if (min1 != Integer.MAX_VALUE) sum += min1;
            if (min2 != Integer.MAX_VALUE) sum += min2;
            if (min3 != Integer.MAX_VALUE) sum += min3;
            if (min4 != Integer.MAX_VALUE) sum += min4;

            ans[qi] = sum;
        }
        return ans;
    }
}
```

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

```
8 6 2
```

Your Output:

```
3
```

Expected Output:

```
3
```

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public int minOperations(int[] arr) {

        PriorityQueue<Double> pq =
                new PriorityQueue<>(Collections.reverseOrder());

        double sum = 0;
        for (int x : arr) {
            pq.add((double) x);
            sum += x;
        }

        double target = sum / 2.0;
        int ops = 0;

        while (sum > target) {
            double x = pq.poll();
            double half = x / 2.0;
            sum -= half;
            pq.add(half);
            ops++;
        }

        return ops;
    }
}
```

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

-1 2 2 -1 0 0

Your Output:

2

Expected Output:

2

Java (21) Start Timer

```java
class Solution {
    public int minMen(int[] arr) {
        int n = arr.length;
        List<int[]> intervals = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            if (arr[i] != -1) {
                int L = Math.max(0, i - arr[i]);
                int R = Math.min(n - 1, i + arr[i]);
                intervals.add(new int[]{L, R});
            }
        }

        intervals.sort((a, b) -> a[0] - b[0]);

        int currEnd = 0, farthest = 0, count = 0, i = 0;

        while (currEnd < n) {
            while (i < intervals.size() && intervals.get(i)[0] <= currEnd) {
                farthest = Math.max(farthest, intervals.get(i)[1]);
                i++;
            }

            if (farthest < currEnd) return -1;

            count++;
            currEnd = farthest + 1;
        }

        return count;
    }
}
```

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 6 2

Your Output:

[-1, 1, 1]

Expected Output:

[-1, 1, 1]

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public static ArrayList<Integer> prevSmaller(int[] arr) {
        ArrayList<Integer> res = new ArrayList<>();
        Stack<Integer> st = new Stack<>();

        for (int x : arr) {
            while (!st.isEmpty() && st.peek() >= x)
                st.pop();

            res.add(st.isEmpty() ? -1 : st.peek());
            st.push(x);
        }
        return res;
    }
}
```

Custom Input Compile & Run Submit

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 2 1

Your Output:

5

Expected Output:

5

Java (21) Start Timer

```java
class Solution {
    public int countSubarrays(int[] arr) {
        int n = arr.length;
        int[] nextSmaller = new int[n];
        java.util.Stack<Integer> stack = new java.util.Stack<>();

        // Find next smaller element index
        for (int i = n - 1; i >= 0; i--) {
            while (!stack.isEmpty() && arr[stack.peek()] >= arr[i]) {
                stack.pop();
            }
            nextSmaller[i] = stack.isEmpty() ? n : stack.peek();
            stack.push(i);
        }

        int count = 0;
        for (int i = 0; i < n; i++) {
            count += (nextSmaller[i] - i);
        }

        return count;
    }
}
```

Custom Input Compile & Run Submit

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

4 7 11 5 13 2

Your Output:

true

Expected Output:

true

```java
import java.util.*;

class Solution {
    public boolean has132Pattern(int[] arr) {
        Stack<Integer> st = new Stack<>();
        int third = Integer.MIN_VALUE;

        for (int i = arr.length - 1; i >= 0; i--) {
            if (arr[i] < third) return true;

            while (!st.isEmpty() && st.peek() < arr[i])
                third = st.pop();

            st.push(arr[i]);
        }
        return false;
    }
}
```

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

6 2 5 4 5 1 6

Your Output:

7

Expected Output:

6

Output Difference:

7 6

```java
class Solution {
    public int maxPeople(int[] arr) {
        int n = arr.length;
        int ans = 0;

        for (int i = 0; i < n; i++) {
            int visible = 0;
            java.util.Stack<Integer> st = new java.util.Stack<>();

            // look left
            for (int j = i - 1; j >= 0; j--) {
                if (arr[j] > arr[i]) {
                    visible++;
                    break;
                }
                visible++;
            }

            // look right
            for (int j = i + 1; j < n; j++) {
                if (arr[j] > arr[i]) {
                    visible++;
                    break;
                }
                visible++;
            }

            ans = Math.max(ans, visible + 1); // +1 for self
        }

        return ans;
    }
}
```

Output Window

Compilation Results | Custom Input

Case 1

Input:

n =

9

k =

3

Your Output:

[[1, 2, 6],
[1, 3, 5],
[2, 3, 4]]

Expected Output:

[[1, 2, 6],
[1, 3, 5],
[2, 3, 4]]

```java
import java.util.*;

class Solution {
    public ArrayList<ArrayList<Integer>> combinationSum(int n, int k) {
        ArrayList<ArrayList<Integer>> res = new ArrayList<>();
        backtrack(1, n, k, new ArrayList<>(), res);
        return res;
    }

    private void backtrack(int start, int sum, int k,
                           ArrayList<Integer> temp,
                           ArrayList<ArrayList<Integer>> res) {

        if (sum == 0 && temp.size() == k) {
            res.add(new ArrayList<>(temp));
            return;
        }

        if (sum < 0 || temp.size() > k)
            return;

        for (int i = start; i <= 9; i++) {
            temp.add(i);
            backtrack(i + 1, sum - i, k, temp, res);
            temp.remove(temp.size() - 1);
        }
    }
}
```

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

2 6 2 5

k =

3

Your Output:

1

Expected Output:

1

Java (21) | Start Timer

```java
import java.util.*;

class Solution {
    public int maxMinDiff(int[] arr, int k) {
        Arrays.sort(arr);
        int n = arr.length;
        int ans = 0;

        for (int i = 0; i + k - 1 < n; i++) {
            int minDiff = Integer.MAX_VALUE;

            for (int j = i; j < i + k - 1; j++) {
                minDiff = Math.min(minDiff, arr[j + 1] - arr[j]);
            }

            ans = Math.max(ans, minDiff);
        }
        return ans;
    }
}
```

Search... | 2 Offers Ending | Courses | Tutorials | Practice | Jobs

Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

6 10 12 15 2 4 5

x =

14

Your Output:

6

Expected Output:

6

Java (21) | Start Timer

```java
class Solution {
    public int countlessEqual(int[] arr, int x) {
        int count = 0;
        for (int i = 0; i < arr.length; i++) {
            if (arr[i] <= x)
                count++;
        }
        return count;
    }
}
```

Custom Input | Compile & Run | Submit