## 2147. Number of Ways to Divide a Long Corridor

Along a long library corridor, there is a line of seats and decorative plants. You are given a **0-indexed** string `corridor` of length `n` consisting of letters `'S'` and `'P'` where each `'S'` represents a seat and each `'P'` represents a plant.

One room divider has **already** been installed to the left of index `0`, and **another** to the right of index `n - 1`. Additional room dividers can be installed. For each position between indices `i - 1` and `i` (`1 <= i <= n - 1`), at most one divider can be installed.

Divide the corridor into non-overlapping sections, where each section has **exactly two seats** with any number of plants. There may be multiple ways to perform the division. Two ways are **different** if there is a position with a room divider installed in the first way but not in the second way.

Return *the number of ways to divide the corridor*. Since the answer may be very large, return it **modulo** $10^9 + 7$. If there is no way, return `0`.

**Example 1:**

index    0   1   2   3   4   5   6

**Input:** corridor = "SSPPSPS"
**Output:** 3
**Explanation:** There are 3 different ways to divide the corridor.
The black bars in the above image indicate the two room dividers already installed.
Note that in each of the ways, **each** section has exactly **two** seats.

**Example 2:**

index    0   1   2   3   4   5

**Input:** corridor = "PPSPSP"
**Output:** 1
**Explanation:** There is only 1 way to divide the corridor, by not installing any additional dividers.
Installing any would create some section that does not have exactly two seats.

**Example 3:**

index    0

**Input:** corridor = "S"
**Output:** 0
**Explanation:** There is no way to divide the corridor because there will always be a section that does not have exactly two seats.

```java
public int numberOfWays(String corridor) {
    int seat = 0, plant = 0, n = corridor.length(), total = 0, mod = (int) 1e9 + 7;
    long ans = 1;
    boolean isFirstDividerInstalled = false;
    for (int i = 0; i < n; i++) {
        char ch = corridor.charAt(i);
        if (ch == 'S') {
            total++;
            seat++;
        } else if (seat == 0)
            plant++;

        if (seat == 2) {
            if (isFirstDividerInstalled)
                ans = (ans * (plant + 1) % mod) % mod;

            isFirstDividerInstalled = true;
            seat = 0;
            plant = 0;
        }
    }

    return (total > 0 && total % 2 == 0) ? (int) ans % mod : 0;
}
```