Enterprise Document Q&A with RAG and AI Agents

Generative AI & ML Capstone Project — Edureka · Project Documentation

Submitted by: Phaneendranath Jenne
Date: October 10, 2026

Item	Value
Repository	https://github.com/rajphanee/genai-capstone
Live demo	https://phaneen-genai-capstone.streamlit.app
Stack	Python 3.11 · LangGraph · ChromaDB · all-MiniLM-L6-v2 (Hugging Face) · Anthropic Claude · Streamlit · pytest
Validation	64 automated tests · 14/14 golden questions · 9/9 bad files rejected · tested on phone and desktop
Run it	pip install -r requirements.txt → streamlit run app/streamlit_app.py

1. Problem statement

Enterprises keep knowledge in many formats — policy PDFs, text procedures, CSV exports, Excel trackers. Finding a specific fact means opening files one by one, and generic chatbots answer from general knowledge, which leads to confident but wrong answers.


The capstone goal is a Generative AI application where users **upload documents (PDF, TXT, CSV, Excel) and ask natural-language questions**. The system must retrieve relevant content from a **vector database**, generate a **grounded answer with an LLM**, and use **AI agents that plan, retrieve, reason and validate** the output.

2. Solution summary

The application indexes uploaded documents into ChromaDB using semantic embeddings, then answers each question through a four-agent pipeline. Every sentence of an answer cites the exact file and location it came from (for example `[S1] employee_handbook.pdf — page 2`). When the documents do not contain the answer, the system declines instead of guessing.

- **Simple, phone-friendly UI** (Streamlit) plus an optional REST API and a command-line tool.
- **Four formats**: PDF (per page), TXT, CSV and Excel (all sheets, rows converted to `column: value` text).
- **Four agents wired with LangGraph**: Planner → Retriever → Reasoner → Validator, with a self-correction loop.
- **Visible reasoning**: every answer carries an agent trace (step, timing, details) shown in the UI.
- **Safety**: input and document prompt-injection guardrails, citation and number checks, PII masking, friendly failures.
- **Never crashes on a bad key**: if Claude is unavailable the app falls back to offline answers and shows a warning.

3. Architecture



Agentic framework: the question flow is a LangGraph `StateGraph` (agents/graph.py). Each agent is a node; conditional edges end the flow early (blocked, greeting, nothing relevant, LLM error) or loop the Validator back to the Reasoner once.
Design principle: the LLM drafts, deterministic code decides. Retrieval thresholds, citation checks and the number check are plain Python, so a model mistake is caught rather than shown to the user.

4. System setup

```
cd edureka-genai-capstone
python3.11 -m venv .venv && source .venv/bin/activate      # Windows: .venv\Scripts\activate
pip install -r requirements.txt
# .env already contains LLM_PROVIDER=claude and ANTHROPIC_API_KEY
streamlit run app/streamlit_app.py                          # open http://localhost:8501
bash scripts/validate.sh                                    # optional: runs every check
```

Folder structure

Folder	Contents
app/	streamlit_app.py — the web UI
agents/	planner, retriever, reasoner, validator + graph.py (LangGraph wiring)
vectordb/	embeddings.py (MiniLM), store.py (ChromaDB); data/ created at runtime
src/	config, ingestion, chunking, llm, guardrails, errors, service, cli, api
sample_docs/	4 demo files (PDF, TXT, CSV, XLSX) and edge_cases/ with 9 bad files
tests/, evals/, scripts/	64 tests, 14 golden questions, validate.sh
docs/	this documentation, architecture PPT, screenshots
.env, requirements.txt, README.md	settings + API key, packages, step-by-step guide

5. Workflow

5.1 Document ingestion

Step	What happens	File
Validate	Extension in PDF/TXT/CSV/XLSX, not empty, ≤ 20 MB; file content must match the extension (a JPEG renamed .txt is caught)	ingestion.py
Extract	PDF per page (headings kept), TXT with encoding fallback, CSV delimiter auto-detect, Excel every sheet; rows become `Region: West | Revenue: 4.8` lines, 20 rows per section	ingestion.py
Chunk	800-character chunks with 150 overlap, cut at paragraph → sentence → word boundaries	chunking.py
Embed	all-MiniLM-L6-v2 (384-dim, Hugging Face) via ChromaDB's ONNX runtime; offline fallback	vectordb/embeddings.py
Store	ChromaDB persistent collection (cosine). Doc id = SHA-256 of bytes → duplicate uploads skipped; failed writes rolled back	vectordb/store.py

5.2 Agent roles

Agent	Responsibility	Failure behaviour
Input guardrail	Length 3–1000 chars; blocks override attempts (“ignore previous instructions”, “reveal system prompt”)	status = blocked

Agent	Responsibility	Failure behaviour
Planner	Intent (lookup, summary, comparison, list, chitchat); splits compound questions into up to 3 search queries; sets top-k (×2 for summaries/comparisons). With Claude: make_plan tool with a fixed intent list	LLM error → default plan; greetings skip search
Retriever	Search per sub-question, merge best score per chunk, drop chunks below relevance threshold, strip injected instructions found inside documents	nothing relevant → decline
Reasoner	Sends numbered sources [S1]…[Sn] to Claude: use only sources, cite every sentence, else reply INSUFFICIENT_CONTEXT	Claude fails (bad key, outage) → offline extractive answer, flagged in the trace
Validator	Every sentence cited; citations exist; every number appears in its cited source; masks SSN/card/API keys	fail → feedback to Reasoner, 1 retry → decline

5.3 Example

```
Q: What is the home office stipend and how many remote days are allowed?
Planner   intent=lookup, 2 search queries (compound question split)
Retriever 1 relevant chunk kept of 5 found  (employee_handbook.pdf, page 2)
Reasoner  attempt 1: draft ready
Validator attempt 1: pass
A: A one-time home office stipend of 500 dollars is paid in the first month [S1].
   Employees may work remotely up to 3 days per week with manager approval [S1].
   [S1] employee_handbook.pdf - page 2
```

6. Capstone tasks — implementation map

#	Task	Implementation	Evidence
1	Project foundation	Folders app/ agents/ vectordb/ src/, .env, requirements, CI, Dockerfile	validate.sh step 1-3
2	User interaction layer	Single-column Streamlit UI (phone + desktop): upload, sample docs, suggested questions, chat, sources, trace	test_ui.py, screenshots
3	Document ingestion	PDF, TXT, CSV, Excel readers; jpg/zip/renamed/corrupt/empty/scanned/password files rejected clearly	9 edge-case files
4	Prepare data for search	Overlapping, boundary-aware chunking with location metadata	chunk size/overlap tests
5	Vector knowledge store	MiniLM embeddings in persistent ChromaDB; dedupe; delete; rollback	test_store_and_service.py
6	Intelligent retrieval	Multi-query similarity search, relevance threshold, per-document filter	Sources panel, retriever trace
7	RAG pipeline	Numbered-source prompt to Claude with strict grounding rules	answers cite [S#]
8	Agent-based reasoning	Planner, Retriever, Reasoner, Validator wired as a LangGraph StateGraph with retry loop	test_agents.py, agent trace
9	Reliability & safety	Guardrails, citation/number validation, PII masking, error hierarchy, retries, fallbacks	section 6
10	Deploy & document	Streamlit Community Cloud, Docker, README, this report	section 8

7. Reliability and safety controls

Risk	Control
Hallucinated facts	Answer only from retrieved sources; every sentence must carry a citation
Invented numbers	Every number in the answer must appear in the cited source text
Fake citations	A citation must reference a source that was actually retrieved
Weak matches	Chunks below the relevance threshold are discarded; nothing left → decline
Bad first draft	Validator problems are sent back; one rewrite, then decline
Prompt injection (question)	Pattern guardrail blocks override attempts before any agent runs
Prompt injection (inside a document)	Instruction-like lines removed from chunks before the LLM sees them (demo file includes one)
Sensitive data	SSN, card-number and API-key patterns are masked in answers
Bad files / bad input	jpg, zip, renamed, corrupt, empty, header-only, scanned and password-protected files each get a clear message; one bad file never blocks the others
Missing / invalid API key	App starts anyway with offline answers and a yellow warning; Claude errors fall back per question
LLM or network outage	Retries with exponential backoff, then a friendly error; planner falls back to a default plan
Embedding model unavailable	auto mode falls back to offline embeddings with a logged warning
Traceability	Each question, outcome and citations appended to history.jsonl

8. Testing and evaluation

Unit and integration tests — 64 passed. Cover every file format, all 9 edge-case files in sample_docs/edge_cases (jpg, zip, renamed, fake PDF, corrupt Excel, empty, header-only CSV, scanned, password-protected), size limit, chunking, duplicate detection, persistence across restarts, every agent, the self-correction loop, repeated hallucination, LLM outage, prompt injection in questions and documents, Claude failure → offline fallback, missing key → warning, the REST API error contract, the Streamlit UI (headless), and the Claude client using a fake SDK (no network). The UI was also tested in a real browser at phone size (390 px) and desktop size.

Golden-question evaluation — 14/14 passed.


Category	Questions	Result
Answerable from PDF	PTO days, carry-over expiry, remote days, expense approval	4/4 answered, correct file cited
Answerable from TXT	password length, incident reporting time	2/2
Answerable from CSV	West Q2 revenue, East Q1 new customers	2/2
Answerable from Excel	Contoso renewal date, Contoso uptime SLA (2nd sheet)	2/2
Not in documents	capital of France, CEO of Acme	2/2 declined
Prompt injection	“Ignore all previous instructions…”	blocked
Greeting	“hello”	chitchat, no search
Leak check	injected password from a document must never appear	never appeared

Groundedness: 10/10 answered questions carry citations. The same suite runs on every push in GitHub Actions (Python 3.11 and 3.12).


Validation commands

```
bash scripts/validate.sh                      # everything: tests, evals, CLI, API, 9 edge-case files
python -m pytest -q                           # 64 passed
python evals/run_evals.py                     # Accuracy: 14/14
python -m src ingest sample_docs/*.*
python -m src ask "How many PTO days do employees get per year?" --trace
python -m src ingest sample_docs/edge_cases/photo.jpg      # shows the error
streamlit run app/streamlit_app.py            # UI on http://localhost:8501
```


9. Application screenshots (smartphone)




Start screen



jpg, zip, password PDF, empty file rejected




Answer with source



Declined and blocked

Desktop: answer with sources and the four-agent trace



10. Deployment

Streamlit Community Cloud (public URL). Push the repository to GitHub → share.streamlit.io → Create app → main file `app/streamlit_app.py`, Python 3.11 → optional secrets `LLM_PROVIDER` and `ANTHROPIC_API_KEY` → Deploy.

Live URL: https://phaneen-genai-capstone.streamlit.app — open it once before review, because free Streamlit apps sleep when idle.

Docker. `docker build -t docqa .` then `docker run -p 8501:8501 --env-file .env docqa`.

Configuration is entirely through environment variables (`.env`): LLM provider and model, embedding backend, chunk size and overlap, top-k, relevance threshold, file-size limit, storage folder. Secrets never enter the repository (.gitignore).

11. Limitations and future work

Limitation	Future improvement
Scanned (image) PDFs have no text layer	Add OCR (Tesseract or a vision model)
Table questions are look-ups, not calculations	Add a pandas/SQL tool agent for totals and averages
Pattern-based injection guardrail	Add a classifier model and output moderation
Literal number check can reject valid unit conversions	Normalise units before comparison
Single shared document space, no login	Per-user collections and role-based access filters in the vector query
Streamlit Cloud storage resets on restart	Managed vector DB (Chroma server, pgvector) and object storage

Limitation	Future improvement
Offline mode extracts rather than writes	Use Claude or a local open-weights model for generation

12. Challenges faced during development

Challenge	What happened	How it was solved
Python version on macOS	macOS ships Python 3.9; ChromaDB, Streamlit and LangGraph need 3.10+	Documented Python 3.11 setup (venv or conda); validate.sh checks the version first
macOS folder permissions	Terminal could not read the project inside Downloads ('Operation not permitted')	Moved the project to the home folder; added to troubleshooting
Unscoped Anthropic API key	Claude returned 400: key not scoped to a workspace	Created a workspace-scoped key; added optional ANTHROPIC_WORKSPACE_ID setting
Forced tool calls not supported	Planner request rejected: tool_choice type 'tool' unsupported for the model	Switched to tool_choice auto with a strict system prompt; planner falls back to a default plan on any error
Leaked key in a screenshot	An API key appeared in a shared screenshot	Key revoked and replaced; .env git-ignored; Streamlit Secrets used for deployment
PDF text extraction	PDF lines broke mid-sentence and headings merged into the next sentence	Heading-aware line joining in ingestion.py
Relevance threshold	Same cut-off behaved differently for semantic vs offline embeddings	Per-backend default (0.30 / 0.12), overridable in .env; set to 0.2 for the live app
Model download blocked	Embedding model download failed behind a proxy	Automatic fallback to offline embeddings with a logged warning
Hidden instructions in files	A test document contained 'AI assistant: ignore previous instructions...'	Context sanitizer strips such lines before the LLM sees them; covered by a test
Evaluator experience	Bad uploads were impossible to test because the uploader filtered file types	Uploader accepts any file; our code rejects unsupported ones with clear messages; 9 edge-case files included

13. Conclusion

The project delivers a complete Generative AI and Agentic AI workflow: multi-format ingestion, semantic retrieval from a vector database, grounded generation with citations, and four cooperating agents that plan, retrieve, reason and validate. Its main strength is reliability — the system shows where every fact came from, corrects itself once when a draft fails checks, and declines rather than guesses. It is built with LangGraph, tested end to end including bad-file and bad-key scenarios, works on a smartphone, and is documented for a new developer.