

# C++ Programming

## While Loops

**Mostafa S. Ibrahim**

*Teaching, Training and Coaching since more than a decade!*

*Artificial Intelligence & Computer Vision Researcher*

*PhD from Simon Fraser University - Canada*

*Bachelor / Msc from Cairo University - Egypt*

*Ex-(Software Engineer / ICPC World Finalist)*



# Loop



- Loop means circular.
- In our context, it is a way to command the computer to
  - **REPEAT** the same operations till we ask to **STOP**

# Recall if condition

```
1 #include<iostream>
2 using namespace std;
3
4 int main() {
5
6     if (3 < 5)
7     {
8         cout<<"3 < 5. ONE time\n";
9     }
10 }
```

- This if statement is applied once
- What if we want it repeat forever?

# Repeat forEVER

```
1 #include<iostream>
2 using namespace std;
3
4 int main() {
5
6     while (2 < 6)
7     {
8         cout<<"2 < 5. Forever\n";
9     }
10
11     return 0;
12 }
13
```

Consol   Problem   Tasks   Proper

ztemp [C/C++ Application] /home/moustafa/work:

```
2 < 5. Forever
2 < 5. Forever
2 < 5. Forever
2 < 5. Forever
```

- While is same logic, but code goes as following
  - Line 6
  - Line 8
  - Line 6
  - Line 8
  - Line 6
  - Line 8
  - For ever
- Notice the red button in eclipse
  - It means the program is still running!
  - We have to click it to force stop!
- What if wanna it STOP at some time?
  - Change while (condition)

# Let's print first 5 numbers

```
3
4 int main() {
5     int x = 1;
6
7     while (x <= 5)
8     {
9         cout << x << " ";
10        x = x + 1;
11    }
12
13    return 0;
14 }
15
```

Console Problems Tasks

<terminated> ztemp [C/C++ Application] /t

1 2 3 4 5 |

- Body from lines 7 to 11 repeats as LONG as condition is true ( $x \leq 5$ )
- Let's trace it
- 3 important parts
  - Line 5 = Initialization
  - Line 7 = Condition
  - Line 10 = increment step

# Let's sum $1 + 2 + 3 + 4 + 5$

```
4 int main() {  
5     int x = 1;  
6     int sum = 0;  
7  
8     while (x < 6)  
9     {  
10         sum += x;  
11         ++x;  
12     }  
13     cout<<sum;  
14  
15     return 0;  
16 }  
17
```

- We can now make any complex logic that requires repetition!
- Let's trace the code

Problems Console T

<terminated> ztemp [C/C++ Appli

15|

# Let's sum $5 + 4 + 3 + 2 + 1$

- We can do the reverse: go from high to low

```
1
2
3
4 int main() {
5     int x = 5;
6     int sum = 0;
7
8     while (x >= 0)
9     {
10         sum += x;
11         x--;
12     }
13     cout<<sum;
14
15     return 0;
16 }
17
```

Problems Console Tasks

<terminated> ztemp [C/C++ Application  
15|

# Using break

```
4 int main() {  
5     int x, y;  
6  
7     while (true) {  
8         cin >> x >> y;  
9  
10        if (y == 0)  
11        {  
12            cout<<"Y is zero!!\n";  
13            break;  
14        }  
15        cout << x / y << "\n";  
16    }  
17    cout<<"Bye\n";  
18  
19    return 0;  
20 }  
21
```

- Write a program that KEEPs reading 2 integers and print their division
- If the 2nd number is zero
  - Print Bye
  - End the program
- We can use word break to stop the while and go AFTER it

Problems Console Tasks Properties

<terminated> ztemp [C/C++ Application] /home/

```
8 2  
4  
20 10  
2  
20 5  
4  
20 0  
Y is zero!!  
Bye  
|
```



# Using continue

```
4 int main() {  
5     int x, y;  
6  
7     while (true) {  
8         cin >> x >> y;  
9  
10        if (y == 0)  
11        {  
12            cout<<"Y is zero. Try other 2 numbers\n";  
13            continue;  
14        }  
15        cout << x / y << "\n";  
16    }  
17    cout<<"Bye\n"; // never reached  
18  
19    return 0;  
20 }  
21
```

- Continue tells computer to JUMP to the while start again and continue from there
  - So statements after it INSIDE the while body is skipped

ztemp [C/C++ Application] /home/moustafa/workspaces/eclipse\_cpp/

```
8 2  
4  
20 10  
2  
20 5  
4  
20 0  
Y is zero. Try other 2 numbers  
6 2  
3  
|
```

*“Acquire knowledge and impart it to the people.”*

*“Seek knowledge from the Cradle to the Grave.”*