# Bison Introduction

Compiler Design WS 17/18

### Lab Assignment 2

• Implement RTSL Parser

#### Lab Assignment 2

- Implement RTSL Parser
- Output: List of syntactic elements, like CLASS, FUNCTION\_DEF, DECLARATION, etc.
- Detect syntactic errors and some semantic errors

#### Lab Assignment 2

- Implement RTSL Parser
- Output: List of syntactic elements, like CLASS, FUNCTION\_DEF, DECLARATION, etc.
- Detect syntactic errors and some semantic errors

testN.rtsl : Input file

testN.out : Expected stdout

testN.err : Expected stderr

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

```
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
 f = foo(i);
  rt_SampleColor = color(f);
```

class Test1 : rt\_Material;

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
 i = 0;
 f = foo(i);
  rt_SampleColor = color(f);
```

## CLASS Test1 of type material RETURN\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

## CLASS Test1 of type material RETURN\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
   return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
 i = 0;
 f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
   return 1.0;
void shade() {
  int i;
  float f;
 i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
 i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
 i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
  float f;
  i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int DECLARATION f of type float

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
 float f;
 f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int DECLARATION f of type float EXPRESSION\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
 float f;
 i = 0;
  f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int DECLARATION f of type float EXPRESSION\_STATEMENT EXPRESSION\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
 float f;
 i = 0;
 f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int DECLARATION f of type float EXPRESSION\_STATEMENT EXPRESSION\_STATEMENT EXPRESSION\_STATEMENT

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
 int i;
 float f;
  f = foo(i)
  rt_SampleColor = color(f);
```

```
CLASS Test1 of type material RETURN_STATEMENT RETURN_STATEMENT IF_ELSE_STATEMENT FUNCTION_DEF foo DECLARATION i of type int DECLARATION f of type float EXPRESSION_STATEMENT EXPRESSION_STATEMENT EXPRESSION_STATEMENT FUNCTION_DEF shade
```

```
class Test1 : rt_Material;
float foo(int i) {
  if(i<0)
    return 0.0;
  else
    return 1.0;
void shade() {
  int i;
 float f;
 i = 0;
 f = foo(i);
  rt_SampleColor = color(f);
```

CLASS Test1 of type material RETURN\_STATEMENT RETURN\_STATEMENT IF\_ELSE\_STATEMENT FUNCTION\_DEF foo DECLARATION i of type int DECLARATION f of type float EXPRESSION\_STATEMENT EXPRESSION\_STATEMENT EXPRESSION\_STATEMENT FUNCTION DEF shade

```
%token IF
%token ELSE
%%
if_statement:
  IF '(' expression ')' statement
 | IF '(' expression ')' statement ELSE statement
expression: /* ... */;
statement: /* ... */;
%%
/* ··· */
```

```
%token IF
%token ELSE
%%
if_statement:
   IF '(' expression ')' statement
     { printf("IF_STATEMENT\n"); }
 | IF '(' expression ')' statement ELSE statement
     { printf("IF_ELSE_STATEMENT"); }
expression: /* ... */;
statement: /* ... */;
/* ··· */
```

```
%token IDENTIFIER TYPE
%%
var_declaration:
   type_specifier IDENTIFIER ';'
type_specifier:
   TYPE
 | /* ... */
%%
/* ··· */
```

```
%token IDENTIFIER TYPE
%%
var_declaration:
   type_specifier IDENTIFIER ';'
     { printf("DECLARATION %s of type %s\n", "???", "???"); }
type_specifier:
   TYPE
/* ... */
/* ··· */
```

```
%token<str> IDENTIFIER TYPE
             yylval.str = ... in the lexer
var_declaration:
   type_specifier IDENTIFIER ';'
     { printf("DECLARATION %s of type %s\n", $2, "???"); }
type_specifier:
   TYPE
 /* ... */
/* ··· */
```

#### %token<str> IDENTIFIER TYPE

```
%%
var_declaration:
   type_specifier IDENTIFIER ';'
     { printf("DECLARATION %s of type %s\n", $2, "???"); }
type_specifier:
   TYPE
 /* ... */
```

```
%token<str> IDENTIFIER TYPE
%type<str> type_specifier
%%
var_declaration:
   type_specifier IDENTIFIER ';'
     { printf("DECLARATION %s of type %s\n", $2, $1); }
type_specifier:
   TYPE { $$ = $1; }
/* ... */
/* ··· */
```