Phishing payload hit 4.2 million The breach exposed 4.2 million customer records and cost the firm **$312 million** in remediation within 48 hours. How did a single email outwit a **$5 billion** security stack?

** NOGLYPH WEEK IN REVIEW — MAJOR BREACHES**

Last week, **FinBank** fell victim to a credential-theft campaign that leveraged the newly disclosed **CVE-2026-0801** in the serverless runtime used for its transaction micro-services. Attackers sent a spear-phishing email that spoofed an internal HR portal, achieving a **68 %** click-through rate among targeted employees. Within minutes, a compromised Lambda function harvested API keys, pivoted to the **S3** data lake, and exfiltrated **4.2 million** records. The human element, not the code, was the

⚠ TECHNICAL RADIANCE

[SYSTEM ANALYSIS] - **Lambda** functions ran with **full-access IAM** roles – a classic privilege-escalation misconfiguration. - The exploit chain used **CVE-2026-0801** to bypass the runtime sandbox, allowing arbitrary code execution.

[THE EXPLOIT] - Phishing email → compromised credentials → stolen **AWS_ACCESS_KEY_ID** → Lambda injection → data dump. - Attackers leveraged an OAuth token refresh flow that **MFA** could not stop because the token was already minted.

[RECOMMENDED REMEDIATION] - Enforce **least-privilege IAM** policies for every serverless component. - Rotate all **API keys** immediately and enable **conditional access** based on device posture. - Deploy a **behavior-based SOAR**