EXCEL MASTER INDEX

Basic to Advanced | English & Roman Hindi

EXCEL CONDITIONAL & STATISTICAL FORMULAS

SUMIF/SUMIFS, COUNTIF/COUNTIFS, SUMPRODUCT, LARGE/SMALL, STDEV, CORREL, FORECAST | Bilingual Guide

---

Created & Developed by

UTKARSH BAJPAI

utkarshbajpai068@gmail.com

Premium Bilingual Resource | For Students, MIS Executives, Data Analysts & Office Professionals

TABLE OF CONTENTS

1. SUMIF
2. SUMIFS
3. COUNTIF
4. COUNTIFS
5. AVERAGEIF
6. AVERAGEIFS
7. MAXIFS
8. MINIFS
9. SUMPRODUCT
10. SUBTOTAL
11. AGGREGATE
12. MEDIAN
13. LARGE
14. SMALL
15. RANK.EQ
16. RANK.AVG
17. STDEV.S
18. STDEV.P
19. VAR.S
20. VAR.P
21. CORREL
22. FORECAST.LINEAR

UTKARSH BAJPAI

CHAPTER 1: SUMIF

PURPOSE - ENGLISH

Adds numbers based on a single condition.

PURPOSE - ROMAN HINDI

Ek condition ke mutabik numbers add karta hai.

SYNTAX

```
=SUMIF(range, criteria, [sum_range])
```

SYNTAX EXPLANATION

SUMIF sums values matching one condition.

Roman Hindi: SUMIF ek condition ke mutabik sum nikaata hai.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=SUMIF(A2:A4, "North", C2:C4)
```

EXPECTED OUTPUT

150

STEP-BY-STEP - ENGLISH

- Add range, criteria and sum range.
- Use =SUMIF(A2:A4, "North", C2:C4).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range, criteria aur sum range dein.
- =SUMIF(A2:A4, "North", C2:C4) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used to total sales by region.

Roman Hindi: Sales ko region ke mutabik total karne ke liye use hota hai.

COMMON MISTAKES

- Forgetting sum_range.

UTKARSH BAJPAI

IMPORTANT TIPS

- Use SUMIFS for multiple conditions.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 2: SUMIFS

PURPOSE - ENGLISH

Adds numbers based on multiple conditions.

PURPOSE - ROMAN HINDI

Multiple conditions ke mutabik numbers add karta hai.

SYNTAX

```
=SUMIFS(sum_range, criteria_range1, criteria1, [criteria_range2, criteria2], ...)
```

SYNTAX EXPLANATION

SUMIFS sums with multiple criteria.

Roman Hindi: SUMIFS multiple criteria ke mutabik sum karta hai.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=SUMIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi")
```

EXPECTED OUTPUT

150

STEP-BY-STEP - ENGLISH

- Add sum range and pairs of criteria.
- Use =SUMIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Sum range aur criteria pairs dein.
- =SUMIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi") likhna.
- Enter dabao.

UTKARSH BAJPAI

REAL OFFICE EXAMPLE

Used for complex sales reports.

Roman Hindi: Complex sales reports ke liye use hota hai.

COMMON MISTAKES

- Criteria ranges must match.

IMPORTANT TIPS

- More powerful than SUMIF.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 3: COUNTIF

PURPOSE - ENGLISH

Counts cells that meet one condition.

PURPOSE - ROMAN HINDI

Ek condition ke mutabik cells ki ginti karta hai.

SYNTAX

```
=COUNTIF(range, criteria)
```

SYNTAX EXPLANATION

COUNTIF counts matching cells.

Roman Hindi: COUNTIF matching cells count karta hai.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=COUNTIF(A2:A4, "North")
```

EXPECTED OUTPUT

2

STEP-BY-STEP - ENGLISH

- Add range and criteria.

UTKARSH BAJPAI

- Use =COUNTIF(A2:A4, "North").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range aur criteria dein.
- =COUNTIF(A2:A4, "North") likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for counting targets achieved.

Roman Hindi: Targets achieve ki ginti karne ke liye use hota hai.

COMMON MISTAKES

- Criteria text needs quotes.

IMPORTANT TIPS

- Use COUNTIFS for multiple conditions.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 4: COUNTIFS

PURPOSE - ENGLISH

Counts cells that meet multiple conditions.

PURPOSE - ROMAN HINDI

Multiple conditions ke mutabik cells ki ginti karta hai.

SYNTAX

```
=COUNTIFS(criteria_range1, criteria1, [criteria_range2, criteria2], ...)
```

SYNTAX EXPLANATION

COUNTIFS counts with multiple criteria.

Roman Hindi: COUNTIFS multiple criteria ke mutabik count karta hai.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=COUNTIFS(A2:A4, "North", C2:C4, ">=100")
```

UTKARSH BAJPAI

EXPECTED OUTPUT

1

STEP-BY-STEP - ENGLISH

- Add criteria ranges and criteria.
- Use =COUNTIFS(A2:A4, "North", C2:C4, ">=100").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Criteria ranges aur criteria dein.
- =COUNTIFS(A2:A4, "North", C2:C4, ">=100") likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for quality checks.

Roman Hindi: Quality checks ke liye use hota hai.

COMMON MISTAKES

- At least one criteria needed.

IMPORTANT TIPS

- Great for filtering data.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 5: AVERAGEIF

PURPOSE - ENGLISH

Returns average of numbers meeting a condition.

PURPOSE - ROMAN HINDI

Condition ke mutabik numberon ki avg nikalta hai.

SYNTAX

```
=AVERAGEIF(range, criteria, [average_range])
```

SYNTAX EXPLANATION

AVERAGEIF averages matching numbers.

Roman Hindi: AVERAGEIF matching numbers ka avg nikaata hai.

SAMPLE DATASET

UTKARSH BAJPAI

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=AVERAGEIF(A2:A4, "North", C2:C4)
```

EXPECTED OUTPUT

75

STEP-BY-STEP - ENGLISH

- Add range, criteria and average range.
- Use =AVERAGEIF(A2:A4, "North", C2:C4).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range, criteria aur average range dein.
- =AVERAGEIF(A2:A4, "North", C2:C4) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for regional performance averages.

Roman Hindi: Regional performance ke averages ke liye use hota hai.

COMMON MISTAKES

- Division by zero if no match.

IMPORTANT TIPS

- Use AVERAGEIFS for multiple conditions.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 6: AVERAGEIFS

PURPOSE - ENGLISH

Returns average with multiple conditions.

PURPOSE - ROMAN HINDI

Multiple conditions ke mutabik avg nikalta hai.

SYNTAX

```
=AVERAGEIFS(average_range, criteria_range1, criteria1, ...)
```

UTKARSH BAJPAI

SYNTAX EXPLANATION

AVERAGEIFS averages with criteria.

Roman Hindi: AVERAGEIFS criteria ke mutabik avg karta hai.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=AVERAGEIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi")
```

EXPECTED OUTPUT

75

STEP-BY-STEP - ENGLISH

- Add average range and criteria pairs.
- Use =AVERAGEIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Average range aur criteria pairs dein.
- =AVERAGEIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi") likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for filtered averages.

Roman Hindi: Filtered averages ke liye use hota hai.

COMMON MISTAKES

- Criteria count must match.

IMPORTANT TIPS

- More flexible than AVERAGEIF.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 7: MAXIFS

PURPOSE - ENGLISH

Returns the maximum value that meets conditions.

UTKARSH BAJPAI

PURPOSE - ROMAN HINDI

Conditions ke mutabik maximum value nikalta hai.

SYNTAX

```
=MAXIFS(max_range, criteria_range1, criteria1, [criteria_range2, criteria2], ...)
```

SYNTAX EXPLANATION

MAXIFS finds max among rows meeting criteria.

Roman Hindi: MAXIFS un rows me se maximum nikalta hai jo criteria meet karte hain.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=MAXIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi")
```

EXPECTED OUTPUT

100

STEP-BY-STEP - ENGLISH

- Add max range and criteria pairs.
- Use =MAXIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Max range aur criteria pairs dein.
- =MAXIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi") likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for top sales region.

Roman Hindi: Sabse badi sales wali region ke liye use hota hai.

COMMON MISTAKES

- Criteria ranges must match.

IMPORTANT TIPS

- Great for top value checks.

EXCEL VERSION COMPATIBILITY

Excel 2019 / Microsoft 365

UTKARSH BAJPAI

CHAPTER 8: MINIFS

PURPOSE - ENGLISH

Returns the minimum value that meets conditions.

PURPOSE - ROMAN HINDI

Conditions ke mutabik minimum value nikalta hai.

SYNTAX

```
=MINIFS(min_range, criteria_range1, criteria1, [criteria_range2, criteria2], ...)
```

SYNTAX EXPLANATION

MINIFS finds min among rows meeting criteria.

Roman Hindi: MINIFS un rows me se minimum nikalta hai jo criteria meet karte hain.

SAMPLE DATASET

Cells: A1:C4 | Values: City,Rep,Sales
North,Delhi,100
South,Mumbai,150
North,Delhi,50

ACTUAL FORMULA

```
=MINIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi")
```

EXPECTED OUTPUT

50

STEP-BY-STEP - ENGLISH

- Add min range and criteria pairs.
- Use =MINIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi").
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Min range aur criteria pairs dein.
- =MINIFS(C2:C4, A2:A4, "North", B2:B4, "Delhi") likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for lowest cost analysis.

Roman Hindi: Sabse kam cost analysis ke liye use hota hai.

COMMON MISTAKES

- Criteria ranges must match.

UTKARSH BAJPAI

IMPORTANT TIPS

- Good for minimum checks.

EXCEL VERSION COMPATIBILITY

Excel 2019 / Microsoft 365

CHAPTER 9: SUMPRODUCT

PURPOSE - ENGLISH

Returns the sum of products of arrays.

PURPOSE - ROMAN HINDI

Arrays ka product ka sum nikalta hai.

SYNTAX

```
=SUMPRODUCT(array1, [array2], ...)
```

SYNTAX EXPLANATION

SUMPRODUCT multiplies arrays and sums.

Roman Hindi: SUMPRODUCT arrays ko multiply karta hai aur sum karta hai.

SAMPLE DATASET

Cells: A1:B2 | Values: 2,3
4,5

ACTUAL FORMULA

```
=SUMPRODUCT(A1:B2, A1:B2)
```

EXPECTED OUTPUT

54

STEP-BY-STEP - ENGLISH

- Add the arrays.
- Use =SUMPRODUCT(A1:B2, A1:B2).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Arrays dein.
- =SUMPRODUCT(A1:B2, A1:B2) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

UTKARSH BAJPAI

Used for weighted totals.

Roman Hindi: Weighted totals ke liye use hota hai.

COMMON MISTAKES

- Array sizes must match.

IMPORTANT TIPS

- Great for quantity x rate totals.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 10: SUBTOTAL

PURPOSE - ENGLISH

Returns a subtotal for a list using function codes.

PURPOSE - ROMAN HINDI

Function codes ke through list ka subtotal deta hai.

SYNTAX

```
=SUBTOTAL(function_num, ref1, [ref2], ...)
```

SYNTAX EXPLANATION

SUBTOTAL supports 9 functions via codes.

Roman Hindi: SUBTOTAL 9 functions ko codes se support karta hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=SUBTOTAL(9, A1:A5)
```

EXPECTED OUTPUT

75

STEP-BY-STEP - ENGLISH

- Add function code and ranges.
- Use =SUBTOTAL(9, A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Function code aur ranges dein.

UTKARSH BAJPAI

- =SUBTOTAL(9, A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for lists with hidden rows.

Roman Hindi: Hidden rows wale lists ke liye use hota hai.

COMMON MISTAKES

- Wrong function code.

IMPORTANT TIPS

- Code 9 is SUM.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 11: AGGREGATE

PURPOSE - ENGLISH

Returns an aggregate with options like ignore errors.

PURPOSE - ROMAN HINDI

Options jaise ignore errors ke saath aggregate deta hai.

SYNTAX

```
=AGGREGATE(function_num, options, array, [k])
```

SYNTAX EXPLANATION

AGGREGATE is SUBTOTAL with options.

Roman Hindi: AGGREGATE SUBTOTAL ke options ke saath hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5
10
15
20
25

ACTUAL FORMULA

```
=AGGREGATE(9, 6, A1:A5)
```

EXPECTED OUTPUT

75

UTKARSH BAJPAI

STEP-BY-STEP - ENGLISH

- Add function code, options and array.
- Use =AGGREGATE(9, 6, A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Function code, options aur array dein.
- =AGGREGATE(9, 6, A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for robust reports.

Roman Hindi: Robust reports ke liye use hota hai.

COMMON MISTAKES

- Options code must be right.

IMPORTANT TIPS

- 6 ignores errors.

EXCEL VERSION COMPATIBILITY

Excel 2010+

CHAPTER 12: MEDIAN

PURPOSE - ENGLISH

Returns the middle value of a dataset.

PURPOSE - ROMAN HINDI

Dataset ka middle value nikalta hai.

SYNTAX

```
=MEDIAN(number1, [number2], ...)
```

SYNTAX EXPLANATION

MEDIAN finds the middle value.

Roman Hindi: MEDIAN dataset ka middle value dhundta hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=MEDIAN(A1:A5)
```

UTKARSH BAJPAI

EXPECTED OUTPUT

15

STEP-BY-STEP - ENGLISH

- Select the range.
- Type =MEDIAN(A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range select karo.
- =MEDIAN(A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for salary or price analysis.

Roman Hindi: Salary ya price analysis ke liye use hota hai.

COMMON MISTAKES

- Odd count needed for single middle.

IMPORTANT TIPS

- Good for income or price checks.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 13: LARGE

PURPOSE - ENGLISH

Returns the largest values from a list.

PURPOSE - ROMAN HINDI

List se sabse bade values nikalta hai.

SYNTAX

```
=LARGE(array, k)
```

SYNTAX EXPLANATION

LARGE returns the k-th largest value.

Roman Hindi: LARGE list ka k-ta sabse bada value deta hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

UTKARSH BAJPAI

ACTUAL FORMULA

```
=LARGE(A1:A5, 2)
```

EXPECTED OUTPUT

20

STEP-BY-STEP - ENGLISH

- Add range and k.
- Type =LARGE(A1:A5, 2).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range aur k dein.
- =LARGE(A1:A5, 2) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for second highest sale.

Roman Hindi: Dusre sabse bade sale ke liye use hota hai.

COMMON MISTAKES

- k must be >= 1.

IMPORTANT TIPS

- Combine with SMALL for both ends.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 14: SMALL

PURPOSE - ENGLISH

Returns the smallest values from a list.

PURPOSE - ROMAN HINDI

List se sabse chote values nikalta hai.

SYNTAX

```
=SMALL(array, k)
```

SYNTAX EXPLANATION

SMALL returns the k-th smallest value.

UTKARSH BAJPAI

Roman Hindi: SMALL list ka k-ta sabse chota value deta hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=SMALL(A1:A5, 1)
```

EXPECTED OUTPUT

5

STEP-BY-STEP - ENGLISH

- Add range and k.
- Type =SMALL(A1:A5, 1).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range aur k dein.
- =SMALL(A1:A5, 1) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for lowest cost items.

Roman Hindi: Sabse kam cost wale items ke liye use hota hai.

COMMON MISTAKES

- k must be >= 1.

IMPORTANT TIPS

- Good for minimum analysis.

EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI

CHAPTER 15: RANK.EQ

PURPOSE - ENGLISH

Ranks values with competition ranking.

PURPOSE - ROMAN HINDI

Values ko rank me sorted karta hai.

SYNTAX

```
=RANK.EQ(number, ref, [order])
```

SYNTAX EXPLANATION

RANK.EQ gives rank.

Roman Hindi: RANK.EQ value ko rank deta hai.

SAMPLE DATASET

Cells: A1:A6 | Values: 5
10
10
20
25
10

ACTUAL FORMULA

```
=RANK.EQ(A6, A1:A5, 0)
```

EXPECTED OUTPUT

3

STEP-BY-STEP - ENGLISH

- Add number, range and order.
- Use =RANK.EQ(A6, A1:A5, 0).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Number, range aur order dein.
- =RANK.EQ(A6, A1:A5, 0) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for performance ranking.

Roman Hindi: Performance ranking ke liye use hota hai.

COMMON MISTAKES

- Ties handling.

IMPORTANT TIPS

- Use RANK.AVG to average ties.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 16: RANK.AVG

PURPOSE - ENGLISH

UTKARSH BAJPAI

Ranks values averaging ties.

PURPOSE - ROMAN HINDI

Ties ko average karke rank deta hai.

SYNTAX

```
=RANK.AVG(number, ref, [order])
```

SYNTAX EXPLANATION

RANK.AVG averages tied ranks.

Roman Hindi: RANK.AVG tied ranks ko average karta hai.

SAMPLE DATASET

Cells: A1:A6 | Values: 5
10
10
20
25
10

ACTUAL FORMULA

```
=RANK.AVG(A6, A1:A5, 0)
```

EXPECTED OUTPUT

3.5

STEP-BY-STEP - ENGLISH

- Add number and range.
- Use =RANK.AVG(A6, A1:A5, 0).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Number aur range dein.
- =RANK.AVG(A6, A1:A5, 0) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for fair ranking.

Roman Hindi: Niyayik ranking ke liye use hota hai.

COMMON MISTAKES

- Same as RANK.EQ mostly.

IMPORTANT TIPS

- Use for dense ranking.

UTKARSH BAJPAI

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 17: STDEV.S

PURPOSE - ENGLISH

Returns standard deviation for a sample.

PURPOSE - ROMAN HINDI

Sample ke liye standard deviation nikalta hai.

SYNTAX

```
=STDEV.S(number1, [number2], ...)
```

SYNTAX EXPLANATION

STDEV.S calculates sample standard deviation.

Roman Hindi: STDEV.S sample standard deviation nikaata hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=STDEV.S(A1:A5)
```

EXPECTED OUTPUT

7.91

STEP-BY-STEP - ENGLISH

- Select the range.
- Type =STDEV.S(A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range select karo.
- =STDEV.S(A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for data consistency checks.

Roman Hindi: Data consistency check ke liye use hota hai.

UTKARSH BAJPAI

COMMON MISTAKES

- Sample vs population.

IMPORTANT TIPS

- STDEV.P for whole data.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 18: STDEV.P

PURPOSE - ENGLISH

Returns standard deviation for a population.

PURPOSE - ROMAN HINDI

Population ke liye standard deviation nikalta hai.

SYNTAX

```
=STDEV.P(number1, [number2], ...)
```

SYNTAX EXPLANATION

STDEV.P calculates population standard deviation.

Roman Hindi: STDEV.P population standard deviation nikaata hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=STDEV.P(A1:A5)
```

EXPECTED OUTPUT

7.07

STEP-BY-STEP - ENGLISH

- Select the range.
- Type =STDEV.P(A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range select karo.
- =STDEV.P(A1:A5) likhna.
- Enter dabao.

UTKARSH BAJPAI

REAL OFFICE EXAMPLE

Used for company wide analysis.

Roman Hindi: Company wide analysis ke liye use hota hai.

COMMON MISTAKES

- Sample vs population.

IMPORTANT TIPS

- STDEV.S for samples.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 19: VAR.S

PURPOSE - ENGLISH

Returns variance for a sample.

PURPOSE - ROMAN HINDI

Sample ke liye variance nikalta hai.

SYNTAX

```
=VAR.S(number1, [number2], ...)
```

SYNTAX EXPLANATION

VAR.S calculates sample variance.

Roman Hindi: VAR.S sample variance nikaata hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=VAR.S(A1:A5)
```

EXPECTED OUTPUT

62.5

STEP-BY-STEP - ENGLISH

- Select the range.
- Type =VAR.S(A1:A5).
- Press Enter.

UTKARSH BAJPAI

STEP-BY-STEP - ROMAN HINDI

- Range select karo.
- =VAR.S(A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for risk analysis.

Roman Hindi: Risk analysis ke liye use hota hai.

COMMON MISTAKES

- Sample vs population.

IMPORTANT TIPS

- Use VAR.P for population.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 20: VAR.P

PURPOSE - ENGLISH

Returns variance for a population.

PURPOSE - ROMAN HINDI

Population ke liye variance nikalta hai.

SYNTAX

```
=VAR.P(number1, [number2], ...)
```

SYNTAX EXPLANATION

VAR.P calculates population variance.

Roman Hindi: VAR.P population variance nikaata hai.

SAMPLE DATASET

Cells: A1:A5 | Values: 5, 10, 15, 20, 25

ACTUAL FORMULA

```
=VAR.P(A1:A5)
```

EXPECTED OUTPUT

50

UTKARSH BAJPAI

STEP-BY-STEP - ENGLISH

- Select the range.
- Type =VAR.P(A1:A5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Range select karo.
- =VAR.P(A1:A5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for company wide variance.

Roman Hindi: Company wide variance ke liye use hota hai.

COMMON MISTAKES

- Sample vs population.

IMPORTANT TIPS

- Use VAR.S for samples.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 21: CORREL

PURPOSE - ENGLISH

Returns correlation between two ranges.

PURPOSE - ROMAN HINDI

Do ranges ke beech correlation nikalta hai.

SYNTAX

```
=CORREL(array1, array2)
```

SYNTAX EXPLANATION

CORREL measures relationship.

Roman Hindi: CORREL relationship ko measure karta hai.

SAMPLE DATASET

Cells: A1:B5 | Values: 5,20
10,40
15,60
20,80
25,100

UTKARSH BAJPAI

ACTUAL FORMULA

```
=CORREL(A1:A5, B1:B5)
```

EXPECTED OUTPUT

1

STEP-BY-STEP - ENGLISH

- Add two ranges.
- Use =CORREL(A1:A5, B1:B5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- Do ranges dein.
- =CORREL(A1:A5, B1:B5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for sales and region analysis.

Roman Hindi: Sales aur region analysis ke liye use hota hai.

COMMON MISTAKES

- Ranges must be same size.

IMPORTANT TIPS

- Value 1 means perfect positive.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 22: FORECAST.LINEAR

PURPOSE - ENGLISH

Returns linear forecast.

PURPOSE - ROMAN HINDI

Linear forecast nikalta hai.

SYNTAX

```
=FORECAST.LINEAR(x, known_y, known_x)
```

SYNTAX EXPLANATION

FORECAST.LINEAR predicts a value.

UTKARSH BAJPAI

Roman Hindi: FORECAST.LINEAR ek value predict karta hai.

SAMPLE DATASET

Cells: A1:B5 | Values: 10,1
20,2
30,3
40,4
50,5

ACTUAL FORMULA

```
=FORECAST.LINEAR(6, A1:A5, B1:B5)
```

EXPECTED OUTPUT

60

STEP-BY-STEP - ENGLISH

- Add x, known y and known x.
- Use =FORECAST.LINEAR(6, A1:A5, B1:B5).
- Press Enter.

STEP-BY-STEP - ROMAN HINDI

- X, known Y aur known X dein.
- =FORECAST.LINEAR(6, A1:A5, B1:B5) likhna.
- Enter dabao.

REAL OFFICE EXAMPLE

Used for sales trend prediction.

Roman Hindi: Sales trend prediction ke liye use hota hai.

COMMON MISTAKES

- Known ranges same size.

IMPORTANT TIPS

- Better with multiple known points.

EXCEL VERSION COMPATIBILITY

Excel 2016 / Microsoft 365

UTKARSH BAJPAI