EXCEL MASTER INDEX

Basic to Advanced | English & Roman Hindi

COMPLETE MIS EXECUTIVE FORMULA HANDBOOK

Practical Office Calculations, MIS Reports, Dashboards & Payroll | Bilingual Guide

Created & Developed by

UTKARSH BAJPAI

utkarshbajpai068@gmail.com

Premium Bilingual Resource | For Students, MIS Executives, Data Analysts & Office Professionals

TABLE OF CONTENTS

1. GROSS SALES
2. NET SALES
3. TOTAL ORDERS
4. DELIVERED ORDERS
5. PENDING ORDERS
6. DELIVERY PERCENTAGE
7. TARGET ACHIEVEMENT
8. EMPLOYEE PERFORMANCE
9. HIGHEST PERFORMER
10. LOWEST PERFORMER
11. ATTENDANCE PERCENTAGE
12. WORKING HOURS
13. OVERTIME
14. SALARY CALCULATION
15. INCENTIVES
16. DUPLICATE IDENTIFICATION
17. MISSING DATA IDENTIFICATION
18. DATA CLEANING
19. MONTHLY SALES REPORT
20. DAILY MIS REPORT
21. MASTER SHEET CREATION
22. MULTIPLE SHEET COMPILATION
23. DYNAMIC DASHBOARD KPI

UTKARSH BAJPAI

CHAPTER 1: GROSS SALES

PURPOSE - ENGLISH

Gross sales = quantity multiplied by rate, before discount.

PURPOSE - ROMAN HINDI

Gross sales = quantity ko rate se multiply karke nikalte hain (discount se pehle).

SYNTAX

```
=Qty*Rate
```

SYNTAX EXPLANATION

Two columns are multiplied cell by cell.

Roman Hindi: Do columns ko cell by cell multiply karte hain.

SAMPLE DATASET

B2 = 10 (Qty), C2 = 500 (Rate)

ACTUAL FORMULA

```
=B2*C2
```

EXPECTED OUTPUT

5000

STEP-BY-STEP - ENGLISH

- Enter =B2*C2 in the Gross column.
- Copy the formula down the column.
- Wrap with SUM for the total.

STEP-BY-STEP - ROMAN HINDI

- Gross column me =B2*C2 likho.
- Formula ko neeche copy karo.
- Total ke liye SUM lagao.

REAL OFFICE EXAMPLE

Monthly sales register where each line item is priced.

Roman Hindi: Monthly sales register jahan har line item ki price hoti hai.

COMMON MISTAKES

- Multiplying the wrong columns.
- Rate stored as text.

IMPORTANT TIPS

UTKARSH BAJPAI

- Format the rate column as Number.
- Use a table so formulas extend automatically.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 2: NET SALES

PURPOSE - ENGLISH

Net sales = gross sales minus discount amount.

PURPOSE - ROMAN HINDI

Net sales = gross sales me se discount amount minus karke.

SYNTAX

```
=Gross-(Gross*Discount%)
```

SYNTAX EXPLANATION

Discount percentage is applied to gross, then subtracted.

Roman Hindi: Discount percentage gross par lagta hai, phir minus hota hai.

SAMPLE DATASET

B2 = 5000 (Gross), C2 = 10% (Discount)

ACTUAL FORMULA

```
=B2-(B2*C2)
```

EXPECTED OUTPUT

4500

STEP-BY-STEP - ENGLISH

- Store discount as a percentage.
- Subtract gross times discount from gross.
- Copy down and total.

STEP-BY-STEP - ROMAN HINDI

- Discount ko percentage me rakho.
- Gross minus (Gross x Discount) karo.
- Neeche copy karke total nikalo.

REAL OFFICE EXAMPLE

Invoices use net sales after trade discount for accounting.

UTKARSH BAJPAI

Roman Hindi: Invoices accounting ke liye trade discount ke baad net sales use karti hain.

COMMON MISTAKES

- Typing 10 instead of 10%.
- Subtracting a fixed amount from every row.

IMPORTANT TIPS

- Format the discount cell as Percentage.
- Use SUMIFS for period totals.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 3: TOTAL ORDERS

PURPOSE - ENGLISH

Counts every order ID recorded in the period.

PURPOSE - ROMAN HINDI

Period me record hue saare order IDs count karta hai.

SYNTAX

```
=COUNTA(OrderIDRange)
```

SYNTAX EXPLANATION

COUNTA counts cells that are not empty.

Roman Hindi: COUNTA khali nahi hone wale cells count karta hai.

SAMPLE DATASET

A2:A100 contains order IDs

ACTUAL FORMULA

```
=COUNTA(A2:A100)
```

EXPECTED OUTPUT

99

STEP-BY-STEP - ENGLISH

- Keep one order ID per row.
- Point COUNTA at the ID column.
- Avoid blank rows inside the range.

STEP-BY-STEP - ROMAN HINDI

UTKARSH BAJPAI

- Har row me ek order ID rakho.
- COUNTA ko ID column par lagao.
- Range ke beech khali rows na rakho.

REAL OFFICE EXAMPLE

Daily order MIS counts volume from the order ID column.

Roman Hindi: Daily order MIS order ID column se volume count karta hai.

COMMON MISTAKES

- Blank formatted rows are counted.
- Duplicated IDs inflate the count.

IMPORTANT TIPS

- Use a dynamic range or an Excel Table.
- Count duplicates separately with COUNTIF.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 4: DELIVERED ORDERS

PURPOSE - ENGLISH

Counts orders whose status is Delivered.

PURPOSE - ROMAN HINDI

Delivered status wale orders count karta hai.

SYNTAX

```
=COUNTIF(StatusRange,"Delivered")
```

SYNTAX EXPLANATION

COUNTIF counts exact text matches.

Roman Hindi: COUNTIF exact text match count karta hai.

SAMPLE DATASET

B2:B100 contains status values

ACTUAL FORMULA

```
=COUNTIF(B2:B100,"Delivered")
```

EXPECTED OUTPUT

45

UTKARSH BAJPAI

STEP-BY-STEP - ENGLISH

- Keep status spelling consistent.
- Use COUNTIF with the status text.
- Combine with a total for the percentage.

STEP-BY-STEP - ROMAN HINDI

- Status ki spelling same rakho.
- COUNTIF me status text do.
- Percentage ke liye total ke saath combine karo.

REAL OFFICE EXAMPLE

Logistics MIS tracks delivery completion each day.

Roman Hindi: Logistics MIS har din delivery completion track karta hai.

COMMON MISTAKES

- Trailing spaces break the match.
- Status captured in mixed case.

IMPORTANT TIPS

- Data-validate the status column.
- Normalise text with TRIM.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 5: PENDING ORDERS

PURPOSE - ENGLISH

Counts orders still marked Pending.

PURPOSE - ROMAN HINDI

Abhi bhi Pending wale orders count karta hai.

SYNTAX

```
=COUNTIF(StatusRange,"Pending")
```

SYNTAX EXPLANATION

Same pattern as delivered orders.

Roman Hindi: Delivered orders jaisa hi pattern hai.

SAMPLE DATASET

B2:B100 contains status values

UTKARSH BAJPAI

ACTUAL FORMULA

```
=COUNTIF(B2:B100,"Pending")
```

EXPECTED OUTPUT

5

STEP-BY-STEP - ENGLISH

- Apply the status filter first.
- Count the pending status with COUNTIF.
- Age the pending list with TODAY().

STEP-BY-STEP - ROMAN HINDI

- Pehle status filter lagao.
- Pending status ko COUNTIF se count karo.
- TODAY() se pending list ki age nikalo.

REAL OFFICE EXAMPLE

Operations review pending shipments in the morning huddle.

Roman Hindi: Operations subah ki meeting me pending shipments review karti hai.

COMMON MISTAKES

- Pending orders hidden by a stale filter.
- Status text typed with different case.

IMPORTANT TIPS

- Sort oldest pending first.
- Alert when pending exceeds a threshold.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 6: DELIVERY PERCENTAGE

PURPOSE - ENGLISH

Delivered orders as a percentage of total orders.

PURPOSE - ROMAN HINDI

Delivered orders, total orders ka kitna percent hain.

SYNTAX

```
=(Delivered/Total)*100
```

UTKARSH BAJPAI

SYNTAX EXPLANATION

Divide delivered by total, then express as a percentage.

Roman Hindi: Delivered ko total se divide karke percentage nikaalo.

SAMPLE DATASET

Delivered = 45, Total = 50

ACTUAL FORMULA

```
=(A2/B2)*100
```

EXPECTED OUTPUT

90%

STEP-BY-STEP - ENGLISH

- Calculate delivered and total counts first.
- Divide and format the result as a percentage.
- Wrap with IFERROR for blank days.

STEP-BY-STEP - ROMAN HINDI

- Pehle delivered aur total count karo.
- Divide karke percentage format do.
- Khali dinon ke liye IFERROR lagao.

REAL OFFICE EXAMPLE

MIS dashboard shows delivery SLA compliance.

Roman Hindi: MIS dashboard delivery SLA compliance dikhata hai.

COMMON MISTAKES

- Dividing by zero on days with no orders.
- Formatting as number instead of percentage.

IMPORTANT TIPS

- Use IFERROR(result,0) for safety.
- Round with ROUND for display.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 7: TARGET ACHIEVEMENT

PURPOSE - ENGLISH

Achieved amount as a percentage of the sales target.

UTKARSH BAJPAI

PURPOSE - ROMAN HINDI

Achieved amount, sales target ka kitna percent hai.

SYNTAX

```
=(Achieved/Target)*100
```

SYNTAX EXPLANATION

Divide achieved by the target and format as a percentage.

Roman Hindi: Achieved ko target se divide karke percentage format do.

SAMPLE DATASET

Achieved = 85,000, Target = 1,00,000

ACTUAL FORMULA

```
=(A2/B2)*100
```

EXPECTED OUTPUT

85%

STEP-BY-STEP - ENGLISH

- Keep achieved and target in comparable units.
- Divide and format as a percentage.
- Add conditional formatting thresholds.

STEP-BY-STEP - ROMAN HINDI

- Achieved aur target same unit me rakho.
- Divide karke percentage format do.
- Conditional formatting ke thresholds lagao.

REAL OFFICE EXAMPLE

Sales reviews compare each branch against its monthly target.

Roman Hindi: Sales review har branch ko uske monthly target se compare karta hai.

COMMON MISTAKES

- Target left blank causing a divide error.
- Mixing monthly and annual targets.

IMPORTANT TIPS

- Lock the target column with $ references.
- Show a red flag below 80% with conditional formatting.

EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI

CHAPTER 8: EMPLOYEE PERFORMANCE

PURPOSE - ENGLISH

Grades employees from a performance score using banded logic.

PURPOSE - ROMAN HINDI

Performance score se employee ka grade banded logic se nikalta hai.

SYNTAX

```
=IF(Score>=90,"Excellent",IF(Score>=75,"Good","Needs Improvement"))
```

SYNTAX EXPLANATION

Nested IF checks the highest band first.

Roman Hindi: Nested IF pehle sabse high band check karta hai.

SAMPLE DATASET

A2 = 82 (Score)

ACTUAL FORMULA

```
=IF(A2>=90,"Excellent",IF(A2>=75,"Good","Needs Improvement"))
```

EXPECTED OUTPUT

Good

STEP-BY-STEP - ENGLISH

- Decide the bands from highest to lowest.
- Write nested IFs in that order.
- Test the boundaries with sample values.

STEP-BY-STEP - ROMAN HINDI

- Bands sabse upar se neeche tak decide karo.
- Usi order me nested IF likho.
- Boundary values se test karo.

REAL OFFICE EXAMPLE

HR appraisal sheets convert scores into grades.

Roman Hindi: HR appraisal sheet scores ko grades me convert karti hai.

COMMON MISTAKES

- Bands written lowest first, so top band never triggers.
- Missing the final default value.

IMPORTANT TIPS

UTKARSH BAJPAI

- Use IFS for readability in Excel 2019+.
- Store band cut-offs in lookup cells rather than hard-coding.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 9: HIGHEST PERFORMER

PURPOSE - ENGLISH

Finds the name of the employee with the highest score.

PURPOSE - ROMAN HINDI

Sabse zyada score wale employee ka naam dhoondhta hai.

SYNTAX

```
=INDEX(NameRange,MATCH(MAX(ScoreRange),ScoreRange,0))
```

SYNTAX EXPLANATION

MAX finds the top score, MATCH locates it, INDEX returns the name.

Roman Hindi: MAX top score nikalta hai, MATCH uski position dhoondta hai, INDEX naam deta hai.

SAMPLE DATASET

A2:A100 names, B2:B100 scores

ACTUAL FORMULA

```
=INDEX(A2:A100,MATCH(MAX(B2:B100),B2:B100,0))
```

EXPECTED OUTPUT

Employee name

STEP-BY-STEP - ENGLISH

- Get the maximum score with MAX.
- Locate its position with MATCH(...,0).
- Return the name with INDEX.

STEP-BY-STEP - ROMAN HINDI

- MAX se sabse zyada score nikalo.
- MATCH(...,0) se position dhoondo.
- INDEX se naam return karo.

REAL OFFICE EXAMPLE

Monthly awards are announced from the top score.

UTKARSH BAJPAI

Roman Hindi: Monthly awards top score se announce hote hain.

COMMON MISTAKES

- Tied top scores return only the first match.
- Name and score ranges of different sizes.

IMPORTANT TIPS

- Use FILTER to list all ties in dynamic-array Excel.
- Keep both ranges the same height.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 10: LOWEST PERFORMER

PURPOSE - ENGLISH

Finds the name of the employee with the lowest score.

PURPOSE - ROMAN HINDI

Sabse kam score wale employee ka naam dhoondhta hai.

SYNTAX

```
=INDEX(NameRange,MATCH(MIN(ScoreRange),ScoreRange,0))
```

SYNTAX EXPLANATION

MIN finds the bottom score, MATCH finds it, INDEX returns the name.

Roman Hindi: MIN sabse kam score nikalta hai, MATCH dhoondta hai, INDEX naam deta hai.

SAMPLE DATASET

A2:A100 names, B2:B100 scores

ACTUAL FORMULA

```
=INDEX(A2:A100,MATCH(MIN(B2:B100),B2:B100,0))
```

EXPECTED OUTPUT

Employee name

STEP-BY-STEP - ENGLISH

- Get the minimum score with MIN.
- Locate its position with MATCH.
- Return the name with INDEX.

STEP-BY-STEP - ROMAN HINDI

UTKARSH BAJPAI

- MIN se sabse kam score nikalo.
- MATCH se position dhoondo.
- INDEX se naam lo.

REAL OFFICE EXAMPLE

Coaching plans are scheduled for the lowest performer.

Roman Hindi: Lowest performer ke liye coaching plan banaye jate hain.

COMMON MISTAKES

- Zero scores from missing data are treated as lowest.

IMPORTANT TIPS

- Clean blanks before running MIN.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 11: ATTENDANCE PERCENTAGE

PURPOSE - ENGLISH

Present days as a percentage of working days.

PURPOSE - ROMAN HINDI

Present days, working days ka kitna percent hain.

SYNTAX

```
=PresentDays/WorkingDays
```

SYNTAX EXPLANATION

Divide present days by working days and format as a percentage.

Roman Hindi: Present days ko working days se divide karke percentage format do.

SAMPLE DATASET

Present = 22, Working days = 25

ACTUAL FORMULA

```
=A2/B2
```

EXPECTED OUTPUT

88%

STEP-BY-STEP - ENGLISH

- Count working days with NETWORKDAYS or a manual total.

UTKARSH BAJPAI

- Count present days from the attendance register.
- Divide and format as a percentage.

STEP-BY-STEP - ROMAN HINDI

- Working days NETWORKDAYS ya manual total se count karo.
- Attendance register se present days count karo.
- Divide karke percentage format do.

REAL OFFICE EXAMPLE

HR payroll uses attendance percentage before releasing salary.

Roman Hindi: HR payroll salary release se pehle attendance percentage use karta hai.

COMMON MISTAKES

- Holidays treated as absent days.

IMPORTANT TIPS

- Pass a holidays range to NETWORKDAYS.
- Format result as Percentage, not General.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 12: WORKING HOURS

PURPOSE - ENGLISH

Calculates hours worked from in-time and out-time.

PURPOSE - ROMAN HINDI

In-time aur out-time se kaam ke ghante nikalta hai.

SYNTAX

```
=(OutTime-InTime)*24
```

SYNTAX EXPLANATION

Excel stores time as a fraction of a day, so multiply by 24 for hours.

Roman Hindi: Excel time ko din ka fraction samajhta hai, hours ke liye 24 se multiply karo.

SAMPLE DATASET

A2 = 09:00, B2 = 18:00

ACTUAL FORMULA

```
=(B2-A2)*24
```

UTKARSH BAJPAI

EXPECTED OUTPUT

9

STEP-BY-STEP - ENGLISH

- Enter in and out times as time values.
- Subtract and multiply by 24.
- Format the result as Number with decimals.

STEP-BY-STEP - ROMAN HINDI

- In aur out time ko time value ke roop me daalo.
- Subtract karke 24 se multiply karo.
- Result ko Number format do.

REAL OFFICE EXAMPLE

Shift MIS prepares payable hours before overtime is applied.

Roman Hindi: Shift MIS overtime lagane se pehle payable hours banata hai.

COMMON MISTAKES

- Shifts crossing midnight produce negative values.
- Times typed as text.

IMPORTANT TIPS

- Add 1 to handle overnight shifts: =(B2-A2+1)*24.
- Use MOD for overnight shifts as an alternative.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 13: OVERTIME

PURPOSE - ENGLISH

Calculates overtime pay from extra hours and the OT rate.

PURPOSE - ROMAN HINDI

Extra hours aur OT rate se overtime pay nikalta hai.

SYNTAX

```
=OvertimeHours*OvertimeRate
```

SYNTAX EXPLANATION

Hours multiplied by the approved overtime rate.

Roman Hindi: Approved overtime rate se hours multiply karte hain.

UTKARSH BAJPAI

SAMPLE DATASET

OT hours = 5, OT rate = 150

ACTUAL FORMULA

```
=A2*B2
```

EXPECTED OUTPUT

750

STEP-BY-STEP - ENGLISH

- Calculate payable overtime hours first.
- Multiply by the approved hourly rate.
- Total the column for payroll.

STEP-BY-STEP - ROMAN HINDI

- Pehle payable overtime hours nikalo.
- Approved hourly rate se multiply karo.
- Payroll ke liye column ka total lo.

REAL OFFICE EXAMPLE

Payroll adds overtime to the monthly salary sheet.

Roman Hindi: Payroll monthly salary sheet me overtime add karta hai.

COMMON MISTAKES

- Overtime below the policy threshold being paid.

IMPORTANT TIPS

- Apply a policy cap with MIN(hours, cap).

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 14: SALARY CALCULATION

PURPOSE - ENGLISH

Builds net salary from earnings and deductions.

PURPOSE - ROMAN HINDI

Earnings aur deductions se net salary banata hai.

SYNTAX

```
=Basic+HRA+Allowances-Deductions
```

UTKARSH BAJPAI

SYNTAX EXPLANATION

Sum all earnings, then subtract statutory deductions.

Roman Hindi: Saare earnings jodo, phir statutory deductions minus karo.

SAMPLE DATASET

Basic 25,000 + HRA 10,000 + Allow 5,000 - PF 1,800 - Tax 2,000

ACTUAL FORMULA

```
=A2+B2+C2-D2-E2
```

EXPECTED OUTPUT

36,200

STEP-BY-STEP - ENGLISH

- Keep earnings and deductions in separate blocks.
- Add earnings and subtract deductions.
- Cross-check the total against payroll.

STEP-BY-STEP - ROMAN HINDI

- Earnings aur deductions alag blocks me rakho.
- Earnings jodo aur deductions minus karo.
- Total payroll se cross-check karo.

REAL OFFICE EXAMPLE

Monthly salary processing for the whole team.

Roman Hindi: Poori team ki monthly salary processing.

COMMON MISTAKES

- Deductions added instead of subtracted.

IMPORTANT TIPS

- Use an Excel Table with a totals row.
- Lock the rate cells.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 15: INCENTIVES

PURPOSE - ENGLISH

Pays an incentive only when the sales target is met.

PURPOSE - ROMAN HINDI

UTKARSH BAJPAI

Target meet hone par hi incentive deta hai.

SYNTAX

```
=IF(Sales>=Target,Sales*IncentiveRate,0)
```

SYNTAX EXPLANATION

The IF checks target achievement before applying the rate.

Roman Hindi: IF pehle target check karta hai, phir rate lagata hai.

SAMPLE DATASET

Sales 1,20,000, Target 1,00,000, Rate 2%

ACTUAL FORMULA

```
=IF(A2>=B2,A2*C2,0)
```

EXPECTED OUTPUT

2400

STEP-BY-STEP - ENGLISH

- Store the incentive rate as a percentage.
- Check achievement with IF.
- Total the incentive column for payroll.

STEP-BY-STEP - ROMAN HINDI

- Incentive rate ko percentage me rakho.
- IF se achievement check karo.
- Payroll ke liye incentive column total karo.

REAL OFFICE EXAMPLE

Sales incentive letters are generated from this column.

Roman Hindi: Sales incentive letter isi column se banate hain.

COMMON MISTAKES

- Rate entered as 2 instead of 2%.

IMPORTANT TIPS

- Use IFS or a lookup for slab-based incentives.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 16: DUPLICATE IDENTIFICATION

UTKARSH BAJPAI

PURPOSE - ENGLISH

Flags repeated values in a column.

PURPOSE - ROMAN HINDI

Column me repeat hone wali values ko flag karta hai.

SYNTAX

```
=COUNTIF($A$2:$A$100,A2)>1
```

SYNTAX EXPLANATION

COUNTIF counts occurrences; more than one means duplicate.

Roman Hindi: COUNTIF occurrences count karta hai; ek se zyada matlab duplicate.

SAMPLE DATASET

A2:A100 = customer codes

ACTUAL FORMULA

```
=COUNTIF($A$2:$A$100,A2)>1
```

EXPECTED OUTPUT

TRUE for duplicates

STEP-BY-STEP - ENGLISH

- Lock the range with $ signs.
- Use a relative reference for the current cell.
- Filter the helper column on TRUE.

STEP-BY-STEP - ROMAN HINDI

- Range ko $ se lock karo.
- Current cell ke liye relative reference use karo.
- Helper column ko TRUE par filter karo.

REAL OFFICE EXAMPLE

Master data audits remove duplicate customer records.

Roman Hindi: Master data audit duplicate customer records hatata hai.

COMMON MISTAKES

- Unlocked range causes wrong results after copy.

IMPORTANT TIPS

- Apply conditional formatting with the same rule.
- Use UNIQUE in Microsoft 365 to list unique values.

EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI

CHAPTER 17: MISSING DATA IDENTIFICATION

PURPOSE - ENGLISH

Finds blank cells that should contain data.

PURPOSE - ROMAN HINDI

Un cells ko dhoondhta hai jahan data hona chahiye tha.

SYNTAX

```
=ISBLANK(A2)
```

SYNTAX EXPLANATION

ISBLANK returns TRUE only for truly empty cells.

Roman Hindi: ISBLANK sirf sach me khali cells par TRUE deta hai.

SAMPLE DATASET

A2:A100 should all be filled

ACTUAL FORMULA

```
=ISBLANK(A2)
```

EXPECTED OUTPUT

TRUE for blanks

STEP-BY-STEP - ENGLISH

- Add a helper column with ISBLANK.
- Filter on TRUE.
- Fix the source blanks before reporting.

STEP-BY-STEP - ROMAN HINDI

- Helper column me ISBLANK lagao.
- TRUE par filter karo.
- Report se pehle source blanks theek karo.

REAL OFFICE EXAMPLE

Data quality checks catch missing mandatory fields.

Roman Hindi: Data quality check missing mandatory fields pakadta hai.

COMMON MISTAKES

- Cells containing a space are not blank.

IMPORTANT TIPS

UTKARSH BAJPAI

- Combine with TRIM: =TRIM(A2)="" to catch spaces.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 18: DATA CLEANING

PURPOSE - ENGLISH

Standardises messy text with PROPER, TRIM and CLEAN.

PURPOSE - ROMAN HINDI

Messy text ko PROPER, TRIM aur CLEAN se standard karta hai.

SYNTAX

```
=PROPER(TRIM(CLEAN(A2)))
```

SYNTAX EXPLANATION

CLEAN removes control characters, TRIM removes extra spaces, PROPER fixes case.

Roman Hindi: CLEAN control characters hatata hai, TRIM extra spaces, PROPER case theek karta hai.

SAMPLE DATASET

A2 = " john   DOE "

ACTUAL FORMULA

```
=PROPER(TRIM(CLEAN(A2)))
```

EXPECTED OUTPUT

John Doe

STEP-BY-STEP - ENGLISH

- Paste values into a helper column.
- Apply CLEAN, then TRIM, then PROPER.
- Copy the cleaned column back as values.

STEP-BY-STEP - ROMAN HINDI

- Helper column me values paste karo.
- CLEAN, TRIM aur PROPER lagao.
- Cleaned column ko values ke roop me wapas copy karo.

REAL OFFICE EXAMPLE

Customer name and address lists are cleaned before mail merge.

Roman Hindi: Mail merge se pehle customer name aur address list clean ki jati hai.

UTKARSH BAJPAI

COMMON MISTAKES

- Leaving the formula instead of pasting values.

IMPORTANT TIPS

- Use SUBSTITUTE for stray symbols such as double spaces.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 19: MONTHLY SALES REPORT

PURPOSE - ENGLISH

Sums sales for a chosen month and product with SUMIFS.

PURPOSE - ROMAN HINDI

Chune gaye month aur product ki sales SUMIFS se nikalta hai.

SYNTAX

```
=SUMIFS(Sales,Month,"Jan",Product,"A")
```

SYNTAX EXPLANATION

Every criteria pair must match for the row to be included.

Roman Hindi: Include hone ke liye har criteria pair match hona chahiye.

SAMPLE DATASET

Sales, Month and Product columns

ACTUAL FORMULA

```
=SUMIFS($C$2:$C$100,$D$2:$D$100,"Jan",$A$2:$A$100,"ProductA")
```

EXPECTED OUTPUT

Monthly total

STEP-BY-STEP - ENGLISH

- Build a small summary table.
- Reference month and product from the table headers.
- Lock the source ranges.

STEP-BY-STEP - ROMAN HINDI

- Chhota summary table banao.
- Month aur product table headers se lo.
- Source ranges lock karo.

UTKARSH BAJPAI

REAL OFFICE EXAMPLE

Monthly business review packs use this summary table.

Roman Hindi: Monthly business review pack isi summary table ko use karta hai.

COMMON MISTAKES

- Month stored as text instead of a date.

IMPORTANT TIPS

- Keep a real date column and group with TEXT(date,"mmm").

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 20: DAILY MIS REPORT

PURPOSE - ENGLISH

Counts today's transactions for the daily report.

PURPOSE - ROMAN HINDI

Daily report ke liye aaj ke transactions count karta hai.

SYNTAX

```
=COUNTIFS(DateRange,TODAY())
```

SYNTAX EXPLANATION

TODAY() refreshes with the date, so the count rolls forward daily.

Roman Hindi: TODAY() har din update hota hai, isliye count daily aage badhta hai.

SAMPLE DATASET

A2:A100 holds transaction dates

ACTUAL FORMULA

```
=COUNTIFS($A$2:$A$100,TODAY())
```

EXPECTED OUTPUT

Today's count

STEP-BY-STEP - ENGLISH

- Keep dates as real dates, not text.
- Use TODAY() as the criteria.
- Refresh the report each morning.

UTKARSH BAJPAI

STEP-BY-STEP - ROMAN HINDI

- Dates ko real date rakho, text nahi.
- Criteria me TODAY() do.
- Har subah report refresh karo.

REAL OFFICE EXAMPLE

The daily operations mail is generated from these counters.

Roman Hindi: Daily operations mail inhi counters se generate hoti hai.

COMMON MISTAKES

- Dates imported as text never match TODAY().

IMPORTANT TIPS

- Convert text dates with DATEVALUE.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 21: MASTER SHEET CREATION

PURPOSE - ENGLISH

Consolidates identically laid out sheets into one master.

PURPOSE - ROMAN HINDI

Same layout wali sheets ko ek master me consolidate karta hai.

SYNTAX

```
=SUM(Jan:Mar!B2)
```

SYNTAX EXPLANATION

A 3-D reference sums the same cell across a sheet range.

Roman Hindi: 3-D reference sheet range me same cell ko sum karta hai.

SAMPLE DATASET

Sheets Jan, Feb, Mar with identical layout

ACTUAL FORMULA

```
=SUM(Jan:Mar!B2)
```

EXPECTED OUTPUT

Combined value

UTKARSH BAJPAI

STEP-BY-STEP - ENGLISH

- Make every sheet layout identical.
- Type SUM(then select the sheet range.
- Click the shared cell and close the bracket.

STEP-BY-STEP - ROMAN HINDI

- Har sheet ka layout same rakho.
- SUM(likhkar sheet range select karo.
- Shared cell par click karke bracket close karo.

REAL OFFICE EXAMPLE

Branchwise sheets roll up into a company master.

Roman Hindi: Branchwise sheets company master me roll up hoti hain.

COMMON MISTAKES

- A single reordered column breaks every total.

IMPORTANT TIPS

- Use Data > Consolidate for non-identical layouts.
- Use VSTACK in Microsoft 365 for stacked tables.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 22: MULTIPLE SHEET COMPILATION

PURPOSE - ENGLISH

References numbered sheets with INDIRECT.

PURPOSE - ROMAN HINDI

Numbered sheets ko INDIRECT se reference karta hai.

SYNTAX

```
=INDIRECT("'Sheet"&ROW()-1&"'!A1")
```

SYNTAX EXPLANATION

INDIRECT builds a reference from text and is volatile.

Roman Hindi: INDIRECT text se reference banata hai aur volatile hai.

SAMPLE DATASET

Sheets named Sheet1, Sheet2, Sheet3

ACTUAL FORMULA

UTKARSH BAJPAI

```
=INDIRECT("'Sheet"&ROW()-1&"'!A1")
```

EXPECTED OUTPUT

Value from each sheet

STEP-BY-STEP - ENGLISH

- Name the sheets with a consistent pattern.
- Build the sheet name from the row number.
- INDIRECT converts it to a live reference.

STEP-BY-STEP - ROMAN HINDI

- Sheets ko consistent pattern se naam do.
- Row number se sheet name banao.
- INDIRECT use live reference me convert karta hai.

REAL OFFICE EXAMPLE

A template pulls one summary row from dozens of outlet sheets.

Roman Hindi: Template dozens of outlet sheets se ek summary row kheenchta hai.

COMMON MISTAKES

- Renaming a sheet breaks the reference silently.
- Volatile formulas slow large workbooks.

IMPORTANT TIPS

- Prefer Power Query or VSTACK for many sheets.
- Keep sheet names in a helper column.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 23: DYNAMIC DASHBOARD KPI

PURPOSE - ENGLISH

Builds an error-safe KPI tile for a dashboard.

PURPOSE - ROMAN HINDI

Dashboard ke liye error-safe KPI tile banata hai.

SYNTAX

```
=IFERROR(SUMIFS(Amount,Status,"Done"),0)
```

SYNTAX EXPLANATION

IFERROR returns 0 instead of an error so the tile never breaks.

UTKARSH BAJPAI

Roman Hindi: IFERROR error ki jagah 0 deta hai, isliye tile kabhi break nahi hota.

SAMPLE DATASET

Status column with Done/Pending

ACTUAL FORMULA

```
=IFERROR(SUMIFS($C$2:$C$100,$E$2:$E$100,"Done"),0)
```

EXPECTED OUTPUT

KPI value

STEP-BY-STEP - ENGLISH

- Decide the KPI aggregation.
- Wrap it in IFERROR.
- Link the tile to a number format.

STEP-BY-STEP - ROMAN HINDI

- KPI aggregation decide karo.
- IFERROR me wrap karo.
- Tile ko number format se link karo.

REAL OFFICE EXAMPLE

Executive dashboards stay clean even when source data is incomplete.

Roman Hindi: Executive dashboard source data adhoora hone par bhi clean rehta hai.

COMMON MISTAKES

- Hiding a genuine modelling error with IFERROR.

IMPORTANT TIPS

- Use IFNA when only lookup misses should be silenced.

EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI