# EXCEL MASTER INDEX

Basic to Advanced | English & Roman Hindi

# EXCEL FINANCIAL & INFORMATION FUNCTIONS

PMT, IPMT, PPMT, FV, PV, NPV, IRR, XIRR, RATE, NPER, ISBLANK, ISNUMBER, TYPE, CELL & More | Bilingual Guide

---

**Created & Developed by**

## UTKARSH BAJPAI

utkarshbajpai068@gmail.com

---

Premium Bilingual Resource | For Students, MIS Executives, Data Analysts & Office Professionals

# TABLE OF CONTENTS


1. PMT
2. IPMT
3. PPMT
4. FV
5. PV
6. NPV
7. XNPV
8. IRR
9. XIRR
10. RATE
11. NPER
12. ISBLANK
13. ISNUMBER
14. ISTEXT
15. ISERROR
16. ISNA
17. ISFORMULA
18. TYPE
19. CELL
20. ERROR.TYPE


UTKARSH BAJPAI

# CHAPTER 1: PMT

### PURPOSE - ENGLISH

Returns the fixed periodic payment for a loan or investment.

### PURPOSE - ROMAN HINDI

Loan ya investment ki fixed periodic payment nikalta hai.

### SYNTAX

```
=PMT(rate, nper, pv, [fv], [type])
```

### SYNTAX EXPLANATION

PMT needs the periodic rate, the number of periods and the present value. The result includes both principal and interest.

Roman Hindi: PMT ko periodic rate, periods ki sankhya aur present value chahiye. Result me principal aur interest dono shamil hote hain.

### SAMPLE DATASET

Cells: A1:B3 | Values: Loan,1000
Months,12
Annual Rate,0.1

### ACTUAL FORMULA

```
=PMT(B3/12, B2, -B1)
```

### EXPECTED OUTPUT

**87.92**

### STEP-BY-STEP - ENGLISH

- Divide the annual rate by 12 for a monthly rate.
- Enter the number of monthly payments.
- Enter the loan amount as a negative pv so the payment comes out positive.

### STEP-BY-STEP - ROMAN HINDI

- Monthly rate ke liye annual rate ko 12 se divide karo.
- Monthly payments ki sankhya likho.
- Loan amount ko negative pv do taaki payment positive aaye.

### REAL OFFICE EXAMPLE

Used to calculate home loan, car loan and equipment EMI before signing an agreement.

Roman Hindi: Home loan, car loan aur equipment EMI nikalne ke liye use hota hai, agreement sign karne se pehle.

### COMMON MISTAKES

UTKARSH BAJPAI

- Using an annual rate with monthly periods gives a wrong EMI.
- Forgetting the minus sign on pv reverses the payment sign.

### IMPORTANT TIPS

- Keep rate and nper in the same unit: both monthly or both annual.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

# CHAPTER 2: IPMT

### PURPOSE - ENGLISH

Returns the interest portion of a specific loan payment.

### PURPOSE - ROMAN HINDI

Loan ki kisi specific payment ka interest hissa nikalta hai.

### SYNTAX

```
=IPMT(rate, per, nper, pv, [fv], [type])
```

### SYNTAX EXPLANATION

IPMT uses the same inputs as PMT but returns only the interest part of one period. Period numbers start at 1.

Roman Hindi: IPMT PMT jaise inputs leta hai lekin sirf ek period ka interest hissa deta hai. Period number 1 se shuru hota hai.

### SAMPLE DATASET

Cells: A1:B3 | Values: Loan,1000
Months,12
Annual Rate,0.1

### ACTUAL FORMULA

```
=IPMT(B3/12, 1, B2, -B1)
```

### EXPECTED OUTPUT

**8.33**

### STEP-BY-STEP - ENGLISH

- Enter the periodic rate.
- Enter the period number, starting from 1.
- Enter nper and pv exactly as you did for PMT.

### STEP-BY-STEP - ROMAN HINDI

- Periodic rate likho.

UTKARSH BAJPAI

- Period number likho, 1 se shuru.
- Nper aur pv waise hi likho jaise PMT me kiya tha.

### REAL OFFICE EXAMPLE

Used to split each EMI into interest and principal for an amortization schedule.

Roman Hindi: Amortization schedule ke liye har EMI ko interest aur principal me todne ke liye use hota hai.

### COMMON MISTAKES

- Using period 0 returns an error; the first period is 1.
- Mixing annual rate with monthly periods gives an incorrect split.

### IMPORTANT TIPS

- IPMT + PPMT always equals the PMT amount for the same period.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 3: PPMT

### PURPOSE - ENGLISH

Returns the principal portion of a specific loan payment.

### PURPOSE - ROMAN HINDI

Loan ki kisi specific payment ka principal hissa nikalta hai.

### SYNTAX

```
=PPMT(rate, per, nper, pv, [fv], [type])
```

### SYNTAX EXPLANATION

PPMT returns the part of the payment that actually reduces the loan balance.

Roman Hindi: PPMT payment ka wo hissa deta hai jo loan balance ko actually kam karta hai.

### SAMPLE DATASET

Cells: A1:B3 | Values: Loan,1000
Months,12
Annual Rate,0.1

### ACTUAL FORMULA

```
=PPMT(B3/12, 1, B2, -B1)
```

### EXPECTED OUTPUT

**79.58**

UTKARSH BAJPAI

### STEP-BY-STEP - ENGLISH

- Use the same rate, nper and pv as PMT.
- Enter the period you want to inspect.
- Press Enter to get only the principal part.

### STEP-BY-STEP - ROMAN HINDI

- PMT jaise rate, nper aur pv use karo.
- Jis period ko dekhna hai wo likho.
- Enter dabao aur sirf principal hissa pao.

### REAL OFFICE EXAMPLE

Used in loan schedules to show how much of each EMI reduces the outstanding amount.

Roman Hindi: Loan schedules me dikhane ke liye use hota hai ki har EMI se outstanding amount kitna kam hota hai.

### COMMON MISTAKES

- PPMT does not include interest, so do not add it to IPMT twice.
- The period must be between 1 and nper.

### IMPORTANT TIPS

- Build a two-column amortization table with IPMT and PPMT side by side.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 4: FV

### PURPOSE - ENGLISH

Returns the future value of a series of equal payments or a lump sum.

### PURPOSE - ROMAN HINDI

Barabar payments ki series ya lump sum ka future value nikalta hai.

### SYNTAX

```
=FV(rate, nper, pmt, [pv], [type])
```

### SYNTAX EXPLANATION

FV compounds each payment forward to the end of the term. Use a negative pmt for money you pay in.

Roman Hindi: FV har payment ko term ke end tak compound karta hai. Jo paisa aap dete hain uske liye negative pmt use karo.

### SAMPLE DATASET

Cells: A1:B3 | Values: Monthly Deposit,1000
Months,12
Annual Rate,0.1

UTKARSH BAJPAI

### ACTUAL FORMULA

```
=FV(B3/12, B2, -B1, 0)
```

### EXPECTED OUTPUT

**12565.57**

### STEP-BY-STEP - ENGLISH

- Enter the periodic rate and number of periods.
- Enter the recurring deposit as a negative pmt.
- Leave pv as 0 when there is no starting amount.

### STEP-BY-STEP - ROMAN HINDI

- Periodic rate aur periods ki sankhya likho.
- Recurring deposit ko negative pmt likho.
- Starting amount na ho to pv 0 rakho.

### REAL OFFICE EXAMPLE

Used to project the maturity value of a recurring deposit or SIP.

Roman Hindi: Recurring deposit ya SIP ki maturity value project karne ke liye use hota hai.

### COMMON MISTAKES

- A positive pmt produces a negative future value.
- The rate and nper must use the same period unit.

### IMPORTANT TIPS

- Add type 1 when deposits are made at the start of each month.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 5: PV

### PURPOSE - ENGLISH

Returns the present value of future equal payments or a lump sum.

### PURPOSE - ROMAN HINDI

Future barabar payments ya lump sum ka present value nikalta hai.

### SYNTAX

```
=PV(rate, nper, pmt, [fv], [type])
```

### SYNTAX EXPLANATION

UTKARSH BAJPAI

PV discounts future payments back to today. It answers how much a stream of payments is worth right now.

Roman Hindi: PV future payments ko aaj ki value me discount karta hai. Ye batata hai ki payments ki stream aaj kitni worth hai.

### SAMPLE DATASET

Cells: A1:B3 | Values: Monthly Income,1000
Months,12
Annual Rate,0.1

### ACTUAL FORMULA

```
=PV(B3/12, B2, -B1, 0)
```

### EXPECTED OUTPUT

**11374.51**

### STEP-BY-STEP - ENGLISH

- Enter the periodic discount rate.
- Enter the number of payments and the payment amount.
- Leave fv as 0 when there is no final lump sum.

### STEP-BY-STEP - ROMAN HINDI

- Periodic discount rate likho.
- Payments ki sankhya aur payment amount likho.
- Final lump sum na ho to fv 0 rakho.

### REAL OFFICE EXAMPLE

Used to value a lease, pension or any fixed income stream.

Roman Hindi: Lease, pension ya kisi fixed income stream ki value nikalne ke liye use hota hai.

### COMMON MISTAKES

- Using an annual rate for monthly payments overstates the present value.
- The payment sign must be opposite to the result you expect.

### IMPORTANT TIPS

- PV is the mirror image of FV; use the same inputs and swap the result.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 6: NPV

### PURPOSE - ENGLISH

Returns the net present value of a series of future cash flows.

UTKARSH BAJPAI

### PURPOSE - ROMAN HINDI

Future cash flows ki series ka net present value nikalta hai.

### SYNTAX

```
=NPV(rate, value1, [value2], ...)
```

### SYNTAX EXPLANATION

NPV discounts each value by one extra period, starting from period 1. The initial investment is usually added outside the function.

Roman Hindi: NPV har value ko ek extra period se discount karta hai, period 1 se shuru karke. Initial investment aam taur par function ke bahar add ki jati hai.

### SAMPLE DATASET

Cells: A1:B3 | Values: Year 1,100
Year 2,200
Year 3,50

### ACTUAL FORMULA

```
=NPV(0.1, B1:B3)
```

### EXPECTED OUTPUT

**293.76**

### STEP-BY-STEP - ENGLISH

- Enter the discount rate first.
- Select the future cash flows in order.
- Add the initial investment outside the NPV result if required.

### STEP-BY-STEP - ROMAN HINDI

- Pehle discount rate likho.
- Future cash flows order me select karo.
- Zaroorat ho to initial investment NPV result ke bahar add karo.

### REAL OFFICE EXAMPLE

Used to check whether a project creates value at the company's cost of capital.

Roman Hindi: Ye check karne ke liye use hota hai ki project company ke cost of capital par value banata hai ya nahi.

### COMMON MISTAKES

- Including the Year 0 investment inside NPV discounts it twice.
- A negative NPV does not automatically mean the project is impossible; check the assumptions.

### IMPORTANT TIPS

- Use XNPV when cash flow dates are irregular.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI

# CHAPTER 7: XNPV

### PURPOSE - ENGLISH

Returns net present value for cash flows that occur on specific dates.

### PURPOSE - ROMAN HINDI

Aisi cash flows ka net present value nikalta hai jo specific dates par hoti hain.

### SYNTAX

```
=XNPV(rate, values, dates)
```

### SYNTAX EXPLANATION

XNPV discounts each cash flow using its exact date and a 365-day year. The first date is treated as today, so its value is not discounted.

Roman Hindi: XNPV har cash flow ko uski exact date aur 365-din wale saal se discount karta hai. Pehli date ko aaj maana jata hai, isliye uski value discount nahi hoti.

### SAMPLE DATASET

Cells: A1:B3 | Values: 2024-01-01,100
2024-06-01,200
2024-09-01,150

### ACTUAL FORMULA

```
=XNPV(0.1, B1:B3, A1:A3)
```

### EXPECTED OUTPUT

**432.96**

### STEP-BY-STEP - ENGLISH

- Enter the discount rate.
- List the cash flows and their dates in matching order.
- Make sure every date is a real Excel date, not text.

### STEP-BY-STEP - ROMAN HINDI

- Discount rate likho.
- Cash flows aur unki dates matching order me likho.
- Har date real Excel date ho, text nahi.

### REAL OFFICE EXAMPLE

Used for project cash flows, invoices and investments where payments arrive on irregular dates.

Roman Hindi: Project cash flows, invoices aur investments ke liye use hota hai jahan payments irregular dates par aati hain.

UTKARSH BAJPAI

### COMMON MISTAKES

- The values and dates arrays must contain the same number of items.
- The first date is the base date and is not discounted.

### IMPORTANT TIPS

- XNPV is more accurate than NPV when the gaps between payments are uneven.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 8: IRR

### PURPOSE - ENGLISH

Returns the internal rate of return for a series of equal-period cash flows.

### PURPOSE - ROMAN HINDI

Barabar period wali cash flows ki series ka internal rate of return nikalta hai.

### SYNTAX

```
=IRR(values, [guess])
```

### SYNTAX EXPLANATION

IRR finds the discount rate that makes the NPV of the cash flows equal to zero. The first cash flow is usually the negative investment.

Roman Hindi: IRR wo discount rate dhundta hai jis par cash flows ka NPV zero ho jata hai. Pehla cash flow aam taur par negative investment hota hai.

### SAMPLE DATASET

Cells: A1:A5 | Values: -1000
300
400
500
600

### ACTUAL FORMULA

```
=IRR(A1:A5)
```

### EXPECTED OUTPUT

**24.89%**

### STEP-BY-STEP - ENGLISH

- Put the negative investment first.
- Add each period's cash flow in order.

UTKARSH BAJPAI

- Use IRR on the whole range.

### STEP-BY-STEP - ROMAN HINDI

- Negative investment pehle rakho.
- Har period ka cash flow order me add karo.
- Poori range par IRR use karo.

### REAL OFFICE EXAMPLE

Used to rank projects and compare their return with the company's hurdle rate.

Roman Hindi: Projects rank karne aur unke return ko company ke hurdle rate se compare karne ke liye use hota hai.

### COMMON MISTAKES

- Cash flows must be equally spaced in time.
- Multiple sign changes can produce more than one IRR.

### IMPORTANT TIPS

- Use XIRR for irregular dates and MIRR when reinvestment rate matters.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 9: XIRR

### PURPOSE - ENGLISH

Returns the internal rate of return for cash flows on specific dates.

### PURPOSE - ROMAN HINDI

Specific dates wali cash flows ka internal rate of return nikalta hai.

### SYNTAX

```
=XIRR(values, dates, [guess])
```

### SYNTAX EXPLANATION

XIRR finds the annual rate that makes the dated cash flows' net present value zero.

Roman Hindi: XIRR wo annual rate dhundta hai jis par dated cash flows ka net present value zero ho jata hai.

### SAMPLE DATASET

Cells: A1:B3 | Values: 2024-01-01,-1000
2024-06-01,400
2024-12-01,800

### ACTUAL FORMULA

```
=XIRR(B1:B3, A1:A3)
```

UTKARSH BAJPAI

### EXPECTED OUTPUT

**27.78%**

### STEP-BY-STEP - ENGLISH

- List every cash flow in one column.
- List the matching dates in the next column.
- Use XIRR with values first and dates second.

### STEP-BY-STEP - ROMAN HINDI

- Har cash flow ek column me likho.
- Matching dates agle column me likho.
- XIRR me pehle values aur phir dates do.

### REAL OFFICE EXAMPLE

Used for SIP returns, real estate deals and any investment with uneven payment dates.

Roman Hindi: SIP returns, real estate deals aur uneven payment dates wali kisi bhi investment ke liye use hota hai.

### COMMON MISTAKES

- Values and dates must be the same length and in the same order.
- XIRR returns an annual rate even if the investment lasted less than a year.

### IMPORTANT TIPS

- Format the result as a percentage to read the return easily.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 10: RATE

### PURPOSE - ENGLISH

Returns the periodic interest rate of a loan or investment.

### PURPOSE - ROMAN HINDI

Loan ya investment ka periodic interest rate nikalta hai.

### SYNTAX

```
=RATE(nper, pmt, pv, [fv], [type], [guess])
```

### SYNTAX EXPLANATION

RATE solves for the rate that makes the present value of the payments equal the loan amount. Excel uses an iterative search.

Roman Hindi: RATE wo rate dhundta hai jis par payments ka present value loan amount ke barabar ho. Excel iterative search use karta hai.

UTKARSH BAJPAI

### SAMPLE DATASET

Cells: A1:B3 | Values: Years,5
Annual Payment,1000
Loan,4000

### ACTUAL FORMULA

```
=RATE(B1, -B2, B3)
```

### EXPECTED OUTPUT

**7.93%**

### STEP-BY-STEP - ENGLISH

- Enter the number of periods.
- Enter the payment as a negative number.
- Enter the loan or investment amount as pv.

### STEP-BY-STEP - ROMAN HINDI

- Periods ki sankhya likho.
- Payment ko negative number likho.
- Loan ya investment amount ko pv likho.

### REAL OFFICE EXAMPLE

Used to find the effective rate on a loan when the EMI and tenure are known.

Roman Hindi: Jab EMI aur tenure pata ho to loan ka effective rate nikalne ke liye use hota hai.

### COMMON MISTAKES

- RATE returns a periodic rate, so multiply by 12 for a monthly loan's annual rate.
- If it does not converge, provide a guess such as 0.1.

### IMPORTANT TIPS

- RATE with pmt 0 and fv gives the compound annual growth rate.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 11: NPER

### PURPOSE - ENGLISH

Returns the number of periods needed to repay a loan or reach an investment goal.

### PURPOSE - ROMAN HINDI

Loan repay karne ya investment goal tak pahunchne ke liye kitne periods chahiye ye batata hai.

### SYNTAX

UTKARSH BAJPAI

```
=NPER(rate, pmt, pv, [fv], [type])
```

### SYNTAX EXPLANATION

NPER calculates how long a fixed payment must continue at a fixed rate to clear the present value or reach the future value.

Roman Hindi: NPER batata hai ki fixed rate par fixed payment kitne samay tak chalti rahegi taaki present value clear ho ya future value mil jaye.

### SAMPLE DATASET

Cells: A1:B3 | Values: Monthly Payment,100
Loan,1000
Annual Rate,0.1

### ACTUAL FORMULA

```
=NPER(B3/12, -B1, B2)
```

### EXPECTED OUTPUT

**10.48**

### STEP-BY-STEP - ENGLISH

- Enter the periodic rate.
- Enter the fixed payment as a negative number.
- Enter the loan amount as pv.

### STEP-BY-STEP - ROMAN HINDI

- Periodic rate likho.
- Fixed payment ko negative number likho.
- Loan amount ko pv likho.

### REAL OFFICE EXAMPLE

Used to answer how many months a loan will take at a given EMI.

Roman Hindi: Ye batane ke liye use hota hai ki di gayi EMI par loan kitne mahine chalega.

### COMMON MISTAKES

- The result is in periods, not years; divide by 12 for years.
- A payment that is too small produces an error because the loan never closes.

### IMPORTANT TIPS

- Use ROUNDUP on NPER to get a whole number of payments.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 12: ISBLANK

UTKARSH BAJPAI

### PURPOSE - ENGLISH

Checks if a cell is empty.

### PURPOSE - ROMAN HINDI

Check karta hai ki cell empty hai ya nahi.

### SYNTAX

```
=ISBLANK(value)
```

### SYNTAX EXPLANATION

ISBLANK returns TRUE for empty cells.

Roman Hindi: ISBLANK empty cells par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values:

### ACTUAL FORMULA

```
=ISBLANK(A1)
```

### EXPECTED OUTPUT

**TRUE**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISBLANK(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISBLANK(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for missing data checks.

Roman Hindi: Missing data checks ke liye use hota hai.

### COMMON MISTAKES

- Empty string vs blank.

### IMPORTANT TIPS

- Good for data cleaning.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI

# CHAPTER 13: ISNUMBER

### PURPOSE - ENGLISH

Checks if a cell contains a number.

### PURPOSE - ROMAN HINDI

Check karta hai ki cell number contain karta hai ya nahi.

### SYNTAX

```
=ISNUMBER(value)
```

### SYNTAX EXPLANATION

ISNUMBER returns TRUE for numbers.

Roman Hindi: ISNUMBER numbers par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values: 123

### ACTUAL FORMULA

```
=ISNUMBER(A1)
```

### EXPECTED OUTPUT

**TRUE**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISNUMBER(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISNUMBER(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for validation.

Roman Hindi: Validation ke liye use hota hai.

### COMMON MISTAKES

- Text numbers are not numbers.

### IMPORTANT TIPS

- Good for dashboards.

UTKARSH BAJPAI

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 14: ISTEXT

### PURPOSE - ENGLISH

Checks if a cell contains text.

### PURPOSE - ROMAN HINDI

Check karta hai ki cell text contain karta hai ya nahi.

### SYNTAX

```
=ISTEXT(value)
```

### SYNTAX EXPLANATION

ISTEXT returns TRUE for text.

Roman Hindi: ISTEXT text par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values: Hello

### ACTUAL FORMULA

```
=ISTEXT(A1)
```

### EXPECTED OUTPUT

**TRUE**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISTEXT(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISTEXT(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for data type checks.

Roman Hindi: Data type checks ke liye use hota hai.

UTKARSH BAJPAI

### COMMON MISTAKES

- None.

### IMPORTANT TIPS

- Combine with ISNUMBER for type checks.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 15: ISERROR

### PURPOSE - ENGLISH

Checks if a value is any error.

### PURPOSE - ROMAN HINDI

Check karta hai ki value error hai ya nahi.

### SYNTAX

```
=ISERROR(value)
```

### SYNTAX EXPLANATION

ISERROR returns TRUE for errors.

Roman Hindi: ISERROR errors par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values: =1/0

### ACTUAL FORMULA

```
=ISERROR(A1)
```

### EXPECTED OUTPUT

**TRUE**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISERROR(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISERROR(A1) likhna.
- Enter dabao.

UTKARSH BAJPAI

### REAL OFFICE EXAMPLE

Used for error handling in reports.

Roman Hindi: Reports me error handling ke liye use hota hai.

### COMMON MISTAKES

- ISERROR ignores #N/A.

### IMPORTANT TIPS

- Use IFERROR to fix errors.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 16: ISNA

### PURPOSE - ENGLISH

Checks if a value is #N/A.

### PURPOSE - ROMAN HINDI

Check karta hai ki value #N/A hai ya nahi.

### SYNTAX

```
=ISNA(value)
```

### SYNTAX EXPLANATION

ISNA returns TRUE for #N/A.

Roman Hindi: ISNA #N/A par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values: #N/A

### ACTUAL FORMULA

```
=ISNA(A1)
```

### EXPECTED OUTPUT

**TRUE**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISNA(A1).
- Press Enter.

UTKARSH BAJPAI

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISNA(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used to handle missing lookups.

Roman Hindi: Missing lookups handle karne ke liye use hota hai.

### COMMON MISTAKES

- None.

### IMPORTANT TIPS

- Good with IFNA.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 17: ISFORMULA

### PURPOSE - ENGLISH

Checks if a cell contains a formula.

### PURPOSE - ROMAN HINDI

Check karta hai ki cell formula contain karta hai ya nahi.

### SYNTAX

```
=ISFORMULA(reference)
```

### SYNTAX EXPLANATION

ISFORMULA returns TRUE for formulas.

Roman Hindi: ISFORMULA formulas par TRUE deta hai.

### SAMPLE DATASET

Cells: A1 | Values: =SUM(A1:A5)

### ACTUAL FORMULA

```
=ISFORMULA(A1)
```

### EXPECTED OUTPUT

**TRUE**

UTKARSH BAJPAI

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ISFORMULA(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ISFORMULA(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for audit checks.

Roman Hindi: Audit checks ke liye use hota hai.

### COMMON MISTAKES

- None.

### IMPORTANT TIPS

- Good for data validation.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 18: TYPE

### PURPOSE - ENGLISH

Returns the data type of a value.

### PURPOSE - ROMAN HINDI

Kisi value ki data type deta hai.

### SYNTAX

```
=TYPE(value)
```

### SYNTAX EXPLANATION

TYPE returns 1-8 for data types.

Roman Hindi: TYPE data type 1 se 8 deta hai.

### SAMPLE DATASET

Cells: A1 | Values: 123

### ACTUAL FORMULA

```
=TYPE(A1)
```

UTKARSH BAJPAI

### EXPECTED OUTPUT

**1**

### STEP-BY-STEP - ENGLISH

- Pass the value.
- Use =TYPE(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Value dein.
- =TYPE(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for debugging data types.

Roman Hindi: Data types ke debugging ke liye use hota hai.

### COMMON MISTAKES

- Numbers are type 1.

### IMPORTANT TIPS

- Type 2 text, 4 number, 6 logical.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 19: CELL

### PURPOSE - ENGLISH

Returns information about a cell.

### PURPOSE - ROMAN HINDI

Cell ke baare mein information deta hai.

### SYNTAX

```
=CELL(info_type, reference)
```

### SYNTAX EXPLANATION

CELL gets cell info.

Roman Hindi: CELL cell info deta hai.

### SAMPLE DATASET

Cells: A1 | Values: 5

UTKARSH BAJPAI

### ACTUAL FORMULA

```
=CELL("format", A1)
```

### EXPECTED OUTPUT

**"$0.00"**

### STEP-BY-STEP - ENGLISH

- Add info type and reference.
- Use =CELL("format", A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Info type aur reference dein.
- =CELL("format", A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for audit and info reports.

Roman Hindi: Audit aur info reports ke liye use hota hai.

### COMMON MISTAKES

- Reference optional.

### IMPORTANT TIPS

- Info types: format, width, etc.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

---

## CHAPTER 20: ERROR.TYPE

### PURPOSE - ENGLISH

Returns the error code number.

### PURPOSE - ROMAN HINDI

Error ki code number deta hai.

### SYNTAX

```
=ERROR.TYPE(value)
```

### SYNTAX EXPLANATION

ERROR.TYPE gets error code.

UTKARSH BAJPAI

Roman Hindi: ERROR.TYPE error code deta hai.

### SAMPLE DATASET

Cells: A1 | Values: #N/A

### ACTUAL FORMULA

```
=ERROR.TYPE(A1)
```

### EXPECTED OUTPUT

**7**

### STEP-BY-STEP - ENGLISH

- Pass the cell.
- Use =ERROR.TYPE(A1).
- Press Enter.

### STEP-BY-STEP - ROMAN HINDI

- Cell pass karo.
- =ERROR.TYPE(A1) likhna.
- Enter dabao.

### REAL OFFICE EXAMPLE

Used for error tracking.

Roman Hindi: Error tracking ke liye use hota hai.

### COMMON MISTAKES

- Returns code not text.

### IMPORTANT TIPS

- Good for logging errors.

### EXCEL VERSION COMPATIBILITY

Excel 2007+

UTKARSH BAJPAI