EXCEL MASTER INDEX

Basic to Advanced | English & Roman Hindi

EXCEL FORMULA COMBINATION MASTER GUIDE

INDEX+MATCH, XLOOKUP+IFERROR, IF+AND/OR, SUMIFS+DATE,
FILTER+SORT, SUMPRODUCT & Dynamic Arrays | Bilingual Guide

Created & Developed by

UTKARSH BAJPAI

utkarshbajpai068@gmail.com

Premium Bilingual Resource | For Students, MIS Executives, Data Analysts & Office Professionals

TABLE OF CONTENTS

1. INDEX + MATCH
2. XLOOKUP + IFERROR
3. IF + AND
4. IF + OR
5. SUMIFS + DATE
6. COUNTIFS MULTI-CRITERIA
7. FILTER + SORT
8. UNIQUE + SORT
9. TEXTJOIN + IF
10. SUMPRODUCT MULTI-CONDITION
11. DYNAMIC ARRAY COMBINATIONS

UTKARSH BAJPAI

CHAPTER 1: INDEX + MATCH

PURPOSE - ENGLISH

Looks up a value in any direction with INDEX and MATCH.

PURPOSE - ROMAN HINDI

INDEX aur MATCH se kisi bhi direction me lookup karta hai.

SYNTAX

```
=INDEX(ReturnRange,MATCH(LookupValue,LookupRange,0))
```

SYNTAX EXPLANATION

MATCH finds the row position and INDEX returns the value from that position.

Roman Hindi: MATCH row position dhoondta hai aur INDEX us position se value deta hai.

SAMPLE DATASET

A2:A10 IDs, C2:C10 values, F2 lookup ID

ACTUAL FORMULA

```
=INDEX(C2:C10,MATCH(F2,A2:A10,0))
```

EXPECTED OUTPUT

Matched value

STEP-BY-STEP - ENGLISH

- Write MATCH first and confirm the position.
- Wrap MATCH inside INDEX for the return column.
- Lock ranges before copying.

STEP-BY-STEP - ROMAN HINDI

- Pehle MATCH likhkar position confirm karo.
- Return column ke liye INDEX me MATCH wrap karo.
- Copy se pehle ranges lock karo.

REAL OFFICE EXAMPLE

Employee lookup by ID in a wide master sheet.

Roman Hindi: Wide master sheet me employee ko ID se lookup karna.

COMMON MISTAKES

- Ranges of different heights return wrong rows.

IMPORTANT TIPS

- Use a two-way INDEX with row and column MATCH.

UTKARSH BAJPAI

- Replace with XLOOKUP in Microsoft 365.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 2: XLOOKUP + IFERROR

PURPOSE - ENGLISH

Returns a friendly message when XLOOKUP finds nothing.

PURPOSE - ROMAN HINDI

XLOOKUP ko kuch na mile to friendly message deta hai.

SYNTAX

```
=IFERROR(XLOOKUP(Lookup,LookupArray,ReturnArray),"Not Found")
```

SYNTAX EXPLANATION

IFERROR catches any lookup error and returns the fallback text.

Roman Hindi: IFERROR koi bhi lookup error pakad ke fallback text deta hai.

SAMPLE DATASET

A2:A10 products, B2:B10 prices, F2 lookup product

ACTUAL FORMULA

```
=IFERROR(XLOOKUP(F2,A2:A10,B2:B10),"Not Found")
```

EXPECTED OUTPUT

Price or Not Found

STEP-BY-STEP - ENGLISH

- Write the XLOOKUP first.
- Wrap it in IFERROR with the message.
- Copy down the column.

STEP-BY-STEP - ROMAN HINDI

- Pehle XLOOKUP likho.
- IFERROR me wrap karke message do.
- Column me neeche copy karo.

REAL OFFICE EXAMPLE

Price lists shared with dealers never show raw errors.

Roman Hindi: Dealer ko bheji price list kabhi raw error nahi dikhati.

UTKARSH BAJPAI

COMMON MISTAKES

- M365/2021 required for XLOOKUP.

IMPORTANT TIPS

- XLOOKUP already has its own if_not_found argument — use either, not both.
- Use IFNA to silence only #N/A.

EXCEL VERSION COMPATIBILITY

Excel 2021 / Microsoft 365

CHAPTER 3: IF + AND

PURPOSE - ENGLISH

Returns one result only when every condition is true.

PURPOSE - ROMAN HINDI

Sirf tab result deta hai jab saare conditions true hon.

SYNTAX

```
=IF(AND(Condition1,Condition2),"Pass","Fail")
```

SYNTAX EXPLANATION

AND returns a single TRUE only if all arguments are true.

Roman Hindi: AND sab arguments true hone par hi TRUE deta hai.

SAMPLE DATASET

A2 = 55, B2 = 60 (minimum 50 each)

ACTUAL FORMULA

```
=IF(AND(A2>=50,B2>=50),"Pass","Fail")
```

EXPECTED OUTPUT

Pass

STEP-BY-STEP - ENGLISH

- State each condition separately.
- Join them with AND inside IF.
- Test one failure case.

STEP-BY-STEP - ROMAN HINDI

- Har condition alag likho.
- IF ke andar AND se jodo.

UTKARSH BAJPAI

- Ek failure case test karo.

REAL OFFICE EXAMPLE

Scholarship eligibility requires marks and attendance.

Roman Hindi: Scholarship eligibility ke liye marks aur attendance dono chahiye.

COMMON MISTAKES

- Using commas outside the AND.

IMPORTANT TIPS

- Use the multiplication trick in SUMPRODUCT for older Excel.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 4: IF + OR

UTKARSH BAJPAI

PURPOSE - ENGLISH

Returns one result when any condition is true.

PURPOSE - ROMAN HINDI

Koi bhi condition true hone par result deta hai.

SYNTAX

```
=IF(OR(Condition1,Condition2),"Bonus","No Bonus")
```

SYNTAX EXPLANATION

OR returns TRUE if at least one argument is true.

Roman Hindi: OR kam se kam ek argument true hone par TRUE deta hai.

SAMPLE DATASET

A2 = 95, B2 = 60

ACTUAL FORMULA

```
=IF(OR(A2>=90,B2>=90),"Bonus","No Bonus")
```

EXPECTED OUTPUT

Bonus

STEP-BY-STEP - ENGLISH

- List the qualifying conditions.
- Join them with OR inside IF.
- Confirm the fallback value.

STEP-BY-STEP - ROMAN HINDI

- Qualifying conditions list karo.
- IF ke andar OR se jodo.
- Fallback value confirm karo.

REAL OFFICE EXAMPLE

Either of two sales channels reaching target earns incentive.

Roman Hindi: Do sales channels me se koi ek target reach kare to incentive milta hai.

COMMON MISTAKES

- Nesting OR inside AND without brackets.

IMPORTANT TIPS

- Wrap each OR group in its own brackets when combining.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 5: SUMIFS + DATE

PURPOSE - ENGLISH

Sums amounts between two dates.

PURPOSE - ROMAN HINDI

Do dates ke beech ke amounts sum karta hai.

SYNTAX

```
=SUMIFS(Amount,DateRange,">="&StartDate,DateRange,"<="&EndDate)
```

SYNTAX EXPLANATION

The & operator concatenates the comparison with the date value.

Roman Hindi: & operator comparison ko date value ke saath jodta hai.

SAMPLE DATASET

Date range A2:A100, amount column C2:C100, F2 start, G2 end

ACTUAL FORMULA

```
=SUMIFS($C$2:$C$100,$A$2:$A$100,">="&F2,$A$2:$A$100,"<="&G2)
```

EXPECTED OUTPUT

Period total

UTKARSH BAJPAI

STEP-BY-STEP - ENGLISH

- Keep start and end dates as real dates.
- Use two criteria on the same date column.
- Concatenate each operator with &.

STEP-BY-STEP - ROMAN HINDI

- Start aur end dates real date rakho.
- Same date column par do criteria lagao.
- Har operator ko & se jodo.

REAL OFFICE EXAMPLE

Week and month MIS totals are driven by a date range picker.

Roman Hindi: Week aur month MIS totals date range picker se bante hain.

COMMON MISTAKES

- Dates stored as text return zero.

IMPORTANT TIPS

- Verify with ISNUMBER on the date column.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 6: COUNTIFS MULTI-CRITERIA

PURPOSE - ENGLISH

Counts rows that satisfy several criteria at once.

PURPOSE - ROMAN HINDI

Ek saath kai criteria satisfy karne wali rows count karta hai.

SYNTAX

```
=COUNTIFS(Range1,Criteria1,Range2,Criteria2)
```

SYNTAX EXPLANATION

All criteria pairs are combined with AND logic.

Roman Hindi: Saare criteria pairs AND logic se combine hote hain.

SAMPLE DATASET

A2:A100 region, B2:B100 status

ACTUAL FORMULA

```
=COUNTIFS($A$2:$A$100,"East",$B$2:$B$100,"Pending")
```

UTKARSH BAJPAI

EXPECTED OUTPUT

Matching rows

STEP-BY-STEP - ENGLISH

- Pair each range with its criteria.
- Keep all ranges the same height.
- Add pairs as more conditions are needed.

STEP-BY-STEP - ROMAN HINDI

- Har range ko uske criteria ke saath pair karo.
- Saari ranges ki height same rakho.
- Aur conditions ke liye pairs badhao.

REAL OFFICE EXAMPLE

Regional status trackers count open items per region.

Roman Hindi: Regional status tracker har region ke open items count karta hai.

COMMON MISTAKES

- Ranges of mismatched size return #VALUE!.

IMPORTANT TIPS

- Reference full columns or an Excel Table.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 7: FILTER + SORT

PURPOSE - ENGLISH

Extracts matching rows and sorts them in one formula.

PURPOSE - ROMAN HINDI

Matching rows nikaal ke ek hi formula me sort karta hai.

SYNTAX

```
=SORT(FILTER(Array,Condition),SortColumn,-1)
```

SYNTAX EXPLANATION

FILTER returns the matching rows, then SORT orders the spilled result.

Roman Hindi: FILTER matching rows deta hai, phir SORT spilled result ko order karta hai.

SAMPLE DATASET

A2:C100 data, B2:B100 amount

UTKARSH BAJPAI

ACTUAL FORMULA

```
=SORT(FILTER(A2:C100,B2:B100>1000),3,-1)
```

EXPECTED OUTPUT

Sorted filtered rows

STEP-BY-STEP - ENGLISH

- Write FILTER with the condition.
- Wrap it in SORT and choose the sort column.
- Enter once and let the result spill.

STEP-BY-STEP - ROMAN HINDI

- FILTER me condition likho.
- SORT me wrap karke sort column chuno.
- Ek baar enter karo aur spill hone do.

REAL OFFICE EXAMPLE

A live top-orders list that updates the moment data changes.

Roman Hindi: Live top-orders list jo data badalte hi update hoti hai.

COMMON MISTAKES

- #SPILL! when the target area is not empty.

IMPORTANT TIPS

- Clear the spill area or place the formula on its own sheet.

EXCEL VERSION COMPATIBILITY

Excel 2021 / Microsoft 365

CHAPTER 8: UNIQUE + SORT

PURPOSE - ENGLISH

Produces a sorted list of unique values.

PURPOSE - ROMAN HINDI

Unique values ki sorted list banata hai.

SYNTAX

```
=SORT(UNIQUE(Array))
```

SYNTAX EXPLANATION

UNIQUE removes repeats, SORT orders what remains.

UTKARSH BAJPAI

Roman Hindi: UNIQUE repeats hatata hai, SORT baaki ko order karta hai.

SAMPLE DATASET

A2:A100 vendor names

ACTUAL FORMULA

```
=SORT(UNIQUE(A2:A100))
```

EXPECTED OUTPUT

Sorted unique vendors

STEP-BY-STEP - ENGLISH

- Apply UNIQUE to the source column.
- Wrap it in SORT.
- Feed the spilled list into a data-validation dropdown.

STEP-BY-STEP - ROMAN HINDI

- Source column par UNIQUE lagao.
- SORT me wrap karo.
- Spilled list ko data-validation dropdown me use karo.

REAL OFFICE EXAMPLE

Vendor dropdowns always show current, deduplicated names.

Roman Hindi: Vendor dropdown hamesha current, deduplicated names dikhata hai.

COMMON MISTAKES

- Extra spaces create near-duplicates.

IMPORTANT TIPS

- TRIM the source, or use UNIQUE(TRIM(range)).

EXCEL VERSION COMPATIBILITY

Excel 2021 / Microsoft 365

CHAPTER 9: TEXTJOIN + IF

PURPOSE - ENGLISH

Joins values that meet a condition into one cell.

PURPOSE - ROMAN HINDI

Condition meet karne wali values ko ek cell me jodta hai.

SYNTAX

```
=TEXTJOIN(", ",TRUE,IF(ConditionRange="Yes",NameRange,""))
```

UTKARSH BAJPAI

SYNTAX EXPLANATION

IF builds an array of names or blanks; TEXTJOIN ignores the blanks.

Roman Hindi: IF names ya blanks ka array banata hai; TEXTJOIN blanks ignore karta hai.

SAMPLE DATASET

A2:A10 names, B2:B10 attended Yes/No

ACTUAL FORMULA

```
=TEXTJOIN(", ",TRUE,IF(B2:B10="Yes",A2:A10,""))
```

EXPECTED OUTPUT

Ravi, Amit, Neha

STEP-BY-STEP - ENGLISH

- Set up the Yes/No flag column.
- Write IF to return names or empty strings.
- Wrap in TEXTJOIN and set ignore_empty to TRUE.

STEP-BY-STEP - ROMAN HINDI

- Yes/No flag column banao.
- IF se naam ya empty string do.
- TEXTJOIN me wrap karke ignore_empty TRUE rakho.

REAL OFFICE EXAMPLE

A single cell lists everyone present in a shift.

Roman Hindi: Ek cell me poori shift me present logon ki list aati hai.

COMMON MISTAKES

- Older Excel may need Ctrl+Shift+Enter.

IMPORTANT TIPS

- Use FILTER + TEXTJOIN in Microsoft 365 for cross-sheet arrays.

EXCEL VERSION COMPATIBILITY

Excel 2019 / Microsoft 365

CHAPTER 10: SUMPRODUCT MULTI-CONDITION

PURPOSE - ENGLISH

Sums values matching multiple conditions without SUMIFS.

PURPOSE - ROMAN HINDI

SUMIFS ke bina kai conditions wali values ka sum karta hai.

UTKARSH BAJPAI

SYNTAX

```
=SUMPRODUCT((Range1="East")*(Range2="Apple")*AmountRange)
```

SYNTAX EXPLANATION

Each condition returns TRUE/FALSE; multiplication acts as AND and coerces values to 1/0.

Roman Hindi: Har condition TRUE/FALSE deti hai; multiply AND ka kaam karta hai aur values ko 1/0 banata hai.

SAMPLE DATASET

A2:A100 region, B2:B100 product, C2:C100 amount

ACTUAL FORMULA

```
=SUMPRODUCT((A2:A100="East")*(B2:B100="Apple")*C2:C100)
```

EXPECTED OUTPUT

Conditional total

STEP-BY-STEP - ENGLISH

- Write each condition in brackets.
- Multiply conditions with the amount range.
- Keep every range the same height.

STEP-BY-STEP - ROMAN HINDI

- Har condition brackets me likho.
- Conditions ko amount range se multiply karo.
- Sab ranges ki height same rakho.

REAL OFFICE EXAMPLE

Legacy workbooks use it where SUMIFS is unavailable or multiple arrays are needed.

Roman Hindi: Purane workbooks me jahan SUMIFS available nahi ya multiple arrays chahiye wahan use hota hai.

COMMON MISTAKES

- Text inside the amount range returns #VALUE!.

IMPORTANT TIPS

- Wrap the amount range in N() or clean the data first.

EXCEL VERSION COMPATIBILITY

Excel 2007+

CHAPTER 11: DYNAMIC ARRAY COMBINATIONS

PURPOSE - ENGLISH

UTKARSH BAJPAI

Chains FILTER, UNIQUE and SORT into one live report.

PURPOSE - ROMAN HINDI

FILTER, UNIQUE aur SORT ko chain karke live report banata hai.

SYNTAX

```
=SORT(UNIQUE(FILTER(Names,Status="Active")))
```

SYNTAX EXPLANATION

Each function passes its spilled result to the next one.

Roman Hindi: Har function apna spilled result agle function ko deta hai.

SAMPLE DATASET

A2:A100 names, B2:B100 status

ACTUAL FORMULA

```
=SORT(UNIQUE(FILTER(A2:A100,B2:B100="Active")))
```

EXPECTED OUTPUT

Sorted active names

STEP-BY-STEP - ENGLISH

- Start from the innermost FILTER.
- Wrap with UNIQUE to remove repeats.
- Wrap with SORT for presentation.

STEP-BY-STEP - ROMAN HINDI

- Sabse andar FILTER se shuru karo.
- UNIQUE se repeats hatao.
- SORT se presentable banao.

REAL OFFICE EXAMPLE

An always-current active-client list on a dashboard.

Roman Hindi: Dashboard par hamesha current active-client list.

COMMON MISTAKES

- Large chains slow older machines.

IMPORTANT TIPS

- Store intermediate results in LET variables.

EXCEL VERSION COMPATIBILITY

Excel 2021 / Microsoft 365

UTKARSH BAJPAI