

U-Boot SPL 2019.04SECOND_INNINGS-g07a0789b-dirty (Oct 13 2025 - 23:06:28 +0530)

Trying to boot from MMC2

Loading Environment from EXT4...

**** Unable to use mmc 0:1 for loading the env ****

U-Boot 2019.04SECOND_INNINGS-g07a0789b-dirty (Oct 13 2025 - 23:06:28 +0530)

CPU : AM335X-GP rev 2.1

Model: TI AM335x EVM

DRAM: 512 MiB

Reset Source: Power-on reset has occurred.

RTC 32KCLK Source: External.

MMC: OMAP SD/MMC: 0, OMAP SD/MMC: 1

Loading Environment from EXT4...

**** Unable to use mmc 0:1 for loading the env ****

Board: BeagleBone Black

<ethaddr> not set. Validating first E-fuse MAC

BeagleBone Black:

BeagleBone: cape eeprom: i2c_probe: 0x54:

BeagleBone: cape eeprom: i2c_probe: 0x55:

BeagleBone: cape eeprom: i2c_probe: 0x56:

BeagleBone: cape eeprom: i2c_probe: 0x57:

Net: eth0: MII MODE

cpsw, usb_ether

Hit any key to stop autoboot: 0

load uEnv.txt file using TFTP

44 bytes read in 18 ms (2 KiB/s)

```
uname_r=[4.19.94-gbce566dcf-dirty] ...
```

```
board_no=[1] ...
```

KM Multi Boot Menu

- 1: Boot From SD Card [MMC0]
- 2: Boot From EMMC [MMC1]
- 3: Boot From Serial [UART0]
- 4: Boot From TFTP [Default CPSW]
- 5: Boot With KGDB-KDB [SDCARD, EMMC, TFTP]
- 6: Select Ethernet [CPSW, ENC]
- 7: Self diagnostic test
- 0: Stay in Boot Mode

Enter Your Choice:

```
***** Booting From EMMC .... *****
```

```
board_name=[A335BNLT] ...
```

```
44 bytes read in 18 ms (2 KiB/s)
```

```
uname_r=[4.19.94-gbce566dcf-dirty] ...
```

```
board_no=[1] ...
```

```
4527328 bytes read in 310 ms (13.9 MiB/s)
```

```
36508 bytes read in 25 ms (1.4 MiB/s)
```

```
kgdb_script:if test ${kgdb_boot} = ${emmc} ; then ; setenv debugargs setenv  
bootargs rootfstype=${mmccrootfstype} root=/dev/mmcbklp1 console=ttyS0,115200n8  
rodata=off nokaslr kgdb=ttyS0,115200 kgdboc=ttyS0,115200n8 kgdbwait rootwait; run  
debugargs ; else ; setenv mmcargs setenv bootargs console=${console}  
root=/dev/mmcbklp1 rootfstype=${mmccrootfstype} crashkernel=32M ; run mmcargs; fi
```

```
***bootz:Start Kernel***
```

Flattened Device Tree blob at 88000000

Booting using the fdt blob at 0x88000000

Loading Ramdisk to 90000000, end 90000000 ... OK

Loading Device Tree to 8fff4000, end 8ffffe9b ... OK

Starting kernel ...

```
[ 0.000000] Booting Linux on physical CPU 0x0
[ 0.000000] Linux version 4.19.94-gbce566dcf-dirty (km@KernelMasters) (gcc
version 8.3.0 (GNU Toolchain for the A-profile Architecture 8.3-2019.03 (arm-rel-
8.36))) #2 SMP Mon Oct 13 23:46:35 IST 2025
[ 0.000000] CPU: ARMv7 Processor [413fc082] revision 2 (ARMv7), cr=10c5387d
[ 0.000000] CPU: PIPT / VIPT nonaliasing data cache, VIPT aliasing instruction
cache
[ 0.000000] OF: fdt: Machine model: Kernel Masters BeagleBone Black Expansion
Board - AM335x
[ 0.000000] Memory policy: Data cache writeback
[ 0.000000] cma: Reserved 16 MiB at 0x9e800000
[ 0.000000] CPU: All CPU(s) started in SVC mode.
[ 0.000000] Reserving 32MB of memory at 2432MB for crashkernel (System RAM:
510MB)
[ 0.000000] AM335X ES2.1 (sgx neon)
[ 0.000000] random: get_random_bytes called from start_kernel+0x8c/0x4a4 with
crng_init=0
[ 0.000000] percpu: Embedded 17 pages/cpu s38056 r8192 d23384 u69632
[ 0.000000] Built 1 zonelists, mobility grouping on. Total pages: 129412
[ 0.000000] Kernel command line: console=tty00,115200n8 root=/dev/mmcblk1p1
rootfstype=ext4 rootwait crashkernel=32M
[ 0.000000] Dentry cache hash table entries: 65536 (order: 6, 262144 bytes)
[ 0.000000] Inode-cache hash table entries: 32768 (order: 5, 131072 bytes)
```

```

[ 0.000000] Memory: 445908K/522240K available (9216K kernel code, 810K rwdatas,
2692K rodata, 1024K init, 7768K bss, 59948K reserved, 16384K cma-reserved, 0K
highmem)

[ 0.000000] Virtual kernel memory layout:

[ 0.000000]    vector : 0xffff0000 - 0xfffff1000    ( 4 kB)
[ 0.000000]    fixmap : 0xffc00000 - 0xfff00000    (3072 kB)
[ 0.000000]    vmalloc : 0xe0000000 - 0xff800000    ( 504 MB)
[ 0.000000]    lowmem : 0xc0000000 - 0xdf000000    ( 510 MB)
[ 0.000000]    pkmap : 0xbfe00000 - 0xc0000000    ( 2 MB)
[ 0.000000]    modules : 0xbf000000 - 0xbfe00000    ( 14 MB)
[ 0.000000]      .text : 0x(ptrval) - 0x(ptrval)    (10208 kB)
[ 0.000000]      .init : 0x(ptrval) - 0x(ptrval)    (1024 kB)
[ 0.000000]      .data : 0x(ptrval) - 0x(ptrval)    ( 811 kB)
[ 0.000000]      .bss : 0x(ptrval) - 0x(ptrval)    (7769 kB)

[ 0.000000] Running RCU self tests

[ 0.000000] rcu: Hierarchical RCU implementation.

[ 0.000000] rcu: RCU event tracing is enabled.

[ 0.000000] rcu: RCU lockdep checking is enabled.

[ 0.000000] rcu: RCU restricting CPUs from NR_CPUS=2 to nr_cpu_ids=1.

[ 0.000000] rcu: Adjusting geometry for rcu_fanout_leaf=16, nr_cpu_ids=1

[ 0.000000] NR_IRQS: 16, nr_irqs: 16, preallocated irqs: 16

[ 0.000000] IRQ: Found an INTC at 0x(ptrval) (revision 5.0) with 128 interrupts

[ 0.000000] OMAP clockevent source: timer2 at 24000000 Hz

[ 0.000019] sched_clock: 32 bits at 24MHz, resolution 41ns, wraps every
89478484971ns

[ 0.000053] clocksource: timer1: mask: 0xffffffff max_cycles: 0xffffffff,
max_idle_ns: 79635851949 ns

[ 0.000113] OMAP clocksource: timer1 at 24000000 Hz

[ 0.000641] timer_probe: no matching timers found

[ 0.001602] Console: colour dummy device 80x30

```

```
[ 0.001666] WARNING: Your 'console=tty00' has been replaced by 'ttyS0'
[ 0.001684] This ensures that you still see kernel messages. Please
[ 0.001700] update your kernel commandline.
[ 0.001718] Lock dependency validator: Copyright (c) 2006 Red Hat, Inc., Ingo
Molnar
[ 0.001734] ... MAX_LOCKDEP_SUBCLASSES: 8
[ 0.001749] ... MAX_LOCK_DEPTH: 48
[ 0.001764] ... MAX_LOCKDEP_KEYS: 8191
[ 0.001780] ... CLASSHASH_SIZE: 4096
[ 0.001795] ... MAX_LOCKDEP_ENTRIES: 32768
[ 0.001811] ... MAX_LOCKDEP_CHAINS: 65536
[ 0.001826] ... CHAINHASH_SIZE: 32768
[ 0.001842] memory used by lock dependency info: 4655 kB
[ 0.001858] per task-struct memory footprint: 1536 bytes
[ 0.001949] Calibrating delay loop... 996.14 BogoMIPS (lpj=4980736)
[ 0.078586] pid_max: default: 32768 minimum: 301
[ 0.079035] Security Framework initialized
[ 0.079318] Mount-cache hash table entries: 1024 (order: 0, 4096 bytes)
[ 0.079343] Mountpoint-cache hash table entries: 1024 (order: 0, 4096 bytes)
[ 0.082712] CPU: Testing write buffer coherency: ok
[ 0.082896] CPU0: Spectre v2: using BPIALL workaround
[ 0.084413] CPU0: thread -1, cpu 0, socket -1, mpidr 0
[ 0.086883] Setting up static identity map for 0x80100000 - 0x80100078
[ 0.087571] rcu: Hierarchical SRCU implementation.
[ 0.089751] smp: Bringing up secondary CPUs ...
[ 0.089782] smp: Brought up 1 node, 1 CPU
[ 0.089803] SMP: Total of 1 processors activated (996.14 BogoMIPS).
[ 0.089822] CPU: All CPU(s) started in SVC mode.
[ 0.093915] devtmpfs: initialized
```

[0.121013] VFP support v0.3: implementor 41 architecture 3 part 30 variant c rev 3

[0.121831] clocksource: jiffies: mask: 0xffffffff max_cycles: 0xffffffff, max_idle_ns: 19112604462750000 ns

[0.121906] futex hash table entries: 256 (order: 2, 16384 bytes)

[0.123629] pinctrl core: initialized pinctrl subsystem

[0.128826] NET: Registered protocol family 16

[0.136197] DMA: preallocated 256 KiB pool for atomic coherent allocations

[0.197370] 14_wkup_cm:clk:0010:0: failed to disable

[0.251491] audit: initializing netlink subsys (disabled)

[0.254412] cpuidle: using governor menu

[0.269621] audit: type=2000 audit(0.250:1): state=initialized audit_enabled=0 res=1

[0.271078] OMAP GPIO hardware version 0.1

[0.298081] No ATAGs?

[0.298094] hw-breakpoint: debug architecture 0x4 unsupported.

[0.337529] edma 49000000.edma: TI EDMA DMA engine driver

[0.344329] vgaarb: loaded

[0.345464] SCSI subsystem initialized

[0.347789] pps_core: LinuxPPS API ver. 1 registered

[0.347817] pps_core: Software ver. 5.3.6 - Copyright 2005-2007 Rodolfo Giometti <giometti@linux.it>

[0.347875] PTP clock support registered

[0.352269] clocksource: Switched to clocksource timer1

[0.515342] VFS: Disk quotas dquot_6.6.0

[0.515555] VFS: Dquot-cache hash table entries: 1024 (order 0, 4096 bytes)

[0.543858] NET: Registered protocol family 2

[0.546046] tcp_listen_portaddr_hash hash table entries: 256 (order: 1, 10240 bytes)

[0.546140] TCP established hash table entries: 4096 (order: 2, 16384 bytes)

[0.546239] TCP bind hash table entries: 4096 (order: 5, 147456 bytes)

[0.546804] TCP: Hash tables configured (established 4096 bind 4096)

[0.547205] UDP hash table entries: 256 (order: 2, 20480 bytes)

[0.547319] UDP-Lite hash table entries: 256 (order: 2, 20480 bytes)

[0.547748] NET: Registered protocol family 1

[0.550614] RPC: Registered named UNIX socket transport module.

[0.550699] RPC: Registered udp transport module.

[0.550718] RPC: Registered tcp transport module.

[0.550736] RPC: Registered tcp NFSv4.1 backchannel transport module.

[0.554551] hw perfevents: enabled with armv7_cortex_a8 PMU driver, 5 counters available

[0.559446] Initialise system trusted keyrings

[0.560538] workingset: timestamp_bits=14 max_order=17 bucket_order=3

[0.564207] NFS: Registering the id_resolver key type

[0.564393] Key type id_resolver registered

[0.564470] Key type id_legacy registered

[0.564658] jffs2: version 2.2. (NAND) (SUMMARY) © 2001-2006 Red Hat, Inc.

[0.572825] Key type asymmetric registered

[0.573061] Asymmetric key parser 'x509' registered

[0.573250] io scheduler noop registered

[0.573276] io scheduler deadline registered

[0.573474] io scheduler cfq registered (default)

[0.573501] io scheduler mq-deadline registered

[0.573521] io scheduler kyber registered

[0.576346] pinctrl-single 44e10800.pinmux: 142 pins, size 568

[0.583606] Serial: 8250/16550 driver, 6 ports, IRQ sharing enabled

[0.597266] 44e09000.serial: ttyS0 at MMIO 0x44e09000 (irq = 30, base_baud = 3000000) is a 8250

[1.302990] console [ttyS0] enabled

```
[ 1.340098] brd: module loaded
[ 1.372276] loop: module loaded
[ 1.378076] mtdoops: mtd device (mtddev=name/number) must be supplied
[ 1.388057] libphy: Fixed MDIO Bus: probed
[ 1.394183] *****
drivers/net/ethernet/microchip/enc28j60.c:enc28j60_init:1668 *****
[ 1.472276] davinci_mdio 4a101000.mdio: davinci mdio revision 1.6, bus freq
1000000
[ 1.480033] davinci_mdio 4a101000.mdio: detected phy mask ffffffff
[ 1.487073] MDIO: davinci_mdio: dt: updated phy_id[0] from phy_mask[fffffff]
[ 1.499117] libphy: 4a101000.mdio: probed
[ 1.503448] davinci_mdio 4a101000.mdio: phy[0]: device 4a101000.mdio:00, driver
SMSC LAN8710/LAN8720
[ 1.514503] cpsw 4a100000.ethernet: Detected MACID = 3c:e0:64:1d:da:d5
[ 1.521925] cpsw 4a100000.ethernet: initialized cpsw ale version 1.4
[ 1.528563] cpsw 4a100000.ethernet: ALE Table size 1024
[ 1.534015] cpsw 4a100000.ethernet: cpts: overflow check period 500 (jiffies)
[ 1.545528] i2c /dev entries driver
[ 1.553022] sdhci: Secure Digital Host Controller Interface driver
[ 1.559262] sdhci: Copyright(c) Pierre Ossman
[ 1.565132] omap_gpio 44e07000.gpio: Could not set line 6 debounce to 200000
microseconds (-22)
[ 1.574034] omap_hsmmc 48060000.mmc: Got CD GPIO
[ 1.580482] omap_hsmmc 48060000.mmc: Linked as a consumer to regulator.1
[ 1.615833] omap_hsmmc 481d8000.mmc: Linked as a consumer to regulator.1
[ 1.646812] sdhci-pltfm: SDHCI platform and OF driver helper
[ 1.653910] ledtrig-cpu: registered to indicate activity on CPUs
[ 1.663336] oprofile: using arm/armv7
[ 1.667811] Initializing XFRM netlink socket
[ 1.672852] NET: Registered protocol family 10
```


[1.682019] Segment Routing with IPv6

[1.686109] sit: IPv6, IPv4 and MPLS over IPv4 tunneling driver

[1.694186] NET: Registered protocol family 17

[1.698745] NET: Registered protocol family 15

[1.703743] Key type dns_resolver registered

[1.708208] ThumbEE CPU extension supported.

[1.712644] Registering SWP/SWPB emulation handler

[1.717476] omap_voltage_late_init: Voltage driver support not added

[1.723961] sr_dev_init: Unknown instance smartreflex0

[1.729628] SmartReflex Class3 initialized

[1.738043] Loading compiled-in X.509 certificates

[1.791037] mmc0: host does not support reading read-only switch, assuming write-enable

[1.804843] mmc0: new high speed SDHC card at address 0001

[1.818776] mmcblk0: mmc0:0001 7.42 GiB

[1.829646] mmcblk0: p1 p2

[1.846287] random: fast init done

[1.875368] mmc1: new high speed MMC card at address 0001

[1.881967] tps65217 0-0024: TPS65217 ID 0xe version 1.2

[1.888288] omap_i2c 44e0b000.i2c: bus 0 rev0.11 at 400 kHz

[1.897853] mmcblk1: mmc1:0001 MK2704 3.53 GiB

[1.904522] mmcblk1boot0: mmc1:0001 MK2704 partition 1 2.00 MiB

[1.912657] mmcblk1boot1: mmc1:0001 MK2704 partition 2 2.00 MiB

[1.921306] omap_i2c 4802a000.i2c: bus 1 rev0.11 at 100 kHz

[1.929090] hctosys: unable to open rtc device (rtc0)

[1.934355] sr_init: No PMIC hook to init smartreflex

[1.942644] mmcblk1rpb: mmc1:0001 MK2704 partition 3 512 KiB, chardev (248:0)

[1.955881] mmcblk1: p1

```
[ 1.986567] EXT4-fs (mmcblk1p1): mounted filesystem with ordered data mode.
Opts: (null)

[ 1.995364] VFS: Mounted root (ext4 filesystem) readonly on device 179:9.

[ 2.005073] devtmpfs: mounted

[ 2.010493] Freeing unused kernel memory: 1024K

[ 2.016268] Run /sbin/init as init process

[ 2.491871] systemd[1]: System time before build time, advancing clock.

[ 2.557067] systemd[1]: Inserted module 'autofs4'

[ 2.621519] systemd[1]: systemd 241 running in system mode. (+PAM +AUDIT
+SELINUX +IMA +APPARMOR +SMACK +SYSVINIT +UTMP +LIBCRYPTSETUP +GCRYPT +GNUTLS +ACL
+XZ +LZ4 +SECCOMP +BLKID +ELFUTILS +KMOD -IDN2 +IDN -PCRE2 default-
hierarchy=hybrid)

[ 2.644939] systemd[1]: Detected architecture arm.
```

Welcome to Debian GNU/Linux 10 (buster)!

```
[ 2.687202] systemd[1]: Set hostname to <KM-BBB>.

[ 3.984409] systemd[1]: File /lib/systemd/system/systemd-journald.service:12
configures an IP firewall (IPAddressDeny=any), but the local system does not
support BPF/cgroup based firewalling.

[ 4.002238] systemd[1]: Proceeding WITHOUT firewalling in effect! (This warning
is only shown for the first loaded unit using IP firewalling.)

[ 4.277838] random: systemd: uninitialized urandom read (16 bytes read)

[ 4.463422] random: systemd: uninitialized urandom read (16 bytes read)

[ 4.474608] systemd[1]: Set up automount Arbitrary Executable File Formats File
System Automount Point.

[ OK ] Set up automount Arbitrary...s File System Automount Point.

[ 4.523616] random: systemd: uninitialized urandom read (16 bytes read)

[ 4.531794] systemd[1]: Listening on Journal Audit Socket.

[ OK ] Listening on Journal Audit Socket.

[ 4.572804] systemd[1]: Reached target Remote File Systems.
```

```
[ OK ] Reached target Remote File Systems.

[ 4.613860] systemd[1]: Started Forward Password Requests to Wall Directory Watch.

[ OK ] Started Forward Password Requests to Wall Directory Watch.

[ 4.654357] systemd[1]: Listening on Journal Socket (/dev/log).

[ OK ] Listening on Journal Socket (/dev/log).

[ OK ] Created slice User and Session Slice.

[ OK ] Reached target Slices.

[ OK ] Reached target Swap.

[ OK ] Listening on initctl Compatibility Named Pipe.

[ OK ] Listening on udev Kernel Socket.

[ OK ] Listening on fsck to fsckd communication Socket.

[ OK ] Created slice system-getty.slice.

[ OK ] Listening on Syslog Socket.

[ OK ] Started Dispatch Password Requests to Console Directory Watch.

[ OK ] Reached target Paths.

[ OK ] Created slice system-serial\x2dgetty.slice.

[ OK ] Reached target Local Encrypted Volumes.

[ OK ] Listening on Journal Socket.

    Starting Restore / save the current clock...

    Starting Load Kernel Modules...

    Starting Create list of modules for the current kernel...

    Starting Journal Service...

    Starting File System Check on Root Device...

[ OK ] Listening on udev Control Socket.

    Starting udev Coldplug all Devices...

    Mounting /sys/kernel/debug...

    Mounting POSIX Message Queue File System...

[ OK ] Started Restore / save the current clock.
```

```
[ OK ] Started Load Kernel Modules.

[ OK ] Started Create list of req... nodes for the current kernel.

[ OK ] Mounted /sys/kernel/debug.

[ OK ] Mounted POSIX Message Queue File System.

[ OK ] Started File System Check on Root Device.

[ OK ] Started File System Check Daemon to report status.

    Starting Remount Root and Kernel File Systems...

    Starting Apply Kernel Variables...

    Mounting Kernel Configuration File System...

[ OK ] Mounted Kernel Configuration File System.

[ OK ] Started Journal Service.

[ OK ] Started Apply Kernel Variables.

[ 7.126931] EXT4-fs (mmcblk1p1): re-mounted. Opts: errors=remount-ro

[ OK ] Started Remount Root and Kernel File Systems.

    Starting Load/Save Random Seed...

    Starting Flush Journal to Persistent Storage...

    Starting Create System Users...

[ OK ] Started Load/Save Random Seed.

[ 7.814078] systemd-journald[78]: Received request to flush runtime journal
from PID 1

[ OK ] Started Flush Journal to Persistent Storage.

[ OK ] Started Create System Users.

    Starting Create Static Device Nodes in /dev...

[ OK ] Started Create Static Device Nodes in /dev.

[ OK ] Reached target Local File Systems (Pre).

[ OK ] Reached target Local File Systems.

    Starting Create Volatile Files and Directories...

    Starting udev Kernel Device Manager...

[ OK ] Started udev Kernel Device Manager.
```

```
[ OK ] Started Create Volatile Files and Directories.

    Starting Network Time Synchronization...

[ OK ] Started Entropy daemon using the HAVEGE algorithm.

    Starting Update UTMP about System Boot/Shutdown...

[ OK ] Started udev Coldplug all Devices.

    Starting Helper to synchronize boot up for ifupdown...

[ OK ] Started Helper to synchronize boot up for ifupdown.

[ 11.375290] omap_wdt: OMAP Watchdog Timer Rev 0x01: initial timeout 60 sec

[ 11.423228] omap_rtc 44e3e000.rtc: registered as rtc0

    Starting Raise network interfaces...

[ 11.528450] am335x-phy-driver 47401300.usb-phy: 47401300.usb-phy supply vcc not
found, using dummy regulator

[ 11.539740] am335x-phy-driver 47401300.usb-phy: Linked as a consumer to
regulator.0

[ 12.027504] am335x-phy-driver 47401b00.usb-phy: 47401b00.usb-phy supply vcc not
found, using dummy regulator

[ 12.038188] am335x-phy-driver 47401b00.usb-phy: Linked as a consumer to
regulator.0

[ OK ] Started Update UTMP about System Boot/Shutdown.

[ 13.026450] omap-mailbox 480c8000.mailbox: omap mailbox rev 0x400

[ 13.276517] rtc-ds1307 1-0068: registered as rtc1

[ 13.575517] omap_rng 48310000.rng: Random Number Generator ver. 20

[ 13.583781] random: crng init done

[ 13.587246] random: 7 urandom warning(s) missed due to ratelimiting

[ 13.694329] at24 0-0050: 32768 byte 24c256 EEPROM, writable, 1 bytes/write

[ OK ] Found device /dev/ttyS0.

[ 15.853386] tps6521x_pwrbutton tps65217-pwrbutton: DMA mask not set

[ OK ] Started Network Time Synchronization.

[ 16.011046] input: tps65217_pwr_but as /devices/platform/ocp/44e0b000.i2c/i2c-
0/0-0024/tps65217-pwrbutton/input/input0
```

```
[ OK ] Reached target System Initialization.

[ OK ] Listening on D-Bus System Message Bus Socket.

[ OK ] Started Daily Cleanup of Temporary Directories.

[ OK ] Listening on Avahi mDNS/DNS-SD Stack Activation Socket.

[ OK ] Reached target Sockets.

[ 16.390374] remoteproc remoteproc0: wkup_m3 is available

[ OK ] Reached target Basic System.

        Starting System Logging Service...

[ 16.881729] remoteproc remoteproc0: powering up wkup_m3

[ 16.904477] PM: Cannot get wkup_m3_ipc handle

[ OK ] Started D-Bus System Message Bus.

[ 17.043721] remoteproc remoteproc0: Direct firmware load for am335x-pm-
firmware.elf failed with error -2

[ 17.054110] remoteproc remoteproc0: request_firmware failed: -2

[ 17.060091] wkup_m3_ipc 44e11324.wkup_m3_ipc: rproc_boot failed

        Starting Connection service...

        Starting LSB: Load kernel ...d to enable cpufreq scaling...

        Starting WPA supplicant...

        Starting Login Service...

        Starting Avahi mDNS/DNS-SD Stack...

[ OK ] Started Regular background program processing daemon.

[ OK ] Reached target System Time Synchronized.

[ OK ] Started Daily rotation of log files.

[ OK ] Reached target Timers.

[ OK ] Started System Logging Service.

[ OK ] Started Raise network interfaces.

[ 22.289426] PM: Cannot get wkup_m3_ipc handle

[ 22.367074] usbcore: registered new interface driver usbfs

[ 22.373613] usbcore: registered new interface driver hub
```

```
[ 22.379188] usbcore: registered new device driver usb
[ 22.439019] PM: Cannot get wkup_m3_ipc handle
[ 22.967046] musb-hdrc musb-hdrc.1: MUSB HDRC host driver
[ 22.973858] musb-hdrc musb-hdrc.1: new USB bus registered, assigned bus number
1
[ 22.985052] PM: Cannot get wkup_m3_ipc handle
[ 23.260914] net eth0: initializing cpsw version 1.12 (0)
[ 23.507514] usb usb1: New USB device found, idVendor=1d6b, idProduct=0002,
bcdDevice= 4.19
[ 23.516388] usb usb1: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 23.523874] usb usb1: Product: MUSB HDRC host driver
[ 23.528880] usb usb1: Manufacturer: Linux 4.19.94-gbce566dcf-dirty musb-hcd
[ 23.535968] usb usb1: SerialNumber: musb-hdrc.1
[ 23.746443] SMSC LAN8710/LAN8720 4a101000.mdio:00: attached PHY driver [SMSC
LAN8710/LAN8720] (mii_bus:phy_addr=4a101000.mdio:00, irq=POLL)
[ 23.907016] IPv6: ADDRCONF(NETDEV_UP): eth0: link is not ready
[ 23.970184] hub 1-0:1.0: USB hub found
[ 24.042563] hub 1-0:1.0: 1 port detected
[ 24.150829] PM: Cannot get wkup_m3_ipc handle
[ 24.195567] PM: Cannot get wkup_m3_ipc handle
[ 25.843995] cpsw 4a100000.ethernet eth0: Link is Up - 100Mbps/Full - flow
control off
[ 25.902729] IPv6: ADDRCONF(NETDEV_CHANGE): eth0: link becomes ready
[ OK ] Started LSB: Load kernel modules to enable cpufreq scaling.
[ OK ] Started Avahi mDNS/DNS-SD Stack.
    Starting Hostname Service...
    Starting LSB: set CPUFreq kernel parameters...
[ OK ] Started Login Service.
[ OK ] Started Connection service.
[ OK ] Started WPA supplicant.
```

```
[ OK ] Reached target Network.

[ OK ] Started description of code.

        Starting OpenBSD Secure Shell server...

        Starting A high performanc... and a reverse proxy server...

        Starting Permit User Sessions...

        Starting Generic Board Startup...

[ OK ] Started Permit User Sessions.

[ OK ] Started Getty on tty1.

[ OK ] Started Serial Getty on ttyS0.

[ OK ] Started LSB: set CPUFreq kernel parameters.

[ OK ] Started Generic Board Startup.

[ OK ] Started Hostname Service.

[ OK ] Started OpenBSD Secure Shell server.

[ OK ] Started A high performance...er and a reverse proxy server.
```

Kernel Masters - BBB - Debian GNU/Linux 10.4 KM-BBB ttyS0

rcn-ee.net Debian Console Image 28th July 2022

Support/FAQ: <http://www.kernelmasters.org>

default username:password is [km:km]

KM-BBB login: km

Password:

Last login: Mon Jul 20 14:47:53 UTC 2020 on ttyS0

The programs included with the Debian GNU/Linux system are free software;

the exact distribution terms for each program are described in the individual files in /usr/share/doc/*/copyright.

Debian GNU/Linux comes with ABSOLUTELY NO WARRANTY, to the extent permitted by applicable law.