



Create Ticket API

Raise a Get-Rescue roadside assistance ticket directly from your own system. A ticket created through this endpoint appears immediately on the Get-Rescue agent dashboard and is handled exactly like any other service request.

ENDPOINT

POST `https://www.zohoapis.in/creator/custom/getrescued/createTicket?publickey=thd8D02kGUyvb13hqwmFndD0H`

Send parameters as a JSON body with `Content-Type: application/json`. The `publickey` above identifies your integration and is required on every call — treat it as a credential and do not expose it in client-side code or a public repository.

PARAMETERS

PARAMETER	TYPE	REQUIRED	DESCRIPTION
customerName	string	REQUIRED	Name of the customer requesting assistance.
mobile	string	REQUIRED	Customer's 10-digit mobile number. This is the number the Get-Rescue agent and the assigned vendor will call, and where the customer receives WhatsApp updates.
email	string	optional	Customer's email address, if available.
vehicle	string	REQUIRED	The vehicle needing assistance. Accepts either a Vehicle record ID or the vehicle name exactly as listed in the Get-Rescue vehicle catalogue. Name matching ignores capitalisation.
issue	string	REQUIRED	The problem reported. Accepts either an Issue record ID or the issue name, again ignoring capitalisation. For more than one issue, separate values with commas — IDs and names may be mixed freely in the same request.

EXAMPLE REQUEST

```
curl -X POST \
  'https://www.zohoapis.in/creator/custom/getrescued/createTicket?
publickey=thd8D02kGUyvb13hqwmFndD0H' \
  -H 'Content-Type: application/json' \
  -d '{
    "customerName": "Ramesh Kumar",
    "mobile": "9876543210",
    "email": "ramesh@example.com",
    "vehicle": "Maruti Suzuki Brezza",
    "issue": "AIR FILL, STEPNEY CHANGE"
  }'
```

Record IDs may be used in place of names for `vehicle` and `issue` — for example `"vehicle": "448881000000221402"`. IDs are the more reliable choice for an automated integration.

SUCCESSFUL RESPONSE

```
{
  "code": "SUCCESS",
  "message": "Service request created",
  "recordId": 448881000000585463,
  "caseId": "RSID585463",
  "serviceType": "RSR"
}
```

FIELD	DESCRIPTION
code	<code>SUCCESS</code> when the ticket was created.
recordId	Internal Get-Rescue record identifier.
caseId	Store this. The human-readable case reference (e.g. <code>RSID585463</code>) used in all correspondence about the ticket.
serviceType	<code>RSR</code> (on-site repair) or <code>TOW</code> (towing). Determined automatically from the issue — see below.
unmatchedIssues	Only present when one or more issue values could not be matched. See <i>Partially matched issues</i> .

HOW THE SERVICE TYPE IS DECIDED

You do not send the service type — Get-Rescue derives it. If **any** of the issues you send is a towing issue, the whole ticket is created as `TOW`. Otherwise it is created as `RSR`. A ticket that needs towing is dispatched to a tow operator rather than an on-site mechanic, so this affects who is assigned.

PARTIALLY MATCHED ISSUES

If you send several issues and only some are recognised, the ticket is **still created** with the ones that matched, and the response lists the rest:

```
{
  "code": "SUCCESS",
  "caseId": "RSID585470",
  "serviceType": "RSR",
  "unmatchedIssues": "BATTERY DEAD"
}
```

Check for this field. A successful response does not guarantee every issue you sent was recorded. If `unmatchedIssues` is present, that issue is missing from the ticket — usually a spelling difference. The request only fails outright when *none* of the issues can be matched.

ERRORS

Every failure returns the same shape, with a message describing the cause:

```
{
  "code": "ERROR",
  "message": "Vehicle is required"
}
```

MESSAGE	CAUSE
Customer Name is required	<code>customerName</code> was missing or blank.
Mobile is required	<code>mobile</code> was missing or blank.
Vehicle is required	<code>vehicle</code> was missing or blank.
Issue is required	<code>issue</code> was missing or blank.
Vehicle not recognised: '...'	The vehicle ID or name did not match the Get-Rescue catalogue. The value you sent is quoted back in the message.
Issue not recognised: '...'	None of the issue values matched. The unrecognised values are quoted back in the message.

WHAT HAPPENS TO THE TICKET

The ticket is created at the **Service Fee Quote** stage with the vehicle recorded as on-road, and service requested immediately. From there a Get-Rescue agent quotes the service fee, assigns a vendor, and drives the case through to completion. Your customer receives WhatsApp updates on the mobile number you supplied.

Each call creates a new ticket. There is no duplicate detection — if a request times out and you retry it, you may create two tickets for the same breakdown. Retry only when you have not received a response, and quote the `caseId` to Get-Rescue if you need a duplicate cancelled.

NOTES & LIMITS

- The `issue` field expects a plain comma-separated string, for example `"AIR FILL , STEPNEY CHANGE"` — not a JSON array.
- Vehicle and issue names must match the Get-Rescue catalogue. Capitalisation and surrounding spaces do not matter; spelling does. Request the current catalogue from Get-Rescue if you plan to send names rather than IDs.
- Record IDs are stable and are the more reliable option for an automated integration.
- Call this endpoint from your server, never from a browser or mobile app — the `publickey` would be exposed to end users. Contact Get-Rescue immediately if you believe it has leaked, so it can be rotated.