## Week 4: Double Machine Learning Using Random Forest

```
library(randomForest)
library(hdm)
library(ggplot2)
library(dplyr)
library(tidyr)
library(lmtest)
library(sandwich)
library(caret)
library(ranger)
```

## **Double Machine Learning**

We consider the data set GrowthData which is included in the package hdm. We evaluate the Convergence Hypothesis using Double Machine Learning.

```
## function to get data
getdata <- function(...) {
    e <- new.env()
    name <- data(..., envir = e)[1]
    e[[name]]
}

## now load your data calling getdata()
growth <- getdata(GrowthData)
dim(growth)</pre>
```

[1] 90 63

```
## create the outcome variable y, treatment d, and control covariates W
y <- growth$Outcome
x <- growth[-which(colnames(growth) %in% c("Outcome", "intercept", "gdpsh465"))]
d <- growth$gdpsh465</pre>
```

## **Unpenalized Linear Regression**

```
## fit the regular OLS
fit <- lm(y ~ ., data = growth[-which(colnames(growth) %in% c("Outcome", "intercept"))])
est <- summary(fit)$coef["gdpsh465", 1]

hcv_coefs <- vcovHC(fit, type = "HC1") ## HC - "heteroskedasticity cosistent"
se <- sqrt(diag(hcv_coefs))[2] ## estimated std errors

## calculate the 95% confidence interval for 'gdpsh465'
lower_ci <- est - 1.96 * se
upper_ci <- est + 1.96 * se
cat("95% Confidence Interval from unpenalized OLS: [", lower_ci, ",", upper_ci, "] \n", "with</pre>
```

```
95% Confidence Interval from unpenalized OLS: [ -0.07292335 , 0.05416737 ] with coefficient estimate: -0.009377989
```

Unpenalized OLS provides a rather noisy estimate (high standard error) of the speed of convergence, and does not allow us to answer the question about the convergence hypothesis since the confidence interval includes zero.

## **Double Machine Learning Using Random Forest**

```
## double machine learning with cross fitting
dml2_for_plm <- function(x, d, y, dreg, yreg, nfold = 5) {

nobs <- nrow(x) ## number of observations
foldid <- rep.int(1:nfold, times = ceiling(nobs / nfold))[sample.int(nobs)] ## define fold
I <- split(1:nobs, foldid) ## split observation indices into folds
ytil <- dtil <- rep(NA, nobs)
cat("fold: ")</pre>
```

```
for (b in seq_along(I)) {
    dfit <- dreg(x[-I[[b]], ], d[-I[[b]]]) ## take a fold out
    yfit \leftarrow yreg(x[-I[[b]], ], y[-I[[b]]]) ## take a foldt out
    dhat <- predict(dfit, x[I[[b]], ], type = "raw") ## predict the left-out fold</pre>
    yhat <- predict(yfit, x[I[[b]], ], type = "raw") ## predict the left-out fold</pre>
    dtil[I[[b]]] \leftarrow (d[I[[b]]] - dhat) ## record residual for the left-out fold
    ytil[I[[b]]] <- (y[I[[b]]] - yhat) ## record residial for the left-out fold
    cat(b, " ")
  rfit <- lm(ytil ~ dtil) ## estimate the main parameter by regressing one residual on the o
  coef.est <- coef(rfit)[2] ## extract coefficient</pre>
  se <- sqrt(vcovHC(rfit)[2, 2]) ## record robust standard error</pre>
  ## calculate the 95% confidence interval for 'qdpsh465'
  lower_ci <- coef.est - 1.96 * se</pre>
  upper_ci <- coef.est + 1.96 * se
  cat("\n 95% Confidence Interval from Double Machine Learning: [", lower_ci, ",", upper_ci,
  return(list(coef.est = coef.est, se = se, dtil = dtil, ytil = ytil)) ## save output and re
}
## treatment regression
dreg <- function(x, d) {</pre>
  train(
   x = x, y = d,
    method = "ranger",
    trControl = trainControl(method = "cv", number = 5),
    tuneGrid = expand.grid(
      mtry = floor(sqrt(ncol(x))),
                                         ## fixed at default
     splitrule = "variance",
     min.node.size = c(1, 5, 10)
                                         ## tune min node size
    ),
    num.trees = 500
                                          ## fix number of trees
  )
}
## outcome regression
yreg <- function(x, y) {</pre>
  train(
    x = x, y = y,
    method = "ranger",
    trControl = trainControl(method = "cv", number = 5),
```

```
tuneGrid = expand.grid(
    mtry = floor(sqrt(ncol(x))),
    splitrule = "variance",
    min.node.size = c(1, 5, 10)
),
    num.trees = 500
)

## execute double ML using random forest
set.seed(1)
dml2_rf <- dml2_for_plm(x, d, y, dreg, yreg, nfold = 5)</pre>
```

fold: 1 2 3 4 5 95% Confidence Interval from Double Machine Learning: [ -0.06324313 , -0.003580002 ] with coefficient estimate: -0.03341156