

# Detection of Epileptic Seizures using EEG Signals

Sarthak Gupta

*Division of Information Technology  
Netaji Subhas University of Technology  
New Delhi, India  
sarthakgupta259@gmail.com*

Siddhant Bagga

*Division of Information Technology  
Netaji Subhas University of Technology  
New Delhi, India  
siddhantbagga1@gmail.com*

Vikas Maheshkar

*Division of Information Technology  
Netaji Subhas University of Technology  
New Delhi, India  
vikas.maheshkar@gmail.com*

M.P.S. Bhatia

*Department of Computer Engineering  
Netaji Subhas University of Technology  
New Delhi, India  
bhatia.mps@gmail.com*

**Abstract**—Epilepsy is a neurological disorder which causes abnormal brain activity such as seizures. Electroencephalogram (EEG) signals are recordings of the electrical activity of brain, which are used extensively in many medical applications, including detection of epileptic seizures. Traditionally, neurologists made inferences by visual inspection. However, this was usually very time consuming and the results are subject to the expertise of the reader. Hence, automatic epileptic seizure detection techniques are needed, which are able to provide high quality results in a short time. In this paper, an approach has been proposed that uses Discrete Wavelet Transform to convert the EEG signal into the time-frequency domain. Approximation and detail coefficients were obtained after the discrete wavelet transform of EEG signals. Then, various features are extracted and then classification is carried out on a number of classifiers including convolutional neural networks, random forests etc for the detection of epilepsy seizure. Results show that our processing technique and the combination of features extracted provide far superior results than those obtained by applying the classifiers on the EEG signals directly. In our work, an accuracy of 99.29 was achieved which outperformed the conventional epileptic seizure detection techniques. The proposed approach is tested on Bonn University's EEG signal dataset.

**Index Terms**—EEG, Epilepsy, Seizure Detection, Discrete Wavelet Transform, CNN, Neural Network

## I. INTRODUCTION

EEG (Electroencephalogram) [1] is a way through which we can retrieve information regarding the physiological situation of a patient. EEG is a non-invasive testing method which contains a lot of information about the state of a patient's health. Through EEG, complicated dynamics of brain can be comprehended. EEG signals are very essential for detecting disorders like epilepsy seizures. The World Health Organisation has stated in a report that more than 50 million people worldwide suffer from epilepsy [2]. Manual detection of epileptic seizures is an extremely time-consuming and laborious task, and it is also subject to the expertise of the neurologist. Accurate and timely diagnosis is extremely important so that patients can start with the treatment procedure as early as possible.

Epileptic seizures are caused by disruption in the neuron firing mechanism [3], i.e. abnormalities in the electrical signals

generated by the brain. Since electroencephalogram (EEG) signals record the electrical activity of the brain, hence it is natural to use these signals for the task of detecting epileptic seizures. Lot of research in the domain of analysis of EEG and its classification is based upon the fact that processing of information in the brain is exhibited in the EEG signals as the transitions of electrical-activity in time and frequency dynamically. Hence, wavelet transforms are very effectively used for capturing the smallest of these transitions in the EEG signals.

Analysis of EEG signals is usually not an easy task, due to their non-linear and non-stationary nature. [4]. Therefore, automated ways are being developed extensively for the purpose of detection of epilepsy seizures. Discrete Wavelet Transform (DWT) is an appropriate tool for dealing with such signals, since it localizes the signal in both the time and the frequency domains. That is why it is preferred over some other methods like Fourier Transform which do not provide temporal resolution.




Fig. 1: (upper) EEG signal without seizure; (lower) EEG signal with seizure

In Figure 1, two signals from the dataset have been shown; one without seizure and the other with the seizure. In this paper, the Bonn University Dataset [5] has been used.

The rest of the paper is organized as follows. In section II, other relevant work utilizing EEG signals has been discussed. In section III, the proposed algorithm has been discussed. Then section V presents the results obtained without any pre-processing as well as results with our algorithm. Finally, section VI concludes this work.

## II. RELATED WORK

In the past few years, analysis of EEG signals has remained a topic of great interest for researchers. In [6], research has been conducted on frontal EEG asymmetry and emotion by applying Fourier Transform to raw EEG signals. Similarly, [7] has also used Fourier Transform for conducting further analysis on these signals. The basic problem with these approaches is that Fourier Transform can only localize the signal in frequency, not in both time and frequency simultaneously.

To overcome this problem of Fourier Transform, short-time Fourier Transform (STFT) was developed. STFT divides the entire signal into windows, and applies Fourier Transform to each window. In [8], the authors have used STFT for epileptic seizure detection. [9] also uses STFT to analyze background activity for autism. This approach succeeds in localizing a signal in both time and frequency to some extent. However, it is still highly dependant on the window size, and moreover, that window is the same for all frequencies.

Discrete Wavelet Transform (DWT) has the ability to localize a signal in both time and frequency simultaneously. It has been used widely for the analysis of EEG signals in the time-frequency domain [10] [11] [12]. In [10] epileptic seizures have been detected using DWT and Artificial Neural Network (ANN).

Empirical Mode Decomposition (EMD) is another algorithm that provides time-frequency representation of the signals. In this, the signal is broken down into many Intrinsic Mode Functions (IMFs). This technique has also been extensively used for EEG signal analysis [13] [14] [15].

In [16], approximation of entropy as well as energy has been used for the purpose of detecting seizure and spikes. DWT along with feature extracted like Hjorth variance has been used in [17]. Various other features have also been used like relative energy, amplitude index of fluctuation, variation coefficient [18] and the variances of wavelets [19]. Lacunarity along with the index of fluctuating [20] have also been explored. In [21] EMD (empirical-mode-decomposition) has been used. In [22] Fractal analysis has been used. In [ ] fuzzy systems have been used.

## III. PROPOSED WORK

The complete process of the method has been described in Figure 2.



Fig. 2: Schematic representation of proposed method

The raw EEG signal is first normalized, as described in Equation 1.

$$Normalize(x) = \frac{x - m}{s} \quad (1)$$

where  $x$  is the signal,  $m$  is the mean of the signal and  $s$  is the standard deviation. Normalizing the data decreases its variance and makes the model less susceptible to change in scale.

After that, Discrete Wavelet Transform is applied to the normalized data. Different types of wavelets could be used in DWT. We used Daubechies 4 (db4) wavelet with decomposition till level 4 (Figure 3). DWT is effectively used for the purpose of decomposition of a signal into approximation-coefficients and detail-coefficients. 1st level of decomposition is obtained after which further decomposition can be carried out into similar approximation and detail coefficients [23]. In our work, 4 levels of decomposition has been carried out. Further extraction of features can be carried out from detail coefficients.




Fig. 3: 4-level DWT decomposition tree [24]

On decomposition of the signal at any one level, we get a vector of detail coefficients and a vector of approximation coefficients. The approximation coefficient vector is obtained by making the signal go through a low-pass filter, while the detail coefficients vector is obtained by making the signal go through a high-pass filter. As can be seen from Figure 3, finally we get four vectors of detail coefficients (d1, d2, d3 and d4) and a vector of the approximation coefficients (a4).

Now, we need to extract features from these coefficients. We have extracted features from all the coefficients so that any significant information from the original signal is not lost. We have extracted seven features, which have been explained below. Each of these metrics was calculated for all the coefficient vectors. In the equations below,  $x$  is the coefficient vector and  $N$  is the number of elements in  $x$ .

### 1) Mean:

$$Mean(x) = \frac{1}{N} \sum_{i=1}^N x_i \quad (2)$$

### 2) Standard Deviation:

$$Standard\_Deviation(x) = \sqrt{\frac{\sum_{i=1}^N (x_i - m)^2}{N}} \quad (3)$$

where  $m$  is  $Mean(x)$ .

3) **Root Mean Square:**

$$Root\_Mean\_Square(x) = \sqrt{\frac{\sum_{i=1}^N (x_i^2)}{N}} \quad (4)$$

4) **Skew:** Skew is a measure of the asymmetry in the data.

$$Skew(x) = \frac{\sum_{i=1}^N (x_i - m)^3 / N}{s^3} \quad (5)$$

where  $s$  is  $Standard\_Deviation(x)$ .

5) **Kurtosis:** Kurtosis is a measure of outliers in the data.

$$Kurtosis(x) = \frac{\sum_{i=1}^N (x_i - m)^4 / N}{s^4} \quad (6)$$

6) **Maximum Fractal Length (MFL):**

$$MFL(x) = \log_{10} \left( \sqrt{\sum_{i=1}^{N-1} (x_{i+1} - x_i)^2} \right) \quad (7)$$

7) **Coefficient of Variation:** It signifies the variations in the amplitude of the signal.

$$V_c(x) = \left( \frac{Standard\_deviation(x)^2}{Mean(x)^2} \right) \quad (8)$$

8) **Shannon Entropy:** Entropy is the degree of uncertainty. Shannon Entropy is the capacity of the information present in the data.

$$H(x) = - \sum_{i=1}^N P(x_i) \log(P(x_i)) \quad (9)$$

where  $P(X)$  is the probability mass function for the EEG signal.

All these features were appended, and then passed through various classifiers which are described as follows. In Logistic Regression, a variable (binary dependent) is modelled using a logistic function. In SVM (Support Vector Machine), a hyperplane is used to separate categories. For instance, a linear straight line will be the hyperplane in case of a 2 dimensional plane by which the plane is divided into two parts. However, transformations can be carried out on the hyperplanes known as 'kernels'. In KNN (K-Nearest-Neighbours), the closest 'k' training instances are used for the predictive analysis. In Random forests, multifarious decision trees are constructed during the training. It is an Ensemble learning method. Xgboost is a library (open source) for gradient boosting. It is also an Ensemble Learning method. ANN refers to Artificial Neural Networks which are computational systems designed to replicate the information processing abilities as that of human neurons. CNN (Convolutional Neural Network) is an important part of Deep Learning consisting of multiple types of layers like Convolutional Layer, Pooling Layer and Fully Connected Layers.




Fig. 4: 1D-CNN Architecture

## IV. DATASET

The Bonn University Dataset [5] has been used. The dataset originally had 5 sets (A,B,C,D and E). All of these sets consisted of 100 single channel EEG recordings of length 23.6 seconds. We divided these signals into segments of 1 second, each containing 178 data points. Out of these 5 sets, only set 5 had EEG data for epileptic seizures. Hence, we modelled this as a binary classification problem, where samples from sets A, B, C and D represent the non-seizure class, while samples from set E represent the seizure class. Recording of these EEG signals was done through an amplifier with 128 channels. The frequency of sampling was 173 Hz.

## V. RESULTS

Results were taken for the following classifiers (Table I) - Logistic Regression, Support Vector Machine (SVM) with gaussian as well as linear kernels, K-Nearest Neighbours (KNN), Random Forest, Xgboost, Artificial Neural Network (ANN), and 1-D Convolutional Neural Network (CNN) (Figure 4).

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 80)	14320
dense_2 (Dense)	(None, 80)	6480
dense_3 (Dense)	(None, 1)	81
Total params: 20,881		
Trainable params: 20,881		
Non-trainable params: 0		

(a) For raw EEG signal

Layer (type)	Output Shape	Param #
dense_4 (Dense)	(None, 15)	465
dense_5 (Dense)	(None, 15)	240
dense_6 (Dense)	(None, 1)	16
Total params: 721		
Trainable params: 721		
Non-trainable params: 0		

(b) For proposed approach

Fig. 5: Number of parameters in ANN

Another important point to note is the number of parameters in ANN and CNN for Raw EEG Signal and for the proposed method. The proposed method produces better results for

Layer (type)	Output Shape	Param #
reshape_2 (Reshape)	(None, 178, 1)	0
conv1d_5 (Conv1D)	(None, 169, 50)	550
conv1d_6 (Conv1D)	(None, 160, 50)	25050
max_pooling1d_2 (MaxPooling1	(None, 80, 50)	0
conv1d_7 (Conv1D)	(None, 71, 50)	25050
conv1d_8 (Conv1D)	(None, 62, 50)	25050
global_average_pooling1d_2 (	(None, 50)	0
dropout_2 (Dropout)	(None, 50)	0
dense_8 (Dense)	(None, 1)	51
Total params: 75,751		
Trainable params: 75,751		
Non-trainable params: 0		

(a) For raw EEG signal

Layer (type)	Output Shape	Param #
reshape_1 (Reshape)	(None, 30, 1)	0
conv1d_1 (Conv1D)	(None, 26, 10)	60
conv1d_2 (Conv1D)	(None, 22, 10)	510
max_pooling1d_1 (MaxPooling1	(None, 11, 10)	0
conv1d_3 (Conv1D)	(None, 7, 10)	510
conv1d_4 (Conv1D)	(None, 3, 10)	510
global_average_pooling1d_1 (	(None, 10)	0
dropout_1 (Dropout)	(None, 10)	0
dense_7 (Dense)	(None, 1)	11
Total params: 1,601		
Trainable params: 1,601		
Non-trainable params: 0		

(b) For proposed approach

Fig. 6: Number of parameters in CNN

both ANN as well as CNN with significantly less number of parameters (Figure 5 and Figure 6).

TABLE I: ACCURACY ON VARIOUS CLASSIFIERS

Classifier	Raw EEG Signal	Proposed Approach
Logistic Regression	80.96	<b>97.57</b>
SVM (Gaussian Kernel)	79.04	<b>97.88</b>
SVM (Linear Kernel)	83.04	<b>97.64</b>
KNN	92.18	<b>97.54</b>
Random Forest	96.14	<b>98.43</b>
Xgboost	97.23	<b>98.26</b>
ANN	95.12	<b>97.56</b>
CNN	79.04	<b>99.29</b>

Table II shows the comparison of our most accurate classifier with a few other approaches. In [25], both wavelet based features (energy, entropy, mean, minimum, maximum and standard deviation) and statistical features from raw signal (interquartile range and mean absolute deviation) have been

extracted, and then a linear classifier has been used for classification of the data. In [26], raw EEG signal has been normalized and fed to a 13-layer 1-D Convolutional Neural Network (CNN). In [12], DWT has been applied and statistical features (average power, standard deviation and mean absolute value) have been extracted. Then k-nearest neighbour (KNN) algorithm is used to classify the data. In this, the test data points are assigned to a class based on the "k" nearest training data points in the feature vector space. [27] explored the Hermite transform for processing of the EEG signal. Permutation entropy, histogram features and statistical features were extracted from the decomposed signal and passed to least-square support vector machine (Ls-SVM) for classification. In [28] the authors have attempted to extract the temporal features of the EEG signal using an architecture of the family of Recurrent Neural Networks, called Long Short Term Memory Networks (LSTM). The authors of [29] have used a 1-D Residual Convolutional Neural Network (Res-CNN) on raw data. Res-CNN consists of CNN-like layers but with residual blocks i.e. blocks with skip connections, which typically allow training deeper networks with richer representation of the data.

TABLE II: Comparison with other approaches

Reference	Method	Accuracy (%)
-	Raw Signal + Xgboost	97.23
Ahammad et al [25]	DWT + Linear Classifier	84.20
Acharya et al [26]	Raw Signal + CNN	88.67
Sharmila et al [12]	DWT + k-NN	97.10
Siuly et al [27]	Hermite Transform + LS-SVM	97.60
Ahmedt et al [28]	Raw Signal + LSTM	95.54
Lu et al [29]	Raw Signal + Res-CNN	99.00
Our approach	DWT + CNN	<b>99.29</b>

## VI. CONCLUSION AND FUTURE WORK

The results exhibit that our proposed approach has improved the accuracy of the epileptic seizure detection by a significant amount. Decomposition of signals using discrete wavelet transform followed by appropriate extraction of features lead to the improvement in the accuracy of detection of epileptic seizure detection. An accuracy of 99.29 percent is achieved in our approach which is considerably much better as compared to conventional classification methods.

In the future, meta-heuristic algorithms can be used to extract the best subset of features. The use of Huang-Hilbert transform in place of DWT can also be explored. Combination of wavelet transforms can also be explored.

## REFERENCES

- [1] H. Ocak, "Automatic detection of epileptic seizures in eeg using discrete wavelet transform and approximate entropy," *Expert Systems with Applications*, vol. 36, no. 2, pp. 2027–2036, 2009.
- [2] "Epilepsy," Feb 2019. [Online]. Available: <https://www.who.int/news-room/fact-sheets/detail/epilepsy>
- [3] H. E. Scharfman, "The neurobiology of epilepsy," *Current neurology and neuroscience reports*, vol. 7, no. 4, pp. 348–354, 2007.

- [4] W. Klonowski, "Everything you wanted to ask about eeg but were afraid to get the right answer," *Nonlinear Biomedical Physics*, vol. 3, no. 1, p. 2, 2009.
- [5] R. G. Andrzejak, K. Lehnertz, F. Mormann, C. Rieke, P. David, and C. E. Elger, "Indications of nonlinear deterministic and finite-dimensional structures in time series of brain electrical activity: Dependence on recording region and brain state," *Physical Review E*, vol. 64, no. 6, p. 061907, 2001.
- [6] J. J. Allen, J. A. Coan, and M. Nazarian, "Issues and assumptions on the road from raw signals to metrics of frontal eeg asymmetry in emotion," *Biological psychology*, vol. 67, no. 1-2, pp. 183–218, 2004.
- [7] W. Sařabun, "Processing and spectral analysis of the raw eeg signal from the mindwave," *Przegląd Elektrotechniczny*, vol. 90, no. 2, pp. 169–174, 2014.
- [8] A. T. Tzallas, M. G. Tsipouras, and D. I. Fotiadis, "Epileptic seizure detection in eegs using time–frequency analysis," *IEEE transactions on information technology in biomedicine*, vol. 13, no. 5, pp. 703–710, 2009.
- [9] H. Behnam, A. Sheikhan, M. R. Mohammadi, M. Noroozian, and P. Golabi, "Analyses of eeg background activity in autism disorders with fast fourier transform and short time fourier measure," in *2007 International Conference on Intelligent and Advanced Systems*. IEEE, 2007, pp. 1240–1244.
- [10] Y. Kumar, M. Dewal, and R. Anand, "Epileptic seizures detection in eeg using dwt-based apen and artificial neural network," *Signal, Image and Video Processing*, vol. 8, no. 7, pp. 1323–1334, 2014.
- [11] I. Omerhodzic, S. Avdakovic, A. Nuhanovic, and K. Dizdarevic, "Energy distribution of eeg signals: Eeg signal wavelet-neural network classifier," *arXiv preprint arXiv:1307.7897*, 2013.
- [12] A. Sharmila and P. Geethanjali, "Dwt based detection of epileptic seizure from eeg signals using naive bayes and k-nn classifiers," *Ieee Access*, vol. 4, pp. 7716–7727, 2016.
- [13] S. Li, W. Zhou, Q. Yuan, S. Geng, and D. Cai, "Feature extraction and recognition of ictal eeg using emd and svm," *Computers in biology and medicine*, vol. 43, no. 7, pp. 807–816, 2013.
- [14] R. J. Martis, U. R. Acharya, J. H. Tan, A. Petznick, R. Yanti, C. K. Chua, E. K. Ng, and L. Tong, "Application of empirical mode decomposition (emd) for automated detection of epilepsy using eeg signals," *International journal of neural systems*, vol. 22, no. 06, p. 1250027, 2012.
- [15] F. Riaz, A. Hassan, S. Rehman, I. K. Niazi, and K. Dremstrup, "Emd-based temporal and spectral features for the classification of eeg signals using supervised learning," *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, vol. 24, no. 1, pp. 28–35, 2015.
- [16] H. Adeli, S. Ghosh-Dastidar, and N. Dadmehr, "A wavelet-chaos methodology for analysis of eegs and eeg subbands to detect seizure and epilepsy," *IEEE Transactions on Biomedical Engineering*, vol. 54, no. 2, pp. 205–211, 2007.
- [17] S. Raghunathan, A. Jaitli, and P. P. Irazoqui, "Multistage seizure detection techniques optimized for low-power hardware platforms," *Epilepsy & behavior*, vol. 22, pp. S61–S68, 2011.
- [18] Y. Liu, W. Zhou, Q. Yuan, and S. Chen, "Automatic seizure detection using wavelet transform and svm in long-term intracranial eeg," *IEEE transactions on neural systems and rehabilitation engineering*, vol. 20, no. 6, pp. 749–755, 2012.
- [19] S. Xie and S. Krishnan, "Wavelet-based sparse functional linear model with applications to eegs seizure detection and epilepsy diagnosis," *Medical & biological engineering & computing*, vol. 51, no. 1-2, pp. 49–60, 2013.
- [20] W. Zhou, Y. Liu, Q. Yuan, and X. Li, "Epileptic seizure detection using lacunarity and bayesian linear discriminant analysis in intracranial eeg," *IEEE Transactions on Biomedical Engineering*, vol. 60, no. 12, pp. 3375–3381, 2013.
- [21] V. Bajaj and R. B. Pachori, "Epileptic seizure detection based on the instantaneous area of analytic intrinsic mode functions of eeg signals," *Biomedical Engineering Letters*, vol. 3, no. 1, pp. 17–21, 2013.
- [22] Q. Yuan, W. Zhou, Y. Liu, and J. Wang, "Epileptic seizure detection with linear and nonlinear features," *Epilepsy & Behavior*, vol. 24, no. 4, pp. 415–421, 2012.
- [23] N. Acir, I. Oztura, M. Kuntalp, B. Baklan, and C. Guzelis, "Automatic detection of epileptiform events in eeg by a three-stage procedure based on artificial neural networks," *IEEE Transactions on Biomedical Engineering*, vol. 52, no. 1, pp. 30–40, 2004.
- [24] S. Narejo, E. Pasero, and F. Kulsoom, "Eeg based eye state classification using deep belief network and stacked autoencoder," *Int. J. Electr. Comput. Eng*, vol. 6, p. 3131, 2016.
- [25] N. Ahammad, T. Fathima, and P. Joseph, "Detection of epileptic seizure event and onset using eeg," *BioMed research international*, vol. 2014, 2014.
- [26] U. R. Acharya, S. L. Oh, Y. Hagiwara, J. H. Tan, and H. Adeli, "Deep convolutional neural network for the automated detection and diagnosis of seizure using eeg signals," *Computers in biology and medicine*, vol. 100, pp. 270–278, 2018.
- [27] S. Siuly, O. F. Alcin, V. Bajaj, A. Sengur, and Y. Zhang, "Exploring hermite transformation in brain signal analysis for the detection of epileptic seizure," *IET Science, Measurement & Technology*, vol. 13, no. 1, pp. 35–41, 2018.
- [28] D. Ahmedt-Aristizabal, C. Fookes, K. Nguyen, and S. Sridharan, "Deep classification of epileptic signals," in *2018 40th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*. IEEE, 2018, pp. 332–335.
- [29] D. Lu and J. Triesch, "Residual deep convolutional neural network for eeg signal classification in epilepsy," *arXiv preprint arXiv:1903.08100*, 2019.