Playwright with Java: compact cheatsheet

STEP 1 Getting started

1.1 What Playwright is and how it works

You write steps Open, type, click, check. In Java, Python, JavaScript or TypeScript.

Messages Each call becomes a small message. The driver is the same for every language.

Real browsers Real clicks and real typing. The page cannot tell it apart from a person.

It waits Visible, stable, enabled. No fixed sleeps, so far fewer flaky tests.

Remember Playwright drives real browsers through one driver, waits for elements before it acts, and works the same way in Java, Python, JavaScript and TypeScript.

```
try (Playwright playwright = Playwright.create()) {
```
start the Playwright driver

```
Browser browser = playwright.chromium().launch();
```
start a real Chromium, with no window

```
Page page = browser.newPage();
```
open a new tab

```
.setPath(java.nio.file.Paths.get("products.png")));
```
save a picture of the page

```
page.navigate("http://localhost:4173/login");
```
Open the sign in page.

```
page.getByLabel("Email").fill("asha@shop.example");
```
Type the email into the box labelled Email.

```
page.getByLabel("Password").fill("s3cret");
```
Type the password.

```
page.getByRole(AriaRole.BUTTON, new Page.GetByRoleOptions().setName("Sign in")).click();
```
Click the button called Sign in. The shop signs Asha in and opens the products page.

```
assertThat(page.getByText("Hello, Asha")).isVisible();
```
Check that the greeting says Hello, Asha. The check waits until it appears.

TRAP People often ask for Playwright in C, C++ or Go. There is no official Playwright for C or C++. For Go there is a community project, playwright-go, which is not made by the Playwright team. This subject sticks to the official languages so that every example is supported and up to date.

1.2 Installing Playwright and your first project

Runtime Install your language first. Check it with a version command.

Package Maven, pip or npm. Pin the exact version.

Browsers Playwright brings its own. --with-deps adds the Linux libraries.

Record Click around, get code. Then clean it up and add a check.

Remember Install the runtime, the Playwright package and its browsers, record a first draft with codegen, then turn it into a real test with a clear name and a check.

TRAP Keep one Playwright version per project and update on purpose. Each Playwright release expects its own browser builds. After you update the package, run the install command again, or the tests stop with an error that says the browser executable does not exist.

STEP 2 Browser handling

2.1 Browsers, contexts, pages and devices

Browser Start once, about 0.5 s. Shared by many tests.

Context A fresh, empty profile. Its own cookies, storage and permissions.

Page One tab. Tabs in a context share the login.

Emulation Size, locale, time zone, location. Set on the context, nothing on your computer changes.

Remember Start one browser, give every test a new context, and set what the site should see, such as a phone or a German user, with context options.

```
.setHeadless(true)
```
no window. Use false to watch it work

```
.setSlowMo(100)
```
wait 100 ms before every action

```
.setGeolocation(28.6139, 77.209)
```
New Delhi

TRAP Emulation catches most layout and touch bugs and costs nothing. Some bugs only show on real hardware, such as a keyboard covering a field or a slow phone. Many teams run emulated phones on every commit and real devices in a cloud service before a release.

2.2 Navigation, frames, dialogs, files and events

Navigation goto waits for load. After a click, wait for the new URL.

Iframes Step in first. Then locate as usual.

Dialogs Dismissed by default. Handle them before the click.

Files Wait for downloads. Fill file inputs directly.

Remember Start waiting before the click for anything the click creates: a new URL, a popup, a dialog or a download.

```
page.waitForURL("**/products");
```
the app moves on by itself

```
page.navigate("http://localhost:4173/frames");
```
Open the checkout page. The card form is an iframe from the payment company.

```
page.frameLocator("iframe[title=\"Payment form\"]").getByLabel("Card number").fill("4111 1111 1111 1111");
```
Step into the iframe and type the card number.

```
page.frameLocator("iframe[title=\"Payment form\"]").getByLabel("Expiry").fill("12/29");
```
Type the expiry date.

```
assertThat(page.getByRole(AriaRole.STATUS)).hasText("Paid with card ending 1111");
```
Back in the main page, the shop shows the result.

```
download.saveAs(Paths.get("reports", download.suggestedFilename()));
```
keep a copy

```
assertThat(page.getByRole(AriaRole.LISTITEM)).hasCount(5);
```
wait for the list

```
Object sum = page.evaluate("([a, b]) => a + b", List.of(20, 199));
```
pass values in

TRAP Do not wait for the network to go quiet. A chat widget or analytics script can keep it busy forever. Wait for what the user is waiting for: a URL, a heading or a message. Every check with expect already waits.

STEP 3 Finding and using elements

3.1 Locators: finding elements

Role and name What the user sees. The first choice.

Forms Boxes by their label. Placeholder when there is none.

Narrow down Card first, then button. hasText, has, hasNot.

One element Actions need exactly one. The error lists them all.

Remember A locator is searched again every time you use it, and an action needs exactly one match.

```
Locator cards = page.getByRole(AriaRole.LISTITEM);
```
nothing is searched yet

```
page.getByText("Remember me").click();
```
clicking a label ticks its box

```
assertThat(page.getByTestId(Pattern.compile("^product-"))).hasCount(5);
```
all product cards

```
assertThat(add).hasCount(4);
```
counting many is fine

```
PlaywrightException error = assertThrows(PlaywrightException.class, () → add.click());
```
acting on many is not

```
page.navigate("http://localhost:4173/orders");
```
Open the orders page. It shows 5 of 7 orders per page.

```
page.getByRole(AriaRole.BUTTON, new Page.GetByRoleOptions().setName("Total")).click();
```
Click the Total column header to sort by total, smallest first.

```
assertThat(page.getByRole(AriaRole.STATUS)).hasText("Order #1004 deleted");
```
The status message confirms which order went away.

```
page.getByRole(AriaRole.BUTTON, new Page.GetByRoleOptions().setName("Next")).click();
```
Go to the next page of the table.

```
assertThat(page.getByText("Page 2 of 2")).isVisible();
```
Check the page counter by its text.

```
.filter(new Locator.FilterOptions().setHas(page.getByRole(AriaRole.CELL)));
```
skip the header row

TRAP Long XPaths copied from the browser tools, such as /html/body/div[2]/div/form/input, break as soon as one box is added to the page. Recorded tests from older tools are full of them, and they are the first thing to replace when a team moves to Playwright.

TRAP first(), last() and nth() depend on the order of the page. When the order changes, they quietly pick another element. Prefer a filter by text when you can.

3.2 Actions and auto-waiting

Auto-waiting Checks before every action. No sleeps needed.

Timeouts The error says which check failed. Read it before using force.

Typing fill for most boxes. pressSequentially for key by key.

Forms check, selectOption, dragTo. Found by their labels.

Remember Never sleep. Every action waits until the element is ready, and when you need more, wait for the exact thing you need.

```
help.hover();
```
the mouse rests on it
```
page.mouse().move(0, 0);
```
move the mouse away
```
help.focus();
```
keyboard users reach it with Tab
```
search.fill("desk");
```
sets the whole value at once
```
search.pressSequentially("mug", new Locator.PressSequentiallyOptions().setDelay(50));
```
one key at a time
```
page.keyboard().press("Control+K");
```
a shortcut for the whole page
```
page.navigate("http://localhost:4173/forms");
```
Open the feedback form.
```
page.getByLabel("Your name").fill("Asha");
```
Type the name into the box labelled Your name.
```
page.getByLabel("Topic").selectOption("delivery");
```
Choose Delivery in the Topic drop down.
```
page.getByLabel("Happy").check();
```
Pick the Happy radio button.
```
page.getByLabel("Message").fill("The parcel came a day early.");
```
Write a short message.
```
page.getByLabel("Send me the newsletter").check();
```
Tick the newsletter box.
```
page.getByRole(AriaRole.BUTTON, new Page.GetByRoleOptions().setName("Send feedback")).click();
```
Send the form. Playwright scrolls the button into view by itself.
```
assertThat(page.getByRole(AriaRole.STATUS)).containsText("Topic: delivery, mood: happy");
```
The thank you line shows every value the page received.
```
page.getByLabel("Topic").selectOption(new SelectOption().setLabel("Payment"));
```
or by the text you see
```
page.getByLabel("Order date").fill("2026-10-01");
```
dates use yyyy-mm-dd
```
page.getByLabel("Volume").fill("8");
```
a slider
```
done.hover();
```
a second move, so the page gets its dragover event

TRAP Reaching for force is often a sign the test found the wrong element, or that a real user could not click it either. Read the call log first.

3.3 Assertions that wait for the page

Web-first Retries until true. 5 seconds by default.

Text Exact or contains. Lists check order too.

Negative Waits for things to go. toHaveCount(0) for none.

Soft Keep going. Report every problem.

Remember Check the page with assertions that retry, and never read a value first and check it later.

```
Locator offer = page.getByTestId("offer");
```
shows up 1.2 s after the click
```
assertThat(offer).isVisible();
```
retries until it shows
```
page.navigate("http://localhost:4173/products");
```
Open the products page.
```
page.getByPlaceholder("Search products").fill("bottle");
```
Search for bottle.
```
assertThat(page.getByRole(AriaRole.LISTITEM)).containsText("Water bottle");
```
One card is left, and it is the right one.
```
assertThat(page.getByPlaceholder("Search products")).hasValue("bottle");
```
The search box keeps what was typed.
```
page.getByPlaceholder("Search products").fill("phone");
```
Search for something the shop does not sell.
```
assertThat(page.getByRole(AriaRole.BUTTON, new Page.GetByRoleOptions().setName("Add to cart"))).hasCount(0);
```
No Add to cart buttons are left. A negative check also waits.
```
assertThat(page.getByText("Loading products…")).not().isVisible();
```
waits until it goes away
```
() → assertThat(page.getByTestId("product-1")).containsText("₹25", quick),
```
wrong on purpose
```
() → assertThat(page.getByTestId("product-4")).containsText("Add to cart", quick),
```
wrong on purpose
```
() → assertThat(page.getByTestId("product-5")).containsText("₹349"));
```
right
```
assertThat(response).isOK();
```
a Playwright check for API answers
```
JsonArray products = new Gson().fromJson(response.text(), JsonArray.class);
```
Gson comes with Playwright
```
assertEquals(5, products.size());
```
plain JUnit checks

TRAP A rule that catches many flaky tests: never put await inside expect. Write `assertThat(locator).isVisible()`, not `assertTrue(locator.isVisible())`.

STEP 4 The test runner

4.1 The test runner: organise, tag, parameterise and configure

Runner Finds and runs tests. One per language.

Tags Run a slice. Smoke now, regression tonight.

Data One test, many rows. Each row is its own result.

Config Settings in one place. Projects for each device.

Remember Tests say what to check. The runner and its configuration decide where, how and with what settings they run.

```
void search(String term, int count, String first, Page page) {
```
the data first, then Page

TRAP A test.only left in the code silently skips every other test. Set forbidOnly in the CI config so such a run fails instead.

4.2 Fixtures, hooks and set up once

Hooks Around every test. Simple and visible.

Fixtures Only when asked for. Set up, use, tear down.

Automatic Every test gets it. Guards and recordings.

Once per run Health check, data. Before any test.

Remember Put set up where it belongs: in the test if one test needs it, in a fixture if several do, and in a setup step if the whole run does.

```
page.waitForTimeout(100);
```
Java hands over browser events only while a Playwright call runs
```
@BeforeAll
```
once for this class

4.3 Parallel runs, retries, timeouts and sharding

Workers Tests at the same time. Each with its own browser.

Isolation No shared data. Lock what must be shared.

Retries Try again on failure. Flaky is still a bug.

Shards Split across machines. Merge the reports.

Remember Parallel runs only work when every test can run alone, in any order, next to any other test.

```
assertThat(page.getByRole(AriaRole.ROW)).hasCount(6);
```
a header row and five orders
```
@ResourceLock("people")
```
never at the same time as another test holding "people"
```
@Test
```
no lock, runs alongside
```
private static int attempt = 0;
```
the rerun happens in the same JVM
```
@Timeout(30)
```
each test, in seconds
```
PlaywrightAssertions.setDefaultAssertionTimeout(5_000);
```
each assertThat check
```
page.setDefaultTimeout(10_000);
```
each click, fill, check and so on
```
page.setDefaultNavigationTimeout(15_000);
```
each navigate
```
assertThat(page.getByTestId("offer")).hasText("Buy 2 mugs, get 1 free");
```
the 5 s default is enough

TRAP The Playwright docs advise against it: isolated tests are faster and easier to retry.

STEP 5 Network and APIs

5.1 Network: watch, mock and change requests

Watch See every call. Wait for the one you need.

Mock Answer with your data. No server needed.

Change Real answer, one field changed. The rest stays real.

Replay Record once. Same data every run.

Remember Mock what you do not own or cannot control. Keep a few tests against the real API, so the mocks do not drift away from it.

```
APIResponse response = route.fetch();
```
ask the real server

```
for (JsonElement product : products) {
```
then change one field

```
page.routeWebSocket("**/ws/stock", ws -> {
```
no real server is contacted

TRAP Replay matches the address and the method exactly, and for POST also the body. A request that matches nothing in the file is aborted, unless you pass notFound: fallback.

5.2 API testing and signing in once

API tests No browser at all. Status, data, errors.

Tokens Proof of who calls. Keep them in secrets.

Mix API for set up. Page for the check.

Sign in once Save the state. Every test starts signed in.

Remember Use the page for what the user sees. Use the API for everything you only need to get ready.

```
assertEquals(401,
request.get("/api/cart").status());
```
nobody is signed in yet

```
page.addInitScript("localStorage.setItem
('token', '" + token + "')");
```
the shop keeps its token here

```
page.request().post("/api/cart",
RequestOptions.create().setData(Map.of("
productId", 3)));
```
arrange the cart without clicking

```
page.navigate("/products");
```
no sign in steps here

```
assertThat(page).hasURL(Pattern.compile(
"/cart$"));
```
not sent to /login

TRAP Keep real passwords and tokens out of test code. Read them from environment variables, such as process.env.SHOP_PASSWORD, os.environ["SHOP_PASSWORD"] or System.getenv("SHOP_PASSWORD"), and set them as secrets in CI. The framework chapter shows a .env file for local runs.

TRAP The state file holds a live session that anyone could use. Add playwright/.auth to .gitignore, and let each run create it fresh.

STEP 6 Debugging and quality

6.1 Debugging failed tests: errors, traces, reports and the Inspector

Error Expected and received. Read it first.

Evidence Screenshot, video, trace. Kept on failure.

Trace Every action replayed. DOM, network, console.

Inspector Run it yourself. One step at a time.

Remember Read the error, then the trace, and only then run the test by hand. Most failures are solved at the first step.

```
assertThat(page.locator("#hello")).hasTe
xt("Hello, Asha!");
```
the page says Hello, Asha

```
.setTrace(Options.Trace.RETAIN_ON_FAILUR
E)
```
keep the trace only when a test fails

```
.setRecordVideoDir(Paths.get("videos")))
;
```
a video of every test

TRAP Remove page.pause() before you commit. It needs a headed browser and is only useful while you debug.

6.2 Visual, accessibility and time checks

Screenshot How it looks. Baseline and diff.

Aria snapshot How it reads. Every language.

axe scan Who can use it. WCAG rules.

Fake clock Any date, any delay. No waiting.

Remember Screenshots check pixels, aria snapshots check structure, axe checks access, and the clock checks time. Use each for the mistakes it is good at.

```
.withTags(List.of("wcag2a", "wcag2aa"))
```
the WCAG 2 A and AA rules

```
page.clock().runFor("05:00");
```
5 minutes of timers, in a moment

TRAP toHaveScreenshot is part of Playwright Test. Python and Java have page.screenshot() to save a picture, but no comparison built in. Teams add a library for it or use a visual testing service. The aria snapshot below works in every language.

TRAP An automatic scan finds only part of the problems. It cannot tell whether alt text is useful or whether the tab order makes sense. Keep a few manual checks with a keyboard and a screen reader, and use the scan to stop the easy mistakes from coming back.

STEP 7 Framework design

7.1 Page objects and components

Page object One class per screen. Locators in one place.

Component Parts that repeat. Root locator first.

Fixtures Hand them out. No set up in tests.

Checks Stay in the test. Easy to read.

Remember The test says what, the page object says how. A change to the screen is fixed in one class.

7.2 Framework design, step by step

Settings From the environment. No secrets in Git.

Layers One job each. Data, API, pages.

Fixtures Fresh session per test. Safe in parallel.

Tests By feature, tagged. Steps and checks only.

Remember Framework code and tests live apart. Tests say what, the framework says how, and the environment says where.

```
page.onceDialog(dialog ->
dialog.accept());
```
the shop asks to confirm the order

```
@BeforeClass(alwaysRun = true)
```
alwaysRun: also when a group such as smoke is chosen

```
api.addToCart(token,
Product.WATER_BOTTLE.id, 2);
```
arrange through the API, test the UI

TRAP Java has no fixtures like Playwright Test or pytest. BaseTest plays that part: TestNG runs @BeforeClass, @BeforeMethod and @AfterMethod around every test, and with parallel="classes" each class keeps its own Playwright on its own thread. Playwright objects are not safe to share between threads.

7.3 CI/CD pipelines

Every push Tests run by themselves. Nobody has to remember.

Fresh machine Install everything each time. Or use the Docker image.

Secrets From the CI settings. Masked in the logs.

Evidence Reports kept, pass or fail. Traces explain failures.

Remember CI runs the same three steps everywhere: a machine that can run browsers, the packages and browsers installed, then the tests with CI settings and secrets.

TRAP Secrets are not given to workflows that run for pull requests from forks, so a fork cannot read your passwords. Tests that need them are skipped or fail there, which is expected.

TRAP Never fix a red pipeline by adding a skip or a longer sleep. Find out whether the app or the test is wrong. The trace from the debugging chapter shows the page at every step of the failed run.

7.4 Reporting labs

For you list, dot, -v. Right now.

For CI Counts and history. Every server reads it.

For testers Error, screenshot, trace. Why it failed.

For everyone Same report, any language. Trends and labels.

Remember Write several reports from one run: a short one for the terminal, JUnit XML for CI, and an HTML report with evidence for people.

```
test.getModel().setStartTime(new
Date(result.getStartMillis()));
```
the real times, not the report time

```
result.setAttribute("screenshot",
test.screenshot());
```
ExtentReporter reads it at the end

TRAP A reporter must not change whether the run passed. It only describes the run, so CI still sees exit code 1 when a test failed.

7.5 What's new, and AI test agents

Releases New browsers each time. Read the notes first.

New APIs In every language. Like consoleMessages.

Test Agents Plan, generate, heal.

Playwright MCP A browser for assistants. Any language.

Remember Update on a branch and read the release notes. Let AI write tests, but review them like any other code, and make sure each one can fail.