Automated Quality Assessment of LLM Generated Unit Tests: A Home Assistant Case Study

MSc Software Engineering, Blekinge Institute of Technology (BTH), Karlskrona, Sweden

Karri Rakesh Reddy

Abstract

LLM generated unit tests are usually judged by whether they run and cover code. We ask whether they are also good tests. As a case study we use the Home Assistant `threshold` integration, whose developer tests already reach 100.0 % line coverage. Claude Sonnet 5.5 generated five samples for each of three target modules, and we compare them with the developer tests on seven quality measures, among them mutation score and test smells. Of the generated tests, 97.6 % pass stably. Coverage could not separate the suites; mutation score could. A single sample is clearly weaker than the developer file, especially for the configuration flow (mutants killed: 5.4 % against 47.6 %), and the union of all samples overtakes the developers only with about 2.5 times as many tests. Automatic scores agree only weakly with a blinded manual review of 60 tests (best: relevance, Spearman ρ = 0.30). Metamorphic prompt changes show no clear effect beyond sampling noise.

Note. The behaviour list (`data/behaviours.yaml`) used for relevance and completeness is a *draft* until the author has checked it.

Introduction

Large language models can write unit tests, and several systems report that a large share of the generated tests compile, run, and add coverage (Alshahwan et al. 2024; Schäfer et al. 2024; Lemieux et al. 2023). Coverage alone is a weak statement about test *quality*, however: a test suite can execute every line and still miss most defects. This study assesses LLM generated unit tests along several automatically measurable dimensions and checks the automatic scores against a blinded manual review.

The case study is the `threshold` integration of Home Assistant core (tag 2026.10.1), a small component with an entity, a configuration flow and a migration path. Its developers' tests form the human baseline and already reach complete line coverage, which is why branch coverage and mutation score are the main comparison measures.

We ask three research questions.

- **RQ1.** How do LLM generated tests compare with the developers' tests on executability, coverage, mutation score, traceability, maintainability (test smells), relevance and completeness?
- **RQ2.** How well do the automatic scores agree with a blinded manual review of a sample (Spearman's ρ, weighted Cohen's κ)?

- **RQ3.** How sensitive are generated tests to metamorphic changes of the prompt (paraphrase, renamed local variables, reordered functions, stripped comments), compared with the normal noise between repeated samples?

Related work

LLM based unit test generation. TestGen-LLM at Meta (Alshahwan et al. 2024) filters generated Kotlin tests through build, pass, and coverage-improvement checks before accepting them. Test-Pilot (Schäfer et al. 2024) evaluates LLM generated tests for JavaScript packages and uses failure feedback to repair them. CodaMosa (Lemieux et al. 2023) couples search based test generation with an LLM to escape coverage plateaus. ChatUniTest (Chen et al. 2024) is a framework for Java that follows a generate, validate, repair loop, and CoverUp (Altmayer Pizzorno and Berger 2025) drives Python test generation with coverage feedback. A survey (Wang et al. 2024) organises the wider field of software testing with LLMs.

Test quality beyond coverage. Mutation testing (Jia and Harman 2011) estimates fault detection ability by injecting small syntactic faults. Siddiq et al. (Siddiq et al. 2024) study LLM generated JUnit tests and report on test smells in them; PyNose (Wang et al. 2021) is a test smell detector for Python, which motivates our own AST based detector. Test-to-code traceability links have been recovered by combining several signals (White et al. 2020), an idea we reuse in a light form.

Robustness. ReCode (Wang et al. 2023) evaluates code generation models under semantics preserving perturbations of prompts. Metamorphic testing (Chen et al. 2018) provides the general idea of relating outputs of related inputs, which we apply to the generation prompt.

Method

Pipeline. The `testquality` tool (this repository) generates tests with the Anthropic Messages API, runs them in the Home Assistant checkout as a subprocess, and computes all metrics from the run artefacts. Every LLM call is logged in full (`data/runs/<run>/calls.jsonl`). The developers' tests are never shown to the model: a prompt contains only the integration's own source files and the tool aborts if a developer test name occurs in a prompt.

Generation. For each of three target modules (`binary_sensor.py`, `config_flow.py`, `__init__.py`) one prompt asks for a pytest module; every test must carry a docstring with `Behaviour:` and `Target:` lines. $k = 5$ samples per prompt are drawn to measure the noise floor. No sampling parameters are sent. The main model is `claude-sonnet-5-5`.

Metrics (full definitions in `docs/metrics.md`).

- *Executability*: collect rate, pass rate over three repeated runs, flaky rate, and failure types. Only stably passing tests are *valid* and count for every other metric.
- *Coverage*: line and branch coverage of the component (coverage.py with per-test contexts).
- *Mutation score*: mutmut 3.x on the component. We report the score over a fixed population of mutants (killed / all) and the conventional killed / (killed + survived).

- *Traceability*: the function suggested by the test name, the last component function entered before the first assertion (dynamic trace), and the declared `Target:` are compared and scored 0, 0.5 or 1.
- *Maintainability*: ten test smells with a custom AST detector.
- *Relevance and completeness*: a draft list of behaviours with code line ranges; a test is relevant if it exercises a listed behaviour, and completeness is the share of behaviours exercised.
- *Manual review (RQ2)*: 60 tests (20 developer, 40 LLM) in random order with the origin hidden, rated 1-5 on relevance, clarity of purpose, maintainability and oracle strength. Agreement is measured by Spearman's ρ and linearly weighted Cohen's κ (Cohen 1968).
- *Metamorphic sensitivity (RQ3)*: MR1 three paraphrases of the prompt; MR2 renamed local variables, MR3 reordered functions and methods, MR4 stripped comments in the shown source. Each transformation is proven meaning preserving by tests (AST equality up to renaming, equal definition sets). Variants are compared with the baseline samples by Mann-Whitney U (Mann and Whitney 1947), Cliff's δ (Cliff 1993), and by the Jaccard overlap of covered lines and of killed mutants relative to the overlap between baseline samples.

Setup

Home Assistant core is checked out at tag 2026.10.1 (branch `study-pinned`) with its own virtual environment. The tool runs in a separate environment (Python 3.12 or newer, `uv`). Generated tests are staged under `tests/components/threshold/_llm_generated/<run_id>/` and removed after each run; no other Home Assistant file is modified. Mutation testing runs in a scratch workspace outside the Home Assistant tree. Coverage uses the `ctrace` core of coverage.py, because the default core of Python 3.12 and newer drops per-test contexts. Model, prompt version, costs and all decisions are recorded in `docs/DECISIONS.md`.

Results

Key findings

- **Executability.** 15 of 15 LLM samples collect; 97.6 % of the 294 generated tests pass in all three runs (developer tests: 100.0 %); flaky rate 0.0 %.
- **Coverage and mutation (suite level).** Line coverage 100.0 % (developer) vs 99.6 % (union of the LLM samples); branch coverage 93.1 % vs 96.5 %; mutation score over the fixed 164 mutants 78.7 % vs 81.1 %.
- **Per target mutation score (global).** binary_sensor: 56.0 % per LLM sample vs 59.8 % for the developer file; config_flow: 5.4 % per LLM sample vs 47.6 % for the developer file; init: 50.0 % per LLM sample vs 54.3 % for the developer file.
- **Traceability.** Mean name-vs-coverage score 0.378 (developer) vs 0.301 (LLM); the LLM's declared `Target:` scores 0.533, and 92.0 % of valid LLM tests carry a parsable declaration.
- **Test smells.** Share of valid tests with at least one smell: 98.3 % (developer) vs 44.2 % (LLM); smell density 2.496 vs 0.662 per test.
- **Relevance and completeness (draft behaviour list).** Relevance 99.1 % (developer) vs 91.6 % (LLM); LLM completeness 100.0 % of the 38 behaviours reachable by the developer tests.

- **Metamorphic sensitivity (binary_sensor, n=5 per variant).** mr1a: 0/7 metrics differ at p<0.05, killed-mutant overlap 0.916 vs noise floor 0.925; mr1b: 0/7 metrics differ at p<0.05, killed-mutant overlap 0.946 vs noise floor 0.925; mr1c: 1/7 metrics differ at p<0.05 (smell_density), killed-mutant overlap 0.922 vs noise floor 0.925; mr2: 0/7 metrics differ at p<0.05, killed-mutant overlap 0.944 vs noise floor 0.925; mr3: 1/7 metrics differ at p<0.05 (valid_tests), killed-mutant overlap 0.942 vs noise floor 0.925; mr4: 0/7 metrics differ at p<0.05, killed-mutant overlap 0.942 vs noise floor 0.925.
- **Agreement with manual review (RQ2, n=60).** relevance: rho 0.30, kappa 0.10; clarity: rho 0.07, kappa 0.01; maintainability: rho 0.10, kappa 0.05; oracle_strength: rho 0.19, kappa −0.00 (table in the RQ2 section).

RQ1: generated tests versus developer tests

Executability

Suite	Units	Collect rate	Tests	Pass rate (mean of 3)	Stable pass rate	Flaky rate
developer	3/3	100.0 %	115	100.0 %	100.0 %	0.0 %
main_sonnet55_v1	15/15	100.0 %	294	97.6 %	97.6 %	0.0 %
mr_mr1a_binary_sensor	5/5	100.0 %	128	100.0 %	100.0 %	0.0 %
mr_mr1b_binary_sensor	5/5	100.0 %	160	100.0 %	100.0 %	0.0 %
mr_mr1c_binary_sensor	5/5	100.0 %	117	100.0 %	100.0 %	0.0 %
mr_mr2_binary_sensor	5/5	100.0 %	160	100.0 %	100.0 %	0.0 %
mr_mr3_binary_sensor	5/5	100.0 %	190	100.0 %	100.0 %	0.0 %
mr_mr4_binary_sensor	5/5	100.0 %	146	100.0 %	100.0 %	0.0 %

Failure types of non-passing tests

Suite	Error type	Tests
main_sonnet55_v1	RuntimeError	6
main_sonnet55_v1	AssertionError	1

Coverage and mutation score (suite level)

Developer rows per target are the matching developer file; the LLM rows are the union over the k = 5 samples of that target.

Target / scope	Suite	Tests passing	Line cov.	Branch cov.	Mutation score (global)	Mutation score (covered)
all	developer	115	100.0 %	93.1 %	78.7 %	78.7 %
all	LLM (union of k=5)	287	99.6 %	96.5 %	81.1 %	81.1 %
target:binary_sensor	developer	97	86.2 %	75.9 %	59.8 %	62.0 %
target:binary_sensor	LLM (union of k=5)	145	86.6 %	77.6 %	59.2 %	82.9 %
target:config_flow	developer	9	84.2 %	56.9 %	47.6 %	59.1 %
target:config_flow	LLM (union of k=5)	80	76.8 %	51.7 %	12.2 %	62.5 %
target:init	developer	9	65.8 %	25.9 %	54.3 %	70.6 %
target:init	LLM (union of k=5)	62	74.4 %	53.4 %	57.9 %	75.4 %




Figure 1: Suite level quality of developer and LLM tests.

Per file / per sample

Target	Developer file	LLM samples (mean ± sd, k=5)
binary_sensor - valid tests	97	29.0 ± 4.9
binary_sensor - line cov.	86.2 %	86.6 % ± 0.0 %
binary_sensor - branch cov.	75.9 %	77.6 % ± 0.0 %
binary_sensor - mutation score (global)	59.8 %	56.0 % ± 2.9 %
config_flow - valid tests	9	16.0 ± 2.1
config_flow - line cov.	84.2 %	48.9 % ± 15.6 %
config_flow - branch cov.	56.9 %	13.1 % ± 21.6 %
config_flow - mutation score (global)	47.6 %	5.4 % ± 3.8 %
init - valid tests	9	12.4 ± 3.2
init - line cov.	65.8 %	68.2 % ± 0.9 %
init - branch cov.	25.9 %	33.4 % ± 4.0 %
init - mutation score (global)	54.3 %	50.0 % ± 2.0 %




Figure 2: Mutation score of each LLM sample and of the developer file per target.

Traceability, smells, relevance, completeness

Behaviour list is a DRAFT (needs human check); completeness is relative to the behaviours the developer tests reach.

Suite	Trace (name target)	Trace (declared target)	Declared present	Smelly tests	Smell density	Relevance	Completeness
developer	0.378	n/a	n/a	98.3 %	2.496	99.1 %	100.0 %
LLM	0.301	0.533	92.0 %	44.2 %	0.662	91.6 %	100.0 %

Test smells (share of valid tests with the smell)

Smell	developer	LLM
assertion_roulette	97.4 %	20.2 %
duplicate_assert	6.1 %	3.8 %
magic_number	60.0 %	27.2 %
conditional_logic	79.1 %	0.0 %
no_assertion	0.0 %	5.6 %
try_except	0.0 %	0.0 %
sleepy_test	0.0 %	0.0 %
redundant_print	0.0 %	0.0 %
eager_test	0.0 %	0.0 %
empty_test	0.0 %	0.0 %

RQ2: agreement with the manual review

RQ2 agreement with manual review

Scale	n	Spearman rho	p	Weighted kappa
relevance	60	0.302	0.019	0.104
clarity	60	0.072	0.586	0.007
maintainability	60	0.104	0.427	0.047
oracle_strength	60	0.189	0.148	−0.001

RQ3: metamorphic sensitivity

RQ3 metamorphic sensitivity (binary_sensor target, n = 5 samples per variant)

Variant	Metric	Baseline mean (sd)	Variant mean	In baseline range	MWU p	Cliff's delta	Effect
mr1a	valid_tests	29.000 (4.899)	25.600	60 %	0.2933	−0.44	medium
mr1a	line_cov	0.866 (0.000)	0.872	80 %	0.4237	0.2	small
mr1a	branch_cov	0.776 (0.000)	0.786	80 %	0.4237	0.2	small
mr1a	mut_global	0.560 (0.029)	0.561	80 %	1.0	−0.04	negligible
mr1a	trace_name	0.225 (0.080)	0.252	100 %	0.462	0.32	small
mr1a	smell_density	0.634 (0.120)	0.710	40 %	1.0	−0.04	negligible
mr1b	valid_tests	29.000 (4.899)	32.000	100 %	0.3398	0.4	medium
mr1b	line_cov	0.866 (0.000)	0.866	100 %	1.0	0.0	negligible
mr1b	branch_cov	0.776 (0.000)	0.776	100 %	1.0	0.0	negligible
mr1b	mut_global	0.560 (0.029)	0.581	100 %	0.2918	0.44	medium
mr1b	trace_name	0.225 (0.080)	0.220	100 %	1.0	0.04	negligible
mr1b	smell_density	0.634 (0.120)	0.961	20 %	0.0952	0.68	large
mr1c	valid_tests	29.000 (4.899)	23.400	80 %	0.14	−0.6	large
mr1c	line_cov	0.866 (0.000)	0.863	80 %	0.4237	−0.2	small
mr1c	branch_cov	0.776 (0.000)	0.765	60 %	0.1797	−0.4	medium
mr1c	mut_global	0.560 (0.029)	0.526	80 %	0.0917	−0.68	large
mr1c	trace_name	0.225 (0.080)	0.240	80 %	0.5476	0.28	small
mr1c	smell_density	0.634 (0.120)	0.961	20 %	0.0952	0.68	large

Overlap of covered lines and of killed mutants

Variant	Set	Noise floor (same prompt)	Variant vs original	MWU p	Cliff's delta
mr1a	lines	1.000	0.990	0.1401	−0.2
mr1a	killed	0.925	0.916	0.7284	−0.08
mr1b	lines	1.000	1.000	1.0	0.0
mr1b	killed	0.925	0.946	0.1293	0.336
mr1c	lines	1.000	0.995	0.1401	−0.2
mr1c	killed	0.925	0.922	1.0	0.0
mr2	lines	1.000	0.993	0.1401	−0.2
mr2	killed	0.925	0.944	0.2208	0.272
mr3	lines	1.000	1.000	1.0	0.0
mr3	killed	0.925	0.942	0.2341	0.264
mr4	lines	1.000	0.993	0.1401	−0.2
mr4	killed	0.925	0.942	0.2206	0.272
mr1_pooled	lines	1.000	0.995	0.2273	−0.1333
mr1_pooled	killed	0.925	0.928	0.6672	0.0853




Figure 3: Overlap of killed mutants between variants and baseline versus the noise floor.

Discussion

Coverage was saturated; mutation score was not. The developer tests already execute every line (100.0 %), and the pooled LLM samples come within a fraction of that (99.6 %). Branch coverage (93.1 % against 96.5 %) moves a little more, but neither number tells a reader which suite would catch more faults. The mutation score does differentiate: it exposes how much a test actually checks, not only what it executes. This is the main reason why the study treats mutation score as the primary quality measure.

One sample is much weaker than the developer file. Per target, a single LLM sample kills 56.0 % of the mutants for `binary_sensor` (developer file: 59.8 %) and 50.0 % for `__init__` (54.3 %), which is close. For `config_flow` it kills only 5.4 % against 47.6 %. The samples for this module mostly exercise a few functions of the flow and leave the rest untouched, so the gap is a real property of the generated tests rather than a measurement artefact. A user who takes one generated file would get a clearly smaller safety net than the file the maintainers wrote.

The union of samples wins, but only with about 2.5 times more tests. Taking the union of the 15 samples gives 81.1 % of the 164 mutants killed against 78.7 % for the developers, but it uses 287 stably passing tests against 115. The advantage is small and is bought with a much larger suite that someone has to maintain; generating several samples and keeping the union is a way of trading review and maintenance cost for fault detection, not a free improvement.

The smell result is partly detector bias. The developer tests show assertion roulette in 97.4 % of valid tests and conditional logic in 79.1 %, the LLM tests in 20.2 % and 0.0 %. Many developer tests are parametrised and loop over lists of values, and the detector counts every executed case

of such a function, so a single data-driven function is counted as many smelly tests. The numbers (smelly tests: 98.3 % against 44.2 %) therefore overstate the difference in maintainability. The LLM suite is still simpler to read, but the figure should not be read as "developers write smelly tests".

What RQ2 says about trusting automatic scores. With 60 rated tests and one rater, none of the four automatic scores agrees well with the human ratings. The best one, relevance, reaches a Spearman ρ of 0.30 and the largest weighted κ over all scales is 0.10, which is slight agreement at most. Relevance (derived from covered behaviours) is weakly related to the human view; clarity (0.07), maintainability (0.10) and oracle strength (0.19) are not. In plain words: automatic scores are useful to screen a large number of tests and to compare suites in aggregate, but they cannot replace a human for judging whether a test is clear, maintainable or has a meaningful oracle. A part of the low κ comes from our binning of continuous scores into five levels, so ρ is the fairer figure; it is also low.

RQ3 shows no clear prompt sensitivity, but power is low. Across 6 variants and six metrics, 2 of 42 comparisons are significant at $p < 0.05$, which is about what chance alone would give without correction for multiple comparisons. The overlap of killed mutants between a variant and the baseline (0.916 to 0.946) stays at the level of the overlap between repeated samples of the same prompt (0.925). With five samples per variant, however, the tests can only detect large effects, and some effect sizes in the table are large but not significant. The honest conclusion is that we found no evidence of sensitivity, not that there is none.

Threats to validity

Construct validity. Traceability is defined operationally; entity properties that Home Assistant reads on every state write (for example `extra_state_attributes`) often become the "last call", which lowers the score for tests of either origin. Relevance and completeness rest on a draft behaviour list written by the assistant that has not yet been reviewed by a human, and a test is mapped to a behaviour by coverage, which does not prove that the behaviour is verified. Mutation tracking in mutmut is function level, so a unit's tests are only run for mutants of functions they execute, and the conventional score flatters narrow suites; we therefore also report the fixed denominator score. Module-level behaviours (schemas executed at import time) cannot be attributed to single tests and are excluded.

Internal validity. The blinding of the manual review is imperfect: naming and structure can reveal the origin even after docstrings are normalised. Failing or flaky tests are excluded from all quality metrics, which favours suites with few tests. The tool was developed together with the analysis, and parts of it (smell thresholds, mapping threshold) were fixed before looking at group differences but are still design choices.

External validity. One small integration of one project, one model family, one prompt template, and $k = 5$ samples per prompt: results may not carry over to other components, languages or models. The model may have seen Home Assistant tests during training, so the isolation of the developer tests applies to the prompt, not to the model's knowledge. The metamorphic experiment uses a single target module and five samples per variant, so its statistical power is low; "no significant

difference" must not be read as "equivalent". Several metrics and variants are tested at once without correction for multiple comparisons, so isolated p-values below 0.05 are weak evidence.

Conclusion validity. Rates over parametrised tests weigh heavily parametrised files more. Agreement statistics for RQ2 depend on one rater and on the binning of automatic scores.

Conclusion

We measured executability, coverage, mutation score, traceability, test smells, relevance and completeness for LLM generated and developer tests of one Home Assistant component, checked the automatic scores against a blinded manual review, and probed the generation with metamorphic prompt changes.

Takeaways.

1. *Do not judge generated tests by coverage.* The developer suite is saturated on lines (100.0 %) and the LLM samples are close; the mutation score (81.1 % for the union of samples against 78.7 %) and the per-file gaps are what show differences.
2. *Treat a single generated file as a draft, and expect a weak spot in stateful code.* The configuration flow was covered far worse (5.4 % against 47.6 %); more samples help but cost about 2.5 times as many tests.
3. *Keep a human in the loop.* Automatic scores agree only weakly with manual ratings (best ρ = 0.30), so they are good for screening and aggregate comparison but not for deciding that a test is good.

Future work.

1. *More integrations*: repeat the study on components of different size and style (for example with coordinators, platforms and external I/O) to test whether the config-flow weakness generalises.
2. *More raters*: use at least two independent raters on a larger sample to report inter-rater agreement and to separate rater noise from the limits of the automatic scores.
3. *Other models*: compare further model families and sizes, and prompt strategies such as repair loops, using the same measurement pipeline and a larger metamorphic experiment with more samples per variant.

Use of AI tools

Claude Code (Anthropic) assisted with the implementation of the measurement tool and the generation of this report from the result files. The research design, the review of the behaviour list, the manual ratings and the interpretation of the results are by the author.

References

Alshahwan, Nadia, Jubin Chheda, Anastasia Finogenova, et al. 2024. "Automated Unit Test Improvement Using Large Language Models at Meta." *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering (FSE Companion '24)*, 185–96. https://doi.org/10.1145/3663529.3663839.

Altmayer Pizzorno, Juan, and Emery D. Berger. 2025. "CoverUp: Effective High Coverage Test Generation for Python." *Proceedings of the ACM on Software Engineering* 2 (FSE): 2897–919. https://doi.org/10.1145/3729398.

Chen, Tsong Yueh, Fei-Ching Kuo, Huai Liu, et al. 2018. "Metamorphic Testing: A Review of Challenges and Opportunities." *ACM Computing Surveys* 51 (1): 1–27. https://doi.org/10.1145/3143561.

Chen, Yinghao, Zehao Hu, Chen Zhi, Junxiao Han, Shuiguang Deng, and Jianwei Yin. 2024. "ChatUniTest: A Framework for LLM-Based Test Generation." *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering (FSE Companion '24)*, 572–76. https://doi.org/10.1145/3663529.3663801.

Cliff, Norman. 1993. "Dominance Statistics: Ordinal Analyses to Answer Ordinal Questions." *Psychological Bulletin* 114 (3): 494–509. https://doi.org/10.1037/0033-2909.114.3.494.

Cohen, Jacob. 1968. "Weighted Kappa: Nominal Scale Agreement Provision for Scaled Disagreement or Partial Credit." *Psychological Bulletin* 70 (4): 213–20. https://doi.org/10.1037/h0026256.

Jia, Yue, and Mark Harman. 2011. "An Analysis and Survey of the Development of Mutation Testing." *IEEE Transactions on Software Engineering* 37 (5): 649–78. https://doi.org/10.1109/TSE.2010.62.

Lemieux, Caroline, Jeevana Priya Inala, Shuvendu K. Lahiri, and Siddhartha Sen. 2023. "CodaMosa: Escaping Coverage Plateaus in Test Generation with Pre-Trained Large Language Models." *2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE)*, 919–31. https://doi.org/10.1109/ICSE48619.2023.00085.

Mann, H. B., and D. R. Whitney. 1947. "On a Test of Whether One of Two Random Variables Is Stochastically Larger Than the Other." *The Annals of Mathematical Statistics* 18 (1): 50–60. https://doi.org/10.1214/aoms/1177730491.

Schäfer, Max, Sarah Nadi, Aryaz Eghbali, and Frank Tip. 2024. "An Empirical Evaluation of Using Large Language Models for Automated Unit Test Generation." *IEEE Transactions on Software Engineering* 50 (1): 85–105. https://doi.org/10.1109/TSE.2023.3334955.

Siddiq, Mohammed Latif, Joanna Cecilia Da Silva Santos, Ridwanul Hasan Tanvir, Noshin Ulfat, Fahmid Al Rifat, and Vinícius Carvalho Lopes. 2024. "Using Large Language Models to Generate JUnit Tests: An Empirical Study." *Proceedings of the 28th International Conference on Evaluation and Assessment in Software Engineering (EASE '24)*, 313–22. https://doi.org/10.1145/3661167.3661216.

Wang, Junjie, Yuchao Huang, Chunyang Chen, Zhe Liu, Song Wang, and Qing Wang. 2024. "Software Testing with Large Language Models: Survey, Landscape, and Vision." *IEEE Transactions on Software Engineering* 50 (4): 911–36. https://doi.org/10.1109/TSE.2024.3368208.

Wang, Shiqi, Zheng Li, Haifeng Qian, et al. 2023. "ReCode: Robustness Evaluation of Code Generation Models." *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 13818–43. https://doi.org/10.18653/v1/2023.acl-long.773.

Wang, Tongjie, Yaroslav Golubev, Oleg Smirnov, Jiawei Li, Timofey Bryksin, and Iftekhar Ahmed. 2021. “PyNose: A Test Smell Detector for Python.” *2021 36th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 593–605. https://doi.org/10.1109/ASE51524.2021.9678615.

White, Robert, Jens Krinke, and Raymond Tan. 2020. “Establishing Multilevel Test-to-Code Traceability Links.” *Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (ICSE ‘20)*, 861–72. https://doi.org/10.1145/3377811.3380921.