```
<div><br class="Apple-interchange-newline"><!DOCTYPE html> <html> <head> <meta
name="viewport" content="width=device-width, initial-scale=1"> <link rel="stylesheet"</pre>
href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/4.7.0/css/font-awesome.min.c
ss"> <style> body { margin: 0; font-family: Arial, Helvetica, sans-serif; } .topnav {
overflow: hidden; background-color: #333; } .topnav a { float: left; display: block;
color: #f2f2f2; text-align: center; padding: 14px 16px; text-decoration: none;
font-size: 17px; } .topnav a:hover { background-color: #ddd; color: black; } .topnav
a.active { background-color: #04AA6D; color: white; } .topnav .icon { display: none; }
@media screen and (max-width: 600px) { .topnav a:not(:first-child) {display: none;}
.topnav a.icon { float: right; display: block; } } @media screen and (max-width:
600px) { .topnav.responsive {position: relative;} .topnav.responsive .icon { position:
absolute; right: 0; top: 0; } .topnav.responsive a { float: none; display: block;
text-align: left; } </style> </head> <body> <div class="topnav" id="myTopnav"> <a</pre>
href="#home" class="active">Home</a> <a href="#news">News</a> <a
href="#contact">Contact</a> <a href="#about">About</a> <a href="javascript:void(0);"</pre>
class="icon" onclick="myFunction()"> <i class="fa fa-bars"></i> </a> </div> <div</pre>
style="padding-left:16px"> <h2>Responsive Topnav Example</h2> Resize the browser
window to see how it works. </div> <script> function myFunction() { var x =
document.getElementById("myTopnav"); if (x.className === "topnav") { x.className += "
responsive"; } else { x.className = "topnav"; } } </script> </body> </html></div>
```

1

3

5

7

9

11

12 13

14

15 16

17

18