

MPLS Data Plane Encapsulation for In-situ OAM Data

draft-gandhi-mpls-ioam-sr-05

Rakesh Gandhi - Cisco Systems (rgandhi@cisco.com) - Presenter

Zafar Ali - Cisco Systems (zali@cisco.com)

Clarence Filsfils - Cisco Systems (cfilsfil@cisco.com)

Frank Brockners - Cisco Systems (fbrockne@cisco.com)

Bin Wen - Comcast (Bin_Wen@cable.comcast.com)

Voitek Kozak - Comcast (Voitek_Kozak@comcast.com)

Agenda

- Requirements and Scope
- Summary
- Next Steps

Requirements and Scope

Requirements:


- Transport In-situ OAM (IOAM) data fields with MPLS Encapsulation

Scope:

- Using data fields defined in:
 - *draft-ietf-ippm-ioam-data*
 - *draft-ietf-ippm-ioam-direct-export*
 - *draft-ietf-ippm-ioam-flags*
- Edge-to-edge (E2E) IOAM
- Hop-by-hop (HbH) IOAM

IOAM Header

IOAM Data Field Encapsulation in MPLS Header



<https://www.iana.org/assignments/g-ach-parameters/g-ach-parameters.xhtml#mpls-g-ach-types>

IOAM G-ACh Header

- New Generic Associated Channel (G-ACh) Type (value [TBA3](#)) defined for IOAM
- Protocol value *0001b* allows to avoid incorrect IP header based hashing over ECMP paths
- Block Number can be used to:
 - Aggregate IOAM data collected in data plane, e.g. compute measurement metrics for each block of a flow
 - Correlate IOAM data from different nodes

IOAM Indicator Label

- “IOAM Indicator Label” is used to indicate the presence of the IOAM data fields after EOS in the MPLS header. How to process the IOAM data field(s) depends on the IOAM Option-Type.
- Separate Indicator Labels are used for E2E IOAM (for edge nodes) and HbH IOAM (*for edge and transit nodes*) to optimize the IOAM processing on transit nodes when not needed.
- In case of E2E IOAM, the IOAM Option-Type(s) in the data packets are processed on edge nodes only. The transit nodes ignore the IOAM Option-Type(s) carried by the data packets.
- In case of HbH IOAM, the IOAM Option-Type(s) in the data packets are processed on transit and edge nodes.

E2E IOAM

E2E IOAM Encapsulation in MPLS Header




Figure: E2E IOAM Encapsulation in MPLS Header

E2E Indicator Label Allocation Methods

1. Extension Label (15) and Label assigned by IANA with value **TBA1**
 - From Extended Special Purpose Labels (eSPL) range
2. Global Label allocated by a controller
 - The controller provisions the label on encapsulating and decapsulating nodes
3. **The IOAM Enabled Label allocated by the decapsulating node**
 - **Signaling/advertisement extensions needed to convey the label to all encapsulating nodes (out of scope)**

E2E Indicator Label Allocation Methods

	Method	Extra Label Stack Size (Note 2)	Location on Stack
1	eSPL Labels	+2 (Note 1)	Bottom
2	Global Label	+1	Bottom
3	Signal/Advertise Label	+1 (compared to PHP)	Bottom

1. This is true for any mechanism that we are defining using eSPL
 - SFC: <https://tools.ietf.org/html/rfc8595>
 - E2E: draft-cheng-mpls-inband-pm-encapsulation
2. IOAM data packets may require Entropy label for ECMP

E2E IOAM Procedure

1. The encapsulating node inserts an E2E Indicator Label and one or more IOAM data field(s) in the MPLS header.
2. The transit (intermediate) nodes do not process IOAM data.
3. The decapsulating node "punts the timestamped copy" of the data packet including IOAM data field(s).
 - a. The decapsulating node for E2E IOAM also pops the IOAM Indicator Label and the IOAM data field(s) from the MPLS header.
 - b. The decapsulating node processes IOAM data field(s).
 - c. The decapsulating node forwards the data packet downstream.

HbH IOAM

HbH IOAM Encapsulation in MPLS Header




Figure: HbH IOAM Encapsulation in MPLS Header

HbH Indicator Label Allocation Methods

1. Extension Label (15) and Label assigned by IANA with value TBA2
 - From Extended Special Purpose Labels (eSPL) range
2. Global Label allocated by a controller
 - The controller provisions the label on encapsulating, transit and decapsulating nodes
3. The IOAM Enabled Label allocated by the transit and decapsulating nodes
 - Signaling/advertisement extensions needed to convey the label to all encapsulating nodes (out of scope)

HbH Indicator Label Allocation Methods

	Method	Extra Label Stack Size (Note 4)	Location on Stack	Scan Label Stack (Notes 3)	Different FIB Entry for Local Label
1	eSPL Labels	+2	Bottom (Note 1)	Yes (Note 2)	No
2	Global Label	+1	Bottom	Yes (Note 2)	No
3	Signal/Advertise Label (like SFL)	+0	Incoming Packet with Top Label	No	Yes

1. eSPL at top of the label stack breaks MPLS forwarding in heterogenous network environment with and without IOAM capable nodes
2. Entropy Label similarly also requires transit nodes to scan label stack, however, entropy label processing is optional whereas IOAM processing is not optional.
3. A transit node may have a limit on how many labels it can scan. With any indicator scheme, the node will have to look past EOS into the packet to find the IOAM data that needs to be processed
4. IOAM data packets may require Entropy label for ECMP

HbH IOAM Procedure

1. The encapsulating node inserts a HbH Indicator Label and one or more IOAM data field(s) in the MPLS header.
2. The transit (intermediate) node processes HbH IOAM data field(s) and forwards the data packet including updated IOAM data field(s).
 - a. Transit node (intermediate) may punt the timestamped copy of the data packet for further IOAM processing
3. The decapsulating node "punts the timestamped copy" of the data packet including IOAM data field(s).
 - a. The decapsulating node for E2E IOAM also pops the IOAM Indicator Label and the IOAM data field(s) from the MPLS header.
 - b. The decapsulating node processes IOAM data field(s).
 - c. The decapsulating node forwards the data packet downstream.

HbH IOAM Encapsulation in MPLS Header




Figure: HbH IOAM Encapsulation in MPLS Header

HbH IOAM Encapsulation Example with SR-MPLS Header




Figure: IOAM Encapsulation Example with SR-MPLS Header

Next Steps

- Welcome your comments and suggestions
- Requesting MPLS WG adoption

Thank you

Open Review Comments

IOAM Data and Control Word

Control Word

- IOAM data is considered part of the MPLS Header, the control word and payload are added after the IOAM data in the packet.
- The decapsulating node removes the MPLS header including the IOAM header and then processes the control word and payload following it.
- IOAM HDR Length allows to find the Control word after the IOAM header.

ACH:

- IOAM data is considered part of the MPLS Header, another ACH and payload are added after the IOAM data in the packet.
- The decapsulating node removes the MPLS header including the IOAM header and then processes the next ACH.
- IOAM HDR Length allows to find the next ACH after the IOAM header.

IOAM Encapsulation in MPLS Header with Control Word [RFC4385]





Figure: IOAM Encapsulation in MPLS Header

IOAM Encapsulation in MPLS Header with PW Data



IOAM Data and DETNET

DETNET

IOAM Data and Fragmentation after EOS

Fragmentation

Thank you